Form 9-331 (May 1963)	UN ED STATES DEPARTMENT OF THE IN GEOLOGICAL SURVEY		
	ORY NOTICES AND REPORT OF THE PROPERTY OF THE	RIS ON WELLER	6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE
1.  OIL X GAS WELL X WELL  2. NAME OF OPERATOR	OTHER		7. UNIT AGREEMENT NAME NONE; 8. FARM OR LEASE NAME
	TEXACO Inc.		A. H. Blinebry NCT-1
3. ADDRESS OF OPERATOR	P. O. Box 728 -	Hobbs, New Mexico	9. WELL NO.
North Line of	660' from the East Line, Section 20, T-22-S, R-3	8-E, Lea County, N. M.	Drinkard  11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  Sec. 20, T-22-S, R-38-1  12. COUNTY OR PARISH 13. STATE
Regular	Check Appropriate Box To Indice	cate Nature of Notice, Report, or	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDISE REPAIR WELL (Other)		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIBING (Other) (NOTE: Report result	REPAIRING WELL  ALTERING CASING  ABANDONMENT®  s of multiple completion on Well pletion Report and Log form.)
nent to this work.) *	Tota	ertinent details, and give pertinent dates ce locations and measured and true vertical Depth - 1400; at 7:00 A. M. April 9, 19	s, including estimated date of starting any cal depths for all markers and zones perti-
at 140	00' with 400 Sx. Trinity at 1370'. Cement Circula	Lite Wate, plus 200 Sx.	Class "C" cement.

Temperature of mixing slurry 72°, - 12 Hour Strength - 1000 P. S. I. Bottom Hole Temperature - 72°, - Job complete 6:15 A. M. April 11, 1966.

Tested 8 5/8" 0. D. Casing for 30 minutes with 600 P. S. I. from 7:00 P. M. to 7:30 P. M. April 11, 1966. Tested 0. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 8:45 P. M. to 9:15 P. M. April 11, 1966. Tested 0. K. Job complete 9:15 P. M. April 11, 1966.

18. I hereby certify that the foregoing is true and correct SIGNED	TITLE Assistant District	DATE April 13, 1966
(This space for Federal or State office use)	Superintendent	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	APPROVED
		APR 15 1966

\*See Instructions on Reverse Side

J. L. GURDUN ACTING DISTRICT ENGINEER