

P. O. BOX 1865
HOBBS, NEW MEXICO 88240

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR
11th floor, Vaughn Bldg.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1830' FWL of Sec.
AT TOP PROD. INTERVAL: 22
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM 0552659 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CURRY FEDERAL

9. WELL NO.
TWO

10. FIELD OR WILDCAT NAME (UNDESIG. GAS)
ANTELOPE RIDGE-MORROW

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 22, T23S, R34E

12. COUNTY OR PARISH
LEA

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3476' GL

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <u>ACID JOB</u>	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-11-82 Finish GIH w/2-7/8" tbg. RU WESTERN ACID EQUIP. Spotted 250 g. 15% HCL Acid across perfs. from 10,629-10,758'. Set Pkr. @ 10,540'. Broke dn perfs. Break down press. 3300#. Pmpd spot acid away @ 3.2 BPM w/4100#. Max. press. 4100#. ISDP 2900#, 15" 2500#. Open to flow.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED David R. Glass TITLE PROD. CLERK DATE 8-11-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)
APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE _____ DATE _____
CONDITIONS OF APPROVAL NOV 1 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

