

HOBBS

U. S. LAND OFFICE New Mexico

SERIAL NUMBER NM 033503

LEASE OR PERMIT TO PROSPECT

Grid for well location with 'X' in the 2nd row, 4th column.

HOBBS OFFICE 000

1962 DEC 4 AM UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

TENNECO CORPORATION BY ITS MANAGING AGENT TENNECO OIL COMPANY Address P. O. Box 307, Hobbs, New Mexico Lessor or Tract USA-Jennings NM 033503 Field Undesignated State New Mexico Well No. 3 Sec. 14 T.24-S.R.32-E Meridian MPM County Lea Location 660 ft. [NX] of N. Line and 1980 ft. [W] of E. Line of Sec. 14 Elevation 3622 (Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records. Signed [Signature] A. W. Lang

Date November 26, 1962 Title Dist. Prod. Supt.

The summary on this page is for the condition of the well at above date.

Commenced drilling October 13, 1962 Finished drilling October 23, 1962

OIL OR GAS SANDS OR ZONES (Denote gas by G)

No. 1, from 4962 to 4980 No. 4, from to No. 2, from to No. 5, from to No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

No. 1, from to No. 3, from to No. 2, from to No. 4, from to

CASING RECORD

Table with columns: Size casing, Weight per foot, Threads per inch, Make, Amount, Kind of shoe, Cut and pulled from, Perforated (From-To), Purpose. Includes entries for 8-5/8 and 5-1/2 casing.

MUDDING AND CEMENTING RECORD

Table with columns: Size casing, Where set, Number sacks of cement, Method used, Mud gravity, Amount of mud used. Includes entries for 8-5/8 and 5-1/2 casing.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth set Adapters—Material Size

SHOOTING RECORD

Table with columns: Size, Shell used, Explosive used, Quantity, Date, Depth shot, Depth cleaned out.

TOOLS USED

Rotary tools were used from 0 feet to 5030 feet, and from feet to feet Cable tools were used from feet to feet, and from feet to feet

DATES

November 26, 1962 Put to producing November 21, 1962 The production for the first 24 hours was 125 barrels of fluid of which 7.2% was oil; 92.8% water; and % sediment. Gravity, °Bé. 38 If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas Rock pressure, lbs. per sq. in.

EMPLOYEES

, Driller , Driller , Driller

FORMATION RECORD

Table with columns: FROM-, TO-, TOTAL FEET, FORMATION. Lists geological layers like KB-GL, Undifferentiated SDS & Shls., Anhydrite, Salt w/Anhydrite Stringers, etc.

