

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
N.M. OIL CODE 100-101
(Reverse side)

LEASE DESIGNATION AND SERIAL NO.
NM-021644

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Conoco Inc.	8. FARM OR LEASE NAME Lynn B-25
3. ADDRESS OF OPERATOR P.O. Box 460 - Hobbs, NM 88240	9. WELL NO. #1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 1650' FEL	10. FIELD AND POOL, OR WILDCAT Jalmat Yates 7 Rivers
14. PERMIT NO. 30-025-09416	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 25, T-23S, R-36E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3346' DF	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>	WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>	FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input checked="" type="checkbox"/>	SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	(Other) <input type="checkbox"/>	(Other) <input type="checkbox"/>

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. MIRU. Spot 65 sx cement from 3380' to 2700'. SION. WOC. GIH and tag TOC. Spot 19 sx cement from 1330' to 1147'.
2. Set surface plug: Perforate 5-1/2" csg. @ 241'. Pump 25 bbls mud to load hole and establish circ. up 7-5/8" x 5-1/2" annulus. Pump 54 sx cement (10 sx excess) to fill up annulus and set plug in 5-1/2" csg.
3. ND BOP and cut off all csg at base of cellar. Fill casing strings (if necessary) from the cement plug to surface with cement. Erect P & A marker.

Contact Mike Bezilla for further technical information at 397-5868.

18. I hereby certify that the foregoing is true and correct

SIGNED W.W. Baker W.W. Baker TITLE Administrative Supervisor DATE Sept. 6, 1989
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE 9-21-89
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side