

# OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

## Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

**Midland, Texas, September 21, 1943**

Place

Date

OIL CONSERVATION COMMISSION,  
Gentlemen:

SANTA FE, NEW MEXICO.

Following is a report on the work done and the results obtained under the heading noted above at the

**Humble Oil & Refining Company** **J. L. Coats** Well No. **1** in the  
Company or Operator Lease

**NW/4 of NE/4** of Sec. **10**, T. **24-S**, R. **36-E**, N. M. P. M.,  
**Cooper** Field, **Lea** County.

The dates of this work were as follows: **Sept. 3, 4, 16, 17, 18, and 20, 1943**

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **August 18**, 19 **43**

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**Pulled 2" tubing. Ran Halliburton Cement Retainer to 2891' and squeezed perforations from 2985' to 3230' with 120 sacks Lone Star Cement. Maximum pressure 1650#. Left top cement plug at 2866'. Filled hole with mud. Pulled 6 joints, 164' of 7" casing. Mudded hole to 2500'. Cement plug placed 2500' to 2316' with 40 sacks. Mudded hole to 1500'. Cement plug placed 1500' to 1316' with 40 sacks. Mudded hole to 150' and cemented to surface with 20 sacks. Set regulation marker in accordance with State regulations. Work done by Lea County Casing Pullers, Contractors.**

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this **21st**

day of **Sept.**, 19 **43**

**Willie Mae Ferguson**  
My commission expires **6-1-45**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **J. L. Coats**

Position **Assistant Division Superintendent**

Representing **Humble Oil & Refining Company**  
Company or Operator

Address **Box 1600, Midland, Texas**

Remarks:

**Roy Yarbrough**  
Name  
**OIL & GAS INSPECTOR**  
Title