WELL REMEDIAL REPORT MEXICO OIL & GAS ENGINEERING C. MITTER RECEIVED BOX 127 HOBBS. NEW MEXICO

D		"—————————————————————————————————————	Sec. 20 T2	OBBS CAME
	OF WORKOVER Drill Deepor Cement plugbac Jement squeeze Plastic sque	ekPlastic eezeSet Pa	plugback Set cker Acidize	Liner Shoot Perso
	RPOSE OF Increase production, OilGa	isShut off	water Shut	off gas
	S SUMMARY Complete success Partial su	ccessFail	ure	
OATE V	iorkover started 12-9-33	Comp	leted 1-6-	<u> </u>
ÆLL DA	ATA D.F. elev. 33400 Completion of	late	Prod. form	ation Tates
C	Oil String 7 inch pipe	set at	3400	
Γ	Depth of hole before 3377	After	3050 P. B.	
F	Formation packer set at	with perf	orations above	below
_	inch liner set.	ТорВо	ttomCem	ented wsax,
É	and perforated with	holes from	to_	
	Section squeezed from 2008		with	sacks cement or
-	gallons plastic.	Maximum pre	ssure used	P.S.I.
7	MENTS RUN IN CONJUNCTION WITH Temperature bomb Electric Vater witch Hole Caliper	logDowel	l pilotGam	ma ray z Seutron Sat er Locator Ar
	S DETAIL		BEFORE Book	AFTER
V C	Dil production Bbls./day Water Production Bbls./day Gas Production M.C.F./day Gas oil ratio			