

O & 3cc - USGS - Roswell

Budget Bureau No. 42-R355.A  
Approval expires 12-31-60.

cc - OCC  
cc - Midland  
cc - File

U. S. LAND OFFICE Las Cruces

SERIAL NUMBER 049439 (B)

LEASE OR PERMIT TO PROSPECT

G. D. Riggs "B"

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

RECEIVED  
JUL - 2 1962  
U. S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

Grid for well location coordinates

LOCATE WELL CORRECTLY  
Ridewater Oil Company - Oper.

Company Getty Oil Co. - Owner Address Box 547, Hobbs, N. Mex.

Lessor or Tract G. D. Riggs "B" Field Justis Blinbify State New Mexico

Well No. 6 Sec. 1 T. 26S R. 37E Meridian NMPM County Lea

Location 660 ft. N of N Line and 560 ft. E of E Line of Sec. 1 Elevation 3038'  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed [Signature]

Date June 25, 1962 Title Field Foreman

The summary on this page is for the condition of the well at above date.

Commenced drilling 5-4-62 Finished drilling 5-25-62, 1962

OIL OR GAS SANDS OR ZONES

No. 1, from 5100 to 5844 No. 4, from 5100 to 5844

No. 2, from 5854 to 5988 (Dry) No. 5, from 5100 to 5844

No. 3, from 5100 to 5844 No. 6, from 5100 to 5844

IMPORTANT WATER SANDS

No. 1, from 5100 to 5844 No. 2, from 5100 to 5844

No. 2, from 5854 to 5988 No. 4, from 5100 to 5844

CASING RECORD

Table with columns: Size casing, Weight per foot, Threads per inch, Make, Amount, Kind of shoe, Cut and pulled from, Perforated, Purpose

MUDDING AND CEMENTING RECORD

Table with columns: Size casing, Where set, Number sacks of cement, Method used, Mud gravity, Amount of mud used

PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

SHOOTING RECORD

Table with columns: Size, Shell used, Explosive used, Quantity, Date, Depth shot, Depth cleaned out

TOOLS USED

Rotary tools were used from 0 feet to 6086 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

DATES

June 26, 1962 Put to producing \_\_\_\_\_, 1962

The production for the first 68 hours was \_\_\_\_\_ barrels of fluid of which 98.2 % was oil; .8 % emulsion; 0 % water; and 0 % sediment. Gravity, °Bé. 36.1

If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_

Rock pressure, lbs. per sq. in. \_\_\_\_\_

EMPLOYEES of Moran Drlg. Co.

H. D. Wilson, Driller D. R. Glover, Driller  
C. B. Riggs, Driller \_\_\_\_\_, Driller

FORMATION RECORD

Table with columns: FROM-, TO-, TOTAL FEET, FORMATION

(OVER)

FORMATION RECORD—CONTINUED

FOLD MARK

