

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15-1/2	255	200	Halliburton			
10-3/4	1150	500	"			
7-5/8	3100	125	"			

PLUGS AND ADAPTERS

Heaving plug -- Material Length Depth Set

Adapters -- Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Nitroglycerine 230 Q.	6-18-37	3130-3206		

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3200 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing July 1 1937

The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours 25,000,000 Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. 920

EMPLOYEES

R. W. Rickel Driller Roy Rodgers Driller

Dick Branson Driller H. E. Kennits Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 30th

April 1934

[Signature]
Notary Public

Jal, New Mexico April 30, 1934

Name *[Signature]*
Position Larry C. Zink Division Geologist
Representing El Paso Natural Gas Company
Address Box 1354, Jal, New Mexico