

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 6840 TD drilled feet, and from _____ feet to _____ feet.
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing June 17, 1954
 OIL WELL: The production during the first 24 hours was 206 barrels of liquid of which 100 was oil; _____% was emulsion; _____% water; and _____% was sediment. A.P.I. Gravity _____
 GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of liquid Hydrocarbon. Shut in Pressure _____ lbs.
 Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	<u>1127</u>	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	<u>1535</u>	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	<u>2578</u>	T. Montoya.....	T. Farmington.....
T. Yates.....	<u>2645</u>	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	<u>2906</u>	T. McKee.....	T. Menefee.....
T. Queen.....	<u>3587</u>	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....	<u>3766</u>	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	<u>3966</u>	T. Granite.....	T. Dakota.....
T. Glorieta.....	<u>5109</u>	T.	T. Morrison.....
T. Drinkard.....	<u>5540</u>	T.	T. Penn.....
T. Tubbs.....		T.	T.
T. Abo.....		T.	T.
T. Penn.....		T.	T.
T. Miss.....		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	90	90	Surface sand & caliche				
90	595	505	Red beds & red rock				
595	1171	666	Red beds & anhydrite				
1171	2578	1407	Anhydrite & salt				
2578	3113	535	Anhydrite, lime & shells				
3113	3607	494	Lime				
3607	6108	2501	Sandy lime & shale				
6108	6840	732	Lime				
	6840		Total depth drilled.				
	6830		PB - left cement in 5-1/2"				
			OD oil string casing.				
	6754		PHTD - Baker model "K"				
			Bridging Plug with 1 sack				
			cement on top of plug at				
			6754' in 5-1/2" OD casing.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

October 30, 1954

Company or Operator Sinclair Oil & Gas Company

Address 520 East Broadway, Hobbs, New Mexico (Date)

Name C. C. Salter

Position or Title District Superintendent

C. C. Salter