Submit 3 Copies to Appropriate District Office

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico

Form C-103 Revised 1-1-89

Energy, Minerals and Natural Resources Department

DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088	WELL API NO. 30-025-25234
DISTRICT III	5. Indicate Type of Lease STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL OAS WELL X WELL OTHER	S.R. COOPER
2. Name of Operator MERIDIAN OIL INC.	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
P.O. Box 51810, Midland, TX 79710-1810	JALMAT-TANSILL-YATES-7RVRS
4. Well Location Unit Letter G: 2310 Feet From The NORTH Line and 2310 Feet From The EAST Line	
Section 23 Township 24-S Range 36-E	NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	NMPM LEA County
//////////////////////////////////////	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING	
PULL OR ALTER CASING CASING TEST AND CE	
OTHER: OTHER:	
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	
NOTIFY NMOCD PRIOR TO STARTING WORK. RIH TO TOP OF CEMENT RETAINER AT 3,055'. CIRCULATE HOLE WITH 9 PPG GELLED BRINE.	
SET A CEMENT PLUG ACROSS THE BASE OF THE SALT AT 2,660' TO 3,055'. USE 45 SXS OF CEMENT. PULL UP TO 1,325'. SPOT A CEMENT PLUG ACROSS THE SURFACE CASING SHOE AND THE TOP OF THE SALT AT 1,185' TO 1,325'. USE 15 SXS OF CEMENT. PULL UP TO 50' AND CIRCULATE CEMENT TO SURFACE; USE 6 SXS OF CEMENT.	
CUT OFF CASING 3' BELOW GROUND LEVEL AND INSTALL P&A MARKER.	
ALL CEMENT WILL BE CLASS "C" WITH 2% CACL2 MIXED TO YIELD 1.32 FT 3/SK.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE Maria I-Pure PRODUCTION ASST	DATE 8-4-92
TYPE OR PRINT NAME MARIA L. PEREZ	TELEPHONE NO. 915-688-6906
(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON	AUG 07'92
DISTRICT I SUPERVISOR	