

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 3-NMOC-D-Hobbs (Lea Co.)
 1-R.J. Starrak-Tulsa
 1-A.B. Cary-Midland
 1-Engr. -JM
 1-File

30-025-26902

Form C-101
 Revised 1-1-65

5A. Indicate Type of Lease
 STATE ☐ FEE ☒

5. State Oil & Gas Lease No.
 --

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		7. Unit Agreement Name Myers Langlie Mattix Unit
b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Water Injection Well SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		8. Farm or Lease Name Myers Langlie Mattix Unit
2. Name of Operator GETTY OIL COMPANY		9. Well No. 59
3. Address of Operator P.O. Box 730, Hobbs, N.M. 88240		10. Field and Pool, or Willist Langlie Mattix
4. Location of Well UNIT LETTER A LOCATED 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE OF SEC. 31 TWP. 23S RGE. 37E NMPM		11. County Lea
18. Proposed Depth 3750		19A. Formation Queen
21. Elevations (show whether DE, RT, etc.) 3311 G.L.		21B. Drilling Contractor to be determined
21A. Kind & Status Plug. Bond Blanket		22. Approx. Date Work will start July 16, 1980

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
11	8 5/8	24	500'	300	Surface
7 7/8	5 1/2	15.5	3750'	1200	Surface

The proposed well will be drilled from the surface to a total depth of 3750' with rotary tools. The pump and plug process will be used in cementing all strings of casing and cement will be circulated to the surface on the 8 5/8" and 5 1/2" casing. The 5 1/2" casing will be perforated as indicated by electric logs opposite the Queen formation.

The drilling fluid will be brine water and mud of sufficient weight to condition the hole for logging and running casing. Blowout preventers will be installed and tested to 5000 psi. See attached BOP schematic.

APPROVAL VALID
 FOR 90 DAYS UNLESS
 EXTENDING COLLECTED

EXPIRES 11.7.80

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE; GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Dale R. Crockett Title Area Superintendent Date June 30, 1980

(This space for State Use)

APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT 1 DATE JUL 7 1980

CONDITIONS OF APPROVAL, IF ANY: