

5-USGS-Hobbs
1-Ad. Unit-Midland

1-JM-Engr.
1-File
1-Conoco-Hobbs

1-Conoco-Midland

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. ☐ oil well ☐ gas well ☒ other
2. NAME OF OPERATOR
GETTY OIL COMPANY
3. ADDRESS OF OPERATOR
P.O. Box 730, Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: Unit Ltr. G, 1650 FNL, 1980 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒ OK
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-02965-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal "33"
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Undesignated Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33, T26S, R33E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3227.6 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 4/1/81 Drilled 6 1/8" hole to 16,180'. Ran 86 jts. (3485') 4 1/2" OD 13.50# SM-95 8rd LF&C R3 casing and set @ 12,695-16,180'.
4/2/81 Halliburton cement 4 1/2" liner with 40 bbls. SAM-4, 510 sxs. class "H" cement, .6% Halad 22, 5/10% CFR-2, 5# KCl, 4% HRC/sk., and 300# gas check. Pumped 5 bbls. SAM-4, 40 bbls. mud, 10 bbls. SAM-4, 80 bbls. mud. Plug down @ 10:32 a.m.
4/3/81 WOC for 18 hrs. Pressured up on liner to 1200# for 30 minutes, OK. Tagged cement @ 12,245'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Superintendent DATE 4/8/81

APPROVED BY Roger A. Chapman TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
APR 14 1981
U.S. GEOLOGICAL SURVEY
ROSWELL, N.M. 87603

See Instructions on Reverse Side

APR 14 1981