

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	40	40	Caliche
40	95	55	Sand - Water at 80'
95	124	29	Red Rock-Set 15" @ 124 cemented with 100 sacks
124	270	146	Red Rock - Reset Socket
270	300	30	Brown Shale
300	345	45	Gray Shale
345	500	155	Red Rock
500	505	5	Anhydrite
505	530	25	Red Mud
530	545	15	Sand Water
545	675	130	Red Rock
675	735	60	" " and Gray Shale
735	740	5	Gray Shale
740	750	10	Blue Shale
750	1095	345	Red Rock - Landed 10" @ 824'
1095	1210	115	Anhydrite
1210	1220	10	Gravel
1220	1230	10	Anhydrite
1230	1270	40	" " and Red Rock
1270	1315	45	Red Rock and Shells
1315	1360	45	" " and Anhydrite
1360	1425	65	Salt
1425	1464	39	Anhydrite-Run @ 5/8" 22# casing 1425' and cemented 150 sacks pulled 824' 102"
1464	1560	96	Salt and shells
1560	1990	430	Salt and Anhydrite
1990	1995	5	Salt-Run 2187' with packer 7" @
1995	2010	14	Anhydrite
2010	2100	90	Salt and Anhydrite
2100	2110	10	Anhydrite and blue shale
2110	2125	15	Anhydrite and Salt
2125	2147	22	Anhydrite
2147	2160	13	Red Rock
2160	2168	8	Salt
2168	2180	12	Salt and Anhydrite
2180	2192	12	Anhydrite
2192	2255	63	Anhydrite and Salt -
2255	2300	45	Salt
2300	2325	25	Salt and Anhydrite
2325	2350	25	Anhydrite
2350	2380	30	Salt and Shells
2380	2410	30	Anhydrite and Salt
2410	2500	90	Salt
2500	2535	35	Salt and Shells
2535	2660	125	Anhydrite
2660	2690	30	Lime and Anhydrite
2690	2745	55	Broken Lime and shale
2745	2830	85	Broken Lime
2830	2865	35	Broken Lime and shale
2865	2880	15	Lime
2880	2890	10	Blue Shale
2890	2905	15	Sand (Gas at 2905)
2905	2915	10	Lime
2915	2919	4	Blue Shale
2919	2937	18	Lime
2937	2940	3	Shale
2940	2948	8	Lime
2948	2980	32	Blue Shale
2980	3000	20	Lime
3000	3005	5	Blue Shale
3005	3270	265	Lime-Set 8 1/2" casing @ 3270 cemented 100 sacks
3270	3300	30	Lime
3300	3387	87	Brown Lime
3387	3438	51	Gray Lime
3438	3455	17	OIL SAND
3455	3471	16	Lime
3471	3476	5	OIL SAND
3476	3490	14	Lime
3490	3515	25	OIL SAND
3515	3526	11	Gray Lime
	3526		TOTAL DEPTH