

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-934	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Humble Oil & Refining Company		N. Mex CE State
3. Address of Operator		9. Well No.
Box 1600, Midland, Texas 79701		1
4. Location of Well		10. Field and Pool, or Willcat
UNIT LETTER A 554 FEET FROM THE N LINE AND 554 FEET FROM		Undesignated
THE E LINE, SECTION 6 TOWNSHIP 24-S RANGE 38-E N.M.P.M.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
To be filed later		Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	
		OTHER Set and drill whipstock ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld to 9144 w/6 1/2" deflection. Lost tools in hole and could not retrieve. Spotted 100 sx cement plug and 1500# sand plus 1% CFR-2. WOC 18 hrs. Found top cement 7700'. Drld to 7925' and set retrievable whipstock @ South 83° West. Drld whipstock w/6 1/4" bit to 7945' and opened hole w/pilot hole opener to 7941'. Drld 6 1/4" hole to 7953. Slope test 2 3/4° south by 56° west @ 7938'. Drld to 7951 and slope test 4° south by 55° west. Reamed 6 1/4" hole to 7 7/8" hole from 7947-7953'. Reamed whipstock hole from 7935-8002'. Sloping 3 3/4° @ 8005'. Set cement plug from 7980'-7747' w/100 sx Class C cement plus 15% sand and 1% CFR-2. WOC 21 hrs. Top cement @ 7747'. Drld to 7915. Ran retrievable whipstock. 3° on directional survey. Drld 3° off whipstock. Reamed 6 1/4" hole to 7 7/8" hole from 7915-7926. Drld 6 1/4" rathole. 1 3/4° @ 7926'. Reamed rathole w/7 7/8" bit. Resumed drilling operations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. L. Clemmer D. L. Clemmer TITLE Agent DATE 5-5-67

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

0.6

3

DO NOT WRITE IN THESE SPACES

UNDESIGNATED

1. FORM REPAIR WORK	2. DRUG AND ABANDON	3. REMOVAL WORK
4. TEMPORARY ABANDON	5. CHANGE PLANS	6. TRANSFER OF RESPONSIBILITY
7. FILL OR ALTER FACING		8. ATTACHMENT AND DETACHMENT
9. OTHER		10. REMOVAL OF AIR

M. I. R. #1, spudded in well at 12:30 A.M. on 3-9-47. Drilled to 4,110' on 11-3/4" 80 surface casing. 447' w/270 sac Incon cement w/41 gal and 2% circulated. W.O.C. 20 hours and 45 minutes. Temp. 185°F casing w/1000 gal and held OK. Resumed drilling operations. Drilled to 4,331' on 8-1/2" casing 6,430' w/500 sac Incon cement w/15 gal and 2% Calcium Chloride. W.O.C. 21 1/2 hrs. Temp. 186°F casing w/1000 gal and held OK. Resume drilling operations.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

2170

Ag: 11

APPROVED BY

• • • • •

CONDITIONS OF APPROVAL, IF ANY: