

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-229

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator North American Resources Corporation	8. Farm or Lease Name Ramsay-State
3. Address of Operator 811 San Jacinto Building Houston, Texas 77002	9. Well No. 1
4. Location of Well UNIT LETTER G , 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 2 TOWNSHIP 25-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Jalmat
15. Elevation (Show whether DF, RT, GR, etc.) Gr. 3251.5	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A. Commencement of Drilling Operations:

Subject well was Spudded at 7:30 P.M., March 19, 1969.

B. Surface Casing - Test and cement job:

Drilled 12-1/4" hole to 368'.



Set 8-5/8", 24#, J-55, ST&C casing @ 365'. Cemented w/300 sx class "C" Cement. Plug down @ 11:20 A.M. (3-20-69).

Circulated 50 sx back to surface.

Test - Option 1: Tested casing w/1000# for 30 minutes.

Held O.K. Cement in place 18 hrs. 10 minutes. Tested at 5:30 A.M. (3-21-69).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  Darol K. Ramsey	TITLE Vice President Drilling & Production	DATE 3-25-69
APPROVED BY 	TITLE	DATE MAR 31 1969
CONDITIONS OF APPROVAL, IF ANY:		