

ITEM	DESCRIPTION	A. B. CHANGE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
A	33' class 6 creosoted pine pole				
B	3 1/2" x 4 1/2" x 8' treated crossarm				
C	High density wet process porcelain pin insulator		63		
D	5/8" x 3" Forged steel pin w/eq. washer, nut, & locknut	881			
E	5/8" x 12" machine bolt w/ nut (or length req'd)	881/2			
F	2 1/4" x 2 1/4" x 3/16" x 11/16" hole w/eq. washer	881/2			
G	5/8" HP locknut	351/2			
H	1/4" x 1 1/4" x 28" flat crossarm brace	71/2			
J	1/2" x 4" B2 Fetter Drive Lag Screw	508754			
K	3/8" x 4 1/2" Carriage Bolt w/ Nut	86341/2			
L	3/8" HP Locknut	3510			
M	Preformed Aluminum Alloy Armor Rods, size req'd				
N	4" x 1/2" x 6' strong alum. alloy			KEARNEY #2102540	X
O	Epoxy Insulator (Extension Link)				
P	35' class 3 creosoted pine pole			KEARNEY SERIES "B1"	X
R	Aluminum double tab Squeeze on Connector for ACSR, Aluminum, or Copper-size req'd	66100			
S	6" Suspension Insulator	6502			
T	3/8" Standard Oval Eye Nut	14050			
U	Primary Head End Clamp				
W	5/8" x 18" (or length req'd) Double Arming Bolt w/eq. nuts	8868			
X	Keying detail - see dwg No. ES-10 for specs.				
Y	Hot Line Clamp				
Z	Squeeze on basket, size required	51520AGP		KEARNEY	X

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER			
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: PRODUCTION DEPT. HOBB'S DIVISION	
		DRAWING NO. ES-1	
		SHEET 1 OF 3	