### STATE OF NEW MEXICO ENERGY, MINERALS AND NATURAL RESOURCES DEPARTMENT OIL CONSERVATION COMMISSION

APPLICATION OF GOODNIGHT MIDSTREAM PERMIAN LLC FOR APPROVAL OF A SALTWATER DISPOSAL WELL, LEA COUNTY, NEW MEXICO.	COMM. CASE NO. 24123
APPLICATIONS OF GOODNIGHT MIDSTREAM PERMIAN LLC FOR APPROVAL	
OF SALTWATER DISPOSAL WELLS, LEA COUNTY, NEW MEXICO.	DIV. CASE NOS. 23614-23617
APPLICATION OF GOODNIGHT	
MIDSTREAM PERMIAN, LLC TO AMEND	
ORDER NO. R-22026/SWD-2403 TO INCREASE	
THE APPROVED INJECTION RATE IN ITS	
ANDRE DAWSON SWD #1,	
LEA COUNTY, NEW MEXICO.	<b>DIV. CASE NO. 23775</b>

APPLICATIONS OF EMPIRE NEW MEXICO LLC TO REVOKE INJECTION AUTHORITY, LEA COUNTY, NEW MEXICO.

DIV. CASE NOS. 24018-24020, 24025

### EMPIRE NEW MEXICO LLC'S NOTICE OF FILING CROSS-EXAMINATION EXHIBITS

Empire New Mexico, LLC, through its undersigned counsel, hereby provides notice that

the following Cross-Examination Exhibits were admitted into the record in the above-captioned

matters.

Respectfully submitted,

By: <u>/s/ Sharon T. Shaheen</u>

Sharon T. Shaheen SPENCER FANE LLP P.O. Box 2307 Santa Fe, NM 87504-2307 (505) 986-2678 sshaheen@spencerfane.com

Dana S. Hardy Jaclyn M. McLean Timothy B. Rode **HARDY MCLEAN LLC** 125 Lincoln Ave., Suite 223 Santa Fe, NM 87505 (505) 230-4410 dhardy@hardymclean.com jmclean@hardymclean.com trode@hardymclean.com

Ernest L. Padilla **PADILLA LAW FIRM, P.A.** P.O. Box 2523 Santa Fe, NM 87504 (505) 988-7577 padillalawnm@outlook.com

Corey F. Wehmeyer SANTOYO WEHMEYER, P.C. IBC Highway 281 N. Centre Bldg. 12400 San Pedro Avenue, Suite 300 San Antonio, Texas 78216 (210) 998-4190 cwehmeyer@swenergylaw.com

Attorneys for Empire New Mexico, LLC

### **CERTIFICATE OF SERVICE**

I hereby certify that a true and correct copy of the foregoing was served on the following by electronic mail on May 8, 2025.

Mathew M. Beck Peifer, Hanson, Mullins & Baker, P.A. P.O. Box 25245 Albuquerque, NM 87125-5245 <u>mbeck@peiferlaw.com</u>

Attorneys for Rice Operating Company and Permian Line Company, LLC <u>/s/ Sharon T. Shaheen</u> Sharon T. Shaheen

Christopher Moander Jesse Tremaine Office of General Counsel New Mexico Energy, Minerals and Natural Resources Department 1220 South St. Francis Drive Santa Fe, NM 87505 <u>Chris.Moander@emnrd.nm.gov</u> Jessek.tremaine@emnrd.nm.gov

Attorneys for Oil Conservation Division

Miguel A. Suazo Sophia Graham James Parrot Beatty & Wozniak, P.C. 500 Don Gaspar Ave. Santa Fe, NM 87505 msuazo@bwenergylaw.com sgraham@bwenergylaw.com jparrot@bwenergylaw.com

Attorneys for Pilot Water Solutions SWD, LLC

Michael H. Feldewert Adam G. Rankin Paula M. Vance Nathan Jurgensen Holland & Hart LLP P.O. Box 2208 Santa Fe, NM 87504 mfeldewert@hollandhart.com pmvance@hollandhart.com nrjurgensen@hollandhart.com

Attorneys for Intervenor Goodnight Midstream, LLC

# Only 99 grid blocks out of 34,500 have vertical permeability greater than zero, thus allowing water influx from San Andres. Below shows a sample of the KZ of Layer 8.

### Vertical Permeability from San Andres into Grayburg Zone

Simulation Model has 115 grid blocks in X direction and 300 grid blocks in Y. Each grid block is 2 acres in size.

	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69
100																0.25																	
101																																	
102																							1										
103																																	
104			0.05																														
105																																	
106																																	
107																										0.25							
108															0.5																		
109																																	
110		•		•		0.125														0.125													
111																																	
112	•								,							,	•			,		•		,				,	,	,			
113																																	
114														•			•				•					•							
115		•				•		•			•										•					•					•		
116	•	•		•	•			•	•	•	•	•		•		•	•	•	•		•	•		•	•	•		•	•		•		•
117	•	•		•				•	•	•			0.125			•	•	•	•		•	•	•	•		•			•	•	•		•
118	•	•		•	•			•		•			•	•			•	•	•			•	•	•	•	•	•		•	•		•	•
119		•						•		•				•			•	•			0.375	•			•	•					•		
120		•	•					•		•		•	•	•	•		•	•	•		•	•				•	•			•			•
121		•	•	•				•	•	•	0.25	•		•		•	•	•	•		•	•	•			•		•	•	•	•	•	•
122	•	•		•	•	•	•		•		•	•		•		•	•	•	•		•	•		•		•	•		•	•	•	•	•
123		•							•	•		•		•		•			•		•			•		•					•		•
124	•	•	•	•				•	•		•	•		•		•	•	•		0.05	•		•	•	•	•		•	•		•		•
125	•	•	•	•		•		•	•	•	•	•			•	•	•	•	•		•	•	•	•	•	•	•	•	•	•	•	•	•
126	•	•		•	•			•		•	•	•		0.125		•	•	•	•	•	•	•	•		•	•		•	•	•	•	•	•
127	•	•		•				•		•		•	•	•	•	•	•	•	•	•	•	•			•	•	•	•	•	•	•	•	•
128	•	•		•	•			•		•			•	•			•	•	•		•					•		•			•	•	•
129	•	•	•	•	•	•	•	•	•	•	•	•		0.275		•	•	•	•		•	5		•		•	•			•	•	•	•
101	•	•	•	•	•				•	•	•	•		0.375	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
131	•	•		•			· ·	•	•	•	•	•	•	•	•	•		•	•	•	•	•				•		•	•		•	•	•
122								•									0.25		•							•							
124	•	•	•	•	•	•		•	•	•		•	•	•	•	•	•	•	•		•			•	•	•		•	•	•	•		•
104		•		•					•		0.275	•		•					•		•		•	•	0.25	•			•		•		•
135	•	•		•		•	•				0.375	•		•		•			0.05		•	•	•	•	0.25	•		•	0.5		•		•
107	•	•		•			•	•	•	· ·		•		•	•	•		•	0.05	•	•	•	•	•	•	•			0.5		•		•
120		•		•				•	•		•	•				•		•	•		•	•		•	•		•	•	•		•		
130		•							•							•		•			•					•		•			•		
140				•					•			•				•	•	•	•		•										•		
140	•	•	•	•					•		•	•	•			•		•	•		•			•				0.25	•		•		
141				•	•			•	•		•	•		•		•		•	•		•							0.25			•		
142	•	•	•	•	•		•	0.05	•		•	•		•		•	•	•	•		•			•		•	•				•		•
143		•		•	•			0.05	•		•	•		•		•	•	•	•		•	0.375	•	•		,			•		•	•	•

## Vertical Permeability Controls Fluid Flow From San Andres to Grayburg

The vertical permeability (KZ) between the San Andres and Grayburg was modified on 99 out of 34,500 grid blocks to allow for water to move from San Andres into Grayburg.



We were provided a bottomhole pressure for the EME-20 SWD by Rice. We asked Dr. Buchwalter to provide the pressures at this well location in his simulation model using the 1450 psi @ -250' subsea original pressure Base Case Model. Here are the results.

## 1959 Pressure Calculation for EME#20

- Depth layer 10 in model = 4921 ft
- 1938 pressure @ 4921 ft in model = 2058 psi
- 1959 pressure @ 4921 ft in model = 1754 psi
- 1959 Corrected model pressure to 5000' = 1754 psi+(5000-4921)\*0.43 = 1788 psi
- 1959 Measured Pressure at 5000' = 1800 psi
- · Variance of 12 psi





## **Rice's EME-20 Bottomhole Pressure Survey**



Received by OCD: 5/8/2025 3:23:28 PM

DUEEN

RAYBURG

AN ANORES

LOVINGTON\_SAND

7" set at 4,445

RICE E M E SWD 20 30025128000000

RICE E B E SWD 20

## Rice's EME-20 Wellbore Diagram

ASE ENALE SWD SYSTEM H-201 SEA NEA SEC. 20- T205-R37E	
EME-20 Wellbore	
	NEW MERCICO OFIL CONSERVATION COMMERSION
0.51	WELL RECORD
998 " casing set at 812 ' with 500 sx of REG- UEAT cement	Rice Engineering & Operating, Inc. Lunice - Monuscint - Eusont SNO
Hole size 12/4 " CEMENT CIRCULATED.	Well No. H-22 56 N of NE N, of Sec. 22 T 20 5 37 E NAME
	Wells 2475 Jun from North Son and 160 Jun from East Son
· · ·	of Series. 20
	Nues of Dellag Conserver Stout & Wouldern
	Elevative divers and lovel at Top of Tables Road 2006* The information gives is to be kept candidated and Not confidential
,	
	· No. L from No. L from
	No. 2, from
	SALT DEPOSITATY WATER GAUGE
	* Include data on rate of wears inflow and elevation as which wears rate in hole. No. 1, from: 4-10.2 450.3 Form
	Ma. 7, fram. 4600' 4725' Jent.
	No. 1, from
3005Y SINEAR DOWN - CAR AVE	CASING BROOKD
W/300 CUFT POZZOLUS + 50# FUCEN	AND PERMIT THE ANTER THE PRESENCE PERMIT
5 casing set at 4446 ' with 150 sx of PPI NEAT comment	9-5/8 32.3 New 793 Texas Surface Casin 7 20 New 4430 Cuide Injection Gay
Hole size 834 " TOP or Cause and and the	
TOT OF CEMENT @ 815 SURVEY.	MUDDOG AND CREENTING RECCERD
}	HELE CALOFE HELE ALLEGED HELE ALLEGED
5%"OD tubul state (red) /	12-1/4 5-0/8 512 500 Hexto 1 plug Vater 8-3/4 7 4:45 752 Hexto 1 plug Vater
I VIA VV IUDIUC SET (1) AA 37	
THIS WANNULLY ON BUNKET - NU PACKED	5 LT
THE ST WANNULUP ON BUDGET - NO PACKED	RECORD OF PRODUCTION AND STRUCTATION (P. )
	BECORD OF PROTECTION AND STRETLATION
	ERCORE OF PRODUCTION AND STRUCTATION
	RECORD OF PRODUCTION AND STRUCTATION      (*)        (Record do Process and, No. of Qs. or Gox. and, instruct or shes)      (Acidized 4882 - 44/30% to/2500 gal. in %, 4600 - 4720 to/5270 tol. 100, and        Acidized 4882 - 44/30% to/2500 gal. in %, 4600 - 4720 to/5270 tol. 100, and      (*)
	Record of Pricetory AND STRETLATION (***) (Record do Prices and, No. of Qs. or Go. and, incred readers) Acidized ASE2 - 4930* m/2500 gal. 15 %, 4600 - 4726 m/2020 mol. 150, and 4451 - 4503* m/2300 gal. 150, French of Production Standards (Gravity injection rats down 7* casing before asid=10,000 H.
Total Depth 5000 '	Record of Protocol AND STRUCTOR AND STRUCTORY (P) (Record do Process and, Sh. of Qa or Gas, and, instructured or des.) Acidized ASE2 - 4930° m/2500 gal. 15 %, 4600 - 4726 m/2270 mpl. 15h. and 4451 - 4503° m/2500 gal. 15k. Acidized ASE2 - 4930° m/2500 gal. 15k. Acidized ASE2 - 4930° m/2500 gal. 15 %, 4600 - 4726 m/2070 mpl. 15h. and 4451 - 4503° m/2500 gal. 15k. Record of Protocols Disorders, Gravity Injection rate down 7° casing before acid-1680000. Cravit: injection rate down 7° casing struct acid-2000.00000

.

RAYBUR

N ANDRES

7" set at 4,445

RICE E B E SAD 20

## Pressure Depletion from EME-20 BHP in 1959 to RFT Pressure Points in 1986

	EME 20			Stop	Overall
	Depth	SS	Pressure	Gradients	Gradient
	0		0	0	
	500	3022	7	0.014	0.01
	1000	2522	26	0.038	0.03
	1500	2022	247	0.442	0.16
	2000	1522	462	0.43	0.23
	3000	522	905	0.443	0.30
Top SA	3896	-374	1312	0.442	0.34
	4000	-478	1347	0.442	0.34
	5000	-1478	1800	0.453	0.36

Top SA = 1800psi-(5000'-3896')\*0.442 psi/ft = 1312 psi

### EMSU 211 RFTs



RICE E M E SWD 20

after no fluids production from San Andres

## **Impact of Rock Facies on Oil Saturation**

Dr. Davidson testifies oil saturation of an average of 40% are possible in the San Andres Poorer rock qualities

- Dr. Davidson describes a spectrum of facies.
- Until a facies gets to MDP and an RI of around 15 and it appears to asymptote before it reaches 30% oil saturation.
- Does it look like Dr. Davidson is giving those facies a chance to show that the40% he says is possible?
- Is it standard practice to discount facies that you show are capable of holding 40% hydrocarbon?
- From this plot does it appear the average saturation is generally higher in the "poorer' facies?



Digitized info from Dr. Davidsons plot where he described the Sc value for points along his spectrum of facies.

## Impact of Rock Facies on Oil Saturation (Corrected Core Oil Saturations) REMOVAL OF SUSPICIOUS DATA

Same plot, same scales, Sc lines are gone. Now plotted with ops geologic (1 - corrected core oil sat)

Dr. Davidson testified that he could have used Archie, he just thought it was inefficient

He showed though, that to match Core oil saturations, you have to use values up to over 100. which would be very strange Black triangle is data that is very suspicious and absolutely should not be used for modeling!

- X is corrected core sw
- Y is Resistivity index
- Color of points is RQI
- Perm is taken from Kmax, largest of horizontal perm, or only horizontal perm available
- Mr. Knights testified yesterday that we have very little core for the amount of looking at.
- That is <u>absolutely why</u> we need to use quality control and not exploit inappropriate data in the areas where we don't have core.
- Core Saturations are absolutely the most uncertain



**Released to Imaging: 5/8/2025 4:43:00 PM** 

## Impact of Rock Facies on Oil Saturation (Uncorrected Core Oil Saturations) REMOVAL OF SUSPICIOUS DATA

Same plot, same scales, Sc lines are gone. Now plotted with ops geologic (1 - corrected core oil sat)

Dr. Davidson testified that he could have used Archie, he just thought it was inefficient He showed though, that to match Core oil saturations, you have to use values up to over 100. which would be very strange Black triangle is data that is very suspicious and absolutely should not be used for modeling!



- X is corrected core
  SW
- Y is Resistivity index
- Color of points is RQI
- Perm is taken from Kmax, largest of horizontal perm, or only horizontal perm available

	Per	meability (N	ND)		% F	uids
Depth	Kmax	K90	Kvert	Por %	H2O	Oil
3741	0.55	0.52	0.75	15.00	26.90	15.80
3742	18.21	11.79	1.39	8.30	35.60	12.00
3743	4.83	4.33	0.68	9.00	28.20	20.00
3744	45.59	2.62	6.81	6.90	39.50	27.70
3745	7.40	5.06	6.01	9.60	27.60	18.20
3746	2.89	0.29	2.26	5.70	29.00	21.60
3747	1.85	Kplug	0.01	7.00	27.70	27.20
3748	31.18	24.22	7.97	13.00	21.30	19.80
3749	759.83	729.22	181.02	18.30	18.30	21.00
3750	47.53	41.60	26.58	14.20	19.30	26.00
3751	175.28	45.46	26.75	4.80	42.50	15.00
3752	0.01	Kplug	12.76	7.50	34.60	12.10
3753	1035.96	773.23	95.51	15.50	32.30	28.00
3754	9876.74	1729.59	162.70	17.90	27.00	11.00
3755	680.64	473.80	196.30	18.50	22.40	22.10
3756	886.07	385.45	TBFA	15.80	23.60	16.30
3758	291.64	237.77	91.03	5.70	22.60	16.50
3759	0.01	Kplug	0.01	3.70	65.10	15.20
3760	1806.34	773.23	32.15	14.20	27.20	17.70
3761	66.09	49.03	TBFA	14.60	21.50	24.40
3762	15.29	12.14	22.39	12.90	24.30	23.50
3763	71.14	69.87	50.92	12.80	20.80	24.10
3764	35.24	24.41	35.38	12.80	25.30	20.70
3765	18.95	3.65	5.48	8.40	22.10	24.70
3766	45.34	44.56	52.50	16.30	25.90	18.30

	Per	meability (N	ND)		% F	uids	
Depth	Kmax	K90	Kvert	Por %	H2O	Oil	
3767	28.22	27.00	19.99	18.00	19.70	10.70	
3768	23.49	19.41	17.75	14.40	26.60	37.70	
3769	10.47	2.41	4.73	12.40	25.30	17.20	
3770	185.79	164.15	17.32	10.30	50.10	15.50	
3771	8515.94	248.84	106.88	19.20	21.50	25.60	
3772	142.00	24.49	39.28	5.40	68.10	8.50	
3773	34.34	18.78	48.89	11.50	25.00	22.50	
3774	47.92	35.34	42.28	14.00	20.70	21.30	
3775	49.47	41.18	85.16	12.80	19.60	20.30	
3776	103.28	69.46	58.07	12.00	20.60	22.20	
3777	23.89	6.24	80.28	4.20	30.50	14.30	
3778	0.01	Kplug	0.09	13.50	28.80	12.00	
3779	0.01	Kplug	TBFA	3.40	37.20	19.90	
3780	8868.80	77.73	64.19	3.50	50.70	6.40	
3781	54.08	30.13	15.33	2.70	42.30	24.00	
3782	4.18	1.55	1.16	3.70	28.50	24.80	
3783	126.02	21.58	17.18	9.20	27.90	27.00	
3784	26.35	9.04	0.75	3.50	58.10	16.00	
3785	376.88	59.66	6.73	6.00	39.50	16.70	
3786	6.94	6.11	15.65	8.10	22.90	19.20	
3787	37.25	35.61	57.96	12.00	18.60	20.60	
3788	58.12	17.85	35.64	11.10	20.50	20.90	
3789	168.09	42.45	134.15	10.60	30.80	9.50	
3790	20.47	20.24	5.84	10.10	16.70	23.90	
3791	14.44	1.96	1.95	10.30	23.40	26.70	

	Per	meability (N		% Fluid		
Depth	Kmax	K90	Kvert	Por %	H2O	Oil
3756	41.92	8.71	43.99	7.10	24.10	25.10
3757	0.72	0.47	0.02	5.20	22.30	23.40
3758	19.02	11.02	18.09	9.80	20.70	23.20
3759	6.48	2.24	2.53	2.10	43.20	19.40
3760	13.26	0.41	16.40	3.70	44.90	17.70
3761	170.81	65.27	21.97	5.70	22.80	24.10
3762	0.26	0.08	0.36	5.10	30.70	27.40
3763	43.23	TBFA	TBFA	4.90	40.50	21.70
3764	70.09	47.44	0.55	11.70	18.80	19.10
3765	58.96	47.70	6.31	12.90	16.50	19.40
3766	432.60	339.77	16.92	11.20	16.10	20.20
3767	2457.59	Plug	N/A	12.70	22.50	25.40
3768	2123.11	1336.69	1054.60	21.70	21.40	22.80
3769	4059.86	Plug	N/A	4.90	38.80	14.10
3770	133.42	9.73	2.77	5.00	24.60	21.30
3771	53.29	35.95	46.37	13.80	20.50	25.40
3772	166.85	84.25	136.87	15.90	20.00	27.50
3773	3.48	Plug	N/A	12.40	22.50	27.30
3774	0.16	Plug	N/A	7.80	27.30	31.00
3775	1166.24	Plug	N/A	17.60	24.70	31.60
3776	395.63	391.91	20.02	12.40	22.40	26.80
3777	23.78	15.16	6.95	6.20	26.50	25.40
3778	32.34	19.68	29.25	13.30	18.60	23.30
3779	3787.63	51.01	33.58	12.30	21.60	25.20
3780	41.29	0.31	0.07	4.80	35.30	29.70

	Per	meability (N	1	% Fluids			
Depth	Kmax	K90	Kvert	Por %	H2O	Oil	
3780	41.29	0.31	0.07	4.80	35.30	29.70	
3781	17.19	14.14	17.72	4.70	38.90	27.00	
3782	6.07	Plug	N/A	7.60	20.20	27.00	
3783	1867.59	699.19	12.71	13.60	20.00	23.90	
3784	373.82	284.27	182.26	16.30	20.50	27.60	
3785	3645.72	531.38	27.32	13.80	20.00	28.50	
3786	934.28	517.49	24.33	11.70	24.80	28.90	
3787	542.68	330.52	25.46	16.50	18.80	23.90	
3788	2386.61	1053.25	21.19	11.20	24.20	28.40	
3789	3753.59	486.02	39.25	14.30	18.00	25.40	
3790	58.93	3.24	0.07	6.40	34.00	23.30	
3791	38.76	26.43	1.38	6.80	28.70	26.40	
3792	7.07	1.21	4.00	5.80	35.20	26.00	
3793	9.69	4.16	2.91	2.30	40.50	25.00	
3794	0.36	0.12	0.58	3.40	41.60	25.60	
3795	0.20	0.14	0.09	2.80	41.50	27.80	
3796	0.04	0.04	0.01	4.30	56.80	14.60	
3797	0.03	0.02	0.01	5.70	50.10	13.00	
3798	0.02	0.02	0.01	5.20	33.70	20.20	
3799	0.03	0.02	0.01	3.90	46.40	16.00	
3800	0.61	0.22	0.01	3.90	47.00	14.30	
3801	5.69	5.69	2.87	7.80	28.20	19.30	
3802	9.49	9.49	5.52	9.90	18.00	21.80	
3803	14.57	14.57	TBFA	9.50	17.50	19.40	
3804	64.64	64.64	26.15	11.20	18.30	19.60	

	Per	meability (N	ND)		Saturation			
Depth	Maximum	90 Deg	Vertical	Porosity	Pore Oil	Pore Water		
3737.0	176.00	171.00	80.80	12.4	17.2	32.7		
3738.0	0.52	0.22	0.23	9.8	27.0	52.0		
3739.0	0.56	0.50	0.26	10.8	29.4	34.6		
3740.0	0.09	0.05	0.07	6.2	38.6	51.4		
3741.0	627.00	191.00	50.90	17.3	17.6	35.2		
3742.0	31.80	3.24	0.71	9.8	14.3	40.5		
3743.0	6434.00	2.03	914.00	8.9	14.0	46.8		
3744.0	105.00	1.03	210.00	4.9	12.0	42.5		
3745.0	312.00	40.80	297.00	16.4	15.4	32.5		
3746.0	3286.00	16.30	118.00	15.1	24.8	27.5		
3747.0	77.10	76.00	15.30	14.4	19.3	34.0		
3748.0	290.00	279.00	58.80	17.9	15.1	35.1		
3749.0	116.00	108.00	61.00	14.9	18.4	25.6		
3750.0	149.00	5.43	5.40	12.6	20.0	33.4		
3751.0	6.28	5.94	1.97	14.1	23.5	30.8		
3752.0	237.00	79.90	76.70	14.6	16.9	27.1		
3753.0	295.00	201.00	71.50	13.7	26.8	29.8		
3754.0	17.90	10.70	10.30	9.1	18.3	38.9		
3755.0	52.50	58.50	46.80	12.5	22.2	29.6		
3756.0	257.00	146.00	92.10	14.4	19.4	34.9		
3757.0	1448.00	80.00	17.00	8.7	11.3	35.5		
3758.0	1340.00	113.00	1422.00	10.9	8.3	33.3		
3759.0	50.90	49.20	20.70	11.3	7.4	28.4		
3760.0	158.00	123.00	14.40	11.7	6.0	28.9		
3761.0	194.00	158.00	31.40	11.8	9.4	22.9		
3762.0	1160.00	162.00	20.30	11.7	5.9	30.4		
3763.0	4900.00	1265.00	27.30	8.5	8.5	31.5		
3764.0	937.00	305.00	13.50	11.5	16.0	24.0		
3765.0	73.20	46.00	10.60	8.8	4.7	47.2		

	Per	meability (N	/ID)		Satu	iration
Depth	Maximum	90 Deg	Vertical	Porosity	Pore Oil	Pore Water
3766.0	7.43	5.41	0.10	3.0	3.9	62.1
3767.0	333.00	1.82	3.79	10.3	18.3	24.4
3768.0	1097.00	539.00	61.40	11.1	15.4	29.3
3769.0	327.00	11.30	1.30	7.3	17.3	36.3
3770.0	2.52	1.46	0.91	6.2	16.2	59.3
3771.0	35.00	31.10	6.47	14.2	15.6	41.0
3772.0	4.54	4.77	1.99	15.9	26.1	31.2
3773.0	8.78	8.70	4.05	14.9	29.4	29.4
3774.0	1.17	0.84	0.85	9.8	35.2	31.7
3775.0	218.00	213.00	60.80	13.6	18.8	34.6
3776.0	1.12	0.73	1.85	5.0	28.8	60.6
3777.0	27.40	27.00	0.99	14.2	17.3	33.0
3778.0	366.00	248.00	1.95	13.8	22.7	28.4
3779.0	226.00	213.00	4.86	12.3	15.1	28.1
3780.0	17.80	17.70	2.26	12.2	20.8	33.3
3781.0	26.50	25.90	25.60	14.1	24.5	25.6
3782.0	7.96	7.45	3.15	7.9	13.7	47.1
3783.0	5.94	39.20	0.10	8.2	23.9	40.6
3784.0	109.00	83.50	81.50	15.7	22.8	26.0
3785.0	56.70	58.00	68.80	13.9	20.3	29.0
3786.0	42.80	29.60	5.71	10.9	15.7	38.0
3787.0	104.00	49.40	12.80	13.1	20.0	26.6
3788.0	40.80	42.10	18.40	13.4	21.9	23.5
3789.0	4.79	12.90	0.40	5.7	28.8	33.9
3790.0	280.00	280.00	5.05	12.1	2.6	38.5
3791.0	54.30	51.70	43.40	14.4	27.8	21.2
3792.0	36.40	36.80	24.70	13.6	18.2	30.4
3793.0	31.30	27.50	8.18	8.8	15.6	34.6
3794.0	7.21	4.71	1.41	7.2	27.7	30.5

	Per	meability (M	ND)		Saturation			
Depth	Porosity	Maximum	90 Deg	Vertical	Pore Oil	Pore Water		
3717.0	17.90	9512.00	145.00	140.00	20.30	60.00		
3718.0	8.50	3.95	0.80	0.43	30.50	39.80		
3719.0	9.60	454.00	387.00	4167.00	17.20	47.40		
3720.0	14.50	24.50	22.90	20.50	28.00	36.00		
3721.0	11.30	3.91	3.37	3.90	23.10	37.20		
3722.0	4.60	0.21	0.21	0.05	23.50	61.10		
3723.0	4.90	1036.00	500.00	134.00	9.80	36.50		
3724.0	7.30	86.10	0.22	132.00	23.30	51.40		
3725.0	9.70	31.50	8.04	9.24	33.90	31.90		
3726.0	13.80	1544.00	680.00	38.90	15.60	34.80		
3727.0	7.10	411.00	109.00	6.13	15.30	37.10		
3728.0	9.20	9578.00	9578.00	15926.00	6.30	29.60		
3729.0	6.40	2517.00	7.01	149.00	21.20	58.80		
3730.0	10.20	1736.00	443.00	501.00	12.10	46.90		
3731.0	9.30	612.00	73.90	297.00	14.30	50.20		
3732.0	2.90	184.00	161.00	15.00	7.70	84.30		
3733.0	3.90	3.84	2.76	0.29	10.90	58.90		
3734.0	4.30	38.40	35.90	10.80	10.60	39.40		
3735.0	6.00	112.00	89.80	4.87	14.90	39.80		
3736.0	4.40	0.01	1176.00		8.00	48.10		
3737.0	11.00	713.00	227.00	26.80	12.00	33.00		
3738.0	9.00	7.96	5.55	0.44	12.30	28.20		
3739.0	4.20	0.01	0.01		23.50	39.10		
3740.0	5.80	0.01	0.04		13.30	34.20		
3741.0	6.70	331.00	11.90	0.62	9.70	27.90		
3742.0	6.20	0.01	0.22		30.70	32.30		
3743.0	9.90	18.40	9.07	2.42	17.10	34.20		
3744.0	10.30	0.01	3.51		28.90	33.50		
3745.0	14.30	149.00	101.00	39.50	25.60	32.00		

	Pe	rmeability (N	ND)	Saturation					
Depth	Porosity	Maximum	90 Deg	Vertical	Pore Oil	Pore Water			
3746.0	16.00	174.00	172.00	91.70	28.20	30.70			
3747.0	6.20	17.40	15.30	0.18	26.10	40.60			
3748.0	3.70	1.69	1.66	0.06	16.00	49.70			
3749.0	7.00	0.26	0.10	0.05	33.00	49.50			
3750.0	5.00	0.02	0.02	0.03	17.60	79.30			
3751.0	5.10	0.12	0.04	0.03	2.50	84.50			
3752.0	4.60	0.07	0.05	0.01	8.80	74.50			
3753.0	14.00	244.00	232.00	84.40	33.00	31.90			
3754.0	4.40	0.25	0.07	0.01	6.40	83.80			
3755.0	9.90	0.05	0.02	0.03	7.40	67.80			
3756.0	10.10	1.46	0.47	0.10	4.40	74.90			
3757.0	7.70	0.01	0.01	0.05	11.00	78.00			
3758.0	11.40	13.90	13.00	3.17	23.80	34			
3759.0	12.80	29.70	29.10	8.57	14.70	31.60			
3760.0	15.10	58.90	56.30	65.60	30.50	28.30			
3761.0	13.90	86.30	83.60	30.30	24.80	39.70			
3762.0	13.40	17.20	15.80	7.49	27.50	22.90			
3763.0	9.40	4.82	3.55	0.46	35.80	39.80			
3764.0	7.60	8.74	7.09	0.09	21.00	52.40			
3765.0	8.90	3.45	1.28	1.60	35.80	31.80			
3766.0	6.80	0.15	0.07	0.03	37.00	51.40			
3767.0	6.70	0.43	0.37	0.01	36.10	41.20			
3768.0	9.00	0.08	0.07	0.01	15.40	61.70			
3769.0	13.10	5.38	3.76	2.19	9.10	48.20			
3770.0	15.50	7.71	7.16	1.54	32.30	30.00			
3771.0	12.90	16.60	16.20	7.23	31.80	26.70			
3772.0	11.90	15.60	11.10	10.10	29.50	28.10			
3773.0	9.30	0.15	0.07	0.07	8.20	66.00			
3774.0	8.70	13.80	6.13	4.19	19.00	67.00			



### SPE 122921

### Estimates of Potential CO<sub>2</sub> Demand for CO<sub>2</sub> EOR in Wyoming Basins

S. Wo, SPE, L.D. Whitman, SPE, and J.R. Steidtmann, Enhanced Oil Recovery Institute, University of Wyoming

#### Copyright 2009, Society of Petroleum Engineers

This paper was prepared for presentation at the 2009 SPE Rocky Mountain Petroleum Technology Conference held in Denver, Colorado, USA, 14-16 April 2009.

This paper was selected for presentation by an SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of SPE copyright.

#### Abstract

A database of Wyoming oil reservoirs is developed to identify candidate reservoirs suitable for miscible or immiscible  $CO_2$  flooding, a method that has already proven to be a viable enhanced oil recovery process at Lost Soldier, Wertz, and Salt Creek fields in Wyoming. Based on the  $CO_2$  usage of existing  $CO_2$ -EOR projects in Wyoming and other regions, the initial and total  $CO_2$  demands are estimated for the identified reservoirs and grouped by basins. The simple formulas presented in this paper provide a quick estimation of the required initial and total  $CO_2$  volumes with specified reservoir parameters. Wyoming has produced about seven billion barrels of oil from more than 1200 oil producing fields. 98% of the oil was produced from the top 400 fields, evaluated in this study, each with a cumulative production exceeding one million barrels of oil. More than 500 oil reservoirs, by passing either miscible or immiscible screening criteria, are identified as potential  $CO_2$ -EOR candidates. Large fields often have multiple oil producing reservoirs suitable for  $CO_2$  flooding. It is estimated that 1.2 to 1.8 billion barrels of additional oil might be recovered by  $CO_2$  flooding and up to 20 trillion cubic feet of  $CO_2$  could be sequestrated after  $CO_2$  EOR in Wyoming's oil basins.

#### Introduction

 $CO_2$  flooding has already proven to be a viable enhanced oil recovery process in many geographic locations. Wyoming has significant natural sources of  $CO_2$  in several of its existing gas reservoirs that have relatively high  $CO_2$  concentration in their natural gases (De Bruin, 2001; Nummdeal et al., 2003). ExxonMobil operates one of the world's largest  $CO_2$ -producing fields at the La Barge anticline in southwestern Wyoming. Five Wyoming fields are currently under  $CO_2$  flooding using the  $CO_2$  supplied by a  $CO_2$  pipeline network that originates at ExxonMobile's gas plant at Shute Creek (Figure 1). Amoco initiated Lost Soldier and Wertz  $CO_2$  miscible floods in late 1980s. The two fields were purchased by Merit Energy Company in 1999 and are still under  $CO_2$  Injection. In 2003, Anadarko constructed a 125-mile pipeline to transport La Barge  $CO_2$  for its EOR project at the Salt Creek field in the Powder River basin and, in the same year, completed another 33-mile pipeline spur to supply  $CO_2$  to flood the Monell Unit at the Patrick Draw field in the Greater Green River basin. The Beaver Creek  $CO_2$  flood, operated by DevonEnergy Corp, is the newest addition to Wyoming's  $CO_2$ -EOR portfolio. The field is located on the west flank of the Wind River basin and has been under  $CO_2$  injection since July 2008. A newly constructed 45-mile pipeline brings the  $CO_2$  from the Bairoil station near Jeffrey City to the Beaver Creek field. The increment oil produced from those  $CO_2$  floods has been substantial. The cumulative oil by  $CO_2$  EOR from the Tensleep reservoir at Lost Soldier alone is more than 22 million barrels of oil (MMBO), or 11% of the estimated original oil-in-place (OOIP). By May 2008,  $CO_2$  flooding has already produced 5.5 MMBO at Salt Creek and 3 MMBO at Monell Unit (Gaines, 2008).

The success of the  $CO_2$  floods has drawn a special interest in Wyoming. Many  $CO_2$ -EOR projects are currently under evaluation or in planning. However, the biggest challenge for many small producers is access to  $CO_2$  at an affordable price. With Wyoming's vast coal reserves and an increasing concern over climate change, new coal-fired power plants and coal-to-liquids plants are being designed to have  $CO_2$  capture capability. The captured  $CO_2$  will provide Wyoming oil producers additional  $CO_2$  sources for their  $CO_2$ -EOR projects. The purpose of this study is two-fold: first, to screen for Wyoming oil reservoirs that are technically suitable for  $CO_2$  flooding and second, to provide a method that quickly estimates the potential  $CO_2$  demand for  $CO_2$ -EOR candidate reservoirs. The resulting database and  $CO_2$  demand estimation should be useful for  $CO_2$  suppliers to foresee the market volume for  $CO_2$  EOR in Wyoming basins.

 $CO_2$  EOR has been tested and developed for more than four decades. It becomes a mature technology as demonstrated by more than 80 projects worldwide. Sequestration of  $CO_2$  in partially depleted oil reservoirs is an attractive option, not only because of the economic benefit from EOR, but also because of the availability of reservoir data and infrastructure that can be utilized to facilitate  $CO_2$  storage projects.

Page 18 of 30

### Screening of CO<sub>2</sub>-EOR Candidate Reservoirs

The primary objective of  $CO_2$  EOR is to remobilize and dramatically reduce the post waterflooding residual oil saturation in reservoir pore space. Miscibility between reservoir oils and injected  $CO_2$  usually develops through a dynamic process of mixing, with component exchange controlled by phase equilibria and local compositional variation along the path of displacement.  $CO_2$  is not miscible on the first contact with reservoir oils. However, with a sufficient high pressure,  $CO_2$  could achieve dynamic miscibility with reservoir oils in a multiple contact process. During this multiple contact process,  $CO_2$  will vaporize the lighter oil fractions into the injected  $CO_2$  phase and  $CO_2$  will condense into the reservoir's oil phase. This leads to two reservoir fluids that become miscible (mixing in all parts), with favorable properties of low viscosity, a mobile fluid and low interfacial tension (Stalk, 1984). As long as a minimum miscibility pressure (MMP) can be achieved in a reservoir,  $CO_2$  flooding should result in an oil recovery greater than 90% OOIP in the swept region (Taber et al., 1997). The slim tube test has been used for decades as a common method for determining MMP. Where no measured MMP is available, MMP is often estimated from empirical correlations, such as the Cronquist correlation, based on reservoir temperature and the molecular weight (MW) of the pentanes and heavier fractions of the reservoir oil.

When reservoir pressure is insufficient or reservoir oil composition is less favorable (heavier), the injected  $CO_2$  is immiscible with reservoir oil. However, the interactions between injected  $CO_2$  and reservoir oil can still remobilize some of the residual oil from waterflooding. The main mechanisms involved in immiscible  $CO_2$  flooding are: (1) oil phase swelling, as the oil becomes saturated with  $CO_2$ ; (2) viscosity reduction of the swollen oil and  $CO_2$  mixture; (3) extraction of lighter hydrocarbon into the  $CO_2$  phase; and, (4) fluid drive plus pressure (Mungan, 1981; Jarrel, 2002). This combination of mechanisms enables a portion of the reservoir's remaining oil to be mobilized and produced. In general, immiscible  $CO_2$ EOR is less efficient than miscible  $CO_2$  EOR in recovering the remaining oil after waterflooding.

By the end of 2008, Wyoming had produced more than 7.1 billion barrels of oil from 1,237 oil producing fields. However, production from many of the fields is small with a few oil producing wells. About 98% of the total oil was produced from the top 400 fields that have a cumulative production exceeding one million barrels of oil (MMBO). For identifying candidate reservoirs suitable for miscible or immiscible  $CO_2$  flooding, a database of Wyoming oil reservoirs was developed, which includes the production data from Wyoming Oil and Gas Conservation Commission (WOGCC), measurements of 901 Wyoming oil samples from the DOE\_coa database and other reservoir parameters digitized from the Wyoming Geological Association (WGA) publications.

A number of screening criteria to identify candidate reservoirs for  $CO_2$  EOR can be found in publications such as Stalkup (1984), Diaz et al. (1996) and Taber et al. (1997). Oil viscosity and API gravity as well as reservoir depth and temperature are commonly used as the key screening parameters. In addition, a good waterflood response, and sufficient porosity (> 7%) and permeability (> 10 md) are also required for a successful  $CO_2$  flood. Because the purpose of this study is to assess the potential  $CO_2$  demand for reservoirs that are technically suitable for  $CO_2$  flooding, economic factors such as oil price and distance to  $CO_2$  source are not included in the screening. Only the top 400 fields were evaluated in this study to exclude fields with a cumulative oil production less than one MMBO. There are 1,368 reservoirs from the top 400 fields generated as the initial pool for screening. 528 reservoirs pass the minimum depth cut off (>1,800 ft), oil gravity cut off (>13 °API), and cumulative production cut off (> 1 MMBO) as  $CO_2$ -EOR candidate reservoirs. Figure 2 shows the number of candidate reservoirs, in the inserted table, and their cumulative oil productions grouped by basins. Lost Soldier and Wertz fields are already in their final phase of  $CO_2$  flooding operation and, therefore, are not included in the screening. The candidate reservoirs are further screened into two groups: miscible and immiscible, based on the following screening criteria.

#### Screening criteria for miscible CO2 flooding

- Sandstone or carbonate reservoir only
- Porosity porosity > 7% and permeability > 10 md
- Oil gravity > 22 °API
- Reservoir depth > 2,500 ft
- Oil viscosity < 10 cp, at reservoir condition
- Cumulative oil production > 1 MMBO

#### Screening criteria for immiscible CO2 flooding

- Sandstone or carbonate reservoir only
- Porosity porosity > 7% and permeability > 10 md
- 13 °API  $\leq$  oil gravity  $\leq$  22 °API
- 1,800 ft  $\leq$  reservoir depth  $\leq$  2,500 ft
- 10 cp  $\leq$  oil viscosity  $\leq$  600 cp, at reservoir condition
- Cumulative oil production > 1 MMBO

#### SPE 122921

The miscibility between reservoir oil and injected  $CO_2$  is a complex process as discussed above. Because of higher reservoir temperature or unfavorable oil composition, a miscible flooding may not be achieved in a reservoir even thought it passes the miscible flooding criteria. Thus, the proposed criteria for miscible  $CO_2$  flooding should be regarded as potentially miscible criteria. As shown in Figures 2 and 3, most of the candidate reservoirs are located within Wyoming's four large oil producing basins: Power River, Bighorn, Wind River and Greater Green River basins. More than half of the total candidate reservoirs are in the Power River basin, which consists of 124 relatively small Minnelusa reservoirs. Large candidate reservoirs are more concentrated in the Bighorn basin, mostly Tensleep, Phosphoria and Madison reservoirs. Tables 1 and 2 list the major reservoirs identified from screening as potentially miscible and immiscible  $CO_2$ -EOR candidates, respectively.

#### Estimation of Total and Initial CO<sub>2</sub> Demand

In many  $CO_2$  flooding projects,  $CO_2$  is injected alternately with water, such as the Lost Soldier and Wertz  $CO_2$  miscible floods in Wyoming. The concept of using  $CO_2$ -WAG (water alternating gas) injection technique is to improve injection profile and reduce gas channeling. The performance of  $CO_2$ -WAG floods from a similar formation may likely be scaled into one dimensionless curve of incremental oil, as a percentage of hydrocarbon pore volume (HCPV), versus injected WAG volume in HCPV. The dimensionless curve obtained from the  $CO_2$ -WAG flood in the Tensleep reservoir of Lost Soldier is shown in Figure 4 and is compared with the typical dimensionless curve from the  $CO_2$ -WAG floods scheme, the dimensionless curve method could provide a quick assessment of potential oil recovery as well as required  $CO_2$  injection volume. In this study, estimation of  $CO_2$  demand is based on the performance of existing  $CO_2$ -WAG floods. For reservoirs with large dip angles or high concentration of vertical fractures, gravity stable  $CO_2$  injection could be a more effective flood scheme, which is discussed in the next section.

#### Estimation of total CO<sub>2</sub> demand for a CO<sub>2</sub>-WAG flood

The duration of a  $CO_2$  flood project usually lasts for a few decades and the majority of the injected  $CO_2$  is produced and re-injected. As given in Eq. 1, the estimated total  $CO_2$  demand only takes account of the net  $CO_2$  volume that needs to be purchased.

$$T_{CO2} = \frac{(1 - \omega_{CO2}) \times C_{WAG} \times H_{WAG} \times B_o \times OOIP}{B_{CO2}}$$
(1)

where  $B_o$  and  $B_{CO2}$  are the oil and CO<sub>2</sub> formation factors, respectively.  $\omega_{CO2}$  represents the average fraction of the injected CO<sub>2</sub> that is produced and re-injected. The CO<sub>2</sub> volume fraction in WAG,  $C_{WAG}$ , is calculated at reservoir condition.  $H_{WAG}$  is the injected total WAG volume in HCPV and  $T_{CO2}$  is the estimated total CO<sub>2</sub> volume in MCF. For the CO<sub>2</sub>-EOR candidate reservoirs in Wyoming basins, a 70% CO<sub>2</sub> re-injection rate, 1:1 WAG ratio and a total WAG injection of 2.5 HCPV are assumed in this evaluation. Consequently, Eq. 1 is further simplified as

$$T_{CO2} = \frac{0.3 \times 0.5 \times 2.5 \times B_o \times OOIP}{B_{CO2}}$$
(2)

Trustworthy OOIP data of Wyoming oil reservoirs are rarely available. Traditionally, volumetric calculation or decline curve analysis is used in the estimation of OOIP but it is difficult to verify the consistency of the methods used in previous estimations, especially if a large number of reservoirs are concerned. In this evaluation, OOIP is estimated from reservoir cumulative production and recovery factor. Most of Wyoming oil reservoirs have been under water-drive production for decades. Many of the reservoirs are naturally fractured and their recovery efficiency can vary substantially depending on reservoir properties and engineering practice. Therefore, instead of assuming one average recovery factor, a low recovery factor of 30% and a high recovery factor of 45% are both used to provide a range of estimated OOIP.

 $CO_2$  formation factor,  $B_{CO2}$ , is determined by reservoir pressure and temperature according to the data table provided by Jarrell et al. (2002). For reservoir pressure or temperature that is not included in the table,  $B_{CO2}$  is estimated by linear interpolation from the four nearest formation factors that are available in the table. The estimated  $CO_2$  demands for miscible and immiscible  $CO_2$  EOR in Wyoming basins are summarized in Figures 5 and 6, respectively. In combination, the estimated total  $CO_2$  demand ranges from 6.1 to 9.2 TCF in Power River, 4.8 to 7.2 TCF in Bighorn, 1.2 to 1.8 TCF in Wind River, 1 to 1.4 TCF in Greater Green River, 0.68 to 1.02 TCF in Overthrust Belt, 0.09 to 0.13 TCF in Laramie, and 0.08 to 0.12 TCF in Denver-Cheyenne basins.

#### Estimation of initial CO<sub>2</sub> demand for a CO<sub>2</sub>-WAG flood

Reservoir injectivity is another key factor for a successful  $CO_2$  flood. An annual WAG injection between 5% and 10% HCPV is typically required in the design of a field flood project. Higher volume injections, 10-15% HCPV per year, have been observed in projects with good flooding performance. A  $CO_2$  flood project may be economically unviable under

Page 20 of 30

very low annual injection volume, i.e. less than 4% HCPV per year. In the initial phase of a WAG flood, no  $CO_2$  will be produced until the breakthrough of  $CO_2$  at the production wells and the injected  $CO_2$  needs to be fully supplied from external sources. The initial  $CO_2$  demand can be estimated from Eq. 3.

$$I_{CO2} = \frac{C_{WAG} \times I_{WAG} \times B_o \times OOIP}{365 \times B_{CO2}}$$
(3)

where  $I_{WAG}$  is the annual WAG injection volume in HCPV and  $I_{CO2}$  is the estimated daily CO<sub>2</sub> injection rate in MCF/day. In this evaluation, a 1:1 WAG ratio and an annual WAG injection of 10% HCPV are used in the estimation of initial CO<sub>2</sub> demand (Eq. 4).

$$I_{CO2} = \frac{0.5 \times 0.1 \times B_o \times OOIP}{365 \times B_{CO2}}$$
(4)

The estimated  $CO_2$  demand for the top 100 reservoirs identified as miscible  $CO_2$ -EOR candidates is given in Table 1, along with reservoir depth and oil API gravity. A similar table of the top 20 reservoirs of immiscible  $CO_2$ -EOR candidates is given in Table 2.

#### **Results and Discussion**

Large fields usually have multiple oil producing reservoirs that are suitable for  $CO_2$  flooding. Because the  $CO_2$  demand is ranked by reservoir, not by field, the estimated volumes in Tables 1 and 2 may not reflect the total  $CO_2$  demand of a field if some of its small reservoirs are not included in the tables. Many existing  $CO_2$ -EOR projects have been developed by phases, often starting with small scale patterns of pilot flooding. Notice that the estimation of initial  $CO_2$  demand in this study is calculated under the assumption of a full reservoir flooding.

As indicated from the dimensionless curves (Figure 4), the miscible  $CO_2$  flooding has recovered about 11% of OOIP from the Tensleep reservoir at the Lost Soldier field and much higher recoverys have been observed from the  $CO_2$  floods in the San Andres reservoirs of west Texas. The recovery factor from immiscible  $CO_2$  floods is generally lower than miscible floods depending on actual oil and reservoir conditions. By assuming an average recovery factor of 10% OOIP for miscible  $CO_2$  floods and 6.5% for immiscible  $CO_2$  floods, it is estimated that 1.21 to 1.81 billion barrels of additional oil might be recovered from  $CO_2$  EOR in Wyoming, in which the recovery from miscible floods accounts for 79% of the total incremental oil.

The estimation of total and initial  $CO_2$  demand, i.e. Eq. 1 and Eq. 3, is essentially based on the  $CO_2$  usage of existing  $CO_2$ -WAG floods. However, for reservoirs with large dip angles or high concentration of vertical fractures, gravity segregation of injected  $CO_2$  and water might leave a large volume of remaining oil uncontacted with injected  $CO_2$  and, consequently, reduce the overall WAG flooding efficiency. For such reservoirs, continuous  $CO_2$  injection at the top of reservoir structure, i.e. gravity stable  $CO_2$  injection, could be more effective than WAG flooding, especially for projects designed for the dual-purpose of  $CO_2$  EOR and  $CO_2$  storage (Wood et al., 2006). Gravity stable  $CO_2$  injection usually requires considerably more  $CO_2$  than WAG injection. For example, the estimated total  $CO_2$  demand for a WAG flood in the Muddy reservoir of Grieve field is between 77 and 116 BCF of  $CO_2$ . By comparison, the  $CO_2$  required for gravity stable  $CO_2$  flooding in the same reservoir is estimated to be in the 119 to 188 BCF range depending on the operation duration and  $CO_2$  injection rate (Wo et al., 2008).

#### Conclusions

Wyoming has a large number of oil reservoirs in the Powder River, Bighorn, Wind River, and Greater Green River basins where  $CO_2$ -based EOR is technically feasible. The state is in a unique position to couple the environmental benefits of  $CO_2$  sequestration in mature oil reservoirs with the economic offset through enhanced oil recovery. The main outcomes from this study are listed below:

- 1. A database of Wyoming oil reservoirs is developed to screen candidate reservoirs suitable for miscible or immiscible CO<sub>2</sub> flooding. 379 reservoirs pass the screening criteria for miscible CO<sub>2</sub> flooding, while 138 reservoirs are identified as potential candidates for immiscible CO<sub>2</sub> flooding.
- 2. Based on the  $CO_2$  usage of existing  $CO_2$ -EOR projects in Wyoming and other regions, simple formulas are provided for allowing a quick estimation of the required initial and total  $CO_2$  volumes for a candidate reservoir.
- 3. The estimated total CO<sub>2</sub> demand for CO<sub>2</sub> EOR ranges from 6.1 to 9.2 TCF in Power River, 4.8 to 7.2 TCF in Bighorn, 1.2 to 1.8 TCF in Wind River, 1 to 1.4 TCF in Greater Green River, 0.68 to 1.02 TCF in Overthrust Belt, 0.09 to 0.13 TCF in Laramie, and 0.08 to 0.12 TCF in Denver-Cheyenne basins.
- 4. It is estimated that 1.2 to 1.8 billion barrels of additional oil could be recovered by CO<sub>2</sub> flooding and up to 20 trillion

SPE 122921

Downloaded from http://onepetro.org/SPERMPTC/proceedings-pdf/09RMPC/AIL-09RMPC/SPE-122921-MS/2719749/spe-122921-ms.pdf/1 by Kimberty Gordon on 06 August 2022

cubic feet of CO<sub>2</sub> could be sequestrated after CO<sub>2</sub> EOR in Wyoming's oil basins.

### Acknowledgements

We thank Wyoming Oil and Gas Conservation Commission for providing field and reservoir production data, Kera Presenkowski and Matthew Johnson for help on data editing. This work was supported by the Enhanced Oil Recovery Institute of the University of Wyoming.

### Nomenclature

- $B_{CO2}$  = CO<sub>2</sub> formation factor
- BO = barrel of oil
- $B_o$  = oil formation factor
- $C_{WAG}$  = fraction of CO<sub>2</sub> volume in total WAG volume
- BCF = billion standard cubic feet
- EOR = enhance oil recovery
- HCPV = hydrocarbon pore volume
- $H_{WAG}$  = total WAG injection volume, HCPV
- $I_{CO2}$  = initial daily CO<sub>2</sub> demand, MCF/day
- $I_{WAG}$  = annual WAG injection volume, HCPV/year
- MMP = minimum miscibility pressure
- MMBO = million barrels of oil
- MCF = thousand standard cubic feet
- OOIP = original oil in place
- TCF = trillion standard cubic feet
- $T_{CO2}$  = total CO<sub>2</sub> demand, MCF
- WAG = water alternating gas
- WGA = Wyoming Geological Association
- WOGCC = Wyoming Oil and Gas Conservation Commission
- $\omega_{CO2}$  = fraction of recycled CO<sub>2</sub> in total injected CO<sub>2</sub>

### References

De Bruin, R.H.: "Carbon Dioxide in Wyoming," Information Pamphlet 8, Wyoming Geological Survey, 2001.

- Diaz, D., Bassiouni, Z., Kimbrell, W. and Wolcott, J.: "Screening Criteria for Application of Carbon Dioxide Miscible Displacement in Waterflooded Reservoirs Containing Light Oil," SPE 35431, presented at the 1996 SPE Symposium on Improved Oil Recovery, Tulsa, OK, April 21-24.
- Gaines, J.: "Monell Unit CO<sub>2</sub> Flood, Patrick Draw Field, Sweetwater County, Wyoming," presentation, May 2008.

Jarrell, P.M., Fox, C.E., Stein, M.H. and Webb, S.L.: "Practical Aspects of CO2 Flooding," SPE Monographs, vol. 22, 2002.

- Mungan, N.: "Carbon Dioxide Flooding Fundamentals", J. Cdn. Pet. Tech. (Jan March 1981), 87-92.
- Nummedal, D., Towler, B., Mason, C. and Allen, M.: "Enhanced Oil Recovery in Wyoming-Prospects and Challenges," report prepared for Governor Dave Freudenthal, University of Wyoming, June 2003.
- Stalk, F.I. Jr.: "Miscible Displacement," SPE of AIME, Monograph, vol. 8, 1984.
- Taber, J.J., Martin, D., and Seright, R.S.: "EOR Screening Criteria Revisited-Part 1: Introduction to Screening Criteria and Enhanced Recovery Field Projects," SPE Reservoir Engineering, August 1997, pp 189-198.
- Wo, S., Yin, P., Blakeney-DeJarnett B. and Mullen, C.: "Simulation Evaluation of Gravity Stable CO<sub>2</sub> Flooding in the Muddy Reservoir at Grieve Field, Wyoming", SPE 113482, presented at the 2008 SPE Improved Oil Recovery Symposium held in Tulsa, Oklahoma, April 19-23, 2008.
- Wood, D.J., Lake, L.W.SPE, and Johns, R.T.: "A Screening Model for CO<sub>2</sub> Flooding and Storage in Gulf Coast Reservoirs Based on Dimensionless Groups," SPE 100021, 2006.

Wyoming Oil and Gas Conservation Commission, http://wogcc.state.wy.us/

6



Figure 1. Wyoming basin map with existing CO<sub>2</sub> pipelines and CO<sub>2</sub> flooding fields



Figure 2. Number of CO<sub>2</sub>-EOR candidate reservoirs and their cumulative oil productions by Wyoming basins



Figure 3. Number of miscible and immiscible CO2-EOR candidate reservoirs by Wyoming basins



Figure 4. Dimensionless curves of incremental oil versus total WAG injection

8



Figure 5. Estimated potential CO<sub>2</sub> demand for miscible CO<sub>2</sub> floods in Wyoming basins



Figure 6. Estimated potential CO<sub>2</sub> demand for immiscible CO<sub>2</sub> floods in Wyoming basins

Downloaded from http://onepetro.org/SPERMPTC/proceedings-pdf/09RMPC/All-09RMPC/SPE-122921-MS/2719749(spe-122921-ms.pdf/1 by Kimberly Gordon on 06 August 2024

### Table 1. Top 100 ranked reservoires for potentially miscible CO<sub>2</sub> flooding in Wyoming

Rank	Field name	Reservoir Name	Reservoir Depth ft	Oil Gravity API	Est. Total CO2 BCF	Est. Initial CO2 MMCF/D	Basin Name
1	HARTZOG DRAW	SHANNON	9485	36	564 - 846	206 - 309	POWDER RIVER
2	ELK BASIN	MADISON	5156	27.3	520 - 780	190 - 285	BIGHORN
3	ELK BASIN	EMBAR-TENSLEEP	4490	30	403 - 605	147 - 221	BIGHORN
4	PAINTER RESERVOIR EAST	NUGGET	10774	55	269 - 404	98 - 147	OVERTHRUST BELT
5	HILIGHT	MUDDY	9680	41.3	248 - 373	90 - 136	POWDER RIVER
6	BYRON	TENSLEEP	5425	25.2	244 - 366	89 - 133	BIGHORN
7	HAMILTON DOME	TENSLEEP	2863	23.8	233 - 350	85 - 128	BIGHORN
8	LANCE CREEK	LEO	5557	44.1	226 - 339	82 - 124	POWDER RIVER
9	STEAMBOAT BUTTE	TENSLEEP	6830	28.7	219 - 329	80 - 120	WIND RIVER
10	FRANNIE	PHOSPHORIA- TENSLEEP	2574	28.3	209 - 314	76 - 115	BIGHORN
11	GRASS CREEK	TENSLEEP	3632	24.5	192 - 288	70 - 105	BIGHORN
12	ARCH	ALMOND	5067	43.4	168 - 252	61 - 92	GREATER GREEN RIVER
13	OREGON BASIN	TENSLEEP	3850	23	159 - 238	58 - 87	BIGHORN
14	BRADY	WEBER	12082	54.7	155 - 232	56 - 85	GREATER GREEN RIVER
15	COTTONWOOD CREEK	PHOSPHORIA	7270	28.6	152 - 228	55 - 83	BIGHORN
16	PAINTER RESERVOIR	NUGGET	9958	46	147 - 221	53 - 80	OVERTHRUST BELT
17	GLENROCK SOUTH	ДАКОТА	6090	34.4	136 - 204	49 - 74	POWDER RIVER
18	HOUSE CREEK	SUSSEX	8238	48.8	123 - 185	45 - 67	POWDER RIVER
19	BRADY	NUGGET	9876	50.5	122 - 183	44 - 67	GREATER GREEN RIVER
20	SUSSEX	TENSLEEP-AMSDEN	5894	33	120 - 181	44 - 66	POWDER RIVER
21	BEAVER CREEK	MADISON	10666	40.5	117 - 176	42 - 64	WIND RIVER
22	BIG SAND DRAW	TENSLEEP	6606	33.6	116 - 174	42 - 63	WIND RIVER
23	SALT CREEK	TENSLEEP	3908	28.2	100 - 150	36 - 54	POWDER RIVER
24	WELL DRAW	ΤΕΑΡΟΤ	7048	42.5	91 - 137	33 - 50	POWDER RIVER
25	STEAMBOAT BUTTE	PHOSPHORIA- TENSLEEP	6000	28.2	91 - 136	33 - 49	WIND RIVER
26	WINKLEMAN	TENSLEEP	2915	25	83 - 124	30 - 45	WIND RIVER
27	POWELL	FRONTIER	11943	48.2	79 - 119	29 - 43	POWDER RIVER
28	BYRON	EMBAR-TENSLEEP	5238	24.5	79 - 119	29 - 43	BIGHORN
29	GRIEVE	MUDDY	6723	38.2	77 - 116	28 - 42	WIND RIVER
30	WINKLEMAN	PHOSPHORIA	2600	25.7	74 - 111	27 - 40	WIND RIVER
31	GAS DRAW	MUDDY	7191	37.39	71 - 107	26 - 39	POWDER RIVER
32	BIG MUDDY	DAKOTA	4298	36.8	70 - 106	25 - 38	POWDER RIVER
33	GRASS CREEK	PHOSPHORIA	3632	24.5	68 - 102	24 - 37	BIGHORN
34	КІТТҮ	MUDDY	9201	42	68 - 102	24 - 37	POWDER RIVER
35	GRASS CREEK	CURTIS	3717	24.3	66 - 100	24 - 36	BIGHORN

10

### Table 1 (continued). Top 100 ranked reservoires for potentially miscible CO<sub>2</sub> flooding in Wyoming

Rank	Field name	Reservoir Name	Reservoir Depth ft	Oil Gravity API	Est. Total CO2 BCF	Est. Initial CO2 MMCF/D	Basin Name
36	SAND DUNES	MUDDY	12600	42	65 - 97	23 - 35	POWDER RIVER
37	STEAMBOAT BUTTE	NUGGET	4164	38.5	61 - 92	22 - 33	WIND RIVER
38	DRY PINEY	NUGGET	10988	52	59 - 89	21 - 32	OVERTHRUST BELT
39	BEAVER CREEK	TENSLEEP	10442	45	59 - 89	21 - 32	WIND RIVER
	WHITNEY CANYON-						
40	CARTER CREEK	MADISON	11790	49.4	59 - 88	21 - 32	OVERTHRUST BELT
41	COYOTE CREEK	DAKOTA	6400	41	55 - 83	20 - 30	POWDER RIVER
42	GARLAND	TENSLEEP	4267	23	54 - 81	19 - 29	BIGHORN
43	RYCKMAN CREEK	NUGGET	5800	47.2	52 - 78	19 - 28	OVERTHRUST BELT
44	ROZET	MINNELUSA	8156	34	50 - 75	18 - 27	POWDER RIVER
45	SALT CREEK	SUNDANCE-3	3000	35	49 - 73	17 - 26	POWDER RIVER
46	STEAMBOAT BUTTE	PHOSPHORIA	6732	31.1	48 - 72	17 - 26	WIND RIVER
47	RENO	MINNELUSA	15006	36.5	48 - 72	17 - 26	POWDER RIVER
48	TIMBER CREEK	MINNELUSA	9360	25	47 - 71	17 - 25	POWDER RIVER
49	MEADOW CREEK	TENSLEEP	9060	29.7	46 - 70	17 - 25	POWDER RIVER
50	BIRCH CREEK	BEAR RIVER 7500	7512	46	44 - 67	16 - 24	GREATER GREEN RIVER
51	SCOTT	PARKMAN	6102	37	44 - 66	16 - 24	POWDER RIVER
52	LANCE CREEK	CONVERSE	4394	41.5	42 - 64	15 - 23	POWDER RIVER
53	DILLINGER RANCH	MINNELUSA	9132	37	42 - 63	15 - 23	POWDER RIVER
54	SUSSEX WEST	SHANNON	2914	39.6	41 - 61	15 - 22	POWDER RIVER
55	LUCKEY DITCH	DAKOTA	14400	43	41 - 61	14 - 22	GREATER GREEN RIVER
56	BLACK MOUNTAIN	TENSLEEP	3125	24.9	39 - 59	14 - 21	BIGHORN
57	RAVEN CREEK	MINNELUSA	8354	33.4	39 - 58	14 - 21	POWDER RIVER
58	BIG MUDDY	WALL CREEK	3069	35.6	39 - 58	14 - 21	POWDER RIVER
59	COLE CREEK	DAKOTA	7947	37	37 - 56	13 - 20	POWDER RIVER
60	MIKES DRAW	ТЕАРОТ	7264	39	37 - 56	13 - 20	POWDER RIVER
61	WHITNEY CANYON- CARTER CREEK	MISSION CANYON	14226	49.4	35 - 53	13 - 19	OVERTHRUST BELT
62	HALVERSON	MINNELUSA	8489	24	35 - 53	12 - 19	POWDER RIVER
63	FINN-SHURLEY	TURNER	4886	38	35 - 52	12 - 19	POWDER RIVER
64	RECLUSE	MUDDY	7530	42.1	35 - 52	12 - 19	POWDER RIVER
65	STEWART	MINNELUSA	8024	22.5	34 - 52	12 - 19	POWDER RIVER
66	GEBO	EMBAR-TENSLEEP	4735	24.9	34 - 51	12 - 18	BIGHORN
67	SAGE SPRING CREEK	ДАКОТА	7590	39.4	34 - 51	12 - 18	POWDER RIVER
68	ELK BASIN SOUTH	EMBAR-TENSLEEP	6846	28	33 - 50	12 - 18	BIGHORN
69	GARLAND	PHOSPHORIA	3060	24.3	33 - 49	12 - 18	BIGHORN
70	COLE CREEK SOUTH	DAKOTA	8309	35.4	32 - 49	11 - 17	POWDER RIVER

### Table 1 (continued). Top 100 ranked reservoires for potentially miscible CO<sub>2</sub> flooding in Wyoming

Rank	Field name	Reservoir Name	Reservoir Depth ft	Oil Gravity API	Est. Total CO2 BCF	Est. Initial CO2 MMCF/D	Basin Name
71	PINE TREE	SHANNON	11720	38	31 - 47	11 - 17	POWDER RIVER
72	SLATTERY	MINNELUSA	6242	30	30 - 45	11 - 16	POWDER RIVER
73	SPRINGEN RANCH	MUDDY	7671	40.4	29 - 43	10 - 16	POWDER RIVER
74	WORLAND	TENSLEEP	9650	24.2	28 - 43	10 - 15	BIGHORN
75	ELK BASIN	BIG HORN	5460	23.3	28 - 42	10 - 15	BIGHORN
76	PATRICK DRAW	ALMOND	5067	43.4	27 - 41	10 - 15	GREATER GREEN RIVER
77	STANDARD DRAW	MESAVERDE	8968	59	27 - 40	9 - 14	RIVER
78	SANDBAR EAST	MINNELUSA	7034	23	27 - 40	9 - 14	POWDER RIVER
79	REEL	MINNELUSA	8429	33	26 - 40	9 - 14	POWDER RIVER
80	NOTCHES	TENSLEEP	2865	22.5	26 - 39	9 - 14	WIND RIVER
81	GARLAND	EMBAR	3060	24	26 - 39	9 - 14	BIGHORN
82	SILO	NIOBRARA	8402	35	26 - 39	9 - 14	DENVER-CHEYENNE
83	POWELL	DAKOTA	12955	46	25 - 38	9 - 14	POWDER RIVER
84	GOLDEN EAGLE	PHOSPHORIA	8890	48.8	25 - 38	9 - 14	BIGHORN
85	SKULL CREEK	NEWCASTLE	3170	34	25 - 37	9 - 13	POWDER RIVER
86	POWNALL RANCH	MINNELUSA	6222	259	24 - 37	9 - 13	POWDER RIVER
87	ROCK RIVER	MUDDY-DAKOTA- LAKOTA	2581	37	24 - 36	8 - 13	LARAMIE
88	POISON SPIDER WEST	CODY	10145	45	24 - 36	8 - 13	WIND RIVER
89	LITTLE MITCHELL CREEK	MINNELUSA	7330	26	24 - 36	8 - 13	POWDER RIVER
90	UTE	MUDDY	6382	41.1	23 - 35	8 - 13	POWDER RIVER
91	HENRY	ДАКОТА	13393	52	23 - 35	8 - 12	GREATER GREEN RIVER
92	BONE PILE	MINNELUSA	8528	31.5	22 - 34	8 - 12	POWDER RIVER
93	ROZET	MUDDY	6935	35.4	22 - 33	8 - 12	POWDER RIVER
94	BIG SAND DRAW	PHOSPHORIA	6850	62.1	22 - 33	8 - 12	WIND RIVER
95	DONKEY CREEK	MINNELUSA	7845	27.7	22 - 33	8 - 12	POWDER RIVER
96	КАҮЕ	ТЕАРОТ	5512	39	22 - 33	8 - 12	POWDER RIVER
97	SUSSEX	TENSLEEP	9140	30.2	22 - 33	8 - 12	POWDER RIVER
98	GLENROCK SOUTH	MUDDY	6300	38.6	22 - 33	8 - 12	POWDER RIVER
99	GOOSEBERRY	PHOSPHORIA- TENSLEEP	5668	22.6	22 - 33	8 - 12	BIGHORN
100	HELDT DRAW	SHANNON	9400	35.6	22 - 33	8 - 12	POWDER RIVER

12

Table 2. Top	20 ranked reservo	ires for immiscible CO <sub>2</sub>	flooding in Wyoming

Rank	Field Name	Reservoir Name	Reservoir Depth ft	Oil Gravity API	Est. Total CO2 BCF	Est. Initial CO2 MMCF/D	Basin Name
1	SALT CREEK	WALL CREEK-2	2200	37	852 - 1278	311 - 467	POWDER RIVER
2	OREGON BASIN	EMBAR	3525	21.6	677 - 1016	247 - 371	BIGHORN
3	GARLAND	MADISON	4424	20.5	230 - 345	84 - 126	BIGHORN
4	LITTLE BUFFALO BASIN	TENSLEEP	3348	19.6	137 - 206	50 - 75	BIGHORN
5	LITTLE BUFFALO BASIN	EMBAR	4781	19.6	99 - 149	36 - 54	BIGHORN
6	OREGON BASIN	MADISON	4465	22	93 - 140	34 - 51	BIGHORN
7	HAMILTON DOME	PHOSPHORIA	2400	26	82 - 123	30 - 45	BIGHORN
8	BYRON	EMBAR	5252	19.5	64 - 96	23 - 35	BIGHORN
9	PITCHFORK	TENSLEEP	3463	18.2	57 - 86	20 - 31	BIGHORN
10	NORTH FORK	TENSLEEP	6484	21.5	48 - 72	17 - 26	POWDER RIVER
11	BIRCH CREEK	MESAVERDE-3	1874	46	46 - 69	16 - 25	GREATER GREEN RIVER
12	SALT CREEK	WALL CREEK 1-2	2235	37	29 - 44	10 - 16	POWDER RIVER
13	TORCHLIGHT	MADISON	3550	20.5	28 - 42	10 - 15	BIGHORN
14	SPRING CREEK SOUTH	TENSLEEP	3796	15.3	27 - 40	9 - 14	BIGHORN
15	LITTLE BUFFALO BASIN	EMBAR-TENSLEEP	4781	19.6	26 - 39	9 - 14	BIGHORN
16	ROCKY POINT	MINNELUSA	5592	16.8	25 - 38	9 - 13	POWDER RIVER
17	FOURBEAR	DINWOODY-PHOSPH- TENSLEEP-DARWIN- MADISON	2900	13.5	24 - 37	9 - 13	BIGHORN
18	KUMMERFELD	MINNELUSA	5962	19	22 - 33	8 - 12	POWDER RIVER
19	ROZET WEST	MINNELUSA	8692	21	20 - 30	7 - 11	POWDER RIVER
20	LABARGE	MESAVERDE	1960	45.6	18 - 27	6 - 10	GREATER GREEN RIVER

## Goodnight Fluid Level Data Indicates San Andres Pressure is Increasing



Well Name	Date	SITime	TP	FL FS
Dawson #1	6/13/23	~18-days	-13	960
Dawson #1	12/18/23	~20-min	-13	868
Dawson #1	7/20/24	72-min	-13	894
Dawson #1	4/7/25	132-min	-13	848
Ernie Banks #1	6/13/23	~20-min	-13	961
Ernie Banks #1	12/18/23	~20-min	-13	849
Ernie Banks #1	7/20/24	110-min	-13	860
Ernie Banks #1	4/7/25	97-min	-13	842
Nolan Ryan #1	11/11/22	~20-min	-12	895
Nolan Ryan #1	6/13/23	~20-min	-12	872
Nolan Ryan #1	12/18/23	~20-min	-13	742
Nolan Ryan #1	7/20/24	52-min	-13	781
Nolan Ryan #1	4/7/25	75-min	-12	736
Pedro #1	11/11/22	~20-min	-10	947
Pedro #1	6/13/23	~20-min	-10	943
Pedro #1	12/18/23	~20-min	-12	818
Pedro #1	7/20/24	90-min	-10	826
Pedro #1	4/7/25	80-min	-12	808
Piper #2	11/11/22	~20-min	-10	856
Piper #2	6/13/23	~11-hours	-12	901
Piper #2	12/18/23	~20-min	-13	680
Piper #2	7/20/24	~2 months	-10	1042
Piper #2	4/7/25	~1 month	-11	1042
Ryno 17 #1	4/7/22	~20-min	-9	1069
Ryno 17 #1	11/11/22	~20-min	-10	993
Ryno 17 #1	6/13/23	~20-min	-10	969
Ryno 17 #1	12/18/23	~20-min	-12	849
Ryno 17 #1	7/20/24	95-min	-13	868
Ryno 17 #1	4/7/25	110-min	-13	858
Sosa 17 #2	4/7/22	~20-min	-11	1074
Sosa 17 #2	11/11/22	~20-min	-10	1003
S05a17#2	6/13/23	~20-min	-12	986
S05a17#2	12/18/23	~20-min	-13	897
S05a17#2	7/20/24	126-min	-13	901
Sosa 17 #2	4/7/25	138-Min	-12	898
Scully #1	101022	~20-min	-11	940
Scutty #1	0/13/23	~20-min	-13	903
Scully #1	12/18/23	~20-min	-13	//1
Scully #1	1/20/24	120-min	-11	011
Tod 28#1	4///20	~20-min	-12	000
Ted 28#1	6/12/22	~20-min	-10	020
Ted 28#1	12/18/22	~20-min	-11	849
Ted 28#1	7/20/24	90-min	-10	847
Ted 20 #1	A/7/25	115 min	.12	822
Var 28 #1	4///20	2 days	-12	022
Vaz 28 #1	6/13/22	~3-days	-8	903
Yaz 28 #1	12/18/23	~20-min	-10	798
Yaz 28 #1	7/20/24	90-min	-10	801
Yaz 28 #2	4/7/25	90-min	-12	773

GNM Fluid Levels 4-7-25 xls

8.0 %

30.0 %

## Dr. James Buckwalter Simulation Model – Initial Water Saturation (Model used 35% instead of 30%)

EUNICE MONUMENT SOUTH UNIT

EUNICE MONUMENT SOUTH UNIT EXPANSION

WORKING INTEREST OWNERS' MEETING

**FEBRUARY 27, 1990** 

### EMSU RESERVOIR PARAMETERS 14190 ACRES UNIT AREA 1450 PSI INITIAL RESERVOIR PRESSURE 250 PSI RESERVOIR PRESSURE AT START OF WATERFLOOD 1372 PSI SATURATION PRESSURE SOLUTION GOR 423 SCF/STB CURRENT PRODUCING GOR 4007 SCF/STB RESERVOIR TEMPERATURE 90 DEG F **OIL GRAVITY** 32 DEG API 1.20 RB/STB INITIAL FORMATION VOLUME FACTOR 1.05 RB/STB CURRENT FORMATION VOLUME FACTOR AVERAGE NET PAY 134 FT

AVERAGE POROSITY

INITIAL WATER SATURATION