

From: [Kyle Summers](#)
To: cory.smith@state.nm.us
Cc: [Miller, Greg](#); [Long, Thomas](#); [Cooksey, Nick](#); [Drewry, Scott](#); [Marc Gentry](#)
Subject: Revised Stage 1 Abatement Plans for AP-131
Date: Thursday, May 23, 2019 12:01:54 PM
Attachments: [Trunk 6C Abatement Plan Final Full Revised v2.pdf](#)

Cory,

The revised Stage 1 Abatement Plan for the above-referenced site is attached for your review.

Respectfully,
Kyle Summers

REVIEWED

By Mike Buchanan at 11:36 am, Jan 25, 2024

Kyle Summers

Ensolum, LLC | Environmental & Hydrogeologic Consultants

606 South Rio Grande, Suite A | Aztec, NM 87410

Mobile 903.821.5603

ksummers@ensolum.com

www.ensolum.com

Stage 1 Abatement
Plan reviewed and
conditionally approved.
Letter of determination
sent electronically on
01/25/2024.





**REVISED TRUNK 6C KUTZ WASH PIPELINE RELEASE
STAGE 1 ABATEMENT PLAN**

Property:
**Trunk 6C Kutz Wash Pipeline Release
SW ¼, S26 T28N R11W
San Juan County, New Mexico**

**New Mexico EMNRD OCD RP No. 3R-438
Abatement Plan No. 131**

March 21, 2019
Revised May 22, 2019
Ensolum Job No: 05A1226011

Prepared for:
**Enterprise Field Services, LLC
P.O. Box 4324
Houston, Texas 77210-4324
Attn: Mr. Gregory E. Miller, P.G.**

Rane Deechilly
Staff Scientist

Kyle Summers, CPG
Senior Project Manager



Table of Contents

1	INTRODUCTION	1
1.1	STANDARD OF CARE AND LIMITATIONS	1
2	SITE DESCRIPTION AND BACKGROUND	2
3	SITE CHARACTERIZATION	2
3.1	REGIONAL GEOLOGY AND HYDROGEOLOGY	2
3.2	LOCAL GEOLOGY AND HYDROGEOLOGY	3
3.3	PROPOSED CLEANUP GOALS	3
4	SUMMARY OF SITE ASSESSMENT ACTIVITIES.....	5
5	PROPOSED MONITORING ACTIVITIES	6
5.1	HEALTH AND SAFETY PLAN	6
5.2	GROUNDWATER SAMPLING PROGRAM	6
5.3	GROUNDWATER LABORATORY ANALYTICAL PROGRAM.....	7
5.4	AQUIFER CHARACTERIZATION	7
5.5	STAGE 2 ABATEMENT PLAN PROPOSAL.....	7
5.6	QUALITY ASSURANCE	8
6	PROPOSED SCHEDULE	8

LIST OF APPENDICES

Appendix A:	Figures	
	Figure 1	Topographic Map
	Figure 2	Site Vicinity Map
	Figure 3	Site Map
	Figure 4A	Benzene RAL Exceedance Zone Map Vadose Zone 0 to 10 Feet BGS
	Figure 4B	BTEX RAL Exceedance Zone Map Vadose Zone 0 to 10 Feet BG
	Figure 4C	TPH RAL Exceedance Zone Map Vadose Zone 0 to 10 Feet
	Figure 4D	Benzene RAL Exceedance Zone Map Capillary Fringe Zone
	Figure 4E	BTEX RAL Exceedance Zone Map Capillary Fringe Zone
	Figure 4F	TPH RAL Exceedance Zone Map Capillary Fringe Zone
	Figure 5A	Groundwater Gradient Map (June 2018)
	Figure 5B	Groundwater Gradient Map (December 2018)
	Figure 5C	Groundwater Quality Standard (GQS) Exceedance Zone Map (June 2018)
	Figure 5D	Groundwater Quality Standard (GQS) Exceedance Zone Map (December 2018)
Appendix B:	Tables	
	Table 1	Soil Analytical Summary
	Table 2	Groundwater Analytical Summary
	Table 3	Groundwater Elevations
Appendix C:	Soil Boring/Monitoring Well Logs	



Appendix D: Public Notice and Landowner Table

Mr. Gregory E. Miller, Enterprise Field Services, LLC
Revised Stage 1 Abatement Plan – Trunk 6C Kutz Wash Pipeline Release

May 22, 2019
Page 1

1 INTRODUCTION

Ensolum, LLC (Ensolum) has prepared a Stage 1 Abatement Plan for the Enterprise Field Services, LLC (Enterprise) Trunk 6C Kutz Wash pipeline release site located within the southwest (SW) 1/4 of Section 26, Township 28 North, Range 11 West, in San Juan County, New Mexico (36.63202°N, 107.97400°W), hereinafter referred to as the "Site".

Based on correspondence from the New Mexico Energy Minerals and Natural Resources Department (EMNRD) Oil Conservation Division (OCD), dated January 22, 2019, Enterprise is required to submit a Stage 1 Abatement Plan no later than March 22, 2019. The Stage 1 Abatement Plan is intended to define site conditions such that an effective abatement option can be selected. Stage 2 is implementation of the remedial option. This Stage 1 Abatement Plan details the site description and background, historic site investigation and remediation activities and the geologic and hydrogeologic characteristics. Additionally, the Stage 1 Abatement Plan may propose additional delineation, monitoring activities, and remediation activities and provides a proposed schedule to complete delineation activities in accordance with New Mexico Administrative Code (NMAC) 19.15.30. Subsequent to the successful completion and the agency approval of the proposed monitoring activities, a Stage 2 Abatement Plan will be developed to address the remediation of constituents of concern (COCs) remaining at the Site in excess of the applicable New Mexico EMNRD closure criteria.

1.1 Standard of Care and Limitations

Ensolum's services will be performed in accordance with standards customarily provided by a firm rendering the same or similar services in the area during the same time period. Ensolum makes no warranties, express or implied, as to the services to be performed hereunder. Additionally, Ensolum does not warrant the work of third parties supplying information to be used in the report (e.g. laboratories, regulatory agencies, or other third parties). This scope of services will be performed in accordance with the scope of work agreed with the client and regulatory agency, as detailed in our discussions.

Findings, conclusions, and recommendations resulting from these services will be based upon information derived from public information resources and it should be noted that this information is subject to change over time. Ensolum's findings are based solely upon data available to Ensolum at the time of these services.

This report will be prepared for the exclusive use of Enterprise Products Operating LLC (Enterprise), and any authorization for use or reliance by any other party (except a governmental entity having jurisdiction over the Site) is prohibited without the express written authorization Enterprise and Ensolum. Any unauthorized distribution or reuse is at the Client's sole risk. Notwithstanding the foregoing, reliance by authorized parties will be subject to the terms, conditions and limitations stated in the Stage 1 Abatement Plan and Ensolum's Agreement with the client. The limitation of liability defined in the agreement is the aggregate limit of Ensolum's liability to the client.

2 SITE DESCRIPTION AND BACKGROUND

The Trunk 6C Kutz Wash pipeline release Site is located on land managed by the United States Bureau of Land Management (BLM). The Site is surrounded by rangeland that is periodically interrupted by oil and gas production and gathering facilities, including the natural gas gathering pipeline that traverses the area from approximately northwest to southeast.

On September 22, 2011, a pipeline release of natural gas and associated pipeline liquids was discovered at the Site and the pipeline was subsequently repaired. A Site assessment conducted by Animas Environmental Services, LLC (AES) during October 2011 identified COC concentrations in “test hole” excavation soil and groundwater that exceeded the New Mexico EMNRD OCD *Remediation Action Levels (RALs)* (which were applicable at that time) for soils and the New Mexico Water Quality Control Commission (WQCC) *Groundwater Quality Standards (GQSs)* for groundwater.

Excavation, delineation, and remediation activities were performed between November 2011 and September 2016. Results from the excavation, delineation, and remediation activities indicated COC concentrations in soil and groundwater above the applicable New Mexico EMNRD OCD and WQCC standards. Semi-annual groundwater monitoring events are ongoing at the Site.

A **Topographic Map** is provided as **Figure 1 of Appendix A**, which was reproduced from a portion of a United States Geological Survey (USGS) 7.5-minute series topographic map. A **Site Vicinity Map**, created from an aerial photograph, is provided as **Figure 2**, and a **Site Map**, which indicates the locations of the monitoring wells and recent soil borings in relation to pertinent structures and general Site boundaries, is provided as **Figure 3 of Appendix A**.

3 SITE CHARACTERIZATION

3.1 Regional Geology and Hydrogeology

The Site is located within the San Juan Basin which is the major structural feature in the northwest corner of New Mexico. The San Juan Basin is classified as an arid region, as most of the area receives less than 10 inches of precipitation per year. Mean annual precipitation in the mountainous regions along the basin margin may be as much as 30 inches a year. Surface water is relatively scarce, with the exception of the San Juan River and its tributaries.

Based upon reference information from the New Mexico Bureau of Geology and Mineral Resources publication on the background geology of the San Juan Basin (Decision-Makers Field Conference 2002) “most of the aquifers in the San Juan Basin exist under confined or semi-confined hydrologic conditions. In Mesozoic rocks of the region, the confined sandstone aquifers are interbedded with shales that behave as aquitards. The Triassic mudrock sequence is the aquitard for the Permian Limestone. Groundwater in the alluvium along streams and in the shallow Tertiary sandstone aquifers is generally unconfined and is open to the atmosphere through pores in the overlying permeable rocks.”

The major aquifer underlying the Site vicinity is listed as the Colorado Plateaus Aquifer, which is made up of four aquifers – Uinta-Anima, Mesa Verde, Dakota-Glen, and Coconino-De Chelly. The Uinta-Animas is the shallowest of these aquifers and is present in the San Juan Basin. The general composition of the aquifers is moderately to well-consolidated sedimentary rocks of an

age ranging from Permian to Tertiary. Each aquifer is separated from the others by an impermeable confining unit. Two of the confining units are completely impermeable and cover the entire area of the aquifers. The other two confining units are less extensive and are thinner. These units allow water to flow between the principal aquifers.

According to the New Mexico Bureau of Geology and Mineral Resource (Geologic Map of New Mexico 2003), the Site is located within the upper Nacimiento Formation. The Nacimiento Formation is a heterogeneous non-marine formation composed of sandstone, siltstone, and shale, comprised of sediment eroded from the San Juan and Brazos-Sangre de Cristo uplifts.

3.2 Local Geology and Hydrogeology

Boring logs were prepared during historic site investigation activities. The boring logs recorded sample identification, depth collected, and method of collection, as well as observations of soil moisture, color, grain size, contaminant presence, and overall stratigraphy. The lithology encountered at the Site during boring activities were composed of Quaternary alluvial and fluvial deposits. Based on the data collected during the completion of the soil borings, the lithology generally consists of brown to tan silty sands, sands, and clayey sand, with some gravel at depths greater than 20 feet below grade surface (bgs). Sandstone bedrock was identified at approximately 25 feet bgs.

The lithology observed during the advancement of soil boring MW-7 at the Site included a brown silty sand from the surface to approximately five (5) feet bgs. The silty sand stratum was underlain by a brown clayey sand from five (5) feet bgs to 10 feet bgs. A brown sand was encountered from 10 feet bgs to 25 feet bgs. Gray bedrock was encountered from 25 feet bgs to the terminus depth of 26 feet bgs. The lithologies observed in the remaining soil borings at the Site were generally similar to that of soil boring MW-7. Detailed lithologic descriptions are presented on the monitoring well soil boring logs included in **Appendix C**.

The initial groundwater-bearing unit at the Site was encountered at depths ranging from 13 to 16 feet bgs during supplemental investigation activities. The groundwater flow direction (gradient) at the Site is generally toward the northwest and averages approximately 0.008 feet per foot (ft/ft) across the Site.

Based on site investigation activities, impact to surface water has not been identified.

Based on Domenico and Schwartz (1990) a default hydraulic conductivity value for the impacted sand unit at the Site would be, on average, 2×10^{-6} m/sec which is equivalent to 0.57 feet per day (ft/day). Additional site-specific aquifer characterization is proposed in this Stage 1 Abatement Plan Proposal.

3.3 Proposed Cleanup Goals

The Site is subject to regulatory oversight by the New Mexico EMNRD OCD. Initial Site activities were performed in accordance with the New Mexico EMNRD OCD *Guidelines for Remediation of Leaks, Spills and Releases*, in addition to the New Mexico EMNRD OCD rules, specifically NMAC 19.15.29 *Release Notification*. This guidance established investigation and abatement action requirements for sites subject to reporting and/or corrective action prior to the update of the rule during August 2018. Groundwater remediation activities at the Site will be performed in accordance with NMAC 19.15.30 *Remediation*.

Mr. Gregory E. Miller, Enterprise Field Services, LLC
Revised Stage 1 Abatement Plan – Trunk 6C Kutz Wash Pipeline Release

May 22, 2019
Page 4

Ensolum utilized information provided by Enterprise, the general site characteristics, and information available from the New Mexico Office of the State Engineer (OSE) and the New Mexico EMNRD OCD Imaging Database to determine the appropriate closure criteria for the Site.

- No water wells were identified within a one (1) mile search radius of the Site on the OSE Water Rights Reporting System (WRRS) database. Based on water levels measured in groundwater monitoring wells located at the Site, the depth to groundwater is less than 50 feet bgs.
- The Site is located within 300 feet of a New Mexico ENMRD OCD-defined continuously flowing watercourse or significant watercourse. The Site is located approximately 127 feet southwest of Kutz Canyon Wash.
- The Site is not located within 200 feet of a lakebed, sinkhole or playa lake.
- The Site is not located within 300 feet of a permanent residence, school, hospital, institution or church.
- No springs, or private domestic fresh water wells used by less than five (5) households for domestic or stock watering purposes were identified within 500 feet of the Site.
- No fresh water wells or springs were identified within 1,000 feet of the Site.
- The Site is not located within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3.
- The Site is not located within 300 feet of a wetland.
- Based on information identified on the New Mexico Mining and Minerals Division's GIS, Maps and Mine Data database, the Site is not located within an area overlying a subsurface mine.
- The Site is not located within an unstable area.
- Based on available Federal Emergency Management Agency data, the Site is located adjacent to, but not within, a 100-year floodplain.

Based on the identified siting criteria, cleanup goals for soils remaining in place at the Site include: 10 milligrams per kilogram (mg/kg) for benzene, 50 mg/kg for total benzene, toluene, ethylbenzene, and total xylenes (BTEX), 100 mg/kg for combined total petroleum hydrocarbon (TPH) gasoline range organics (GRO) diesel range organics (DRO) and motor oil/lube oil range organics (MRO) and 600 mg/kg for chlorides.

In addition, cleanup/delineation goals for groundwater located at the Site include: 10 micrograms per liter (µg/L) for benzene, 750 µg/L for toluene, 750 µg/L for ethylbenzene, and 620 µg/L for total xylenes.

4 SUMMARY OF SITE ASSESSMENT ACTIVITIES

On September 22, 2011, a pipeline release of an unknown volume of natural gas and associated liquids was discovered at the Site and the pipeline was subsequently repaired. AES collected one (1) soil sample from the floor of the repair excavation. Based on field screening results, the soil sample exhibited elevated levels of volatile organic compounds (VOCs). A site assessment was conducted by AES on October 11, 2011, which included the collection of soil samples from four (4) test holes (TP-1 through TP-4) which were advanced near the release area, as well as groundwater samples from two (2) of the four (4) test holes. Based on laboratory analytical results, BTEX and TPH were identified in soils from two (2) of the test holes (TP-1 and TP-2) at concentrations above the New Mexico EMNRD OCD RALs. The test hole water samples collected from TP-2 and TP-4 exhibited concentrations of benzene, toluene, and total xylenes above WQCC GQSs. Additional detail regarding the initial site assessment activities are provided in the *Release Assessment Report, dated October 28, 2011- AES*.

During November 2011, AES advanced eight (8) soil borings (SB-1 through SB-8) at the Site to further delineate the extent of hydrocarbon affected soil and potentially impacted groundwater. Laboratory analytical results for the soil and groundwater samples collected from the soil borings identified COC concentrations in soil above the New Mexico EMNRD OCD RALs (SB-2, SB-7, and SB-8) and in groundwater above the WQCC GQSs (SB-2W, SB-3W, and SB-7W) (*Site Investigation Report, dated February 20, 2012 – AES*).

During September 2012, nine (9) additional soil borings were advanced at the Site by AES to further evaluate the extent of dissolved phase COCs in groundwater. Subsequent to advancement, the soil borings were completed as groundwater monitoring wells (MW-1 through MW-9). Laboratory analytical results did not indicate COCs in soil above the New Mexico EMNRD OCD RALs at these soil boring/monitoring well locations. However, COCs were confirmed in groundwater above the WQCC GQSs (*Groundwater Investigation Report, dated October 31, 2012 – AES*).

On October 16, 2013, AES advanced four (4) additional soil borings/monitoring wells (MW-10 through MW-13) in and around the release area to further evaluate the extent of COCs in groundwater. Laboratory analytical results indicated COC concentrations in soil and groundwater from soil boring/monitoring well MW-10 were present at levels above the New Mexico EMNRD OCD RALs and the WQCC GQSs (*3rd Quarter 2013 Groundwater Monitoring and Well Installation Report, dated December 10, 2013 – AES*).

On October 28, 2013, an additional leak was discovered in the immediate vicinity of the original release and the pipeline was subsequently repaired and placed back in service. AES collected 20 discrete soils samples from the final pipeline repair excavation and the resulting analytical data identified COC concentrations above the New Mexico EMNRD OCD RALs. In addition, aquifer pumping tests were conducted in four (4) wells by AES to estimate hydraulic conductivity (*4th Quarter 2013 Groundwater Monitoring and Continued Investigation Report, dated July 23, 2014 – AES*).

During September 2016, Apex TITAN, Inc (Apex) performed site investigation activities to further evaluate and delineate the concentrations of COCs in soil and groundwater at the Site. Five (5) soil borings were advanced and three (3) of the soil borings were completed as groundwater monitoring wells MW-14, MW-15, and MW-17. Laboratory analytical results indicated COC concentrations in soil (MW-15 and MW-17) and groundwater (MW-17) were above the New

Mexico EMNRD OCD RALs and the WQCC GQSs (*Supplemental Environmental Site Investigation (September 2016) and Annual Groundwater Monitoring Report (June and December 2016)*, dated February 13, 2017 – Apex).

Soil laboratory results, including data from previous site investigations, are provided in **Table 1 (Appendix B)**. Groundwater analytical results are summarized in **Table 2 (Appendix B)**. Groundwater measurements (including historical data) are presented with top of casing (TOC) elevations in **Table 3 (Appendix B)**. Benzene, BTEX, and TPH RAL Exceedance Zone soil maps for vadose and capillary fringe zones are provided as **Figure 4A through Figure 4F (Appendix A)** and included the estimated area of soil impact based on available and current historical data. Groundwater gradient maps and groundwater quality standards exceedance zone maps that include the June and December 2018 exceedances are provided as **Figure 4A, Figure 4B, Figure 5A and Figure 5B (Appendix A)**. Available soil boring logs are provided in **Appendix C**. Please note that the historic soil analytical data tables reference the Remediation Action Levels provided in the now obsolete New Mexico ENMRD OCD *Guidelines for Remediation of Leaks, Spills and Releases*.

5 PROPOSED MONITORING ACTIVITIES

5.1 Health and Safety Plan

Ensolum will develop a site-specific Health and Safety Plan (HSP) for the performance of the proposed scope of services described in this work plan. For the purposes of this HSP, it is assumed that the COCs include petroleum hydrocarbons constituents. For the purposes of this proposed plan, it is assumed that the scope of services can be conducted under modified Level D personal protective equipment (PPE), which will include a hard hat, steel-toed boots, protective eyewear, and gloves. Should the need arise to upgrade PPE (e.g. respiratory protection), the client will be notified, and the HSP will be modified accordingly. Although it is not anticipated at this time, it should be noted that a PPE upgrade will constitute a change in scope of work, requiring a change order.

5.2 Groundwater Sampling Program

Ensolum will collect one (1) groundwater sample from each of the 15 monitor wells on a semi-annual schedule through 2019. The purpose of the groundwater monitoring program is to evaluate and document dissolved-phase COC concentrations at the Site.

Prior to sampling, fluid levels in each of the monitoring wells will be gauged utilizing an interface probe capable of detecting non-aqueous phase liquid (NAPL).

Groundwater samples will be collected utilizing low-flow sampling or bailer-purge sampling methods.

Low-flow refers to the velocity with which groundwater enters the pump intake and that is imparted to the formation pore water in the immediate vicinity of the well screen. Water level drawdown provides the best indication of the stress imparted by a given flow-rate for a given hydrological situation. The objective is to pump in a manner that minimizes stress (drawdown) to the system, to the extent practical, taking into account established Site sampling objectives. Flow rates on the order of 0.1 to 0.5 liters per minute (L/min) are maintained during sampling activities, using

dedicated or decontaminated sampling equipment. The pump intake is placed within the screened interval such that the groundwater recovered is drawn in directly from the formation with little mixing of casing water or disturbance to the sampling zone.

The groundwater samples will be collected from each monitoring well once produced groundwater is consistent in color, clarity, pH, temperature, and conductivity. Measurements are taken every three to five minutes while purging. Purging is considered complete once key parameters (especially pH and conductivity) have stabilized for three successive readings.

If a disposable bailer is utilized to sample the monitoring well, the monitoring well will be purged until effectively dry and once groundwater recovers to static or near static levels, a groundwater sample will be collected.

Samples will be collected in laboratory supplied containers, labels/sealed using the laboratory supplied custody seals, and placed on ice in a cooler. The samples will be relinquished to the courier for Hall Environmental Analysis Laboratory (HEAL) of Albuquerque, New Mexico under proper chain-of-custody procedures.

5.3 Groundwater Laboratory Analytical Program

The groundwater samples collected from the monitoring wells will be analyzed for BTEX utilizing EPA Method SW-846 8021/8260.

A summary of the analytes, sample type, estimated number of samples per event, and EPA-approved methods are presented below:

Analytes	Sample Type	No. of Samples	Method
BTEX	Water	15	SW-846 8021/8260

5.4 Aquifer Characterization

Ensolum will evaluate site specific groundwater characteristics in the initial groundwater bearing unit. Ensolum's groundwater characterization program will be developed based on Ensolum's understanding of the geologic and hydrogeologic conditions present at the Site and will be conducted utilizing a bail-down method with recharge observations. In this method, the well is pumped/bailed as near as practicable to the base of the well screen and recovery is measured utilizing a pressure transducer capable of recording measurements for use by modeling software. The test is deemed complete when groundwater is fully recharged or when the test duration reaches 4 hours, whichever occurs first.

5.5 Stage 2 Abatement Plan Proposal

Based on the data generated from the groundwater sampling and aquifer testing, Ensolum will prepare a Stage 2 Abatement Plan Proposal. The plan will include an evaluation of the cumulative laboratory analytical data develop and justify a preferred abatement option for the Site. In addition, the Stage 2 Abatement Plan Proposal will include a modification to the groundwater monitoring program, Site maintenance activities, a proposed schedule for duration of abatement activities

and public notification proposal designed to satisfy the requirement of Subsections A through C of 19.15.30.15 NMAC.

5.6 Quality Assurance

Sampling and analytical techniques have been identified in the text above and conforms with the references identified in Subsection B of 20.6.2.3107 NMAC and with 20.6.4.14 NMAC of the water quality standards for interstate and intrastate surface waters in New Mexico.

6 PROPOSED SCHEDULE

Based on the available data, soil and groundwater impact at the Site appears to be delineated.

Public Notice

Enterprise will provide Public Notice within 15 days of notice from NMOCD that this Abatement Plan is administratively complete as required per NMAC 19.15.30.15. Enterprise will provide written notice of the Stage 1 Abatement Plan to the following parties:

- Surface owners of record within one (1) mile of the perimeter of the identified impacted area as currently delineated in the Stage 1 Abatement Plan. The list of Landowners is provided in **Table A (Appendix D)**.
- The County Commission of San Juan County, New Mexico.
- The Office of Natural Resources Trustee for the State of New Mexico.

Please note the release was not identified to be within one (1) mile of any city limits or tribal boundaries.

Enterprise understands that the NM EMNRD OCD may request additional notification to persons or entities that have requested such, as well as other local, state, or federal governmental agencies upon approval of the Stage 1 Abatement Plan.

Once approval is received, Enterprise will publish the NM EMNRD OCD approved notice in the Farmington Daily Times, a newspaper circulated in San Juan County, New Mexico, and in the Albuquerque Journal, a newspaper of general circulation across the state of New Mexico. The newspaper publications will run for a cycle of one (1) business day.

Enterprise will issue the public notice via the newspapers and certified mailings within 15 days after the NM EMNRD OCD has provided determination that the Stage 1 Abatement Plan is administratively complete. Proposed verbiage for the public notice and a list of landowners within a one-mile radius are provided in **Appendix D**.

If no public comments are received within 30 days of posting public notice, Ensolum will proceed with permitting and scheduling supplemental site investigation activities.

Field Activities

Enterprise proposes to continue semi-annual groundwater monitoring activities at the Site until the additional aquifer testing activities are evaluated and the Stage 2 Abatement Plan Proposal

Mr. Gregory E. Miller, Enterprise Field Services, LLC
Revised Stage 1 Abatement Plan – Trunk 6C Kutz Wash Pipeline Release

May 22, 2019
Page 9

has been approved and implemented. The additional aquifer testing activities are proposed to be completed before the end of June 2019. Prior to any field work, Ensolum and/or Enterprise will provide the NM EMNRD OCD with 48-hour notification.


Quarterly Progress Reports

In accordance with NMAC 19.15.30.13 C. (5), Enterprise will provide the New Mexico ENMRD OCD with summary quarterly progress reports of the Stage 1 Abatement Plan implementation beginning 30 days after the approval and initiation of the Stage 1 activities. At this time the summary quarterly progress reports are anticipated to begin in July 2019.



APPENDIX A

Figures




ENSOLUM
 Environmental & Hydrogeologic Consultants

TOPOGRAPHIC MAP

ENTERPRISE FIELD SERVICES, LLC
 TRUNK 6C KUTZ WASH PIPELINE RELEASE
 SW ¼, S26 T28N R11W, San Juan County, New Mexico
 36.63202° N, 107.97400° W

PROJECT NUMBER: 05A1226011

FIGURE
1




SITE VICINITY MAP

ENTERPRISE FIELD SERVICES, LLC
TRUNK 6C KUTZ WASH PIPELINE RELEASE
SW ¼, S26 T28N R11W, San Juan County, New Mexico
36.63202° N, 107.97400° W

PROJECT NUMBER: 05A1226011

FIGURE
2



SITE MAP

ENTERPRISE FIELD SERVICES, LLC
TRUNK 6C KUTZ WASH PIPELINE RELEASE
SW ¼, S26 T28N R11W, San Juan County, New Mexico
36.63202° N, 107.97400° W

PROJECT NUMBER: 05A1226011














FIGURE
3


NOTE:

All Concentrations are Listed in mg/kg.

All Depths are Listed in Feet BGS.

LEGEND:

-  Release Point
-  Monitoring Well Location
-  Soil Boring Location
-  Test Hole Location
-  Excavation Confirmation Soil Sample Location
-  Approximate Benzene RAL Exceedance Zone in Vadose Zone
-  Enterprise Trunk 6C Kutz Wash Pipeline Location
-  Enterprise X89608 Well Tie Pipeline Location
-  Enterprise X90628 Well Tie Pipeline Location
-  XTO Underground Pipeline Location
-  Overhead Electric Line
-  Unpaved Road
-  Extent of Former Excavation



**BENZENE RAL EXCEEDANCE ZONE MAP
VADOSE ZONE 0 TO 10 FEET BGS**

ENTERPRISE FIELD SERVICES, LLC
TRUNK 6C KUTZ WASH PIPELINE RELEASE
SW ¼, S26 T28N R11W, San Juan County, New Mexico
36.63202° N, 107.97400° W

PROJECT NUMBER: 05A1226011

**FIGURE
4A**


NOTE:

All Concentrations are Listed in mg/kg.

All Depths are Listed in Feet BGS.

LEGEND:

- Release Point
- Monitoring Well Location
- Soil Boring Location
- Test Hole Location
- Excavation Confirmation Soil Sample Location
- Approximate BTEX RAL Exceedance Zone in Vadose Zone
- Enterprise Trunk 6C Kutz Wash Pipeline Location
- Enterprise X89608 Well Tie Pipeline Location
- Enterprise X90628 Well Tie Pipeline Location
- XTO Underground Pipeline Location
- Overhead Electric Line
- Unpaved Road
- Extent of Former Excavation




NOTE:

All Concentrations are Listed in mg/kg.

All Depths are Listed in Feet BGS.

LEGEND:

- Release Point
- Monitoring Well Location
- Soil Boring Location
- Test Hole Location
- Excavation Confirmation Soil Sample Location
- Approximate TPH RAL Exceedance Zone in Vadose Zone
- Enterprise Trunk 6C Kutz Wash Pipeline Location
- Enterprise X89608 Well Tie Pipeline Location
- Enterprise X90628 Well Tie Pipeline Location
- XTO Underground Pipeline Location
- Overhead Electric Line
- Unpaved Road
- Extent of Former Excavation

















NOTE:

All Concentrations are Listed in mg/kg.

All Depths are Listed in Feet BGS.

LEGEND:

-  Release Point
-  Monitoring Well Location
-  Soil Boring Location
-  Test Hole Location
-  Excavation Confirmation Soil Sample Location
-  Approximate Benzene RAL Exceedance Zone in Capillary Fringe Zone
-  Enterprise Trunk 6C Kutz Wash Pipeline Location
-  Enterprise X89608 Well Tie Pipeline Location
-  Enterprise X90628 Well Tie Pipeline Location
-  XTO Underground Pipeline Location
-  Overhead Electric Line
-  Unpaved Road
-  Extent of Former Excavation



BENZENE RAL EXCEEDANCE ZONE MAP CAPILLARY FRINGE ZONE

ENTERPRISE FIELD SERVICES, LLC
TRUNK 6C KUTZ WASH PIPELINE RELEASE
SW ¼, S26 T28N R11W, San Juan County, New Mexico
36.63202° N, 107.97400° W

PROJECT NUMBER: 05A1226011














FIGURE
4D


NOTE:

All Concentrations are Listed in mg/kg.

All Depths are Listed in Feet BGS.

LEGEND:

-  Release Point
-  Monitoring Well Location
-  Soil Boring Location
-  Test Hole Location
-  Excavation Confirmation Soil Sample Location
-  Approximate BTEX RAL Exceedance Zone in Capillary Fringe Zone
-  Enterprise Trunk 6C Kutz Wash Pipeline Location
-  Enterprise X89608 Well Tie Pipeline Location
-  Enterprise X90628 Well Tie Pipeline Location
-  XTO Underground Pipeline Location
-  Overhead Electric Line
-  Unpaved Road
-  Extent of Former Excavation




NOTE:


All Concentrations are Listed in mg/kg.


All Depths are Listed in Feet BGS.


LEGEND:


- Release Point
- Monitoring Well Location
- Soil Boring Location
- Test Hole Location
- Excavation Confirmation Soil Sample Location
- Approximate TPH RAL Exceedance Zone in Capillary Fringe Zone
- Enterprise Trunk 6C Kutz Wash Pipeline
- Enterprise X89608 Well Tie Pipeline
- Enterprise X90628 Well Tie Pipeline
- XTO Underground Pipeline Location
- Overhead Electric Line
- Unpaved Road
- Extent of Former Excavation













APPENDIX B

Tables



TABLE 1
Trunk 6C Kutz Wash Pipeline Release
SOIL ANALYTICAL SUMMARY

Sample I.D.	Date	Sample Depth (feet)	Benzene (mg/kg)	Toluene (mg/kg)	Ethylbenzene (mg/kg)	Xylenes (mg/kg)	Total BTEX (mg/kg)	TPH GRO (mg/kg)	TPH DRO (mg/kg)
New Mexico Energy, Mineral & Natural Resources Department, Oil Conservation Division, Remediation Action Level			10	NE	NE	NE	50	100	
Test Hole Excavation and Soil Boring Soil Samples Collected by AES									
TP-1	10.11.11	10	6.2	84	7.8	71	169	1,400	29
TP-2	10.11.11	12	<0.047	<0.047	<0.047	<0.094	ND	<4.7	<9.8
TP-2	10.11.11	15	45	200	8.3	260	513	5,000	170
TP-3	10.11.11	10	<0.048	<0.048	<0.048	<0.095	ND	<4.8	<10
TP-4	10.11.11	12	<0.050	<0.050	<0.050	<0.10	ND	<5.0	<10
TP-4	10.11.11	15	<0.048	<0.048	0.12	0.50	0.62	20	39
SB-1	11.30.11	14	<0.049	<0.049	<0.049	<0.098	ND	<4.9	<10
SB-2	11.30.11	12	31	240	20	290	581	7,300	230
SB-3	11.30.11	14	<0.048	<0.048	<0.048	<0.096	ND	<4.8	<10
SB-4	11.30.11	14	<0.049	<0.049	<0.049	<0.097	ND	<4.9	<10
SB-5	11.30.11	14	<0.047	<0.047	<0.047	<0.095	ND	<4.7	<9.6
SB-6	11.30.11	13	<0.047	<0.047	<0.047	<0.093	ND	<4.7	<9.9
SB-7	11.30.11	14	<0.24	0.61	<0.24	2.0	2.6	58	53
SB-8	11.30.11	14	<0.050	<0.050	<0.050	<0.099	ND	6	1,200
Excavation Soil Samples Collected by AES									
S-2	12.17.13	8	66	710	54	500	1,330	15,000	320
S-3	12.17.13	15	21	270	25	270	586	6,200	100
S-4	12.17.13	1 to 15	<0.49	21	6.0	59	86	1,000	69
S-9	12.17.13	8	<0.12	1.4	0.45	4.8	6.7	94	49
S-10	12.17.13	15	0.63	19	3.5	35	58	680	45
S-11	12.17.13	4	<0.049	<0.049	<0.049	<0.097	ND	<4.9	<10
S-13	12.17.13	15	<0.048	<0.048	<0.048	0.11	0.11	5.6	<10
S-17	12.17.13	1 to 15	<0.048	<0.048	<0.048	<0.095	ND	<4.8	<10
S-18	12.17.13	1 to 15	<0.048	<0.048	<0.048	0.16	0.16	<4.8	<10
S-20	12.17.13	8	<0.12	0.31	0.28	3.2	3.8	40	330
Soil Borings Advanced by AES									
MW-1	8.20.12	5 to 7	<0.049	<0.049	<0.049	<0.097	ND	<4.9	<9.9
	8.20.12	10 to 12	<0.048	<0.048	<0.048	<0.097	ND	<4.8	<9.9
MW-2	8.20.12	5 to 7	<0.048	<0.048	<0.048	<0.097	ND	<4.8	<9.8
	8.20.12	10 to 12	<0.049	<0.049	<0.049	<0.097	ND	<4.9	<10
MW-3	8.21.12	0 to 2	<0.050	<0.050	<0.050	<0.10	ND	<5.0	<10
	8.21.12	10 to 12	<0.050	<0.050	<0.050	<0.099	ND	<5.0	<9.8
MW-4	8.21.12	5 to 7	<0.050	<0.050	<0.050	<0.099	ND	<5.0	<9.9
	8.21.12	10 to 12	<0.047	<0.047	<0.047	<0.094	ND	<4.7	<9.8
MW-5	8.23.12	5 to 7	<0.048	<0.048	<0.048	<0.096	ND	<4.8	<10
	8.23.12	10 to 12	<0.050	<0.050	<0.050	<0.10	ND	<5.0	<9.9
MW-6	8.23.12	5 to 7	<0.050	<0.050	<0.050	<0.10	ND	<5.0	<10
	8.23.12	10 to 12	<0.048	<0.048	<0.048	<0.096	ND	<4.8	<9.9
MW-7	8.23.12	5 to 7	<0.048	<0.048	<0.048	<0.097	ND	<4.8	<9.7
	8.23.12	10 to 12	<0.047	<0.047	<0.047	<0.094	ND	<4.7	<9.8
MW-8	8.21.12	5 to 7	<0.046	<0.046	<0.046	<0.093	ND	<4.6	<9.6
	8.21.12	10 to 12	<0.047	<0.047	<0.047	<0.095	ND	<4.7	<10
MW-9	8.23.12	5 to 7	<0.048	<0.048	<0.048	<0.096	ND	<4.8	<9.6
	8.23.12	10 to 12	<0.047	<0.047	<0.047	<0.093	ND	<4.7	<10
MW-10	10.16.13	13.5 to 14	1.7	20	2.5	28	52	530	11
MW-11	10.16.13	13.5 to 14	<0.047	<0.047	<0.047	<0.095	ND	<4.7	<10
MW-12	10.16.13	13.5 to 14	<0.046	<0.046	<0.046	<0.093	ND	<4.6	<10
MW-13	10.16.13	13.5 to 14	<0.048	<0.048	<0.048	<0.097	ND	<4.8	<10



TABLE 1
Trunk 6C Kutz Wash Pipeline Release
SOIL ANALYTICAL SUMMARY

Sample I.D.	Date	Sample Depth (feet)	Benzene (mg/kg)	Toluene (mg/kg)	Ethylbenzene (mg/kg)	Xylenes (mg/kg)	Total BTEX (mg/kg)	TPH GRO (mg/kg)	TPH DRO (mg/kg)
New Mexico Energy, Mineral & Natural Resources Department, Oil Conservation Division, Remediation Action Level			10	NE	NE	NE	50	100	
Soil Borings Advanced by Apex									
MW-14	9.6.16	12 to 16	<0.025	<0.050	<0.050	<0.10	ND	<5.0	<9.8
MW-15	9.6.16	14 to 16	0.070	<0.046	<0.046	0.78	0.85	160	330
SB-16A	9.6.16	12 to 14	<0.024	<0.048	<0.048	<0.096	ND	<4.8	<9.5
MW-17	9.6.16	7 to 12	<0.024	<0.047	<0.047	0.16	0.16	17	15
MW-17	9.6.16	12 to 14	3.8	12	2.1	17	35	590	140
SB-18A	9.6.16	14 to 16	<0.12	<0.24	<0.24	0.80	0.80	61	230

Note: Concentrations in **bold** and yellow exceed the applicable OCD Remediation Action Level

mg/kg = milligrams per kilograms

ND = Not Detected above the Laboratory Reporting Limits

NE = Not established

BTEX = Benzene, Toluene, Ethylbenzene, and Total Xylenes

TPH = Total Petroleum Hydrocarbon

GRO = Gasoline Range Organics

DRO = Diesel Range Organics



TABLE 2
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ANALYTICAL SUMMARY

Sample I.D.	Sample Date	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Xylenes (µg/L)
New Mexico Water Quality Control Commission Groundwater Quality Standards		10	750	750	620
Monitoring Wells Installed by AES					
MW-1	9.7.12	2,200	350	68	650
	12.20.12	1,100	250	37	180
	3.20.13	NAPL	NAPL	NAPL	NAPL
	6.19.13	NAPL	NAPL	NAPL	NAPL
	9.17.13	NAPL	NAPL	NAPL	NAPL
	12.16.13	NAPL	NAPL	NAPL	NAPL
	3.14.15	NAPL	NAPL	NAPL	NAPL
	9.9.15	1,900	440	54	400
	6.15.15	6,900	2,700	170	1,400
	12.7.15	3,900	1,400	120	870
	6.02.16	1,400	850	41	330
	12.20.16	76	59	2.5	23
	6.28.17	3,500	4,200	180	1,800
	1.10.18	1,300	710	59	350
	6.22.18	3,800	2,400	140	740
	12.14.18	590	400	33	99
MW-2	9.7.12	270	1,100	66	1,800
	12.20.12	26	49	5.1	250
	3.20.13	<5.0	<5.0	<5.0	67
	6.19.13	NAPL	NAPL	NAPL	NAPL
	9.17.13	NAPL	NAPL	NAPL	NAPL
	12.16.13	NAPL	NAPL	NAPL	NAPL
	3.14.14	1,200	1,600	74	660
	9.9.14	78	76	2.9	110
	6.15.15	<1.0	1.1	<1.0	44
	12.7.15	<1.0	<1.0	<1.0	13
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.14.18	<1.0	<1.0	<1.0	<2.0
MW-3	9.7.12	<2.0	<2.0	<2.0	<4.0
	12.20.12	<2.0	<2.0	<2.0	<4.0
	3.20.13	<2.0	<2.0	<2.0	<4.0
	6.19.13	780	130	2.5	15
	9.18.13	150	28	<5.0	15
	12.16.13	660	340	16	130
	3.14.14	200	86	4.0	49
	9.9.14	2.5	1.7	<1.0	3.3
	6.12.15	1.3	<1.0	<1.0	2.2
	12.7.15	<1.0	<1.0	<1.0	<2.0
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.28.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.14.18	<1.0	<1.0	<1.0	<2.0



TABLE 2
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ANALYTICAL SUMMARY

Sample I.D.	Sample Date	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Xylenes (µg/L)
New Mexico Water Quality Control Commission Groundwater Quality Standards		10	750	750	620
MW-4	9.7.12	18	5.1	<2.0	<4.0
	12.20.12	<2.0	<2.0	<2.0	<4.0
	3.20.13	290	110	<2.0	15
	6.19.13	600	45	<10	<20
	9.18.13	830	39	<20	<30
	12.16.13	300	110	10	63
	3.14.14	4.0	<1.0	<1.0	<3.0
	9.9.14	<2.0	<2.0	<2.0	<4.0
	6.11.15	<1.0	<1.0	<1.0	<2.0
	12.4.15	<1.0	<1.0	<1.0	<2.0
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.28.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.13.18	<1.0	<1.0	<1.0	<2.0
MW-5	9.7.12	<2.0	<2.0	<2.0	<4.0
	12.20.12	<2.0	<2.0	<2.0	<4.0
	3.20.13	<2.0	<2.0	<2.0	<4.0
	6.19.13	<1.0	<1.0	<1.0	<2.0
	9.17.13	<1.0	<1.0	<1.0	<1.5
	12.16.13	2.1	4.7	4.0	17
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<1.0	<1.0	<1.0	<2.0
	6.12.15	<1.0	<1.0	<1.0	<2.0
	12.4.15	<1.0	<1.0	<1.0	<2.0
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.13.18	<1.0	<1.0	<1.0	<2.0
MW-6	9.7.12	<5.0	<5.0	260	2,200
	12.20.12	<5.0	<5.0	180	1,200
	3.20.13	<5.0	<5.0	120	800
	6.19.13	9.6	6.2	150	1,100
	9.18.13	<5.0	<5.0	180	1,200
	12.16.13	<5.0	<5.0	140	990
	3.14.14	<1.0	<1.0	150	990
	9.9.14	<5.0	<5.0	49	400
	6.12.15	<5.0	<5.0	89	590
	12.4.15	<2.5	<5.0	41	210
	6.02.16	<1.0	<1.0	16	70
	12.19.16	<1.0	<1.0	26	80
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	3.6	12
	6.21.18	<1.0	<1.0	2.1	5.9
	12.13.18	<1.0	<1.0	2.7	9.8



TABLE 2
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ANALYTICAL SUMMARY

Sample I.D.	Sample Date	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Xylenes (µg/L)
New Mexico Water Quality Control Commission Groundwater Quality Standards		10	750	750	620
MW-7	9.7.12	<2.0	<2.0	<2.0	<4.0
	12.20.12	<2.0	<2.0	<2.0	2.4
	3.20.13	<2.0	<2.0	<2.0	<4.0
	6.19.13	<1.0	<1.0	<1.0	<2.0
	9.17.13	<1.0	<1.0	<1.0	<1.5
	12.16.13	1.6	3.9	3.6	16
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<1.0	<1.0	<1.0	<2.0
	6.12.15	<1.0	<1.0	<1.0	<2.0
	12.7.15	<1.0	<1.0	<1.0	<2.0
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.13.18	<1.0	<1.0	<1.0	<2.0
MW-8	9.7.12	41	40	3.8	320
	12.20.12	<2.0	<2.0	<2.0	20
	3.20.13	41	36	<2.0	89
	6.19.13	21	12	<1.0	6.8
	9.18.13	<1.0	<1.0	3.4	27
	12.16.13	18	21	5.1	74
	3.14.14	66	190	10	210
	9.9.14	NAPL**	NAPL**	NAPL**	NAPL**
	6.15.15	<1.0	<1.0	<1.0	10
	12.7.15	1.3	<1.0	<1.0	53
	6.02.16	4.0	1.6	<1.0	5.1
	12.19.16	<1.0	<1.0	<1.0	2.1
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.14.18	<1.0	<1.0	<1.0	<2.0
MW-9	9.7.12	<2.0	2.4	<2.0	<4.0
	12.20.12	<2.0	<2.0	<2.0	<4.0
	3.20.13	<2.0	<2.0	<2.0	<4.0
	6.19.13	<1.0	<1.0	<1.0	<2.0
	9.17.13	<1.0	<1.0	<1.0	<1.5
	12.16.13	1.5	3.5	2.9	12
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<2.0	<2.0	<2.0	<4.0
	6.11.15	<1.0	<1.0	<1.0	<2.0
	12.4.15	<1.0	<1.0	<1.0	<2.0
	6.02.16	<1.0	<1.0	<1.0	<2.0
	12.19.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.09.18	<1.0	<1.0	<1.0	<2.0
	6.21.18	<1.0	<1.0	<1.0	<1.5
	12.13.18	<1.0	<1.0	<1.0	<2.0



TABLE 2
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ANALYTICAL SUMMARY

Sample I.D.	Sample Date	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Xylenes (µg/L)
New Mexico Water Quality Control Commission Groundwater Quality Standards		10	750	750	620
MW-10	12.16.13	950	34	12	39
	3.14.14	560	4.0	16	27
	9.9.14	580	<10	34	<20
	6.15.15	75	<1.0	12	2.9
	12.7.15	17	<1.0	2.0	<2.0
	6.03.16	16	<1.0	<1.0	<2.0
	12.20.16	4.8	<1.0	<1.0	<1.5
	6.27.17	3.4	<1.0	<1.0	<2.0
	1.10.18	<1.0	<1.0	<1.0	<2.0
	6.22.18	5.0	<1.0	<1.0	2.7
	12.14.18	<1.0	<1.0	<1.0	<2.0
MW-11	12.16.13	2.6	3.5	<1.0	6
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<2.0	<2.0	<2.0	<4.0
	6.12.15	<1.0	<1.0	<1.0	<2.0
	12.4.15	<1.0	<1.0	<1.0	<2.0
	6.03.16	<1.0	<1.0	<1.0	<2.0
	12.20.16	<1.0	<1.0	<1.0	<1.5
	6.28.17	Insufficient volume of water to sample.			
	1.10.18	<1.0	<1.0	<1.0	<1.5
	6.22.18	<1.0	<1.0	<1.0	<1.5
	12.14.18	<1.0	<1.0	<1.0	<2.0
MW-12	12.16.13	3.3	3.8	<1.0	6
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<2.0	<2.0	<2.0	<4.0
	6.12.15	Casing Obstruction			
	12.4.15	Casing Obstruction			
	6.02.16	Casing Obstruction			
	12.20.16	Casing Obstruction			
	6.27.17	Casing Obstruction			
	1.10.18	Casing Obstruction			
	6.21.18	Casing Obstruction			
	12.13.18	Casing Obstruction			
MW-13	12.16.13	4.4	5.1	1.2	8
	3.14.14	<1.0	<1.0	<1.0	<3.0
	9.9.14	<2.0	<2.0	<2.0	<4.0
	6.15.15	<1.0	<1.0	<1.0	<2.0
	12.4.15	<1.0	<1.0	<1.0	<2.0
	6.03.16	<1.0	<1.0	<1.0	<2.0
	12.20.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.10.18	<1.0	<1.0	<1.0	<2.0
	6.22.18	<1.0	<1.0	<1.0	<1.5
	12.14.18	<1.0	<1.0	<1.0	<2.0



TABLE 2
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ANALYTICAL SUMMARY

Sample I.D.	Sample Date	Benzene (µg/L)	Toluene (µg/L)	Ethylbenzene (µg/L)	Xylenes (µg/L)
New Mexico Water Quality Control Commission Groundwater Quality Standards		10	750	750	620
Monitoring Wells Installed by APEX					
MW-14	9.16.16	<1.0	<1.0	<1.0	<2.0
	12.20.16	<1.0	<1.0	<1.0	<1.5
	6.27.17	<1.0	<1.0	<1.0	<2.0
	1.10.18	<1.0	<1.0	<1.0	<2.0
	6.22.18	<1.0	<1.0	<1.0	<1.5
	12.13.18	2.7	<1.0	<1.0	6.1
MW-15	9.16.16	3.6	<1.0	4.1	43
	12.20.16	<1.0	<1.0	6.2	87
	6.27.17	4.1	<1.0	4.6	89
	1.10.18	4.7	<1.0	2.8	33
	6.21.18	6.5	<1.0	2.6	13
	12.13.18	1.2	<1.0	<1.0	<2.0
MW-17	9.16.16	380	790	33	1,200
	12.20.16	200	100	11	310
	6.28.17	130	<5.0	<5.0	950
	1.10.18	5.2	2.2	1.2	13
	6.22.18	29	<1.0	2.4	<1.5
	12.14.18	29	<1.0	1.8	<2.0

Note: Concentrations in **bold** and yellow exceed the applicable WQCC GQS

µg/L = micrograms per liter

NAPL = Non-aqueous phase liquid

** - Field personnel recorded the presence of NAPL utilizing an interface probe, but the product was not documented as visually verified.

<1.0 = the numeral (in this case "1.0") identifies the laboratory RL or PQL



TABLE 3 Trunk 6C Kutz Wash Pipeline Release GROUNDWATER ELEVATIONS						
Well I.D.	Date	Depth to Product (feet BTOC)	Depth to Water (feet BTOC)	Product Thickness	TOC Elevations (feet AMSL)	Groundwater Elevation* (feet AMSL)
MW-1*	9.7.12	ND	15.78	ND	5579.73	5563.95
	12.20.12	ND	15.69	ND		5564.04
	3.20.13	15.31	15.73	0.42		5564.31
	6.19.13	15.49	15.75	0.26		5564.17
	9.17.13	15.79	16.27	0.48		5563.81
	12.16.13	15.59	15.75	0.16		5564.10
	3.14.14	15.35	15.36	0.01		5564.38
	9.9.14	15.98	15.99	0.01		5563.75
	6.10.15	15.29	15.30	0.01		5564.44
	12.04.15	ND	15.81	ND		5563.92
	6.02.16	ND	15.41	ND		5564.32
	9.16.16	16.12	16.13	0.01	5579.43	5563.31
	12.19.16	ND	15.83	ND		5563.60
	6.27.17	ND	15.39	ND		5564.04
	1.09.18	ND	15.61	ND		5563.82
	6.21.18	ND	15.65	ND		5563.78
	12.13.18	ND	15.89	ND		5563.54
MW-2*	9.7.12	ND	16.29	ND	5579.39	5563.10
	12.20.12	ND	16.22	ND		5563.17
	3.20.13	ND	15.97	ND		5563.42
	6.19.13	15.96	16.40	0.44		5563.31
	9.17.13	16.40	16.54	0.14		5562.95
	12.16.13	16.14	16.22	0.08		5563.23
	3.14.14	ND	15.89	ND		5563.50
	9.9.14	ND	16.50	ND		5562.89
	6.10.15	ND	15.81	ND		5563.58
	12.04.15	ND	16.32	ND		5563.07
	6.02.16	ND	15.93	ND		5563.46
	9.16.16	ND	16.61	ND	5579.15	5562.54
	12.19.16	ND	16.35	ND		5562.80
	6.27.17	ND	15.95	ND		5563.20
	1.09.18	ND	16.13	ND		5563.02
	6.21.18	ND	16.19	ND		5562.96
	12.13.18	ND	16.45	ND		5562.70
MW-3*	9.7.12	ND	15.98	ND	5579.52	5563.54
	12.20.12	ND	15.79	ND		5563.73
	3.20.13	ND	15.50	ND		5564.02
	6.19.13	ND	15.66	ND		5563.86
	9.18.13	ND	15.96	ND		5563.56
	12.16.13	ND	15.70	ND		5563.82
	3.14.14	ND	15.39	ND		5564.13
	9.9.14	ND	16.10	ND		5563.42
	6.10.15	ND	15.28	ND		5564.24
	12.04.15	ND	15.87	ND		5563.65
	6.02.16	ND	15.47	ND		5564.05
	9.16.16	ND	16.24	ND	5579.24	5563.00
	12.19.16	ND	15.87	ND		5563.37
	6.27.17	ND	15.45	ND		5563.79
	1.09.18	ND	15.65	ND		5563.59
	6.21.18	ND	15.76	ND		5563.48
	12.13.18	ND	15.97	ND		5563.27



TABLE 3
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ELEVATIONS

Well I.D.	Date	Depth to Product (feet BTOC)	Depth to Water (feet BTOC)	Product Thickness	TOC Elevations (feet AMSL)	Groundwater Elevation* (feet AMSL)
MW-4*	9.7.12	ND	15.59	ND	5580.36	5564.77
	12.20.12	ND	15.51	ND		5564.85
	3.20.13	ND	15.25	ND		5565.11
	6.19.13	ND	15.41	ND		5564.95
	9.18.13	ND	15.74	ND		5564.62
	12.16.13	ND	15.45	ND		5564.91
	3.14.14	ND	15.14	ND		5565.22
	9.9.14	ND	15.80	ND		5564.56
	6.10.15	ND	15.06	ND		5565.30
	12.04.15	ND	15.56	ND		5564.80
	6.02.16	ND	15.22	ND	5579.95	5565.14
	9.16.16	ND	15.92	ND		5564.03
	12.19.16	ND	15.55	ND		5564.40
	6.27.17	ND	15.22	ND		5564.73
	1.09.18	ND	15.34	ND		5564.61
	6.21.18	ND	15.45	ND		5564.50
	12.13.18	ND	15.60	ND		5564.35
MW-5*	9.7.12	ND	19.35	ND	5583.53	5564.18
	12.20.12	ND	19.28	ND		5564.25
	3.20.13	ND	19.10	ND		5564.43
	6.19.13	ND	19.21	ND		5564.32
	9.17.13	ND	19.55	ND		5563.98
	12.16.13	ND	19.28	ND		5564.25
	3.14.14	ND	19.03	ND		5564.50
	9.9.14	ND	19.58	ND		5563.95
	6.10.15	ND	18.98	ND		5564.55
	12.04.15	ND	19.41	ND		5564.12
	6.02.16	ND	19.08	ND	5583.41	5564.45
	9.16.16	ND	19.69	ND		5563.72
	12.19.16	ND	19.42	ND		5563.99
	6.27.17	ND	19.12	ND		5564.29
	1.09.18	ND	19.22	ND		5564.19
	6.21.18	ND	19.27	ND		5564.14
	12.13.18	ND	19.44	ND		5563.97
MW-6*	9.7.12	ND	18.55	ND	5582.22	5563.67
	12.20.12	ND	18.49	ND		5563.73
	3.20.13	ND	18.27	ND		5563.95
	6.19.13	ND	18.38	ND		5563.84
	9.18.13	ND	18.74	ND		5563.48
	12.16.13	ND	18.46	ND		5563.76
	3.14.14	ND	18.21	ND		5564.01
	9.9.14	ND	18.75	ND		5563.47
	6.10.15	ND	18.16	ND		5564.06
	12.04.15	ND	18.60	ND		5563.62
	6.02.16	ND	18.25	ND	5581.98	5563.97
	9.16.16	ND	18.86	ND		5563.12
	12.19.16	ND	18.61	ND		5563.37
	6.27.17	ND	18.29	ND		5563.69
	1.09.18	ND	18.43	ND		5563.55
	6.21.18	ND	18.47	ND		5563.51
	12.13.18	ND	18.70	ND		5563.28



TABLE 3 Trunk 6C Kutz Wash Pipeline Release GROUNDWATER ELEVATIONS						
Well I.D.	Date	Depth to Product (feet BTOC)	Depth to Water (feet BTOC)	Product Thickness	TOC Elevations (feet AMSL)	Groundwater Elevation* (feet AMSL)
MW-7*	9.7.12	ND	19.03	ND	5582.24	5563.21
	12.20.12	ND	18.97	ND		5563.27
	3.20.13	ND	18.79	ND		5563.45
	6.19.13	ND	18.87	ND		5563.37
	9.17.13	ND	19.22	ND		5563.02
	12.16.13	ND	18.46	ND		5563.78
	3.14.14	ND	18.73	ND		5563.51
	9.9.14	ND	19.24	ND		5563.00
	6.10.15	ND	18.65	ND		5563.59
	12.04.15	ND	19.10	ND		5563.14
	6.02.16	ND	18.76	ND		5563.48
	9.16.16	ND	19.37	ND		5562.68
	12.19.16	ND	19.13	ND	5582.05	5562.92
	6.27.17	ND	18.80	ND		5563.25
	1.09.18	ND	18.95	ND		5563.10
	6.21.18	ND	18.98	ND		5563.07
	12.13.18	ND	19.22	ND		5562.83
MW-8*	9.7.12	ND	14.96	ND	5577.81	5562.85
	12.20.12	ND	14.87	ND		5562.94
	3.20.13	ND	14.63	ND		5563.18
	6.19.13	ND	14.74	ND		5563.07
	9.18.13	ND	15.08	ND		5562.73
	12.16.13	ND	14.81	ND		5563.00
	3.14.14	ND	14.53	ND		5563.28
	9.9.14**	15.12**	15.25	0.13**		5562.65
	6.10.15	ND	14.44	ND		5563.37
	12.04.15	ND	14.97	ND		5562.84
	6.02.16	ND	14.61	ND		5563.20
	9.16.16	ND	15.29	ND	5577.47	5562.18
	12.19.16	ND	15.00	ND		5562.47
	6.27.17	ND	14.62	ND		5562.85
	1.09.18	ND	14.80	ND		5562.67
	6.21.18	ND	14.88	ND		5562.59
	12.13.18	ND	15.11	ND		5562.36
MW-9*	9.7.12	ND	17.55	ND	5582.48	5564.93
	12.20.12	ND	17.47	ND		5565.01
	3.20.13	ND	17.28	ND		5565.20
	6.19.13	ND	17.42	ND		5565.06
	9.17.13	ND	17.74	ND		5564.74
	12.16.13	ND	17.48	ND		5565.00
	3.14.14	ND	17.21	ND		5565.27
	9.9.14	ND	17.83	ND		5564.65
	6.10.15	ND	17.18	ND		5565.30
	12.04.15	ND	17.61	ND		5564.87
	6.02.16	ND	17.30	ND		5565.18
	9.16.16	ND	17.94	ND	5582.35	5564.41
	12.19.16	ND	17.60	ND		5564.75
	6.27.17	ND	17.34	ND		5565.01
	1.09.18	ND	17.40	ND		5564.95
	6.21.18	ND	17.49	ND		5564.86
	12.13.18	ND	17.63	ND		5564.72



TABLE 3
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ELEVATIONS

Well I.D.	Date	Depth to Product (feet BTOC)	Depth to Water (feet BTOC)	Product Thickness	TOC Elevations (feet AMSL)	Groundwater Elevation* (feet AMSL)
MW-10*	12.16.13	ND	16.93	ND	5577.80	5560.87
	3.14.14	ND	14.63	ND		5563.17
	9.9.14	ND	15.34	ND		5562.46
	6.10.15	ND	14.58	ND		5563.22
	12.04.15	ND	15.10	ND		5562.70
	6.02.16	ND	14.74	ND		5563.06
	9.16.16	ND	15.49	ND	5578.10	5562.61
	12.19.16	ND	15.12	ND		5562.98
	6.27.17	ND	14.73	ND		5563.37
	1.09.18	ND	14.90	ND		5563.20
	6.21.18	ND	15.05	ND		5563.05
	12.13.18	ND	15.21	ND		5562.89
MW-11*	12.16.13	ND	15.15	ND	5578.65	5563.50
	3.14.14	ND	14.82	ND		5563.83
	9.9.14	ND	15.63	ND		5563.02
	6.10.15	ND	14.76	ND		5563.89
	12.04.15	ND	15.35	ND		5563.30
	6.02.16	ND	14.98	ND		5563.67
	9.16.16	ND	15.74	ND	5579.04	5563.30
	12.19.16	ND	15.35	ND		5563.69
	6.27.17	ND	15.00	ND		5564.04
	1.09.18	ND	15.11	ND		5563.93
	6.21.18	ND	15.28	ND		5563.76
	12.13.18	ND	15.45	ND		5563.59
MW-12*	12.16.13	ND	15.54	ND	5579.99	5564.45
	3.14.14	ND	15.27	ND		5564.72
	9.9.14	ND	15.96	ND		5564.03
	6.10.15	ND	15.22	ND		5564.77
	12.04.15	NG	NG	NG		NG
	6.02.16	NG	NG	NG		NG
	9.16.16	NG	NG	NG	5580.28	NG
	12.19.16	NG	NG	NG		NG
	6.27.17	NG	NG	NG		NG
	1.09.18	NG	NG	NG		NG
	6.21.18	NG	NG	NG		NG
	12.13.18	Plugged				NG
MW-13*	12.16.13	ND	19.88	ND	5583.03	5563.15
	3.14.14	ND	19.63	ND		5563.40
	9.9.14	ND	20.18	ND		5562.85
	6.10.15	ND	19.57	ND		5563.46
	12.04.15	ND	20.01	ND		5563.02
	6.02.16	ND	19.67	ND		5563.36
	9.16.16	ND	20.27	ND	5583.34	5563.07
	12.19.16	ND	20.03	ND		5563.31
	6.27.17	ND	19.74	ND		5563.60
	1.09.18	ND	19.85	ND		5563.49
	6.21.18	ND	19.89	ND		5563.45
	12.13.18	ND	20.13	ND		5563.21



TABLE 3
Trunk 6C Kutz Wash Pipeline Release
GROUNDWATER ELEVATIONS

Well I.D.	Date	Depth to Product (feet BTOC)	Depth to Water (feet BTOC)	Product Thickness	TOC Elevations (feet AMSL)	Groundwater Elevation* (feet AMSL)
MW-14	9.16.16	ND	14.48	ND	5576.39	5561.91
	12.19.16	ND	14.18	ND		5562.21
	6.27.17	ND	13.83	ND		5562.56
	1.09.18	ND	13.99	ND		5562.40
	6.21.18	ND	14.10	ND		5562.29
	12.13.18	ND	14.33	ND		5562.06
MW-15	9.16.16	ND	16.75	ND	5578.83	5562.08
	12.19.16	ND	16.48	ND		5562.35
	6.27.17	ND	16.12	ND		5562.71
	1.09.18	ND	16.30	ND		5562.53
	6.21.18	ND	16.36	ND		5562.47
	12.13.18	ND	16.60	ND		5562.23
MW-17	9.16.16	ND	16.02	ND	5579.86	5563.84
	12.19.16	ND	15.68	ND		5564.18
	6.27.17	ND	15.30	ND		5564.56
	1.09.18	ND	15.45	ND		5564.41
	6.21.18	ND	15.55	ND		5564.31
	12.13.18	ND	15.72	ND		5564.14

BTOC - below top of casing

AMSL - above mean sea level

TOC - top of casing

NG - Well not gauged, or Errant Gauge.

* - Monitoring wells resurveyed during September 2016



** - Field personnel recorded the presence of NAPL utilizing an interface probe, but the product was not visually verified.

NA - not applicable








APPENDIX C



Soil Boring/Monitoring Well Logs

 				SB-1			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous	Latitude : 36.632133° Longitude : -107.974467° Survey By : GPS Logged By : Tami Ross		
Depth in Feet	Surf. Elev. 5588	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5588	SP		SILTY SAND, brown, fine to medium grained, dry		0.0	
2	5586						
4	5584						
6	5582	SP				0.0	
8	5580			SAND, brown, coarse, moist (groundwater encountered at 15 feet)			
10	5578						
12	5576	SP				0.0	
14	5574						
16	5572						
18	5570	SP		SAND, brown, coarse, wet			
20							





02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-1.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche St. Farmington, NM 87401</div></div></div>				SB-2			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous	Latitude : 36.632267° Longitude : -107.974333° Survey By : GPS Logged By : Tami Ross		
Depth in Feet	Surf. Elev. 5586	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5586	SP		SAND, brown, dry		812	
2	5584			SAND, brown, dry			
4	5582	SP		SAND, brown, dry		3,009	
6	5580			SAND, brown, dry			
8	5578	SP		SAND, brown, coarse, dry		442	
10	5576			SAND, brown, coarse, dry			
12	5574	SP		SAND, gray, coarse, wet (groundwater encountered at 15 feet)			
14	5572			SAND, gray, coarse, wet (groundwater encountered at 15 feet)			
16							



02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-2.bor

 				SB-3			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11	Latitude : 36.631867°	Date Completed : 11/30/11	Longitude : -107.974133°
				Hole Diameter : 2.25 in.	Survey By : GPS	Drilling Method : Geoprobe	Logged By : Tami Ross
				Sampling Method : Continuous			
Depth in Feet	Surf. Elev. 5589	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5589	SP		SAND, brown, coarse, dry		1.5	
2	5587						
4	5585						
6	5583						
8	5581						
10	5579	SP				1.1	
12	5577			SAND, brown, coarse, slightly moist			
14	5575						
16	5573	SP				0.4	
18	5571			SAND, gray, coarse, wet (groundwater encountered at 15 feet)			
20							






02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-3.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche St. Farmington, NM 87401</div></div></div>				SB-4			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous		Latitude : 36.63185° Longitude : -107.973783° Survey By : GPS Logged By : Tami Ross	
Depth in Feet	Surf. Elev. 5588	USCS	GRAPHIC	DESCRIPTION		Blow Count	PID (ppm) 0,20,5
0	5588	SP		SAND, brown, dry		30.2	
2	5586						
4	5584						
6	5582	SP		SAND, brown, coarse, moist		2.5	
8	5580						
10	5578						
12	5576	SP				0.0	
14	5574						
16	5572						
18	5570	SP		SAND, gray, coarse, wet (groundwater encountered at 18 feet)		0.5	
20							






02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-4.bor

 				SB-5			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous	Latitude : 36.632317° Longitude : -107.974117° Survey By : GPS Logged By : Tami Ross		
Depth in Feet	Surf. Elev. 5585	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5585	SP		SAND, brown, loose, dry		0.0	
2	5583						
4	5581						
6	5579	SP				14.6	
8	5577			SAND, brown, loose, moist			
10	5575						
12	5573	SP		SAND, grey, coarse, wet (groundwater encountered at 13 feet)		26.2	
14	5571						
16							



02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-5.bor

 				SB-6			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous	Latitude : 36.632183° Longitude : -107.973883° Survey By : GPS Logged By : Tami Ross		
Depth in Feet	Surf. Elev. 5585	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5585	SP		SAND, brown, loose, dry		0.0	
2	5583						
4	5581						
6	5579	SP		SAND, brown, coarse, moist		0.0	
8	5577						
10	5575						
12	5573	SP		SAND, gray, coarse, wet (groundwater encountered at 15 feet)			
14	5571						
16							










02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-6.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche St. Farmington, NM 87401</div></div></div>				SB-7			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous		Latitude : 36.63205° Longitude : -107.973983° Survey By : GPS Logged By : Tami Ross	
Depth in Feet	Surf. Elev. 5588	USCS	GRAPHIC	DESCRIPTION		Blow Count	PID (ppm) 0,20,5
0	5588	SW		Backfill			1,982
2	5586						
4	5584						
6	5582						
8	5580	SP		SAND, brown, coarse, moist			
10	5578						
12	5576	SP		SAND, gray, black silt, coarse, moist			
14	5574						
16	5572	SP		SAND, gray, coarse/small rocks, wet (groundwater encountered at 17 feet)			
18	5570						
20							








02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-7.bor

 				SB-8			
LATERAL 6C PIPELINE RELEASE ENTERPRISE PRODUCTS COMPANY SAN JUAN COUNTY, NEW MEXICO				Date Started : 11/30/11 Date Completed : 11/30/11 Hole Diameter : 2.25 in. Drilling Method : Geoprobe Sampling Method : Continuous	Latitude : 36.6323° Longitude : -107.97422° Survey By : GPS Logged By : Tami Ross		
Depth in Feet	Surf. Elev. 5586	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm) 0,20,5	
0	5586	SP		SAND, brown, loose, dry		364	
2	5584						
4	5582						
6	5580						
8	5578	SP		SAND, brown, loose, moist		134	
10	5576						
12	5574	SP		SAND, dark gray, coarse, wet (groundwater encountered at 13 feet)		36	
14	5572						
16	5570	SP		SAND, gray, coarse/small rocks, wet			
18	5568						
20							


02-22-2012 S:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\SB-8.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div></div></div>				MW-1			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/20/12 Date Completed : 8/20/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63216 Long. : W107.97405 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5577	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5577	SC		Clayey Sand, Brown, Dry, No Odor, No Staining	85.8		<div>Well: MW-1 Elev: 5579.73</div> <div></div>
2	5575						
4	5573	SM		Silty Sand, Brown, Fine Grained, Dry, No Odor, No Staining	87.4		
6	5571						
8	5569	SP		Sand, Brown/Tan, Moist, No Odor, No Staining	190		
10	5567						
12	5565	SP		Sand, Brown, Fine Grained, Wet, Very Little Recovery, Slight Odor	NA		
14	5563						
16	5561	CG		Cobble/Gravel, Brown, Wet, No Odor, No Staining	2.4		
18	5559						
20	5557	SP		Cobble/Gravel, Brown, Wet, No Odor, No Staining	15.3		
22	5555						
24	5553						
26		SP		Sand, Gray, Fine Grained, Wet, Slight Odor, Slight Staining			








11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-1.bor

<div><div><div>AES</div><div></div></div><div><div>Animas Environmental Services, LLC.</div><div>624 East Comanche Farmington, NM 87401</div></div></div>				MW-2			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/20/12 Date Completed : 8/20/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63228 Long. : W107.97419 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5577	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	<div>Well: MW-2 Elev: 5579.39</div> <div></div>
0	5577	SP		Sand, Brown, Fine Grained, Moist, No Odor, No Staining	93.1		
2	5575						
4	5573						
6	5571						
8	5569	SP		Sand, Brown, Moist/Wet, No Odor, No Staining	108		
10	5567						
12	5565						
14	5563	SP		Sand, Brown, Medium Grained, Wet, Very Little Recovery, No Odor, No Staining	NA		
16	5561						
18	5559						
20	5557	CG		Cobble/Gravel, Brown, Wet, Slight Odor, No Staining	38.7		
22	5555						
24	5553						
26		SS		Sandstone, Gray, Fine Grained, Wet, Slight Odor, No Staining	16.1		


Well: MW-2
Elev: 5579.39











11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-2.bor

		Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401		MW-3			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/21/12 Date Completed : 8/21/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63230 Long. : W107.97403 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5577	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5577	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	5.6		
2	5575						
4	5573						
6	5571						
8	5569	SP		Sand, Brown, Fine Grained, Wet, No Odor, No Staining	2.8		
10	5567						
12	5565						
14	5563	SP		Sand, Gray, Fine to Medium Grained, Wet, No Odor, No Staining	2.9		
16	5561						
18	5559						
20	5557	SP		Sand, Gray, Fine to Coarse Grained, Some Gravel, Wet, No Odor, No Staining	0.8		
22	5555						
24	5553						
26		SS		Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining	2.1		
					2.3		


Well: MW-3
 Elev: 5579.52











11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-3.bor

 <div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div>				MW-4			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/21/12 Date Completed : 8/21/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63230 Long. : W107.97403 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5578	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	<div>Well: MW-4 Elev: 5580.36</div> 
0	5578	SC		Interbedded Sand and Clay, Brown, Fine Grained, Dry, No Odor, No Staining	22.1		
2	5576						
4	5574						
6	5572	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	54.8		
8	5570						
10	5568	SP		Sand, Brown, Fine Grained, Wet, No Odor, No Staining	58.2		
12	5566						
14	5564	SP		Sand, Brown, Fine Grained, Wet, No Odor, No Staining, Very Little Recovery	NA		
16	5562						
18	5560	SP		No Recovery	NA		
20	5558						
22	5556	SS			3.6		
24	5554						
26				Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining			









Well: MW-4
 Elev: 5580.36




11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-4.bor

		Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401		MW-5			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/23/12 Date Completed : 8/23/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63182 Long. : W107.97417 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5581	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5581	SC		Interbedded Sand and Clay, Brown, Fine Grained, Dry, No Odor, No Staining	0.4		<div>Well: MW-5 Elev: 5583.53</div> 
2	5579						
4	5577						
6	5575	SC		Clayey Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.5		
8	5573						
10	5571	SP		Sand, Brown, Fine Grained, Wet, No Odor, No Staining	0.9		
12	5569						
14	5567	SC		Clayey Sand, Brown, Fine Grained, Wet, No Odor, No Staining	0.7		
16	5565						
18	5563	SP		Sand, Brown, Fine to Coarse Grained, Wet, Some Gravel, No Odor, No Staining	0.6		
20	5561						
22	5559	SS			0.8		
24	5557						
26				Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining			









11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-5.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div></div></div>				MW-6			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/23/12 Date Completed : 8/23/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63201 Long. : W107.97427 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5580	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5580	SM		Silty Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.3		<div>Well: MW-6 Elev: 5582.22</div> <div></div>
2	5578						
4	5576	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.5		
6	5574						
8	5572	SP		Sand, Brown, Fine Grained, Wet, No Odor, No Staining	0.6		
10	5570						
12	5568	SP		Sand, Brown, Fine Grained, Some Clay, Wet, Slight Odor, Slight Staining	3.0		
14	5566						
16	5564	SP		Sand, Brown, Fine Grained, Some Clay, Wet, Slight Odor, Slight Staining	NA		
18	5562						
20	5560	SP		Sand, Brown, Fine to Coarse Grained, Some Gravel, Very Little Recovery, No Staining	1.9		
22	5558						
24	5556	SS		Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining			
26							


Well: MW-6
 Elev: 5582.22






11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-6.bor

<div><div><div>AES</div><div></div></div><div><div>Animas Environmental Services, LLC.</div><div>624 East Comanche Farmington, NM 87401</div></div></div>				MW-7			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/23/12 Date Completed : 8/23/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.632122 Long. : W107.97444 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5579	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5579	SM		Silty Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.5		<div>Well: MW-7 Elev: 5582.24</div> <div></div>
2	5577						
4	5575	SC		Clayey Sand, Brown, Moist, No Odor, No Staining	0.6		
6	5573						
8	5571	SP		Sand, Brown, Fine Grained, Moist, No Odor, No Staining	0.5		
10	5569						
12	5567	SP		Sand, Brown, Fine Grained, Some Clay, Wet, Slight Odor, Slight Staining	0.7		
14	5565						
16	5563	SP		Sand, Brown, Fine Grained, Some Clay, Wet, Slight Odor, Slight Staining	0.7		
18	5561						
20	5559	SP		Sand, Brown, Fine to Coarse Grained, Some Gravel, Wet, No Odor, No Staining	0.5		
22	5557						
24	5555	SS		Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining	0.8		
26							


Well: MW-7
Elev: 5582.24











11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-7.bor

<div><div>AES</div><div><div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div></div></div>				MW-8			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/21/12 Date Completed : 8/21/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63245 Long. : W107.97430 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5576	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	
0	5576	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	82.8		<div>Well: MW-8 Elev: 5577.81</div> <div><p>Stickup Completion 4"x4" Steel Concrete Bentonite Seal 2" PVC Casing Sand Pack (10/20) 2" PVC 0.010" Screen</p></div>
2	5574						
4	5572	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	219		
6	5570						
8	5568	SP		Sand, Brown, Fine Grained, Wet, Slight Odor, No Staining	144		
10	5566						
12	5564	SP		Sand, Gray, Fine to Medium Grained, Wet, Slight Odor, No Staining	147		
14	5562						
16	5560	SP		Sand, Gray, Fine to Medium Grained, Some Gravel, Wet, Slight Odor, No Staining	87.3		
18	5558						
20	5556	SP					
22	5554						
24	5552	SS					
26							


Well: MW-8
 Elev: 5577.81




11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-8.bor

<div><div><div>AES</div><div></div></div><div><div>Animas Environmental Services, LLC.</div><div>624 East Comanche Farmington, NM 87401</div></div></div>				MW-9			
ENTERPRISE PRODUCTS COMPANY LATERAL 6C PIPELINE GW INVESTIGATION SAN JUAN COUNTY, NEW MEXICO NE1/4 SW1/4, SEC. 26, T28N, R11W N36.63202, W107.97400				Date Started : 8/23/12 Date Completed : 8/23/12 Hole Diameter : 2.25 Drilling Method : HSA Sampling Method : Split Spoon		Lat. : N36.63185 Long. : W107.97378 Survey By : Enterprise Products Co. Logged By : Tom Long	
Depth in Feet	Surf. Elev. 5580	USCS	GRAPHIC	DESCRIPTION	Blow Count	PID (ppm)	<div>Well: MW-9 Elev: 5582.48</div> <div></div>
0	5580	SP		Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.3		
2	5578						
4	5576	SM		Silty Sand, Brown, Fine Grained, Dry, No Odor, No Staining	0.3		
6	5574						
8	5572	SP		Sand, Brown, Fine Grained, Moist, No Odor, No Staining	0.4		
10	5570						
12	5568	SP		Sand, Gray, Fine to Medium Grained, Wet, No Odor, No Staining	0.2		
14	5566						
16	5564	SP		Sand, Gray, Some Gravel, Wet, No Odor, No Staining	0.1		
18	5562						
20	5560	SS		Sandstone, Gray, Fine Grained, Wet, No Odor, No Staining			
22	5558						
24	5556						
26							


Well: MW-9
 Elev: 5582.48



11-05-2012 R:\Animas 2000\2012 Projects\Enterprise\Lateral 6C\Soil Boring Logs\GW Investigation\MW-9.bor

 Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401				LOG OF : MW-10	
ENTERPRISE FIELD SERVICES, LLC LATERAL 6C SEPT. 2011 PIPELINE RELEASE NE1/4 SW1/4 SEC. 26, T28N, R11W SAN JUAN COUNTY, NEW MEXICO N36.63202, W107.97400				Date Started : 10/16/13 Date Completed : 10/16/13 Hole Diameter : 2.35 in. Drilling Method : GeoProbe Sampling Method : Continuous	
				Latitude : To Be Surveyed Longitude : To Be Surveyed Survey By : Logged By : H. Woods	
Depth in Feet	Surf. Elev.	USCS	GRAPHIC	DESCRIPTION	PID (ppm)
0				Silty Sand, Brown, Moist, Very Fine to Fine Grained, No Staining, No Odor	
2		SM			0.2
4				Poorly Graded Sand with Silt, Brown, Dry to Moist, Fine to Medium Grained, No Staining, No Odor	
6		SP			1.7
8					
10					23.8
12		SP		Poorly Graded Sand, Brown, Moist, Fine to Medium Grained, No Staining, Moderate to Heavy Odor	
14		SC		Clayey Sand, Brown to Black, Moist to Wet at 14 feet, Moderate to Heavy Staining, Heavy Odor to 14.5 feet	786
16		SC		Clayey Sand, Brown to Gray, Wet, Slight to No Staining, Slight to No Odor	
18					
20					

Well: MW-10
Elev.: TBS



Stick-Up Cover

Concrete







Bentonite Seal

1" PVC Casing






Sand Pack (20/40)

1" PVC 0.010" with Pre-Pack Screen











11-20-2013 R:\Animas 2000\Dropbox\2013 Projects\Enterprise\Lateral 6C\Soil Boring Logs\MW-10.bor

 <div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div>		LOG OF : MW-11				
ENTERPRISE FIELD SERVICES, LLC LATERAL 6C SEPT. 2011 PIPELINE RELEASE NE1/4 SW1/4 SEC. 26, T28N, R11W SAN JUAN COUNTY, NEW MEXICO N36.63202, W107.97400		Date Started : 10/16/13 Date Completed : 10/16/13 Hole Diameter : 2.35 in. Drilling Method : GeoProbe Sampling Method : Continuous		Latitude : To Be Surveyed Longitude : To Be Surveyed Survey By : Logged By : H. Woods		
Depth in Feet	Surf. Elev.	USCS	GRAPHIC	DESCRIPTION	PID (ppm)	<div>Well: MW-11 Elev.: TBS</div> <div></div>
0		SM		Silty Sand, Brown, Moist to Dry, Very Fine Grained, No Staining, No Odor	0.0	
2						
4		SP		Poorly Graded Sand, Brown, Moist, Fine to Medium Grained, No Staining, No Odor, Silty Sand Lense at 7.5 feet, Trace Gravel from 8 to 12 feet	0.0	
6						
8						
10						
12		SC		Clayey Sand, Brown, Moist to Wet at 14 feet, Fine to Medium Grained	0.0	
14						
16		SP		Poorly Graded Sand, Brown to Gray, Wet, Fine to Large Grained, Traces of Gravel, No Staining, No Odor, Trace Silt		
18						
20						



11-20-2013 R:\Animas 2000\Dropbox\2013 Projects\Enterprise\Lateral 6C\Soil Boring Logs\MW-11.bor

 Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401				LOG OF : MW-12			
ENTERPRISE FIELD SERVICES, LLC LATERAL 6C SEPT. 2011 PIPELINE RELEASE NE1/4 SW1/4 SEC. 26, T28N, R11W SAN JUAN COUNTY, NEW MEXICO N36.63202, W107.97400				Date Started : 10/16/13 Date Completed : 10/16/13 Hole Diameter : 2.35 in. Drilling Method : GeoProbe Sampling Method : Continuous		Latitude : To Be Surveyed Longitude : To Be Surveyed Survey By : Logged By : H. Woods	
Depth in Feet	Surf. Elev.	USCS	GRAPHIC	DESCRIPTION	PID (ppm)	Well: MW-12 Elev.: TBS 	
0		SC		Clayey Sand, Brown, Moist, Fine to Medium Grained, No Staining, No Odor	0.0		
2							
4		SP		Interbedded Poorly Graded Sand with Silt, Clayey Sand and Silty Sand Lenses 0.5 to 1 foot, Brown, Moist to Dry, No Staining, No Odor	0.0		
6							
8							
10		SP		Sand, Brown to Gray, Moist to Wet at 14 feet, Fine to Medium Grained, Traces of Large Grains Increasing with Depth, No Staining, No Odor	0.0		
12							
14					0.0		
16							
18							
20							



11-20-2013 R:\Animas 2000\Dropbox\2013 Projects\Enterprise\Lateral 6C\Soil Boring Logs\MW-12.bor

 <div>Animas Environmental Services, LLC. 624 East Comanche Farmington, NM 87401</div>		LOG OF : MW-13				
ENTERPRISE FIELD SERVICES, LLC LATERAL 6C SEPT. 2011 PIPELINE RELEASE NE1/4 SW1/4 SEC. 26, T28N, R11W SAN JUAN COUNTY, NEW MEXICO N36.63202, W107.97400		Date Started : 10/16/13 Date Completed : 10/16/13 Hole Diameter : 2.35 in. Drilling Method : GeoProbe Sampling Method : Continuous		Latitude : To Be Surveyed Longitude : To Be Surveyed Survey By : Logged By : H. Woods		
Depth in Feet	Surf. Elev.	USCS	GRAPHIC	DESCRIPTION	PID (ppm)	<div>Well: MW-13 Elev.: TBS</div>  <div>Stick-Up Cover</div> <div>Concrete</div> <div>Bentonite Seal</div> <div>1" PVC Casing</div> <div>Sand Pack (20/40)</div> <div>1" PVC 0.010" with Pre-Pack Screen</div>
0		SC		Clayey Sand, Brown, Fine to Medium Grained, No Staining, No Odor	0.0	
2						
4						
6		SP		Poorly Graded Sand with Silt, Brown, Fine to Medium Grained, Moist to Dry, No Staining, No Odor	0.0	
8						
10		CL		Lean Clay Lense, Brown, Moist, No Staining, No Odor	0.0	
12		SP		Sand with Silt, Brown, Fine to Medium Grained, Moist to Dry, No Staining, No Odor		
14						
16		SC		Lean Clay Grading to Clayey Sand, Brown, Fine Grained, Moist, No Staining, No Odor	0.0	
18		SP		Poorly Graded Sand, Brown, Moist, Fine to Medium Grained, No Staining, No Odor		
20						
22		SC		Clayey Sand, Brown with Orange Lenses, Fine Grained, Moist to Wet at 18 feet, No Staining, No Odor	0.0	
24		SP		Sand, Brown with 2 to 3 inch Orange and Gray Lenses, Wet, Medium Grained, Slight to No Staining, No Odor		


11-20-2013 R:\Animas 2000\Dropbox\2013 Projects\Enterprise\Lateral 6C\Soil Boring Logs\MW-13.bor

 Apex TITAN, Inc. 606 South Rio Grande, Suite A Aztec, New Mexico 87410 Phone: (505) 334-5200 www.apexcos.com A Subsidiary of Apex Companies, LLC				Trunk 6C Kutz Wash Pipeline Release SW 1/4 Sec 26, T28N, R11W San Juan County, New Mexico 36.63202 N, 107.97400 W Project No. 725040112183				Soil Boring/Monitoring Well <h1>MW-14</h1>			
Date Sampled: <u>9/6/2016</u> Drilled by: <u>Earthworx</u> Driller: <u>L. Trujillo</u> Logged by: <u>R. Deechilly</u> Sampler: <u>R. Deechilly</u> Project Manager: <u>K. Summers</u>				Ground Surface Elevation: <u>5573.63'</u> Top of Casing Elevation: <u>5579.39'</u> North Coordinate: <u>2049613.84</u> West Coordinate: <u>2681706.40</u> Bench Mark Elevation: <u>5575.44'</u> GW Elev: <u>At Completion</u> <u>At Well Stabilization</u>				Borehole Diameter: <u>3.25"</u> Casing Diameter: <u>2"</u> Well Materials: <u>0.010" SCH40 PVC</u> Surface Completion: <u>Above Ground Vault</u> Boring Method: <u>Geoprobe</u>			
Depth (Feet BGS)	Sample Interval	Sample ID	Recovery (%)	PID Value (ppm)	Groundwater Elevation	Geologic Symbol	Geologic Description	Boring/Well Completion (Graphic Depiction)			
0			0	-			NO RECOVERY, Hydrovac				
2.5											
5											
7.5			60	0.0			SAND, Light Olive Gray, Medium to Coarse Grained, No Staining, Moist, No Odor				
10											
12.5		12-16	35	0.0			SAND, Light Olive Gray, Coarse Grained, No Staining, Wet, No Odor				
15				0.0			SAND, Light Olive Gray, Coarse to Very Coarse Grained, with Trace Gravel, No Staining, Wet to Very Wet, No Odor				
17.5			85	0.0							
20							Bottom of Boring at 20 Feet BGS				
22.5											
25							NOTE: Survey Elevations are Listed in Feet as Measured at Local OPUS Adjusted Control Point. Coordinates are Listed in Feet, NAD 1983 2011 State Plane New Mexico West FIPS 3003				



C:\Users\jsimpson\appdata\local\temp\AcPublish_11712\Boring Logs.dwg Modified 10/4/2016 by JSimpson

 Apex TITAN, Inc. 606 South Rio Grande, Suite A Aztec, New Mexico 87410 Phone: (505) 334-5200 www.apexcos.com A Subsidiary of Apex Companies, LLC				Trunk 6C Kutz Wash Pipeline Release SW 1/4 Sec 26, T28N, R11W San Juan County, New Mexico 36.63202 N, 107.97400 W Project No. 725040112183				Soil Boring/Monitoring Well <h1 style="color: blue;">MW-15</h1>			
Date Sampled: <u>9/6/2016</u> Drilled by: <u>Earthworx</u> Driller: <u>L. Trujillo</u> Logged by: <u>R. Deechilly</u> Sampler: <u>R. Deechilly</u> Project Manager: <u>K. Summers</u>				Ground Surface Elevation: <u>5575.93'</u> Top of Casing Elevation: <u>5578.83'</u> North Coordinate: <u>2049549.05</u> West Coordinate: <u>2681664.07</u> Bench Mark Elevation: <u>5575.44'</u> GW Elev: <u>At Completion</u> <u>At Well Stabilization</u>				Borehole Diameter: <u>3.25"</u> Casing Diameter: <u>2"</u> Well Materials: <u>0.010" SCH40 PVC</u> Surface Completion: <u>Above Ground Vault</u> Boring Method: <u>Geoprobe</u>			
Depth (Feet BGS)	Sample Interval	Sample ID	Recovery (%)	PID Value (ppm)	Groundwater Elevation	Geologic Symbol	Geologic Description	Boring/Well Completion (Graphic Depiction)			
0							NO RECOVERY, Hydrovac				
2.5			0	-							
5											
7.5							SILTY SAND, Light Olive Gray, Fine Grained, No Staining, Moist, No Odor				
10			100	0.0			SAND, Light Olive Gray, Medium Grained, with Trace Silt, No Staining, Moist, No Odor				
12.5				0.2			SAND, Light Olive Gray, Medium to Coarse Grained, with Trace Gravel, No Staining, Moist, No Odor				
15		14-16	100	1,062	9/6/2016		SAND, Medium Dark Gray, Medium to Coarse Grained, Staining, Wet, Strong Hydrocarbon Odor				
17.5				0.0			SAND, Light Olive Gray, Coarse Grained, No Staining, Wet, No Odor				
20			100	0.0			Becoming Saturated at 18 Feet BGS				
22.5							Bottom of Boring at 20 Feet BGS				
25							NOTE: Survey Elevations are Listed in Feet as Measured at Local OPUS Adjusted Control Point. Coordinates are Listed in Feet, NAD 1983 2011 State Plane New Mexico West FIPS 3003				



C:\Users\jsimpson\appdata\local\temp\AcPublish_11712\Boring Logs.dwg Modified 10/4/2016 by JSimpson

 Apex TITAN, Inc. 606 South Rio Grande, Suite A Aztec, New Mexico 87410 Phone: (505) 334-5200 www.apexcos.com A Subsidiary of Apex Companies, LLC				Trunk 6C Kutz Wash Pipeline Release SW 1/4 Sec 26, T28N, R11W San Juan County, New Mexico 36.63202 N, 107.97400 W Project No. 725040112183				Soil Boring/Monitoring Well <h1 style="color: blue;">SB-16A</h1>			
Date Sampled: <u>9/6/2016</u> Drilled by: <u>Earthworx</u> Driller: <u>L. Trujillo</u> Logged by: <u>R. Deechilly</u> Sampler: <u>R. Deechilly</u> Project Manager: <u>K. Summers</u>				Ground Surface Elevation: <u>N/A</u> Top of Casing Elevation: <u>N/A</u> North Coordinate: <u>N/A</u> West Coordinate: <u>N/A</u> Bench Mark Elevation: <u>N/A</u> GW Elev: <u>▽</u> At Completion <u>▽</u> At Well Stabilization				Borehole Diameter: <u>3.25"</u> Casing Diameter: <u>N/A</u> Well Materials: <u>N/A</u> Surface Completion: <u>N/A</u> Boring Method: <u>Geoprobe</u>			
Depth (Feet BGS)	Sample Interval	Sample ID	Recovery (%)	PID Value (ppm)	Groundwater Elevation	Geologic Symbol	Geologic Description	Boring/Well Completion (Graphic Depiction)			
0			0	-			NO RECOVERY, Hydrovac				
2.5											
5											
7.5			70	1.0			SAND, Light Olive Gray, Medium Grained, No Staining, Moist, No Odor				
10				1.2							
12.5		12-14	70	0.3			SAND, Light Olive Gray, Coarse to Very Coarse Grained, No Staining, Wet to Very Wet, No Odor				
15				0.0							
17.5			85	0.0			SAND, Light Olive Gray, with Trace Gravel, Coarse to Very Coarse Grained, No Staining, Saturated, No Odor				
20				0.0			Bottom of Boring at 20 Feet BGS				
22.5											
25											

C:\Users\jsimpson\appdata\local\temp\AcPublish_11712\Boring Logs.dwg Modified 10/4/2016 by JSimpson

 Apex TITAN, Inc. 606 South Rio Grande, Suite A Aztec, New Mexico 87410 Phone: (505) 334-5200 www.apexcos.com A Subsidiary of Apex Companies, LLC				Trunk 6C Kutz Wash Pipeline Release SW 1/4 Sec 26, T28N, R11W San Juan County, New Mexico 36.63202 N, 107.97400 W Project No. 725040112183				Soil Boring/Monitoring Well <h1>MW-17</h1>			
Date Sampled: <u>9/6/2016</u> Drilled by: <u>Earthworx</u> Driller: <u>L. Trujillo</u> Logged by: <u>R. Deechilly</u> Sampler: <u>R. Deechilly</u> Project Manager: <u>K. Summers</u>				Ground Surface Elevation: <u>5577.16'</u> Top of Casing Elevation: <u>5579.86'</u> North Coordinate: <u>2049413.60</u> West Coordinate: <u>2681834.71</u> Bench Mark Elevation: <u>5575.44'</u> GW Elev: <u>At Completion</u> <u>At Well Stabilization</u>				Borehole Diameter: <u>3.25"</u> Casing Diameter: <u>2"</u> Well Materials: <u>0.010" SCH40 PVC</u> Surface Completion: <u>Above Ground Vault</u> Boring Method: <u>Geoprobe</u>			
Depth (Feet BGS)	Sample Interval	Sample ID	Recovery (%)	PID Value (ppm)	Groundwater Elevation	Geologic Symbol	Geologic Description	Boring/Well Completion (Graphic Depiction)			
0			0	-			NO RECOVERY, Hydrovac				
7.5	7-12		25	3,094		SAND, Light Olive Gray, Medium Grained, No Staining, Moist, Moderate Hydrocarbon Odor					
12.5	12-14		40	2,198		SAND, Medium Gray, with Trace Clay, Medium to Coarse Grained, Staining, Wet, Strong Hydrocarbon Odor					
15				52		SAND, Light Olive Gray, Coarse Grained, No Staining, Wet, No Odor					
17.5			70	9.3		SAND, Light Olive Gray, with Trace Gravel, Coarse Grained, No Staining, Very Wet to Saturated, No Odor					
20				3.7		Bottom of Boring at 20 Feet BGS					
22.5							NOTE: Survey Elevations are Listed in Feet as Measured at Local OPUS Adjusted Control Point. Coordinates are Listed in Feet, NAD 1983 2011 State Plane New Mexico West FIPS 3003				

C:\Users\jsimpson\appdata\local\temp\AcPublish_11712\Boring Logs.dwg Modified 10/4/2016 by JSimpson

 Apex TITAN, Inc. 606 South Rio Grande, Suite A Aztec, New Mexico 87410 Phone: (505) 334-5200 www.apexcos.com A Subsidiary of Apex Companies, LLC				Trunk 6C Kutz Wash Pipeline Release SW 1/4 Sec 26, T28N, R11W San Juan County, New Mexico 36.63202 N, 107.97400 W Project No. 725040112183				Soil Boring/Monitoring Well <h1 style="color: blue;">SB-18A</h1>			
Date Sampled: <u>9/6/2016</u> Drilled by: <u>Earthworx</u> Driller: <u>L. Trujillo</u> Logged by: <u>R. Deechilly</u> Sampler: <u>R. Deechilly</u> Project Manager: <u>K. Summers</u>				Ground Surface Elevation: <u>N/A</u> Top of Casing Elevation: <u>N/A</u> North Coordinate: <u>N/A</u> West Coordinate: <u>N/A</u> Bench Mark Elevation: <u>N/A</u> GW Elev: <u>▽ At Completion</u> <u>▽ At Well Stabilization</u>				Borehole Diameter: <u>3.25"</u> Casing Diameter: <u>N/A</u> Well Materials: <u>N/A</u> Surface Completion: <u>N/A</u> Boring Method: <u>Geoprobe</u>			
Depth (Feet BGS)	Sample Interval	Sample ID	Recovery (%)	PID Value (ppm)	Groundwater Elevation	Geologic Symbol	Geologic Description	Boring/Well Completion (Graphic Depiction)			
0							NO RECOVERY, Hydrovac				
2.5			0	-							
5											
7.5			35	0.7			SAND, Light Olive Gray, with Trace Silt, Fine to Medium Grained, No Staining, Moist, No Odor				
10											
12.5			50	27			SAND, Light Olive Gray, Medium to Coarse Grained, No Staining, Moist, No Odor				
15	X	14-16		315	<u>9/6/2016</u> 		SAND, Medium Dark Gray, Medium to Coarse Grained, Apparent Staining, Wet, Moderate Hydrocarbon Odor				
17.5			70	104			SAND, Light Olive Gray, Coarse Grained, No Staining, Very Wet to Saturated, Hydrocarbon Odor				
20				0.3							
22.5											
25							Bottom of Boring at 20 Feet BGS				

C:\Users\jsimpson\appdata\local\temp\AcPublish_11712\Boring Logs.dwg Modified 10/4/2016 by JSimpson



APPENDIX D

Public Notice and Landowner Table

Enterprise proposes the following verbiage for public notice:

Enterprise Field Services, LLC (Enterprise) hereby announces the publication of a Stage 1 Abatement Plan for soil and groundwater impacts identified at the Trunk 6C Kutz Wash pipeline release site located at latitude 36.63202° and longitude -107.97400° within the southwest (SW) ¼, in Section 26 of Township 28 North, Range 11 West in rural San Juan County, approximately 7 miles southeast of Bloomfield.

On September 11, 2011, a release of natural gas condensate was identified due to a leak on the Trunk 6C pipeline. Initial site assessments and subsurface investigations performed at the Site between October 2011 and September 2016 concluded that soil and groundwater impacts were present above applicable New Mexico (NM) Energy, Minerals and Natural Resource Department (EMNRD) Oil Conservation Division (OCD) standards for soil and Water Quality Control Commission (WQCC) standards for groundwater. The current extent of groundwater impact is estimated to be less than 0.3 acres. No surface water was impacted.

The Director of the NM EMNRD OCD has approved a Stage 1 Abatement Plan in which Enterprise proposes implementation of groundwater monitoring at the site to evaluate the concentrations of constituents of concern (COC) and the implementation of additional site-specific aquifer characterization. The data obtained from the Stage 1 Abatement Plan activities will be evaluated to determine a preferred abatement plan remediation option at the site. In order to determine that the Stage 1 Abatement Plan is administratively complete, the NM EMNRD OCD Director has complied with Subsection B of 19.15.30.15 of the New Mexico Administrative Code (NMAC) by reviewing the document and concluding that it satisfies the requirements of Subsection C of 19.15.30.13 NMAC.

Members of the public may view a copy of the Stage 1 Abatement Plan at the NM EMNRD OCD's Santa Fe office located at 1220 South St Francis Drive, #3, Santa Fe, New Mexico or at the NM EMNRD OCD's district office at 1000 Rio Brazos Road, Aztec, New Mexico. Additionally, the Stage 1 Abatement Plan is available for viewing electronically on the NM EMNRD OCD public database at <http://www.emnrd.state.nm.us/OCD/>.

The NM EMNRD OCD is accepting written comments and requests for consideration if they are received within 30 days after the publication date of this public notice. Any person seeking to comment on a Stage 1 Abatement Plan should submit written comments to:

Mr. Corey Smith
Environmental Specialist
New Mexico Oil Conservation Division
1000 Rio Brazos Road
Aztec, New Mexico 87410

The NM EMNRD OCD shall distribute notice of the submittal of the Stage 1 Abatement Plan with the next division and commission hearing docket following receipt of the plan.

Additional information can be obtained from the Enterprise project contact:

Gregory E. Miller, P.G.
1100 Louisiana Street
Houston, Texas 77002-5227
(713) 381-8780

Table A
Property Owners Within One (1) Mile Radius

Trunk 6C Kutz Wash Pipeline Release
San Juan County, New Mexico
Enterprise Field Services, LLC

Parcel Number	Owner Name	Owner Address	Owner City, State, Zip Code
2099199900900	Federal	6251 College Blvd., Suite A	Farmington, NM 87402

State of New Mexico
Energy, Minerals and Natural Resources Department

Michelle Lujan Grisham
Governor

Dylan M. Fuge
Deputy Secretary

Dylan Fuge, Division Director (Acting)
Oil Conservation Division



Greg E Miller
Enterprise Field Services, LLC
PO Box 4324
Houston, TX 77210

RE: Determination of Administratively Complete Stage 1 Abatement Plan & Public Notice and Participation for the Trunk 6C Kutz Wash Pipeline Release (Incident #nJK1201237146) 3R-438 & AP-131

Mr. Miller,

The Oil Conservation Division (OCD) received a Stage 1 Abatement Plan as well as a Proposed Public Notice and Participation submittal prepared on Enterprise Field Services, LLC's behalf by Ensolum, LLC. OCD has reviewed the plan and determined it to be administratively complete. In addition, OCD also approves the proposed draft of the Public Notice and Participation Proposal. The required public notice and participation should now proceed under the provisions of Subsections A and B of 19.15.30.15 NMAC. Proof of Public Notice must be provided to the OCD.

According to Table 2 of the Stage 1 Abatement Plan, MW-12 has not been sampled since 6/12/2015. Either the well must be re-drilled or the casing obstruction that has prevented access down the well must be removed for continued sampling.

Additionally, please include sampling analysis for TPH (MRO, DRO, GRO) using EPA method 8015M/B for lab analysis, due to the past presence of NAPL in wells MW-1, MW-2, and MW-8. Include sampling analysis for Polycyclic aromatic hydrocarbons (PAH), EPA method 8100.

The division shall distribute notice of an abatement plan's filing with the next division and commission hearing docket following the plan's receipt.

OCD's approval of the Stage 1 Abatement Plan does not relieve Enterprise of any other requirements imposed by any other regulatory agencies.

If you have any questions, please contact Mike Buchanan of the Environmental Incident Group at (505) 490-0798 or by email at michael.buchanan@emnrd.nm.gov.

Respectfully,

Rosa M Romero

Rosa Romero Environmental
Bureau Chief
RR/mb

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 265681

CONDITIONS

Operator: Enterprise Field Services, LLC PO Box 4324 Houston, TX 77210	OGRID: 241602
	Action Number: 265681
	Action Type: [UF-GWA] Ground Water Abatement (GROUND WATER ABATEMENT)

CONDITIONS

Created By	Condition	Condition Date
michael.buchanan	Stage 1 Abatement Plan reviewed and conditionally approved. Letter of determination sent electronically on 01/25/2024.	1/25/2024