State of New Mexico

Form C-101 Permit 49873

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

A.	PPLICATI					11/7		T			
Operator Name and Address COMOCODIUM LIPS COMPANIX									2. OGR		per
CONOCOPHILLIPS COMPANY 3401 E. 30TH STREET									21	7817	
				ON, NM 87402					3. API 1	Amber	
				,					30-02	25-383	64
	4. Property Co.	de		9	5. Property Nar	ne		168	i ii	6. W	ell No.
	31257			VACUUM	GLORIETA	EAST UN	IIT		Ę.	0	25
				7. S	urface Loc	ation					
UL - Lo	ot Section						e Feet From		E/W Line Con		County
K	32	17S	351	E K	2630			W		LEA	
	•	•	•	8 P	ool Inform	ation					
ACUU	M;GLORIET	'A		0.1	001 11110111				2.0		621
	•			Addition	al Well In	formatio			385		
0.32	ork Type	10. Wel	Time	10	an wen m able/Rotary	iormatio		. Lease Type	12	George	Level Elevation
	www.v.Well	OI	0005 THE	11.0	aole/Rotaty		12.	State	15.		3966
14.	Multiple	15. Propo	sed Depth	16	. Formation		1	7. Contractor		18.	Spud Date
	N	64	Ю0		Glorieta					6.	/1/2007
D	epth to Ground v	vater		Distance :	from nearest fres	n water well			Distanc	e to nea	rest surface water
the state of the s					> 1000					> 1	1000
	15	C 1000 COST - 10							2.0		
	er: Synthetic 🔀		mils thick	Clay Pit V	olume: 20910	bbls Dril					
	4.7/19		100.00.00	A SANT	obume: <u>20910</u>	Fres	h Wat	ter 🗙 Brine 🗆	Diesel/Oil-	based [Gas/Air
Clos	er: Symthetic 🔀 sed Loop System	1	19	. Proposed C	ohme: 20910	Free Cement 1	h Wat Prog	er⊠Brine □ gram			
Clos Type	er: Synthetic 🔀 sed Loop System Hole Size	Casing	19. Гуре	. Proposed C Casing Weigh	ohme: 20910	Free Cement 1 ting Depth	h Wat Prog	ram Sacks of C	Cement		stimated TOC
Clos Type Surf	er: Synthetic Sed Loop System Hole Size 12.25	Casing	19. Гуре	. Proposed C Casing Weigh 24	ohme: 20910	Free Cement I ting Depth 1600	h Wat Prog	ram Sacks of 0 840	Cement		stimated TOC 0
Clos Type	er: Synthetic 🔀 sed Loop System Hole Size	Casing	19. Гуре	. Proposed C Casing Weigh	ohme: 20910	Free Cement 1 ting Depth	h Wat Prog	ram Sacks of C	Cement		stimated TOC
Clos Type Surf	er: Synthetic Sed Loop System Hole Size 12.25	Casing	19 Гуре	. Proposed C Casing Weigh 24	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400	Prog	er X Brine Tram Sacks of (840	Cement		stimated TOC 0
Clos Type Surf	er: Synthetic Sed Loop System Hole Size 12.25	Casing	19 Гуре	. Proposed C Casing Weigh 24 15.5	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400	Prog	er X Brine Tram Sacks of (840	Cement		stimated TOC 0
Clos Type Surf	er: Synthetic Sed Loop System Hole Size 12.25	Casing	19 Гуре	. Proposed C Casing Weigh 24 15.5	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400	Prog	er X Brine Tram Sacks of (840	Cement		stimated TOC 0
Clos Type Surf	er: Synthetic Sed Loop System Hole Size 12.25	Casing	19 Type 5 Casin	. Proposed C Casing Weigh 24 15.5 ng/Cement Pr	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400 Iditional	Prog	ram Sacks of 0 840 120 nments	Cement		stimated TOC 0
Type Surf Prod	er: Synthetic Seed Loop System Hole Size 12.25 7.875	Casing	19. Type 5 Casin	. Proposed C Casing Weigh 24 15.5 ng/Cement Proposed Blo	asing and the state of the stat	Free Cement I ting Depth 1600 6400 Iditional	Prog	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0 0
Type Surf Prod	er: Synthetic Seed Loop System Hole Size 12.25 7.875	Casing	19 Type 5 Casin	. Proposed C Casing Weigh 24 15.5 ng/Cement Proposed Blor Proposed Blor	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400 Iditional	Con	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0
Type Surf Prod	er: Synthetic Seed Loop System Hole Size 12.25 7.875	Casing	19 Type 5 Casim	. Proposed C Casing Weigh 24 15.5 ng/Cement Pr Proposed Blor Pressure	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400 Iditional	Con	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0 0
Type Surf Prod	er: Synthetic Seed Loop System Hole Size 12.25 7.875 Type nnular Blind	Casing	19 Type 5 Casin	. Proposed C Casing Weigh 24 15.5 ag/Cement Proposed Blor Proposed Blor Pressure 00	asing and the state of the stat	Free Cement 1 ting Depth 1600 6400 Iditional	Programogramogramogramogramogramogramogra	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0 0
Type Surf Prod	er: Synthetic Seed Loop System Hole Size 12.25 7.875	Casing	19 Type 5 Casin Working 500	. Proposed C Casing Weigh 24 15.5 ag/Cement Proposed Blor Proposed Blor Pressure 00	asing and the state of the stat	rest Prest P	Programogramogramogramogramogramogramogra	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0 0
Type Surf Prod T An Hereby of	er: Synthetic Seed Loop System Hole Size 12.25 7.875 Type Innular Blind Pipe ertify that the infowledge and belie	Casing 8.62	19. Type 5 Casin Working 500 500 500	Proposed C Casing Weigh 24 15.5 ng/Cement Pr Proposed Blor Pressure 00 00 00 00 rue and complete to	asing and the state of the best	ting Depth 1600 6400 Iditional Internal Prince Pr	Progra Con Con 00 00	ram Sacks of 0 840 120 nments	Cement) O	Es	stimated TOC 0 0
Type Surf Prod T An F hereby co	Fype Innular Blind Pipe ertify that the inforwiedge and belie	Casing 8.62	19 Type 5 Casim Working 500 500 1 above is to	Proposed C Casing Weigh 24 15.5 ag/Cement Pr Proposed Blor Pressure 00 00	asing and the set of the best of the best of the best of the set o	ention Process	Progra Con Con Con Con Con Con	ram Sacks of C 840 120 nments m	Cement) O	Es	stimated TOC 0 0
Type Surf Prod T An H hereby co further imoch	Hole Size 12.25 7.875 Type nnular Blind Pipe ertify that the inforwledge and belie certify that the guidelines [] proved plan []	Casing 8.62 5.5 5.5 connation gives f. drilling pit va general per	19 Type 5 Casim Working 500 500 1 above is to all be consmit X, or a	Proposed C Casing Weigh 24 15.5 ag/Cement Pr Proposed Blor Pressure 00 00 00 outer and complete to chructed according in (attached) alternal	asing and the state of the best to hastive App	rest Prest P	Con Con Con Paul	ram Sacks of C 840 120 nments m	Cement) O	Es	stimated TOC 0 0
Type Surf Prod T An Hereby of further (MOCD) Printed	Hole Size 12.25 7.875 Type nnular Blind Pipe ertify that the infinitely served plan Name: Electro	Casing 8.62 5.5 5.5 comation gives f. drilling pit value a general per	19 Type 5 Casim Working 500 500 1 above is to all be consmit X, or a	Proposed C Casing Weigh 24 15.5 ag/Cement Pr Proposed Blor Pressure 00 00 00 outer and complete to chructed according in (attached) alternal	asing and the state of the best to native App	ention Proceedings of the control of	Con Con Con Con Con Con Con Con	ram Sacks of C 840 120 nments NSERVA Kautz	Cement 0 0	Manut	Stimated TOC 0 0 facturer
Type Surf Prod T An	Hole Size 12.25 7.875 Type nnular Blind Pipe ertify that the inforwledge and belie certify that the guidelines [] proved plan []	Casing 8.62 5.5 5.5 connation gives f. drilling pit v. a general periodically filed	Type 5 Casim Working 500 500 above is to all be consmit X, or a	Proposed C Casing Weigh 24 15.5 Ig/Cement Pr Proposed Blor Pressure 00 00 The and complete to structed according in (attached) alternitia Farrell	asing and the state of the best to native App	rest Prest P	Con Con Con Con Con Con Con Con	ram Sacks of C 840 120 nments NSERVA Kautz	Cement 0 0	Manut	stimated TOC 0 0

DISTRICT I 1625 N. French Dr., Hobbs, NM 88240

State of New Mexico

Energy, Minerals & Natural Resources Department

Form C-102 Revised August 15, 2000 Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

DISTRICT II P.O. Drawer DD, Artesia, NM 88211-0719

2040 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION 1000 Rio Brazos Rd., Aztec, NM 87410 2040 South Pacheco Santa Fe, NM 87505 DISTRICT IV

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code	Pool Name		
30-025-	62160	Vacuum; Glorieta		
Property Code	Proper	ty Name	Well Number	
31257	VACUUM GLOF	19-025		
ogrid no. 217817	operate CONOCOF	Elevation 3966'		
	Surface	Location		

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
K	32	17 S	35 E		2630	SOUTH	1650	WEST	LEA

Bottom Hole Location If Different From Surface

UL o	r lot l	ĭo.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedi	cated .	Acres	Joint or	r Infill C	onsolidation (Code Ore	ier No.				
	40										

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

NOTE: 1) Plane Coordinates shown hereon are Transverse Mercator Grid and Conform to the "New Mexico Coordinate System", New Mexico East Zone, North American Datum of 1927. Distances shown hereon are mean horizontal surface values.	OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. Little M. Man
Plane Coordinate X = 761,426.7 Y = 652,625.5 3966.4 ——————————————————————————————————	Celeste G. Dale Printed Name Regulatory Specialist Title 03/27/07 Date SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison and that the same is true and correct to the best of my belief. January 8 12007 ME KMT Signature & Seal of Professional Surveyor W.O. Num 2007-0019

Permit Conditions of Approval

Operator: CONOCOPHILLIPS COMPANY, 217817 Well: VACUUM GLORIETA EAST UNIT #025

API: 30-025-38364

OCD Reviewer	Condition
Inkautz	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines