District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### State of New Mexico

# Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 152243

#### APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operato DEVON ENERGY PR	OGRID Number     6137	
	333 W. Sheridan Avenue Oklahoma City, OK 73102	
4. Property Code	5. Property Name	6. Well No.
39356	PERIDOT 13 STATE 004H	

#### 7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
H	12	198	29E	H	1475	N	1070	E	EDDY

#### 8. Pool Information

SCANLON DRAW:BONE SPRING	55510

#### Additional Well Information

	T	Additional Well Informe	tton	
9. Work Type New Well	10. Weti Type OIL	11. Cable/Rotary	12. Lesse Type State	13. Ground Level Elevation 3392
14. Multiple 15. Proposed Depth N 17100		16. Formation 2nd Bone Spring Sand	17. Contractor	18. Spud Date
Depth to Ground	water	Distance from nearest fresh water v	vell	Distance to nearest surface water

19. Proposed Casing and Cement Program

Туре	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	250	285	.0
Int1	12.25	9.625	40	3600	1140	0
Prod	8.75	5.5	17	17100	2450	0
Prod	8.75	5.5	17	7600	860	3100

#### Casing/Cement Program: Additional Comments

13-3/8" Surface-Lead: 285 sx Cl C + 2% bwoc Calcium Chloride + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx, TOC @ surface. 9-5/8" Intermediate - Lead: 830 sx(65:35) C1 C:Poz (Fly Ash): + 5% bwow Sodium Chloride + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx, TOC @ surface; Tail: 310 sx C1 C + 0.125 #/sx Poly-E-Flake + 63.5% Water, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production - Lead: 860 sx(65:35) Cl H:Poz (Fly Ash) + 6% bwoc Bent + 0.125 #/sx Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx; Tail: 2450 sx(50:50) Cl H:Poz (Fly Ash) + 1 lb/sx Sodium Chloride + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx, TOC @ 3100 ft.

Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

of my knowledge and belief.	ation given above is true and complete to the best ling pit will be constructed according to	OIL CONSERVATION DIVISION			
	neral permit , or an (attached) alternative	Approved By: Randy Dade			
Printed Name: Electronic	ally filed by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulator	ry Affairs	Approved Date: 7/23/2012	Expiration Date: 7/23/2014		
Email Address: randy.bo	lles@dvn.com				
Date: 7/18/2012	Phone: 405-228-8588	Conditions of Approval Attac	ched		

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

District IV

State of New Mexico

## Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

August 1, 2011 Permit 152243

Form C-102

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Poc	ol Name
30-015-40504	55510	W;BONE SPRING	
4. Property Code 39356	5. Property Name PERIDOT 13 STATE		6. Well No. 004H
7. OGRID No. 6137	8. Operato DEVON ENERGY PRODU	9. Elevation 3392	

#### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
Н	12	198	29E		1475	N	1070	E	EDDY

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	13	198	29E	P	330	S	990	E	EDDY
10.7	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

#### NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

#### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/18/2012

#### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 5/3/2012 Certificate Number: 12797

# **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: PERIDOT 13 STATE #004H

API: 30-015-40504

Created By	Comment	Comment Date
doook	BOP DESIGN: The BOP system used to drill the intermediate and production holes will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the prior casing shoe.	The second secon
dœok	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	
dcook	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line). The line will be kept as straight as possible with minimal turns.	7/18/2012
CSHAPARD	Land s/S	7/18/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: PERIDOT 13 STATE #004H

API: 30-015-40504

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string