<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Depth to Ground water

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Form C-101 August 1, 2011

Distance to nearest surface water

1220 S. St Francis Dr. Santa Fe, NM 87505

1. Operator	Name and Address	OGRID Number	
	ERATING LLC oncho Center	229137	
	nd. TX 79701	3. API Number 30-015-41274	
Iviloidi	11 ///01		
4. Property Code	5. Property Name	6. Well No.	
308169 SRO STATE UNIT		T 020H	

7. Surface Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	3	26S	28E	A	190	N	1090	E	EDDY

8. Proposed Bottom Hole Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
H	10	26S	28E	H	2310	N	660	E	Eddy

9. Pool Information

		Additional Well Inform	nation	
11. Work Type	12. Well Type	13. Cable/Rotary	14. Lesse Type	15. Ground Level Elevation
New Well	OIL		State	2918
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
N	15319	Bone Spring		4/23/2013

21. Proposed Casing and Cement Program

Distance from nearest fresh water well

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	350	360	
Int1	12.25	9.625	36	2520	865	
Prod	7.875	5.5	17	15319	2375	2220

Casing/Cement Program: Additional Comments

Drill 17-1/2" hole to ~350" w/ fresh water spud mud. Run 13-3/8" 48# H40 STC casing to TD and cement to surface in one stage. Will use 1" tubing and Class C w/ 2% CaCl2 to cement to surface, if necessary. Drill 12-1/4" hole to ~2520' with saturated brine water. Rus 9-5/8" 36# J55 LTC casing to TD and cement to surface in one stage. Drill 7-7/8" pilot hole to 9500', log and plug back with cement plugs f/ 9250' - 9500' and f/7400' - 8300'. Drill 7-7/8" curve and lateral to 15319' with cut brine. Run 5-1/2" 17# P110 LTC casing to TD and cement in one stage bringing TOC to 2220' (300' overlap).

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Cameron
54			

best of my knowledge and belief		OIL CONSERVATION DIVISION				
I further certify I have compl 19.15.14.9 (B) NMAC ⊠, if a	ied with 19.15.14.9 (A) NMAC 🛮 and/or pplicable.	Approved By: Randy Dade				
Signature:						
Printed Name: Electronica	lly filed by Diane Kuykendall	Title: District Supervisor				
Title: Production Reportin	ng Mgr	Approved Date: 4/16/2013	Expiration Date: 4/16/2015			
Email Address: dkuykend	all@conchoresources.com					
Date: 4/16/2013	Phone: 432-683-7443	Conditions of Approval Attached				

District I
1625 N. French Dr., Hobbs, NM 88240
Phones(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phones(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax:(505) 334-6170

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.

August 1, 2011 Permit 165628

Form C-102

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

	API Number -015-41274		2. Pool Code 3. Pool Name 51010 RED BLUFF;BONE SPRING, SOUT:						JTH	
	Property Code 308169		5. Property Name SRO STATE UNIT					6. Well No. 020H		
7. OGRID No. 229137			8. Operator Name COG OPERATING LLC					9. Elevation 2918		
				10. 5	Surface Loc	ation				
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
A	3	268	28E	1	190	N	1090	E	EDDY	

11. Bottom Hole Location If Different From Surface									
UL - Lot H	Section 10	Township 26S	Range 28E	Lot Idn H	Feet From 2310	N/S Line N	Feet From 660	E/W Line E	County EDDY
	cated Acres	13. J	oint or Infill	14	Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. E-Signed By: Diane Kuykendall Title: Production Reporting Mgr Date: 4/16/2013 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Surveyed By: Chad Harcrow Date of Survey: 3/22/2013 Certificate Number: 17777

Permit Comments

Operator: COG OPERATING LLC , 229137 Well: SRO STATE UNIT #020H

API: 30-015-41274

Created By	Comment	Comment Date
mreyes1	OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	4/16/2013
CSHAPARD	Land s/S	4/16/2013

Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137 Well: SRO STATE UNIT #020H API: 30-015-41274

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string