<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Santa Fe, NM 87505

1220 S. St Francis Dr.

Form C-101 August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator	Name and Address	2. OGRID Number	
	N ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue	6137 3. API Number	
	City, OK 73102		
Oklahonia	oky, ok 75102	30-025-41254	
4. Property Code	5. Property Name	6. Wett No.	
30884	THISTLE UNIT	049H	

7. Surface Location

	7. Surface Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
N	34	238	33E	N	280	S	2611	W	LEA	l

8. Proposed Bottom Hole Location

				Troposee	Dottom II	ore Eccuero			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	34	238	33E	В	330	N	1980	E	Lea

#### 9. Pool Information

TRIPLE X;BONE SPRING	59900

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3639
16. Multiple         17. Proposed Depth           N         15788		18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date
Depth to Ground	water	Distance from nearest fresh water w	rel1	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1325	1180	0
Int1	12.25	9.625	40	5250	1465	0
Prod	8.75	5.5	17	15788	1255	
Prod	8.75	5.5	17	10600	810	4750

# Casing/Cement Program: Additional Comments

13 3/8" Surface: Lead w/740 sx C1 C Cmt: + 4% bwoc Bent + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake 80.9% FW, 13.5 ppg, Yld: 1.75 cf/sx. Tail w/440 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx; TOC @ surface. 9 5/8" Intermediate: Lead w/1035 sx(65:35) C1 C Cmt:Poz (Fly Ash): + 5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 49.2% FW, 12.5 ppg, Yld: 2.04 cf/sx. Tail w/430 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% Water, 14.8 ppg, Yld: 1.33 cf/sx; TOC @ surface. 5 ½ " Production: 1st Lead w/485 sx(50:50) Cl H: Poz (Fly.Ash) + 10% bwoc Bent + 8 #/sx CaCL + 0.15 #/sx FWCA, 0.125 #/sx Poly-E-Flake, 0.3% bwoc HR-601, 0.25 #/sx D-AIR 5000 + 64.9% FW, 11.8 ppg, Yld: 2.54 cf/sx. See Comments section for continuation of 5 1/2" production cement.

22 Proposed Blowout Prevention Program

	22. I toposed blowdet I evention I togram								
Type	Working Pressure	Test Pressure	Manufacturer						
Annular	3000	3000							
DoubleRam	3000	3000	6						

best of my knowledge and belief.	ation given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied 19.15.14.9 (B) NMAC ⊠, if app	l with 19.15.14.9 (A) NMAC 🛮 and/or olicable.	Approved By: Paul Kautz				
Signature:						
Printed Name: Electronically	y filed by Randy Bolles	Title: Geologist				
Title: Manager, Regulatory	Affairs	Approved Date: 7/9/2013	Expiration Date: 7/9/2015			
Email Address: randy.bolles	@dvn.com	170 Kg	500000000000000000000000000000000000000			
Date: 7/3/2013	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011

Form C-102

1220 S. St Francis Dr. Santa Fe, NM 87505

### WELL LOCATION AND ACREAGE DEDICATION PLAT

	VLLE LOCATION AND ACK	AGE DEDICATION TEA	
1. API Number	2. Pool Code	3. Pool	Name
30-025-41254	59900	TRIPLE X;BO	ONE SPRING
4. Property Code	5. Property !	Name	6. Well No.
30884	THISTLE	JNIT	049H
7. OGRID No.	8. Operator 1	Name	9. Elevation
6137	DEVON ENERGY PRODUC	TION COMPANY, LP	3639


### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	34	238	33E		280	S	2611	W	LEA

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	34	238	33E	В	330	N	1980	E	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

## NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



# OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/3/2013

### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 6/7/2013 Certificate Number: 12797

# **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: THISTLE UNIT #049H API: 30-025-41254

Created By	Comment	Comment Date
doook	2nd Lead: 325 sacks (65:35) Class H Cement + 6% bwow Bentonite + 0.25% bwoc HR-601+ 0.125 lbs/sack Poly-E-Flake + 49.1% Fresh Water, 12.5 ppg Yield: 1.96 cf/sk	7/3/2013
doook	Tail: 1255 sacks (50:50) Class H Cement + 2% bwow Bentonite + 0.5% bwoc Halad-344 + 0.3% bwoc CRF-3 + 1 lb/sk Salt+ 0.2% bwoc HR-801+ 33.6% Fresh Water, 14.5 ppg, Yield: 1.23cf/sk. TOC @ 4750'.	7/3/2013
pkautz	Land s/S	7/9/2013
DMULL	OCD Hobbs office has received form C-144clez. OCD Permit Number P1-06482.	7/9/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: THISTLE UNIT #049H

API: 30-025-41254

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite