District I 1625 N. French Dr., Hobbs, NM 88240 Phone;(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone;(575) 748-1283 Fax:(575) 748-9720

Phones (3/5) (48-1283 FBX (3/5)) (48-9/20)
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones (505) 334-6178 FBX (505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phones (505) 475, 3470 FBX (505) 475, 3465

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

Form C-101 August 1, 2011

Permit 169828

1220 S. St Francis Dr. Santa Fe, NM 87505

	100 100 100 100 100 100 100 100 100 100		rator Name				N, PLUGBAC	2. OGRID N			
	DEVO	ON ENERGY I			IPANY, LP	ř, LP					
			V. Sherida	OK 73102				3. API Numi	ber		
		Oklano	ша Спу,	OK /3102					30-015-41537		
,	4. Property Code	e			5. Property Nam	se .	3/0	6.	Well No.		
					TON DRAW	UNIT		214H			
		2/3		7. S	urface Loc	ation					
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
C	36	24S	31E	С	200	N	1710	W	EDDY		
	3		8	Proposed	Bottom H	ole Locat	ion				
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
M	36	24S	31E	1	330	S	660	W	Eddy		
				0 D	ool Inform	ation					
ADUCA	A; BONE SPR	ING (O)		у. г	ooi iniorni	ation			96		
				Addition	al Well Int	formation					
11. We	ork Type	12. Well Ty	pe	13. C	able/Rotary	ary 14. Lease Type		15. Ground Level Elevation			
New Well		OIL	DIL			State		3508			
16. 1	Multiple	17. Proposed	Depth	18. Formation			19. Contractor		20. Spud Date		
		15301		Bone Spring				,]			
Depth to Ground water				Distance from nearest fresh water well				Distance to nearest surface water			
			21. Pı	oposed Ca	asing and C	ement P	rogram				
Type	Hole Size	Casing Typ	40.00	asing Weight	_	ing Depth	Sacks of C	ement	Estimated TOO		
Surf	17.5	13.375		48		750	800		0		
Int1	12.25	9.625		40		4350	1340		0		
Prod	8.75	5.5				15301	2550		3850		
		(Casing/C	ement Pr	ogram: Ad	ditional (Comments				
				1.1		111111111111111111111111111111111111111					
			22 D.	onosed Pi	owout Prev	ontion D	rogram				
	Type			g Pressure	.c.aout 116		ressure Manufacturer		anufacturer		
	Annular	100	3000			3000					
DoubleRam 3000						30	000				
3 I hereby	certify that the	information given	above is tr	ne and complet	te to the	OII C	ONICEDIA	TION DIV	TICION		
	knowledge and b	oelief.		the first and the	187	100000000000000000000000000000000000000	CONSERVA	HON DI	ISION		
	(B) NMAC X,	if applicable.	15.14.9 (A)	NMAC □ an	Appr	oved By: F	landy Dade				
further ce 9.15.14.9			Dan de D	allas	Tief	District Co.	unarinar				
further co 9.15.14.9 Signature		Printed Name: Electronically filed by Randy Bolles					Title: District Supervisor				
further of 9.15.14.9 Signature Printed N	Name: Electron				Λ	nand Date.	7/12/2012	Engineering D	ata: 7/12/2015		
further ce 9.15.14.9 Signature Printed N Fitle: Ma	Name: Electron anager, Regula				Appr	oved Date:	7/13/2013	Expiration D	ate: 7/13/2015		

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u> 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

Phone: (575) 748-1283 Fax: (575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 169828

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-41537	The second secon		1 Name NE SPRING (O)
4. Property Code	5. Property No		6. Well No.
300635	COTTON DRAN		214H
7. OGRID No.	8. Operator No	9. Elevation	
6137	DEVON ENERGY PRODUCT	3508	


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	36	24S	31E		200	N	1710	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	36	24S	31E	1	330	S	660	W	EDDY
12. Dedicated Acres 159.11		13. J	13. Joint or Infit1		14. Consolidation Code		15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/11/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 6/1/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: COTTON DRAW UNIT #214H API: 30-015-41537

Created By	Comment	Comment Date
RDELONG	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. A 3M system will be installed prior to drilling out the intermediate casing shoe. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2.	7/11/2013
RDELONG	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	7/11/2013
RDELONG	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line); if an H&P rig drills this well. Otherwise no flex line is needed. The line will be kept as straight as possible with minimal turns.	7/11/2013
CSHAPARD	Land s/S	7/12/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: COTTON DRAW UNIT #214H

API: 30-015-41537

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string