

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised February 15, 2012							
		1. WELL API NO. 30-015-40334							
		2. Well Name: BELLATRIX 28 FEDERAL COM #004H							
		3. Well Number: 004H							
HYDRAULIC FRACTURING FLUID DISCLOSURE ☒ Original ☐ Amendment		4. Surface Hole Location: Unit: I Lot: I Section: 29 Township: 19S Range: 31E Feet from: 1510 N/S Line: S Feet from: 200 E/W Line: E							
		5. Bottom Hole Location: Unit: I Lot: I Section: 29 Township: 19S Range: 31E Feet from: 1510 N/S Line: S Feet from: 200 E/W Line: E							
		6. Latitude: 32.6282853662169 longitude: - 103.883480034275							
		7. County: Eddy							
8. Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue Oklahoma City 73102		9. OGRID: 6137		10. Phone Number: 405-228-8588					
11. Last Fracture Date: 8/28/2013 Frac Performed by: BHI		12. Production Type: O							
13. Pool Code(s): 29345		14. Gross Fractured Interval: Confidential							
15. True Vertical Depth (TVD): 9,105 ft		16. Total Volume of Fluid Pumped: 2,452,254 gals							
17. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:									
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)			
Water	Operator	Carrier	Water	7732-18-5	100%	91.0398%			
HCl, 10.1 - 15%	Baker Hughes	Acidizing	Hydrochloric Acid	7647-01-0	15%	0.32284%			
Superset-W, 55 gal drum	Baker Hughes	Activator	Water	7732-18-5	85%	1.82943%			
			Methanol	67-56-1	50%	0.01159%			
			Poly (Oxyethylene) Nonylphenol Ether	9016-45-9	50%	0.01159%			
Alpha 125	Baker Hughes	Biocide	Water	7732-18-5	75%	0.02317%			
GBW-5	Baker Hughes	Breaker	Ammonium persulphate	7727-54-0	100%	0.03406%			
ClayCare, tote	Baker Hughes	Clay Control	Choline Chloride	67-48-1	75%	0.07285%			
Clay Master-5C CI-27	Baker Hughes	Clay Control	Water	7732-18-5	30%	0.02914%			
			Oxyalkylated Amine Quat	138879-94-4	60%	0.00145%			
			Fatty Acids	Trade Secret	30%	0.00189%			
			Methanol	67-56-1	60%	0.00379%			
			Olefin	Trade Secret	5%	0.00032%			
			Polyoxyalkylenes	Trade Secret	30%	0.00189%			
			Propargyl Alcohol	107-19-7	10%	0.00063%			
			Thiourea Polymer	68527-49-1	30%	0.00189%			
MaxPerm-20A, 265 gallon tote	Baker Hughes	Friction Reducer	Aliphatic Hydrocarbon	Trade Secret	30%	0.01233%			
			Oxyalkylated Alcohol	Trade Secret	5%	0.01347%			
			Oxyalkylated Hydrocarbon	Trade secret	5%	0.00206%			
			Petroleum Distillates	64742-47-8	30%	0.08084%			
			Polyacrylate	Trade Secret	60%	0.16168%			
			Sodium Chloride	7647-14-5	3%	0.00808%			
			Acrylic Polymers	26006-22-4	50%	0.00255%			
			Distillates, Petroleum, Hydrotreated Middle	64742-47-8	21.1%	0.00107%			
AG-12	Baker Hughes	Gelling Agent	2-Mercaptoethanol	60-24-2	100%	0.0112%			
			Ammonium Hydroxide	1336-21-6	5%	0.00056%			
			Cupric Chloride	7447-39-4	5%	0.00056%			
NE-35, 330 gl tote	Baker Hughes	Non-emulsifier	Mixture of Surfactants	Trade Secret	50%	0.04412%			
			Propylene Glycol	57-55-6	30%	0.02647%			
Sand, White, 40/70	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100%	4.41307%			
Sand, White, 100 mesh	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100%	0.19398%			
Super LC, 40/70	Baker Hughes	Proppant	Hexamethylenetetramine	100-97-0	0.01%	0.00012%			
			Phenol-formaldehyde Resin	9003-35-4	5%	0.05962%			
			Silicon Dioxide (Silica Sand)	14808-60-7	97%	1.15655%			
Super LC, 20/40	Baker Hughes	Proppant	Hexamethylenetetramine	100-97-0	0.01%	1E-05%			
			P/F Resin	9003-35-4	5%	0.00642%			
			Silicon Dioxide (Silica Sand)	14808-60-7	97%	0.12451%			
Flo-Back Prime (tote)	Baker Hughes	Surfactant	Essential Oils	Trade Secret	60%	0.03027%			
			Isopropanol	67-63-0	30%	0.01513%			
Ingredients shown above are subject to 29 CFR 1910			Citrus Terpenes	94266-47-4	0%	0.0302657%			
			Fatty Acid Esters	67701-32-0	0%	9.68E-05%			
			Fatty Acid Oxyalkylate	70142-34-6	0%	1.02E-05%			
			Formaldehyde	50-00-0	0%	3.2E-06%			
			Glutaraldehyde	111-30-8	0%	0.0092682%			
			Methanol	67-56-1	0%	7.72E-05%			
			Oleate Ester	1338-43-8	0%	0.008084%			
			Organic Polyol	112-27-6	0%	0.0050443%			
			Oxyalkylated Alkylphenol	9016-45-9	0%	9.17E-05%			
			Polysorbate	9005-65-6	0%	0.008084%			
			Sodium Chloride	7647-14-5	0%	0.007598%			
			Surfactants	Trade Secret	0%	0.03531%			
			Water	7732-18-5	0%	0.1450248%			
			Xylene	1330-20-7	0%	3.06E-05%			
			diester of sulfosuccinic acid sodium salt	2673-22-5	0%	2.55E-05%			
			18. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.						
			Signature: Signed Electronically Printed Name: Derek Berg		Title: Engineering Technician				
			Date: 10/14/2013						
			E-mail Address: derek.berg@dm.com						

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.