

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised February 15, 2012				
		1. WELL API NO: 30-015-41547				
		2. Well Name: PARKWAY 36 STATE #006H				
		3. Well Number: 006H				
HYDRAULIC FRACTURING FLUID DISCLOSURE ☐ Original ☒ Amends disclosure submitted on 10/21/2013		4. Surface Hole Location: Unit: L Lot: Section: 36 Township: 19S Range: 29E Feet from: 2310 N/S Line: S Feet from: 330 E/W Line: E				
		5. Bottom Hole Location: Unit: L Lot: Section: 36 Township: 19S Range: 29E Feet from: 2193 N/S Line: S Feet from: 380 E/W Line: W				
		6. Latitude: longitude: 32.6160241526575 - 104.020951064617				
		7. County: Eddy				
8. Operator Name and Address: SM ENERGY COMPANY 3300 N. A Street, Bldg. #7 Suite 200 Midland 79705		9. OGRID: 154903	10. Phone Number: 432-688-1789			
11. Last Fracture Date: 10/7/2013 Frac Performed by: WEATHERFORD FRACTURING TECHNOLOGIES		12. Production Type: O				
13. Pool Code(s): 49622		14. Gross Fractured Interval: 8,017 ft to 11,714 ft				
15. True Vertical Depth (TVD): 7,378 ft		16. Total Volume of Fluid Pumped: 1,550,532 gals				
17. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:						
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water	SM Energy Company	Carrier / Base Fluid	Carrier / Base Fluid - Water	7732-18-5	100%	87.3916%
Ottawa Sand 20/40 (2.63 sg)	WFT	Proppant	Crystalline Silica in the form of Quartz	14808-60-7	100%	9.9966%
Super LC 20/40 (2.51 sg)	WFT	Proppant	Crystalline Silica (Quartz)	14808-60-7	73%	1.2844%
			Formaldehyde	50-00-0	0%	0.0002%
			Hexamethylenetetramine	100-97-0	1%	0.0176%
			Hydrated Aluminum Silicate	1332-58-7	5%	0.088%
			Iron Oxide (fume)	1309-37-1	15%	0.264%
			Phenol	108-95-2	0%	0.0002%
			Phenol-Formaldehyde Resin	9003-35-4	6%	0.1056%
WBK-133	WFT	Breaker	Ammonium Persulfate	7727-54-0	100%	0.0227%
WBK-134	WFT	Breaker	Ammonium Persulfate	7727-54-0	75%	0%
Superset W	Santrol	Activator	Methanol	67-56-1	50%	0.0249%
			Poly(oxytethylene) nonylphenol ether	9016-45-9	50%	0.0249%
Bio-Clear® 5000	WFT	Bactericide	2,2-dibromo-3-nitrioproppionamide	10222-01-2	5%	0.001%
WGA-15L	WFT	Gelling Agents	Polyethylene Glycol	25322-68-3	50%	0.0097%
			Petroleum Distillates	64742-47-8	60%	0.2282%
WPB-584L	WFT	ph Adjusting Agents	Potassium Carbonate	584-08-7	40%	0.0472%
WNE-363L	WFT	Surfactant	Potassium Hydroxide	1310-58-3	20%	0.0236%
			2-Ethylhexanol	104-76-7	7%	0.0062%
			Dodecylbenzenesulfonic acid, monoethanolamine salt	26836-07-7	15%	0.0132%
			Ethylene/Propylene Oxide Polymer	9003-11-6	30%	0.0265%
			Poly(oxy-1,2-ethanediyl), a-isotridecyl-w-hydroxy-	9043-30-5	5%	0.0044%
			Ingredients shown above are subject to 29 CFR 1910			
			2-Butoxyethanol	111-76-2	0%	0.0038%
			Alcohol Ethoxylate	68002-97-1	0%	0.0038%
			Alcohols, C12-16, Ethoxylated	68551-12-2	0%	0.0038%
			Arlacel 83	8007-43-0	0%	0.0038%
			Choline Chloride	67-48-1	0%	0.1215%
			Crystalline Silica in the form of Quartz	14808-60-7	0%	0.0038%
			Deionized Water	7732-18-5	0%	0.0097%
			Guar gum	9000-30-0	0%	0.1902%
Proprietary Ingredient	Proprietary	0%	0.0192%			
18. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.						
Signature: Signed Electronically Printed Name: Vickie Martinez		Title: Engineering Tech				
Date: 10/21/2013						
E-mail Address: vmartinez@sm-energy.com						

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.