# District I 1625 N. French Dr., Hobbs, NM 88240 Enery District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410

# State of New Mexico Energy Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr. Form C-144 Revised June 6, 2013

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office.

For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 Santa Fe, NM 87505 Santa Fe, NM 87505 Santa Fe, NM 87505 Pit Below-Grade Tank or	
Pit Polovy Grado Tonk or Z013 0€1 22 ₱ 1. 30	-
Tit, Below Glade Tulk, of	
Proposed Alternative Method Permit or Closure Plan Application	
Type of action:  Below grade tank registration  Permit of a pit or proposed alternative method  Closure of a pit, below-grade tank, or proposed alternative method  Modification to an existing permit/or registration  Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank, or proposed alternative method	
Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request	
Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.	
t. Operator:BP America Production CoOGRID #:778	
Address:200 Energy Ct. Farmington, NM. 87401	
Facility or well name:Riddle F LS 008	
API Number:	
U/L or Qtr/Qtr M Section 8 Township 28N Range 8W County: San Juan	
Center of Proposed Design: Latitude36.670937 Longitude107.710388 NAD: □1927 ☒ 1983	
Surface Owner: M Federal M State Private Tribal Trust or Indian Allotment	
Pit: Subsection F, G or J of 19.15.17.11 NMAC   Temporary: □ Drilling □ Workover   Permanent □ Emergency □ Cavitation □ P&A □ Multi-Well Fluid Management □ Low Chloride Drilling Fluid □ yes □ no   Lined □ Unlined □ Liner type: Thicknessmil □ LLDPE □ HDPE □ PVC □ Other   String-Reinforced	
Liner Seams: Welded Factory Other Volume: bbl Dimensions: L x W x D	
Below-grade tank: Subsection I of 19.15.17.11 NMAC  Volume:	
4.	
Alternative Method:  Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
5.	
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)	
Chain link, six feet in height, two strands of barbed wire at top (Required if located within 1000 feet of a permanent residence, school, hospital, institution or church)	
Four foot height, four strands of barbed wire evenly spaced between one and four feet	
Alternate. Please specify	

6.	
Netting: Subsection E of 19.15.17.11 NMAC (Applies to permanent pits and permanent open top tanks)	
Screen Netting Other	
Monthly inspections (If netting or screening is not physically feasible)	
7.	
Signs: Subsection C of 19.15.17.11 NMAC	
12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers	
Signed in compliance with 19.15.16.8 NMAC	
8. <u>Variances and Exceptions:</u> Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.	
Please check a box if one or more of the following is requested, if not leave blank:  Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.  Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.	
9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of accumaterial are provided below. Siting criteria does not apply to drying pads or above-grade tanks.	eptable source
General siting	
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	Yes No
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☑ No ☐ NA
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks)  - Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No
Within the area overlying a subsurface mine. (Does not apply to below grade tanks)  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No
Within an unstable area. (Does not apply to below grade tanks)  - Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map	☐ Yes ☐ No
Within a 100-year floodplain. (Does not apply to below grade tanks) - FEMA map	Yes No
Below Grade Tanks	
Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)	
Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.)  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application.	☐ Yes ☐ No
- Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	
Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300 feet of any other fresh water well or spring, in existence at the time of the initial application.  NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	☐ Yes ☐ No

Within 100 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pit Non-low chloride drilling fluid								
Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image								
Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application;  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site								
Within 300 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Permanent Pit or Multi-Well Fluid Management Pit								
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	Yes No							
Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	Yes No							
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No							
Within 500 feet of a wetland.  - US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No							
Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.  Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Design Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC  Previously Approved Design (attach copy of design) API Number: or Permit Number:								
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC  Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached.  Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  A List of wells with approved application for permit to drill associated with the pit.  Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC  Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Previously Approved Design (attach copy of design) API Number:  or Permit Number:								

12.	
Permanent Pits Permit Application Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the	e documents are
attached.  Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Climatological Factors Assessment  Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC  Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC  Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC  Quality Control/Quality Assurance Construction and Installation Plan  Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC  Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC  Nuisance or Hazardous Odors, including H <sub>2</sub> S, Prevention Plan  Emergency Response Plan  Oil Field Waste Stream Characterization  Monitoring and Inspection Plan  Erosion Control Plan  Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC	
Proposed Closure: 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.	
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well I Alternative	Fluid Management Pit
Proposed Closure Method: Waste Excavation and Removal  Waste Removal (Closed-loop systems only)	
On-site Closure Method (Only for temporary pits and closed-loop systems)  In-place Burial On-site Trench Burial  Alternative Closure Method	
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be closure plan. Please indicate, by a check mark in the box, that the documents are attached.  ☐ Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC ☐ Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.13 NMAC ☐ Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings) ☐ Soil Backfill and Cover Design Specifications - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC ☐ Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	
Siting Criteria (regarding on-site closure methods only): 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sout provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. In 19.15.17.10 NMAC for guidance.	rce material are Please refer to
Ground water is less than 25 feet below the bottom of the buried waste.  - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Ground water is more than 100 feet below the bottom of the buried waste.  NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA
Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).  - Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application.  - Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	☐ Yes ☐ No
Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application.  - NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Written confirmation or verification from the municipality; Written approval obtained from the municipality	☐ Yes ☐ No
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	☐ Yes ☐ No
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance	

adopted pursuant to NMSA 1978, Section 3-27-3, as amended.	C " C "								
- Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No								
Within the area overlying a subsurface mine.  - Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division	☐ Yes ☐ No								
Within an unstable area.									
<ul> <li>Engineering measures incorporated into the design; NM Bureau of Geology &amp; Mineral Resources; USGS; NM Geological Society; Topographic map</li> </ul>	Yes No								
Within a 100-year floodplain FEMA map	Yes No								
16.									
On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.  Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC  Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC  Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17.11 NMAC  Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC  Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC  Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC  Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cannot be achieved)  Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC  Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC									
17. Operator Application Certification:									
I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and believe	ef.								
Name (Print):Courtney Cochran Title: Field Environmental Advisor									
	_								
Signature: 0/21/2013	-								
e-mail address:Courtney.cochran@bp.com									
e-mail address:Courtney.Cochran@bp.com Telephone:505-326-9457	m/3								
e-mail address:Courtney.Cochran@bp.com	m/3								
e-mail address:Courtney.Cochran@bp.com	m/3								
e-mail address:Courtney.Cochran@bp.com	complete this								
e-mail address:Courtney.Cochran@bp.com Telephone: 505-326-9457	complete this								
e-mail address:Courtney.Cochran@bp.com	complete this								
e-mail address: _Courtney.Cochran@bp.com	op systems only)								
e-mail address:Courtney.Cochran@bp.com Telephone:505-326-9457	op systems only)								
e-mail address:Courtney.Cochran@bp.com	op systems only)								
e-mail address: _Courtney.Cochran@bp.com	op systems only)								
e-mail address:Courtney.Cochran@bp.com	op systems only)								
e-mail address: _Courtney.Cochran@bp.com	op systems only)								
e-mail address: _Courtney.cochran@bp.com	op systems only)								
e-mail address: _Courtney@ochran@bp.com	op systems only)								

22.	9
Operator Closure Certification:	
I hereby certify that the information and attachments submitted with this closure report	rt is true, accurate and complete to the best of my knowledge and
belief. I also certify that the closure complies with all applicable closure requirements	s and conditions specified in the approved closure plan.
Name (Print): Construcy Cocheca	Title: Field Environmental Advisor
Name (Print):	Title: PIETO CONTICOMMUTAL / 10415012
Signature:	1/1.10.00
Signature:	Date:
A	<b>-</b>
e-mail address: Courtney. Cochran @ bp. com	Telephone: 505- 326.1457



RECEIVED OCD

2014 JUL-8 P 2:51

Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

November 19, 2013

Nelson Velez
Blagg Engineering
P. O. Box 87
Bloomfield, NM 87413
TEL: (505) 220, 2480

TEL: (505) 320-3489 FAX (505) 632-3903

RE: Riddle F LS # 8 OrderNo.: 1311337

#### Dear Nelson Velez:

Hall Environmental Analysis Laboratory received 5 sample(s) on 11/8/2013 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to <a href="www.hallenvironmental.com">www.hallenvironmental.com</a> or the state specific web sites. In order to properly interpret your results it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0190

Sincerely,

Andy Freeman

Laboratory Manager

andyl

4901 Hawkins NE

Albuquerque, NM 87109

## Lab Order 1311337

Date Reported: 11/19/2013

# Hall Environmental Analysis Laboratory, Inc.

CLIENT: Blagg Engineering **Project:** Riddle F LS # 8

**Lab ID:** 1311337-001

Chent Sample II

Client Sample ID: TH-EB @ 9.5'(UPP)

 $\textbf{Collection Date:}\ 11/7/2013\ 10{:}23{:}00\ AM$ 

Received Date: 11/8/2013 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	SE ORGANICS				Analy	st: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/13/2013 11:01:19	AM 10292
Surr: DNOP	76.9	66-131	%REC	1	11/13/2013 11:01:19	AM 10292
EPA METHOD 8015D: GASOLINE RA	ANGE				Analy	st: NSB
Gasoline Range Organics (GRO)	ND	4.9	mg/Kg	1	11/12/2013 3:18:38 F	M 10281
Surr: BFB	91.3	74.5-129	%REC	1	11/12/2013 3:18:38 F	M 10281
EPA METHOD 8021B: VOLATILES					Analy	st: NSB
Benzene	ND	0.049	mg/Kg	1	11/12/2013 3:18:38 F	M 10281
Toluene	ND	0.049	mg/Kg	1	11/12/2013 3:18:38 F	M 10281
Ethylbenzene	ND	0.049	mg/Kg	1	11/12/2013 3:18:38 F	M 10281
Xylenes, Total	ND	0.098	mg/Kg	1	11/12/2013 3:18:38 F	M 10281
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	11/12/2013 3:18:38 F	M 10281
EPA METHOD 300.0: ANIONS					Analy	st: JRR
Chloride	ND	1.5	mg/Kg	1	11/13/2013 12:42:39	PM 10324
EPA METHOD 418.1: TPH					Analy	st: BCN
Petroleum Hydrocarbons, TR	28	20	mg/Kg	1	11/14/2013	10298

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 1 of 11

- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

Lab Order 1311337

Date Reported: 11/19/2013

# Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Project: Riddle F LS # 8

Lab ID: 1311337-002 Client Sample ID: 1-NSW @ 2'(UPP)

Collection Date: 11/7/2013 11:05:00 AM

Received Date: 11/8/2013 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANG	E ORGANICS				Analys	st: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/13/2013 3:51:20 Pi	M 10292
Surr: DNOP	78.5	66-131	%REC	1	11/13/2013 3:51:20 PI	M 10292
EPA METHOD 8015D: GASOLINE RA	NGE				Analys	st: NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	11/12/2013 4:44:16 Pi	M 10281
Surr: BFB	89.6	74.5-129	%REC	1	11/12/2013 4:44:16 PI	M 10281
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.050	mg/Kg	1	11/12/2013 4:44:16 PI	M 10281
Toluene	ND	0.050	mg/Kg	1	11/12/2013 4:44:16 PI	M 10281
Ethylbenzene	ND	0.050	mg/Kg	1	11/12/2013 4:44:16 PI	M 10281
Xylenes, Total	ND	0.099	mg/Kg	1	11/12/2013 4:44:16 Pi	M 10281
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	11/12/2013 4:44:16 PI	M 10281
EPA METHOD 300.0: ANIONS					Analys	t: <b>JRR</b>
Chloride	92	7.5	mg/Kg	5	11/13/2013 1:32:17 Pt	M 10324
EPA METHOD 418.1: TPH					Analys	t: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/14/2013	10298

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Н Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 2 of 11

- Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit

## Lab Order 1311337

Date Reported: 11/19/2013

# Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Project: Riddle F LS # 8

Lab ID: 1311337-003 Client Sample ID: 2-ESW @ 2'(UPP)

Collection Date: 11/7/2013 11:02:00 AM

Received Date: 11/8/2013 10:00:00 AM

Analyses	Result	RL Qu	Qual Units		Date Analyzed	Batch	
EPA METHOD 8015D; DIESEL RANGE	ORGANICS				Analy	st: BCN	
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/15/2013 10:08:40	AM 10292	
Surr: DNOP	83.1	66-131	%REC	1	11/15/2013 10:08:40	AM 10292	
EPA METHOD 8015D: GASOLINE RANG	SE .				Analy	st: NSB	
Gasoline Range Organics (GRO)	ND	4.7	mg/Kg	1	11/12/2013 6:09:54 P	M 10281	
Surr: BFB	89.4	74.5-129	%REC	1	11/12/2013 6:09:54 P	M 10281	
EPA METHOD 8021B: VOLATILES					Analy	st: NSB	
Benzene	ND	0.047	mg/Kg	1	11/12/2013 6:09:54 P	M 10281	
Toluene	ND	0.047	mg/Kg	1	11/12/2013 6:09:54 P	M 10281	
Ethylbenzene	ND	0.047	mg/Kg	1	11/12/2013 6:09:54 P	M 10281	
Xylenes, Total	ND	0.095	mg/Kg	1	11/12/2013 6:09:54 P	M 10281	
Surr: 4-Bromofluorobenzene	107	80-120	%REC	1	11/12/2013 6:09:54 P	M 10281	
EPA METHOD 300.0: ANIONS					Analy	st: <b>JRR</b>	
Chloride	27	1.5	mg/Kg	1	11/13/2013 2:21:56 P	M 10324	
EPA METHOD 418.1: TPH					Analy	st: BCN	
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/14/2013	10298	

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit

Page 3 of 11

- Sample pH greater than 2 for VOA and TOC only.
- Reporting Detection Limit

Lab Order 1311337

Date Reported: 11/19/2013

# Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Riddle F LS # 8 Project:

Lab ID: 1311337-004 Client Sample ID: 3-SSW @ 2'(UPP)

Collection Date: 11/7/2013 11:00:00 AM

Received Date: 11/8/2013 10:00:00 AM

Analyses	Result	RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RANGE (	DRGANICS				Analys	t: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/13/2013 4:35:13 PM	1 10292
Surr: DNOP	89.2	66-131	%REC	1	11/13/2013 4:35:13 PM	1 10292
EPA METHOD 8015D: GASOLINE RANG	SE .				Analys	t: NSB
Gasoline Range Organics (GRO)	ND	5.0	mg/Kg	1	11/12/2013 6:38:28 PM	1 10281
Surr: BFB	91.1	74.5-129	%REC	1	11/12/2013 6:38:28 PM	1 10281
EPA METHOD 8021B: VOLATILES					Analys	t: NSB
Benzene	ND	0.050	mg/Kg	1	11/12/2013 6:38:28 PM	1 10281
Toluene	ND	0.050	mg/Kg	1	11/12/2013 6:38:28 PM	1 10281
Ethylbenzene	ND	0.050	mg/Kg	1	11/12/2013 6:38:28 PM	1 10281
Xylenes, Total	ND	0.10	mg/Kg	1	11/12/2013 6:38:28 PM	1 10281
Surr: 4-Bromofluorobenzene	109	80-120	%REC	1	11/12/2013 6:38:28 PM	1 10281
EPA METHOD 300.0: ANIONS					Analys	t: JRR
Chloride	ND	1.5	mg/Kg	1	11/13/2013 2:46:46 PM	1 10324
EPA METHOD 418.1: TPH					Analys	t: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/14/2013	10298

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- Analyte detected below quantitation limits
- RSD is greater than RSDlimit 0
- RPD outside accepted recovery limits
- Spike Recovery outside accepted recovery limits
- Analyte detected in the associated Method Blank
- Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
  - Page 4 of 11 Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

# Lab Order 1311337

Date Reported: 11/19/2013

# Hall Environmental Analysis Laboratory, Inc.

**CLIENT:** Blagg Engineering

Client Sample ID: 4-WSW @ 2'(UPP)

Project: Riddle F LS # 8

Collection Date: 11/7/2013 11:07:00 AM

Lab ID: 1311337-005

Received Date: 11/8/2013 10:00:00 AM

Analyses Res		RL Qu	al Units	DF	Date Analyzed	Batch
EPA METHOD 8015D: DIESEL RAN	GE ORGANICS				Analys	st: BCN
Diesel Range Organics (DRO)	ND	10	mg/Kg	1	11/13/2013 4:57:07 P	M 10292
Surr: DNOP	98.2	66-131	%REC	1	11/13/2013 4:57:07 P	M 10292
EPA METHOD 8015D: GASOLINE R	ANGE				Analys	st: NSB
Gasoline Range Organics (GRO)	ND	4.8	mg/Kg	1	11/12/2013 7:06:57 PI	M 10281
Surr: BFB	90.5	74.5-129	%REC	1	11/12/2013 7:06:57 PI	M 10281
EPA METHOD 8021B: VOLATILES					Analys	st: NSB
Benzene	ND	0.048	mg/Kg	1	11/12/2013 7:06:57 PI	M 10281
Toluene	ND	0.048	mg/Kg	1	11/12/2013 7:06:57 Pi	M 10281
Ethylbenzene	ND	0.048	mg/Kg	1	11/12/2013 7:06:57 PI	M 10281
Xylenes, Total	ND	0.095	mg/Kg	1	11/12/2013 7:06:57 PI	M 10281
Surr: 4-Bromofluorobenzene	108	80-120	%REC	1	11/12/2013 7:06:57 PI	M 10281
EPA METHOD 300.0: ANIONS					Analys	st: <b>JRR</b>
Chloride	17	7.5	mg/Kg	5	11/13/2013 3:11:35 PI	M 10324
EPA METHOD 418.1: TPH					Analys	st: BCN
Petroleum Hydrocarbons, TR	ND	20	mg/Kg	1	11/14/2013	10298

Matrix: SOIL

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

#### Qualifiers:

- \* Value exceeds Maximum Contaminant Level.
- E Value above quantitation range
- J Analyte detected below quantitation limits
- O RSD is greater than RSDlimit
- R RPD outside accepted recovery limits
- S Spike Recovery outside accepted recovery limits
- B Analyte detected in the associated Method Blank
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- P Sample pH greater than 2 for VOA and TOC only.
- RL Reporting Detection Limit

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1311337

19-Nov-13

Client:

Blagg Engineering

Project:

Riddle F LS # 8

Sample ID MB-10324

SampType: MBLK

TestCode: EPA Method 300.0: Anions

Client ID: **PBS** 

Batch ID: 10324

RunNo: 14791

Prep Date: 11/13/2013 Analysis Date: 11/13/2013

Result

SeqNo: 426109

Units: mg/Kg

HighLimit

%RPD **RPDLimit** 

Qual

Analyte Chloride

ND 1.5

Sample ID LCS-10324

SampType: LCS

TestCode: EPA Method 300.0: Anions

Client ID: LCSS

Batch ID: 10324

RunNo: 14791

Prep Date: 11/13/2013 Analysis Date: 11/13/2013

SeqNo: 426111

Units: mg/Kg

%RPD

PQL SPK value SPK Ref Val Analyte Result %REC LowLimit 15.00 14 1.5

Sample ID 1311337-001AMS

0

SPK value SPK Ref Val %REC LowLimit

91.3 90

HighLimit 110 **RPDLimit** 

Qual

Chloride

SampType: MS

TestCode: EPA Method 300.0: Anions

Client ID: TH-EB @ 9.5'(UPP) Prep Date:

Batch ID: 10324

RunNo: 14791

Analyte

Client ID:

11/13/2013

Analysis Date: 11/13/2013

SeqNo: 426114

Units: mg/Kg

PQL

1.5

1.5

SPK value SPK Ref Val 0.4859

%REC LowLimit HighLimit 90.5 58.8

%RPD **RPDLimit**  Qual

Chloride

Sample ID 1311337-001AMSD

TH-EB @ 9.5'(UPP)

SampType: MSD Batch ID: 10324

TestCode: EPA Method 300.0: Anions

RunNo: 14791

Units: mg/Kg

109

Analyte

Prep Date: 11/13/2013

Result

Analysis Date: 11/13/2013

SeqNo: 426115

**RPDLimit** Qual

Chloride

Result

14

15.00

15.00

SPK value SPK Ref Val

0.4859

%REC 90.1

LowLimit 58.8 HighLimit 109

0.345

%RPD

20

Qualifiers:

Value exceeds Maximum Contaminant Level,

E Value above quantitation range

Analyte detected below quantitation limits

O RSD is greater than RSDlimit

R RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit

Page 6 of 11

# Hall Environmental Analysis Laboratory, Inc.

WO#: 1311337

19-Nov-13

**Client:** 

Blagg Engineering

Project:

Riddle F LS # 8

Sample ID MB-10298

SampType: MBLK

TestCode: EPA Method 418.1: TPH

Client ID:

PBS

Batch ID: 10298

RunNo: 14800

Prep Date: 11/12/2013

Analysis Date: 11/14/2013 **PQL** 

20

SeqNo: 426345

Units: mg/Kg

HighLimit

Qual

Analyte Petroleum Hydrocarbons, TR

Sample ID LCS-10298

ND

Result

SampType: LCS

TestCode: EPA Method 418.1: TPH

%REC LowLimit

Client ID: LCSS

Batch ID: 10298

RunNo: 14800

Prep Date: 11/12/2013

Analysis Date: 11/14/2013 **PQL** 

Batch ID: 10298

Analysis Date: 11/14/2013

20

SeqNo: 426346

Units: mg/Kg

**RPDLimit** 

Petroleum Hydrocarbons, TR

Sample ID LCSD-10298

Prep Date: 11/12/2013

20

100.0

SPK value SPK Ref Val %REC 99.9

LowLimit

HighLimit %RPD

%RPD

Qual

100

80

120

**RPDLimit** 

Qual

Client ID: LCSS02

SampType: LCSD

SPK value SPK Ref Val

TestCode: EPA Method 418.1: TPH

Units: mg/Kg

**RPDLimit** 

%RPD

Analyte

**PQL** 

SPK value SPK Ref Val

%REC 99.9

80

HighLimit 120

20

Petroleum Hydrocarbons, TR

Result 100

100.0

RunNo: 14800

SeqNo: 426347

LowLimit

0

Qualifiers:

R

Value exceeds Maximum Contaminant Level.

E Value above quantitation range

Analyte detected below quantitation limits

0 RSD is greater than RSDlimit

RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits В Analyte detected in the associated Method Blank

Н Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit RL

Page 7 of 11

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1311337

19-Nov-13

Client: Project: Blagg Engineering

Sample ID MB-10292

Riddle F LS # 8

SampType: MBLK

TestCode: EPA Method 8015D: Diesel Range Organics

PBS Client ID:

Batch ID: 10292

RunNo: 14724

Prep Date: 11/12/2013 Analysis Date: 11/12/2013

SeqNo: 424197

Units: mg/Kg

%RPD

Analyte Diesel Range Organics (DRO) Result **PQL** ND

87.6

HighLimit

**RPDLimit** 

Qual

10.00

66

Surr: DNOP

8.8

131

Sample ID LCS-10292

Client ID: LCSS

SampType: LCS

TestCode: EPA Method 8015D: Diesel Range Organics RunNo: 14724

Prep Date: 11/12/2013

Batch ID: 10292

10

Analysis Date: 11/12/2013

SeqNo: 424198

Units: mg/Kg

HighLimit

127

131

Analyte Diesel Range Organics (DRO) Surr: DNOP

Result **PQL** 47

SPK value SPK Ref Val 10 50.00

5.000

50.20

5.020

49.80

4.980

%REC 0 94.4

SPK value SPK Ref Val %REC LowLimit

62.1

LowLimit

%RPD **RPDLimit** 

Qual

Sample ID 1311337-001AMS

SampType: MS

Result

44

4.7

94.1

TestCode: EPA Method 8015D: Diesel Range Organics

Client ID:

TH-EB @ 9.5'(UPP)

Batch ID: 10292

**PQL** 

10

RunNo: 14753

148

131

Prep Date: 11/12/2013 Analysis Date: 11/13/2013

SPK value SPK Ref Val

SPK value SPK Ref Val

SeqNo: 425368 %REC

86.8

108

Units: mg/Kg HighLimit

%RPD **RPDLimit** Qual

Analyte Diesel Range Organics (DRO) Surr: DNOP

5.4

0

n

Sample ID 1311337-001AMSD

SampType: MSD Batch ID: 10292

**PQL** 

10

RunNo: 14753

%REC

85.6

103

47.4

66

LowLimit

47.4

TestCode: EPA Method 8015D: Diesel Range Organics

0

Qual

**RPDLimit** 2.25 22.7

Client ID: TH-EB @ 9.5'(UPP) Prep Date: 11/12/2013

Surr: DNOP

Diesel Range Organics (DRO)

Analyte

Analysis Date: 11/13/2013 Result

43

5.1

SeqNo: 425394

Units: mg/Kg LowLimit

HighLimit 148

131

%RPD

0

Qualifiers:

R

Value exceeds Maximum Contaminant Level.

E

J

RSD is greater than RSDlimit O

Value above quantitation range

Analyte detected below quantitation limits

RPD outside accepted recovery limits

Spike Recovery outside accepted recovery limits

В Analyte detected in the associated Method Blank

Η Holding times for preparation or analysis exceeded ND Not Detected at the Reporting Limit

Р Sample pH greater than 2 for VOA and TOC only.

RLReporting Detection Limit Page 8 of 11

# Hall Environmental Analysis Laboratory, Inc.

19-Nov-13

1311337

Client:

Blagg Engineering

Project:

Riddle F LS # 8

Sample ID MB-10281 MK

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Client ID: **PBS** 

Batch ID: R14740

RunNo: 14740

Analysis Date: 11/12/2013

SeqNo: 424557

Units: %REC

Prep Date: Analyte

**RPDLimit** 

WO#:

Qual

Surr: BFB

Result 920 SPK value SPK Ref Val 1000

%REC LowLimit 92.4

HighLimit 129

Sample ID LCS-10281 MK

SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: LCSS

Batch ID: R14740

RunNo: 14740

SeqNo: 424558

Units: %REC

129

Analyte

Prep Date:

Analysis Date: 11/12/2013 **PQL** 

SPK value SPK Ref Val %REC

LowLimit

%RPD

**RPDLimit** 

Surr: BFB

Client ID:

Result 980

1000

98.2

HighLimit 74.5

74.5

%RPD

Qual

Sample ID MB-10281

SampType: MBLK

TestCode: EPA Method 8015D: Gasoline Range

Batch ID: 10281

RunNo: 14740 SeqNo: 424578

Units: mg/Kg

Analyte Gasoline Range Organics (GRO)

Prep Date: 11/11/2013

**PQL** SPK value SPK Ref Val ND 5.0

Analysis Date: 11/12/2013

%REC

LowLimit HighLimit %RPD **RPDLimit** 

Qual

Surr: BFB

920

1000

92 4

74.5

Sample ID LCS-10281 SampType: LCS

TestCode: EPA Method 8015D: Gasoline Range

Client ID: Prep Date:

LCSS

11/11/2013

Batch ID: 10281 Analysis Date: 11/12/2013

RunNo: 14740

SeqNo: 424579

126

129

129

Units: mg/Kg

Analyte Gasoline Range Organics (GRO)

Result

25 5.0 980

**PQL** 

SPK value SPK Ref Val %REC

LowLimit

HighLimit

%RPD

**RPDLimit** Qual

Surr: BFB

n

0

74.5

74.5

11/11/2013

Sample ID 1311337-001AMS TH-EB @ 9.5'(UPP)

SampType: MS Batch ID: 10281

SPK value SPK Ref Val

SPK value SPK Ref Val

ND

24.61

984.3

TestCode: EPA Method 8015D: Gasoline Range RunNo: 14740

99.9

98.2

Analyte

Client ID:

Prep Date:

**PQL** 

Analysis Date: 11/12/2013

25.00

1000

SeqNo: 424584

Units: mg/Kg

156

129

Qual

Gasoline Range Organics (GRO) Surr: BFB

Prep Date: 11/11/2013

23 980

Result

28

980

Result

24.63 49 985.2

%REC 92 2 99 1

LowLimit HighLimit 76

%RPD **RPDLimit** 

SampType: MSD

Analysis Date: 11/12/2013

POL

4.9

TestCode: EPA Method 8015D: Gasoline Range

SeaNo: 424585

74.5

Sample ID 1311337-001AMSD

TH-EB @ 9.5'(UPP)

Batch ID: 10281

RunNo: 14740

%REC

115

99.3

Units: mg/Kg

HighLimit

156

129

%RPD

21.7

O

**RPDLimit** 

17.7

0

Page 9 of 11

Qual

R

Analyte Gasoline Range Organics (GRO)

Surr: BFB

Client ID:

Qualifiers:

Value exceeds Maximum Contaminant Level.

E Value above quantitation range Analyte detected below quantitation limits В Analyte detected in the associated Method Blank

LowLimit

76

74.5

Η Holding times for preparation or analysis exceeded

Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only. Reporting Detection Limit

0 RSD is greater than RSDlimit

R RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1311337 19-Nov-13

Client: Project: Blagg Engineering Riddle F LS # 8

Sample ID MB-10281 MK

SampType: MBLK

TestCode: EPA Method 8021B: Volatiles

Client ID: **PBS** 

Batch ID: R14740

PQL

RunNo: 14740

Prep Date:

Analysis Date: 11/12/2013

SeqNo: 424628

Units: %REC

120

%RPD **RPDLimit**  Qual

Analyte Surr: 4-Bromofluorobenzene

1.1

Result

1.000

SPK value SPK Ref Val

111

%REC LowLimit HighLimit 80

Sample ID LCS-10281 MK

SampType: LCS

TestCode: EPA Method 8021B: Volatiles

Client ID: LCSS

Batch ID: R14740

RunNo: 14740

Units: %REC

Prep Date:

Analysis Date: 11/12/2013 **PQL** 

SeqNo: 424629

HighLimit %RPD

Analyte

Result 1.2 SPK value SPK Ref Val 1.000

%REC 116

LowLimit 80 120 **RPDLimit** 

Qual

Surr: 4-Bromofluorobenzene

11/11/2013

TestCode: EPA Method 8021B: Volatiles

Sample ID MB-10281 Client ID: PRS

SampType: MBLK

Batch ID: 10281

Analysis Date: 11/12/2013

0.050

0.10

RunNo: 14740 SeqNo: 424645

Units: mg/Kg

Qual

Analyte Benzene

Prep Date:

Result ND PQL SPK value SPK Ref Val

%REC LowLimit

HighLimit

%RPD

**RPDLimit** Qual

Toluene Ethylbenzene

Prep Date:

Xylenes, Total

ND 0.050 ND 0.050 ND

1.1

1.000

3.000

1.000

0.9911

0.9911

0.9911

2.973

SPK value SPK Ref Val

0.008276

0.01212

0

111

80

120

Surr: 4-Bromofluorobenzene

SampType: LCS

TestCode: EPA Method 8021B: Volatiles

Sample ID LCS-10281 Client ID: LCSS

Batch ID: 10281 Analysis Date: 11/12/2013

n

RunNo: 14740 SeqNo: 424646

80

80

80

80

120

120

120

120

Units: mg/Kg %RPD **RPDLimit** HighLimit

Analyte Result **PQL** SPK value SPK Ref Val %REC LowLimit 1.0 0.050 Benzene 1.000 0 99.7 Toluene 1.0 0.050 1.000 0 102 Ethylbenzene 1.0 0.050 1.000 0 102

0.10

Surr: 4-Bromofluorobenzene

SampType: MS

TestCode: EPA Method 8021B: Volatiles

104

116 80 120

Sample ID 1311337-002AMS Client ID:

Xylenes, Total

1-NSW @ 2'(UPP)

11/11/2013

Batch ID: 10281

RunNo: 14740

67.3

66.8

61.9

65.8

LowLimit

HighLimit

Page 10 of 11

Qual

Analyte Benzene Toluene

Prep Date: 11/11/2013 Result PQL

1.0

1.0

1.1

3.3

3.1

1.2

Analysis Date: 11/12/2013

0.050

0.050

0.050

0.099

SeqNo: 424654

%REC

102

105

108

109

Units: mg/Kg

145

144

153

149

%RPD **RPDLimit** 

Ethylbenzene Xylenes, Total

Qualifiers:

E Value above quantitation range

RSD is greater than RSDlimit O

Analyte detected in the associated Method Blank

Р

Reporting Detection Limit

Value exceeds Maximum Contaminant Level.

Analyte detected below quantitation limits

R RPD outside accepted recovery limits Spike Recovery outside accepted recovery limits

Н Holding times for preparation or analysis exceeded ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

# Hall Environmental Analysis Laboratory, Inc.

WO#:

1311337 19-Nov-13

Client:

Blagg Engineering

Project:

Riddle F LS # 8

Sample ID 1311337-002AMS

SampType: MS

TestCode: EPA Method 8021B: Volatiles

1-NSW @ 2'(UPP)

Batch ID: 10281

RunNo: 14740

Prep Date: 11/11/2013

Analysis Date: 11/12/2013

SeqNo: 424654

Units: mg/Kg

Analyte

Result

SPK value SPK Ref Val %REC

Surr: 4-Bromofluorobenzene

1.1

0.9911

116

HighLimit 120

**RPDLimit** 

Qual

SampType: MSD

TestCode: EPA Method 8021B: Volatiles

%RPD

Sample ID 1311337-002AMSD

Client ID: 1-NSW @ 2'(UPP)

Batch ID: 10281

RunNo: 14740

		•										
Prep Date: 11/11/2013		Analysis Date: 11/12/2013			S	SeqNo: 424655 Units: mg			Kg			
	Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual	
	Benzene	1.1	0.050	0.9930	0	106	67.3	145	4.02	20		
	Toluene	1.1	0.050	0.9930	0.008276	110	66.8	144	4.66	20		
	Ethylbenzene	1.1	0.050	0.9930	0	113	61.9	153	4.91	20		
	Xylenes, Total	3.4	0.099	2.979	0.01212	114	65.8	149	4.62	20		
	Surr: 4-Bromofluorobenzene	1.1		0.9930		115	80	120	0	0		

#### Qualifiers:

Value exceeds Maximum Contaminant Level.

Value above quantitation range

Analyte detected below quantitation limits

RSD is greater than RSDlimit 0

RPD outside accepted recovery limits R

Spike Recovery outside accepted recovery limits

Analyte detected in the associated Method Blank В

Η Holding times for preparation or analysis exceeded

ND Not Detected at the Reporting Limit

Sample pH greater than 2 for VOA and TOC only.

Reporting Detection Limit

Page 11 of 11



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87105

TEL: 505-345-3975 FAX: 505-345-4107 Website: www.hallenvironmental.com

# Sample Log-In Check List

**BLAGG** Work Order Number: 1311337 RcptNo: 1 Client Name: Received by/date: \ Logged By: 11/8/2013 10:00:00 AM **Ashley Gallegos** 11/8/2013 2:24:47 PM Completed By: Ashley Gallego: Reviewed By: Chain of Custody No 🗌 Yes Not Present ✓ 1. Custody seals intact on sample bottles? No 🗌 Not Present 2. Is Chain of Custody complete? 3. How was the sample delivered? Client Log In No 🗌 NA 🗆 Yes 🗸 4. Was an attempt made to cool the samples? NA 🗌 5. Were all samples received at a temperature of >0° C to 6.0°C Yes 🗸 No 🗌 No 🗆 Yes 🗹 Sample(s) in proper container(s)? 7. Sufficient sample volume for indicated test(s)? Yes 🗸 No 🗌 8. Are samples (except VOA and ONG) properly preserved? No 🗹 NA 🗌 Yes 9. Was preservative added to bottles? No 🗆 No VOA Vials 10.VOA vials have zero headspace? Yes 🗌 Yes No 🗹 11. Were any sample containers received broken? # of preserved bottles checked for pH: Yes 🗹 No 🗌 12. Does paperwork match bottle labels? (<2 or >12 unless noted) (Note discrepancies on chain of custody) No 🗆 Adjusted? 13. Are matrices correctly identified on Chain of Custody? **~** No 🗌 14. Is it clear what analyses were requested? Checked by: 15. Were all holding times able to be met? Yes 🗸 No 🗌 (if no, notify customer for authorization.) Special Handling (if applicable) Yes No 🗌 NA 🗹 16. Was client notified of all discrepancies with this order? Person Notified: Date: eMail Phone Fax In Person By Whom: Via: Regarding: Client Instructions: 17. Additional remarks: 18. Cooler Information Cooler No Temp C Condition Seal Intact Seal No Seal Date 1.0 Good Not Present

# BP AMERICA PRODUCTION COMPANY

SAN JUAN BASIN, NORTHWEST NEW MEXICO

#### UNLINED PERMANENT PIT CLOSURE PLAN

Riddle F LS 8 3004520921 Section: 8 T28N R08W RECEIVED OGD

2014 JAN -8 P 2:51

This plan will address the method, procedures, and protocols for closure of unlined permanent pits (UPPs) on BP America Production Company (BP) well sites pursuant to Subsection A of 19.15.17.13 NMAC. As stipulated in Paragraph (1) of Subsection C of 19.15.17.13 NMAC, BP will not commence closure without first obtaining approval of the closure plan submitted. If deviations from this plan are necessary, BP will request preapproval from the New Mexico Oil Conservation Division (NMOCD) of any specific changes and will be included on form C-144.

# **General Closure Plan**

1. BP shall notify the surface owner by certified mail, return receipt requested that it plans to close a UPP. Notice given will be at least 72 hours in advanced, but not more than one week prior to any closure operation. The notice shall include the well name, API number, and legal description of the location. Evidence of mailing of the notice to the address of the surface owner shown in the county tax records demonstrates compliance with this requirement.

BP notified the surface owner of this well that BP would be sampling and closing the UPP prior to commencement of any work. A copy of the letter sent to the surface owner is included with this submission.

2. BP is notifying the Santa Fe office at least 60 days prior to cessation of operations and providing a proposed schedule for closure enclosed with this submission, prior to any closure operation. The notice shall include the name, and the location of the UPP to be closed by unit letter, section, township and range. If the UPP closure is associated with a particular well, then the notice shall also include the well's name, number and API number.

Copies of the C-144 along with the proposed schedule are included with this submission. All approvals and signatures were obtained before the commencement of any work.

- 3. BP shall remove liquids and sludge from the UPP prior to implementing a closure method and dispose of the liquids and sludge in a NMOCD approved facility. The facilities to be used are:
  - a. BP Crouch Mesa Landfarm, Permit NM-02-003 (Solids)
  - b. JFJ Landfarm, Permit NM-01-010(B) (Solids and Sludge)
  - c. Basin Disposal, Permit NM-01-0005 (Liquids)
  - d. Envirotech Inc Soil Remediation Facility, Permit NM-01-0011 (Solids and Sludge)
  - e. BP Operated E.E. Elliott SWD #1, API 30-045-27799 (Liquids)
  - f. BP Operated 13 GCU SWD #1, API 30-045-28601 (Liquids)
  - g. BP Operated GCU 259 SWD, API 30-045-20006 (Liquids)
  - h. BP Operated GCU 306 SWD, API 30-045-24286 (Liquids)
  - i. BP Operated GCU 307 SWD, API 30-045-24248 (Liquids)
  - j. BP Operated GCU 328 SWD, API 30-045-24735 (Liquids)
  - k. BP Operated Pritchard SWD #1, API 30-045-28351 (Liquids)

No liquids or sludge remained in the UPP; therefore, no material was removed from the UPP.

4. BP shall remove any on-site equipment associated with a UPP unless the equipment is required for some other purpose.

No on-site equipment remained, so no equipment was removed.

BP Closure Plan for HPPs

5. BP shall test the soils beneath the UPP to determine whether a release has occurred. BP shall collect at a minimum: a five (5) point composite sample to include any obvious stained or wet soils, or other evidence of a release shall be collected under the UPP and analyze for the constituents listed in Table 1. The testing methods for those constituents are as follows;

Laboratory analysis was conducted on a representative sample, and all constituents returned results below the listed standards. A copy of the laboratory analysis is included with this submission.

Table 1 Closure Criteria for Soils Beneath Unlined Permanent Pit			
Depth below bottom of pit to groundwater less than 10,000 mg/l TDS	Constituent	Method*	Limit**
>100 feet	Chloride	EPA 300.0	20,000 mg/kg
	ТРН	EPA SW-846 Method 418.1	2,500 mg/kg
	GRO + DRO	EPA SW – 846 Method 8015M	1,00 mg/kg
	BTEX	EPA SW-846 Method 8021B or 8260B	50 mg/kg
	Benzene	EPA SW-846 Method 8021B or 8015M	10 mg/kg

Notes: mg/Kg = milligram per kilogram, BTEX = benzene, toluene, ethylbenzene, and total xylenes, TPH = total petroleum hydrocarbons, TDS = total dissolved solids.

- Or other test methods approved by the division
- \*\* Numerical limits or natural background level, whichever is greater
- If any contaminant exceeds the standards set in Table 1, greater than 100 feet to groundwater, BP will acknowledge NMOCD's position to require additional delineation upon review of the results. BP will not proceed with any further closure activities until approval is first granted by NMOCD.

#### No contaminants exceeded the listed standards.

7. If the sampling demonstrates that any contaminant concentrations are less than or equal to the parameters listed in Table 1, greater than 100 feet to groundwater, then BP shall backfill the excavation, with non-waste containing, uncontaminated, earthen material.

#### The UPP was backfilled with clean fill material.

8. BP shall reclaim the UPP location and all areas associated with the UPP including associated access roads to a safe and stable condition that blends with the surrounding undisturbed area. BP shall substantially restore the impacted surface area to the condition that existed prior to oil and gas operations by placement of the soil cover as provided in Paragraph (2) of Subsection H of 19.15.17.13 NMAC, re-contour the UPP location and associated areas to a contour that approximates the original contour and blends with the surrounding topography and re-vegetate according to Paragraph (5) of Subsection H of 19.15.17.13 NMAC.

BP will reclaim the UPP area specific to BLM standards for reclamation.

9. BP may propose an alternative to the re-vegetation or re-contouring requirement if it can demonstrate to the NMOCD's District III office that the proposed alternative provides equal or greater prevention of erosion, and protection of fresh water, public health and the environment. BP will seek surface owner approval of the proposed alternative and provide written documentation of the surface owner's approval to NMOCD for its approval.

BP will re-vegetate the UPP area along with the remainder of the P&A'd well pad with an approved BLM seed mix specific to the vegetative community the well is located in.

10. Areas reasonably needed for production operations or for subsequent drilling operations shall be compacted, covered, paved, or otherwise stabilized and maintained in such a way as to minimize dust and erosion to the extent practicable.

None exist.

11. The soil cover for closures after site contouring, shall include either the background thickness of topsoil or one foot of suitable material to establish vegetation at the site, whichever is greater.

The soil cover will match the remainder of the graded well pad including background thickness.

12. The soil cover will be constructed to the site's existing grade and all practicable efforts will be made to prevent ponding of water and erosion of the cover material.

The UPP area will be graded along with the remainder of P&A'd well pad to match existing grade and control erosion.

13. All areas disturbed by the closure of the UPP, except areas reasonably needed for production operations or for subsequent drilling operations, shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable.

The UPP area along with the entire P&A'd well pad will be reclaimed and re-vegetated as soon as practicable.

14. Top-soils and sub-soils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded in the first favorable growing season following closure the UPP.

The UPP area will be graded along with the remainder of the P&A'd well pad. The area along with the remainder of the well pad will be re-seeded as soon as possible for successful re-vegetation.

15. Reclamation of all disturbed areas no longer in use shall be considered complete when all ground surface disturbing activities at the site have been completed, and a uniform vegetative cover has been established that reflects a life-form ratio of plus or minus fifty percent (50%) of pre-disturbance levels and a total percent plant cover of at least seventy percent (70%) of pre-disturbance levels, excluding noxious weeds.

Reclamation including grading and seeding operations will be completed along-side the remainder of the P&A'd well pad.

16. The re-vegetation and reclamation obligations imposed by other applicable federal or tribal agencies on lands managed by those agencies shall supersede these provisions and govern the obligations of BP subject to those provisions, provided that the other requirements provide equal or better protection of fresh water, human health and the environment.

# The UPP area along with the remainder of the P&A'd well location will be reclaimed to BLM standards.

17. Pursuant to Subparagraph (e) of Paragraph (5) of Subsection H of 19.15.17.13 NMAC, BP shall notify the NMOCD when reclamation and re-vegetation has been successfully achieved.

#### Reclamation and re-vegetation will commence as soon as practicable.

- 18. Within 60 days of closure completion, BP shall submit a closure report on NMOCD's form C-144, and will include the following;
  - a. necessary attachments to document all closure activities
  - b. sampling results
  - c. information required by 19.15.17 NMAC
  - d. details on back-filling, capping and covering, where applicable.

#### This submission will contain all the required documents related to closure activities.

19. BP shall certify that all information in the report and attachments is accurate, truthful, and compliant with all applicable closure requirements and conditions specified in the approved closure plan.

# bp

# RECEIVED OCD

2014 JAN -8 P 2:51



BP America Production Company 200 Energy Court Farmington, NM 87401 Phone: (505) 326-9200

October 24, 2013

Bureau of Land Management Mark Kelly 6251 College Blvd, Suite A Farmington, NM 87402

# VIA CERTIFIED MAIL - RETURN RECEIPT REQUESTED

Re: Notification of plans to close/remove a below grade tank UPP Well Name: Riddle F LS 8

Dear Mr. Kelly,

As part of the NM "Pit Rule": 19.15.17.13 Closure Requirements, Paragraph J. BP America Production Company (BP) is required to notify the surface owner of BP's plans to close/remove and below grade tank. BP wishes to inform you of our plans to close/remove the below grade tank on its well pad located on your surface. BP plans to commence this work on or about November 18, 2013. If there aren't any unforeseen problems, the work should be completed within 10 working days.

Unless you have questions about this notice, there is no need to respond to this letter. If you do have any questions or concerns, please contact me at 505-326-9214

Sincerely,

Jerry Van Riper

9D Vale

Surface Land Negotiator

**BP** America Production Company

# Proposed Schedule for closure and remediation of unlined permanent pit in San Juan Co. New Mexico

- BP will notify the surface owner by certified mail of its plans to close an UPP. Will occur before request for closure permit submitted to Santa Fe office.
- Request unlined permanent pit closure permit from environmental bureau in the division's Santa Fe office. Five business days for permit to be signed and returned.
- *One business day for sampling*: samples collected in accordance with Subsection C of 19.15.17.13 NMAC.
- Five business days for laboratory analytical results to be returned.
- The division will be notified of results on form C-141. The division may require additional delineation upon review of results. *One business day to be completed.*
- If laboratory analytical results do not exceed the standards set forth in Table 1 of 19.15.17.13 NMAC then the unlined permanent pits will be backfilled, recontoured and reseeded in accordance with Subsection C and H of 19.15.17.13 NMAC and BP America Production Company Unlined Permanent Pit Closure Plan. Five working days for work to be completed.
- If laboratory analytical results determine that a release has occurred that exceeds the standards set forth in Table I of 19.15.17.13 NMAC, then additional division review may be required and approval must be received before proceeding with closure. Ten to fourteen working days for work to be completed.
- BP will submit a closure report on form C-144. Within 60 days of closure.



