District I State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 August 1, 2011 **Energy, Minerals and Natural Resources** Permit 182664 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 WELL API NUMBER Oil Conservation Division 30-015-41145 District III 1000 Rio Brazos Rd., Aztec, NM 87410 5. Indicate Type of Lease 1220 S. St Francis Dr. Phone:(505) 334-6178 Fax:(505) 334-6170 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease No. 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS DOC HOLLIDAY 32 STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 001 9. OGRID Numb DEVON ENERGY PRODUCTION COMPANY, LP 6137 3. Address of Operato 10. Pool name or Wildcat 333 W. Sheridan Avenue, Oklahoma City, OK 73102 4. Well Location Unit Letter D : 150 feet from the Nfrom the W line and feet 330 Township 24S Range 27E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3408 GR Pit or Below-grade Tank Application or Closure ___ Depth to Groundwater____ Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PLUG AND ABANDON CHANGE OF PLANS PERFORM REMEDIAL WORK REMEDIAL WORK ALTER CASING TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING ☐ MULTIPLE COMPL CASING/CEMENT JOB X Other: Other: Spud 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 2/7/2014 Spudded well. Additional drilling information under comments. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square . SIGNATURE Electronically Signed Manager, Regulatory Affairs 3/7/2014 Type or print name Randy Bolles E-mail address randy.bolles@dvn.com Telephone No. 405-228-8588

District Supervisor

DATE

3/11/2014

For State Use Only: APPROVED BY:

Randy Dade

TITLE

Comments

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
311 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 182664

NOTICESPUD COMMENTS

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 W. Sheridan Avenue	Permit Number:
Oklahoma City, OK 73102	182664
	Permit Type:
	NoticeSpud

Comments

Created By	Comment	Comment Date
	(2/7/14-2/8/14) Spud @ 13:30. TD 17-1/2" hole @ 387'. RIH w/ 9 jts 13-3/8" 48# H40 STC csg, set @ 387'. Lead w/ 410 sx Halcem, yld 1.33 cu fl/sk. Disp w/ 54.1 bbls FW. Circ 20 bbl cmt to surf.	3/7/2014
	(2/11/14-2/11/14) TD 12-1/4" hole @ 2250'. RIH w/ 55 jts 9-5/8" 40# K55 STC csg, set @ 2250'. Lead w/ 600 sx CIC, yld 1.85 cu ft/sk. Tail w/ 220 sx CIC, yld 1.33 cu ft/sk. Disp w/ 168 bbls FW. Circ 206 sx good cmt to surf.	3/7/2014
mmoravec	(2/20/14-2/21/14) RIH w/ whipstock, top set at 7064'. Pump 955 sx CIC, yld 1.2 cu ft/sk. Set whipstock. No cmt circ off of whipstock. TOC @ 6519'.	3/7/2014
	(2/28/14-3/3/14) TD 8-3/4" hole @ 12135'. RIH w/ 274 jts 5-1/2" 17# HCP110 BTC csg, set @ 12118'. 1st lead w/ 220 sx Tuned Light, yld 2.65 cu ft/sk. Tail w/ 865 sx Econocem, yld 1.96 cu ft/sk. 2nd lead w/ 2020 sx Versacem, yld 1.2 cu ft/sk. Pump 5 bbls sugar water. Disp w/ 276 bbls 2% KCl water. Continued to disp of 281 bbls. Pump additional 5 bbls 2% KCl water. RR @ 06:00 hrs.	3/7/2014