District I Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 August 1, 2011 Energy, Minerals and Natural Resources Permit 205452 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 WELL API NUMBER Oil Conservation Division 30-015-42629 District III 1000 Rio Brazos Rd., Aztec, NM 87410 5. Indicate Type of Lease 1220 S. St Francis Dr. Phone:(505) 334-6178 Fax:(505) 334-6170 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease No 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS BURTON FLAT DEEP UNIT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 8. Well Number 1. Type of Well: 062H 2. Name of Operator 9. OGRID Numbe DEVON ENERGY PRODUCTION COMPANY, LP 6137 3. Address of Operato 10. Pool name or Wildcat 333 W. Sheridan Avenue, Oklahoma City, OK 73102 4. Well Location : 1950 feet from the S Unit Letter L line and feet 100 from the W Township 21S Range 27E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3213 GR Pit or Below-grade Tank Application Or Closure ___ Depth to Groundwater___ Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _ 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTER CASING TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB X Other: Drilling/Cement Other: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore Drilling, casing and cement information.4/13/2015 Spudded well. Casing and Cement Program String Weight Grade Est TOC Dpth Sacks Yield Class Csg Dpth Hole Size Size lb/ft Set Held Drop 04/13/15 Surf 26 20 94 J-55 0 225 630 1.33 C Υ Y J-55 145 04/13/15 Surf 26 20 94 225 88 1.34 C 04/27/15 Int1 17.5 13.375 54.5 J-55 0 757 1050 1.34 C Y 05/01/15 Int2 12.25 9.625 40 J-55 0 2812 790 1.87 C Y 2812 9 625 40 J-55 C 05/01/15 Int2 12.25 0 265 1.33 RYP110 05/24/15 Prod 8.5 5.5 17 6788 12415 430 1.2 05/24/15 5.5 17 **RYP110** 1880 12415 2.29 Prod 8.5 05/24/15 Prod 8.5 5.5 17 RYP110 1880 12415 320 1.97 Н 05/24/15 Prod 8.5 5.5 17 RYP110 1880 12415 955 1.22 Н I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square . SIGNATURE Electronically Signed TITLE Manager, Regulatory Affairs DATE 6/4/2015

randy.bolles@dvn.com

District Supervisor

Telephone No.

DATE

405-228-8588

6/8/2015 6:35:27 AM

Randy Bolles

Randy Dade

Type or print name

For State Use Only:

APPROVED BY:

E-mail address

TITLE

Comments

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
311 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 205452

DRILLING COMMENTS

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 W. Sheridan Avenue Oklahoma City, OK 73102	Permit Number: 205452
	Permit Type: Drilling

Comments

Created By	Comment	Comment Date
mmoravec	First Intermediate cmt circ listed in bbls (6 bbls cmt circ to surf).	6/4/2015
	Production csg as follows: TD 8-3/4" hole @ 7726', TD 8-1/2" hole @ 12415'. Whipstock cmt plug included with production cement information. Lead w/ 430 sx	6/4/2015
	CIH, yld 1.20 cu ft/sk. TOC @ 6788', btm @ 7858'.	
mmoravec	RR on 5/26/15 @ 0:00.	6/4/2015