District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011 Permit 222839

APPLICATION FOR PERMIT	TO DRILL, RE-	ENTER, DEEPEN, F	PLUGBACK,	OR ADD A ZONE

DE		ODUCTION COMP.	ANY, LP		,	•		2. OGRID Nur 61	mber 137		
	3 W. Sheridan Aver ahoma City, OK 7						1	3. API Numbe 30	r 0-025-43317		
4. Property Coo 308	180/03/2007-07-08/2007-07-06							8. Well No. 11	16H		
				7. Su	rface Location						
JL - Lot B	Section 22	Township 23S	Range 33E	Lot Idn B	Feet From 305	N/S Line N	Feet From 17	'00	/W Line E	County	Lea
				8. Proposed	Bottom Hole Location	on					
JL - Lot H	Section 27	Township 23S	Range 33E	Lot Idn	Feet From 2630	N/S Line	Feet From	270 E	E/W Line E	County	Lea
				9. Po	ol Information						
TRIPLE X;B	ONE SPRING			12/04/2				5990	0		
				Addition	al Well Information						
11. Work Type Ne	w Well	12. Well Type OIL	13. Cable	13. Cable/Rotary		14. Lease Type State		15. Ground Level Elevation 3714			
16. Multiple N		17. Proposed Depth 17160	18. Form	18. Formation Upper Bone Spring			20	20. Spud Date 10/1/2016			
Depth to Ground water			Distance	property of the control of the contr				Distance to nearest surface water			

■ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1400	1230	0
Int1	12.25	9.625	40	5100	1630	0
Prod	8.75	5.5	17	17160	2500	4900

Casing/Cement Program: Additional Comments

13-3/8" Surface: Lead w/680sx (65:35) CI C Cmt: Poz (Fly Ash): 6% BWOC Bent + 5% BWOW Sodium Chloride + 0.125 #/sx Poly-E-Flake, 12.9 ppg, Water: 9.81 gal/sx, Yld: 1.85 ft3/sx; Tail w/550 sx CI C Cmt + 0.125 #/sx Poly-E-Flake, 14.8 ppg, Water: 6.32 gal/sx, Yld: 1.33 ft3/sx. TOC @ surface: 9-5/8" Inter:: Lead w/1060sx (65:35) CI C Cmt: Poz (Fly Ash): 6% BWOC Bent + 5% BWOW Sodium Chloride + 0.125 #/sx Poly-E-Flake, 12.9 ppg, Water: 9.81 gal/sx, Yld: 1.85 ft3/sx; Tail w/570 CI C Cmt + 0.125 #/sx Poly-E-Flake, 14.8 ppg, Water: 6.32 gal/sx, Yld: 1.85 ft3/sx; Tail w/570 CI C Cmt + 0.125 #/sx Poly-E-Flake, 14.8 ppg, Water: 6.32 gal/sx, Yld: 1.33 ft3/sx, TOC @ surface: 5-1/2" Prod: Lead w/420sx (50:40:10) CI C: Silicalite: Enhancer 923 + 10% BWOC Bent + 0.05% BWOC SA-1015 + 0.3% BWOC HR-800 + 0.2% BWOC FE-2 + 0.125 #/sx Pol-E-Flake + 0.5 #/sx D-Air 5000, 10.9 ppg, Water: 20.6 gal/sx, Yld. 3.31 ft3/sx. Tail w/2080sx (50:50) CI H Cmt: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bent, 14.5 ppg, Water: 5.31 gal/sx, Yld. 1.2 ft3/sx. TOC @ 4900'

22 Dropoend Playout Provention Program

22. Proposed Blowout Prevention Program						
Туре	Working Pressure	Test Pressure	Manufacturer			
Annular 3000		3000				
Double Ram	3000	3000				

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒, if applicable. Signature:				OIL CONSERVATIO	ON DIVISION
Printed Name:	Electronically filed by Randy Bolles	3	Approved By:	Paul Kautz	
Title:	Manager, Regulatory Affairs		Title:	Geologist	
Email Address:	randy.bolles@dvn.com		Approved Date:	6/23/2016	Expiration Date: 6/23/2018
Date:	6/23/2016	Phone: 405-228-8588	Conditions of Approval Attached		

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 222839

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-025-43317	2. Pool Code 59900	3. Pool Name TRIPLE X;BONE SPRING
4. Property Code 30884	5. Property Name THISTLE UNIT	6. Well No. 116H
7. OGRID No.	8. Operator Name	9. Elevation
6137	DEVON ENERGY PRODUCTION COMPANY, LP	3714

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	22	23S	33E	В	305	N	1700	E	Lea

11. Bottom Hole Location If Different From Surface

UL - Lot	Section 27	Township 23S	Range 33E	Lot Idn H	Feet From 2630	N/S Line N	Feet From 1270	E/W Line	County Lea
	12. Dedicated Acres 240.00		13. Joint or Infill		14. Consolidation Code			15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY

-	THE DIVISION
owns a working inter	OPERATOR CERTIFICATION the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either rest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling lered by the division.
E-Signed By:	Randy Bolles
Title:	Manager, Regulatory Affairs
Date:	6/23/2016
	SURVEYOR CERTIFICATION the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that d correct to the best of my belief.
Surveyed By:	Filimon Jaramillo
Date of Survey:	5/24/2016
Certificate Number:	PLS 12797

Form APD Comments

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>:
311 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>:
1000 Rio Brazos Rd., Azteo, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>:
1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 222839

PERMIT COMMENTS

Operator Name and Address:	API Number:
DEVON ENERGY PRODUCTION COMPANY, LP [6137]	30-025-43317
333 W. Sheridan Avenue	Well:
Oklahoma City, OK 73102	THISTLE UNIT #116H

Created By	Comment	Comment Date
dcook	BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.	6/23/2016
dcook	Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.	6/23/2016
dcook	Devon proposes the option of using a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi.	6/23/2016

Form APD Conditions

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>:
311 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>:
1000 Rio Brazos Rd., Azteo, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>:
1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 222839

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
DEVON ENERGY PRODUCTION COMPANY, LP [6137]	30-025-43317
333 W. Sheridan Avenue	Well:
Oklahoma City, OK 73102	THISTLE UNIT #116H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface 2) PRODUCTION CASING - Cement must tie back into intermediate casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	Must notify OCD Hobbs Office if lost circulation is encountered at 575-370-3186
pkautz	Must notify OCD Hobbs Office of any water flows in the Salado Formation at 575-370-3186. Report depth and flow rate
pkautz	1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.