UL - Lot

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210

Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Section

35

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 232181

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE
--

		APPLICATIO	N FOR PERMIT	O DRILL, RE-	ENTER, DEEPE	N, PLUGBACK	K, OR ADD A ZON	IE .		
Operator Name a BLACk	and Address K MOUNTAIN OF	PERATING LLC					2. OGRIE	371127		
	ain Street orth, TX 76102						3. API Nu	umber 30-025-43620		
4. Property Code 31744	1	5. Pro	perty Name GRAMA RIDGE	STATE COM			6. Well N	o. 013H		
				7. Sur	ace Location					
UL - Lot O	Section 2	Township 22S	Range 34E	Lot Idn O	Feet From 150	N/S Line S	Feet From 2335	E/W Line	County Le	ea

8. Proposed Bottom Hole Location Feet From

N/S Line

Feet From

1744

E/W Line

County

Lea

Lot Idn

	9. Pool Information	
GRAMA PINGE-BONE SPRING NE	1.54 (55.4) (4.7) (4.7)	20/25

GIVAMA RIBOE, BOINE SI RING, INE		20433
		90,000
	Additional Well Information	

New Well	OIL	13. CablerRotary	State	3572
16. Multiple N	17. Proposed Depth 22000	18. Formation Wolfcamp	19. Contractor	20. Spud Date 6/1/2017
Depth to Ground water		Distance from nearest fresh water well	£.9	Distance to nearest surface water

We will be using a closed-loop system in lieu of lined pits

Township

218

Range

34E

21 Droposed Casing and Coment Drogram

				Zi. Fioposeu Casing	and Cement Frogram		
[Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
	Surf	17.5	13.375	54.5	1750	1850	0
1	Int1	12.25	9.625	40	5820	1200	0
1	Int2	8.75	7	29	10500	990	0
ı	Prod	6	4.5	13.5	22000	1390	10250

Casing/Cement Program: Additional Comments

22. Proposed Blowout Prevention Program

22. Floposed Blowout Flevelition Flogram					
Type	Working Pressure	Test Pressure	Manufacturer		
Annular	3500	3500			
Double Ram	5000	5000			

knowledge and	I have complied with 19.15.14.9 (A)			OIL CONS	ERVATION DIVISION
Printed Name:	Electronically filed by Michael McC	Cracken	Approved By:	Paul Kautz	
Title:	COO		Title:	Geologist	
Email Address:	ail Address: michael.mccracken@blackmtn.com		Approved Date:	2/21/2017	Expiration Date: 2/21/2019
Date:	2/21/2017	Conditions of Apr	proval Attached	No. of the second second second	

WWW.WWW.		M.	IN.	OPERATOR CERTIFICATION
71 STORM (AL SCHOOL (AL SCHOOL (A				
DATE OF THE PARTY		Ш	1	Name to
71.50 A.C. 51.00 A.C.	1215/046		j	Tograma
100 00 00 00 00 00 00 00 00 00 00 00 00	TOO CHOOL	ě	1	SERVEYOR CERTIFICATION
CORNER COORDINATES TABLE (MAD 27) A 17-02675-20, IN-1704-6-29		Jan.	-	2,0207
E THERDICK BYTESHO C THERDICK BYTESHO B THERDICK BYTESHO	Proposed Provinces Print 180 FSL Year FSL		1	2.10.207
	*107800°E	SI.	NW.	Zeos Office

Form APD Comments

Permit 232181

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>:
311 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>:
1000 Rio Brazos Rd., Azteo, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>:
1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

PERMIT COMMENTS

Operator Name and Address:	API Number:
BLACK MOUNTAIN OPERATING LLC [371127]	30-025-43620
500 Main Street	Well:
Fort Worth, TX 76102	GRAMA RIDGE STATE COM #013H

Created By Comment Comment Date District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Frencis Dr., Santa Fe. NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 232181

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
BLACK MOUNTAIN OPERATING LLC [371127]	30-025-43620
500 Main Street	Well:
Fort Worth, TX 76102	GRAMA RIDGE STATE COM #013H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERMEDIATE1 CASING - Cement must circulate to surface 2) INTERMEDIATE2 CASING - Cement must tie back into intermediate1 casing 3) PRODUCTION CASING - Cement must tie back into intermediate2 casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	Only Fresh Water and Air are Valid Drilling Fluids for Surface Casing
pkautz	Operator shall notify appropriate District office when setting conductor pipe.
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of spudding a well.
pkautz	It is the operator's responsibility to monitor cancellation dates of approved APDs. APD's are good for 2 years and may be extended for one year. Only one 1 year extension will be granted if submitted by C-103 before expiration date. After expiration date or after a 1 year extension must submit new APD.
pkautz	If an APD expires and if site construction has occurred, site remediation is required.
pkautz	Stage Tool 1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.
pkautz	Submit Gas Capture Plan form prior to spudding or initiating recompletion operations