

Form 3160-3  
(June 2015)

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

|   |                                   |   |
|---|-----------------------------------|---|
| 1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER   |                                   | 5. Lease Serial No.                               |
| 1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other                              |                                   | 6. If Indian, Allottee or Tribe Name              |
| 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone |                                   | 7. If Unit or CA Agreement, Name and No.          |
| 2. Name of Operator<br><b>[372165]</b>  |                                   | 8. Lease Name and Well No.<br><b>[322254]</b>     |
| 3a. Address   | 3b. Phone No. (include area code) | 9. API Well No. <b>30-025-48390</b><br><b>000</b> |
| 4. Location of Well (Report location clearly and in accordance with any State requirements. *)<br>At surface<br>At proposed prod. zone            |                                   | 10. Field and Pool, or Exploratory <b>[96434]</b> |
| 14. Distance in miles and direction from nearest town or post office*   |                                   | 11. Sec., T. R. M. or Blk. and Survey or Area     |
| 15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)                             |                                   | 12. County or Parish                              |
| 16. No of acres in lease  |                                   | 13. State   |
| 17. Spacing Unit dedicated to this well   |                                   |   |
| 18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.  |                                   | 20. BLM/BIA Bond No. in file                      |
| 21. Elevations (Show whether DF, KDB, RT, GL, etc.)   |                                   | 22. Approximate date work will start*             |
| 23. Estimated duration  |                                   |   |
| 24. Attachments   |                                   |   |

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

|                         |                      |      |
|-------------------------|----------------------|------|
| 25. Signature           | Name (Printed/Typed) | Date |
| Title                   |                      |      |
| Approved by (Signature) | Name (Printed/Typed) | Date |
| Title                   | Office               |      |

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**GCP Rec 01/25/2021**



*KZ*  
**01/25/2021**

SL

(Continued on page 2)

\*(Instructions on page 2)



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Application Data Report

06/10/2020

APD ID: 10400049567

Submission Date: 10/17/2019

Highlighted data  
reflects the most  
recent changes

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: RAIDER FEDERAL

Well Number: 401H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - General

APD ID: 10400049567

Tie to previous NOS? N

Submission Date: 10/17/2019

BLM Office: CARLSBAD

User: Kanicia Schlichting

Title: Sr. Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM126971

Lease Acres: 240

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? Y

Permitting Agent? NO

APD Operator: CENTENNIAL RESOURCE PRODUCTION LLC

Operator letter of designation:

## Operator Info

Operator Organization Name: CENTENNIAL RESOURCE PRODUCTION LLC

Operator Address: 1001 17th Street, Suite 1800

Zip: 80202

Operator PO Box:

Operator City: Denver

State: CO

Operator Phone: (720)499-1400

Operator Internet Address:

## Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: RAIDER FEDERAL

Well Number: 401H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: 2ND BONE  
SPRING SHALEPool Name: RED HILLS; BONE  
SPRING, NORTH

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,OIL

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Is the proposed well in an area containing other mineral resources?** USEABLE WATER,NATURAL GAS,OIL

**Is the proposed well in a Helium production area?** N **Use Existing Well Pad?** N **New surface disturbance?**

**Type of Well Pad:** MULTIPLE WELL

**Multiple Well Pad Name:**

**Number:** 302

**Well Class:** HORIZONTAL

RAIDER PAD

**Number of Legs:** 1

**Well Work Type:** Drill

**Well Type:** OIL WELL

**Describe Well Type:**

**Well sub-Type:** INFILL

**Describe sub-type:**

**Distance to town:** 18 Miles

**Distance to nearest well:** 30 FT

**Distance to lease line:** 433 FT

**Reservoir well spacing assigned acres Measurement:** 160 Acres

**Well plat:** RAIDER\_FEDERAL\_401H\_\_\_C102\_20191016122132.pdf

RAIDER\_FEDERAL\_401H\_\_\_Lease\_C102\_20191016122132.pdf

**Well work start Date:** 04/20/2020

**Duration:** 30 DAYS

### Section 3 - Well Location Table

**Survey Type:** RECTANGULAR

**Describe Survey Type:**

**Datum:** NAD83

**Vertical Datum:** NAVD88

**Survey number:** 23782

**Reference Datum:** GROUND LEVEL

| Wellbore   | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude  | Longitude   | County | State       | Meridian    | Lease Type | Lease Number | Elevation | MD   | TVD  | Will this well produce from this lease? |
|------------|---------|--------------|---------|--------------|------|-------|---------|-------------------|-----------|-------------|--------|-------------|-------------|------------|--------------|-----------|------|------|---|
| SHL Leg #1 | 433     | FNL          | 1302    | FEL          | 24S  | 34E   | 21      | Aliquot NENE      | 32.209109 | -103.470598 | LEA    | NEW MEXI CO | NEW MEXI CO | F          | NMNM 126971  | 3531      | 0    | 0    | Y                                       |
| KOP Leg #1 | 433     | FNL          | 1302    | FEL          | 24S  | 34E   | 21      | Aliquot NENE      | 32.209109 | -103.470598 | LEA    | NEW MEXI CO | NEW MEXI CO | F          | NMNM 126971  | -6396     | 9963 | 9927 | Y                                       |

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

| Wellbore     | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude  | Longitude   | County | State       | Meridian    | Lease Type | Lease Number | Elevation | MD    | TVD   | Will this well produce from this lease? |
|--------------|---------|--------------|---------|--------------|------|-------|---------|-------------------|-----------|-------------|--------|-------------|-------------|------------|--------------|-----------|-------|-------|---|
| PPP Leg #1-1 | 100     | FNL          | 1650    | FEL          | 24S  | 34E   | 21      | Aliquot NWNE      | 32.210026 | -103.471724 | LEA    | NEW MEXI CO | NEW MEXI CO | F          | NMNM 126971  | -6969     | 10863 | 10500 | Y                                       |
| EXIT Leg #1  | 100     | FSL          | 1650    | FEL          | 24S  | 34E   | 21      | Aliquot SWSE      | 32.196069 | -103.471704 | LEA    | NEW MEXI CO | NEW MEXI CO | F          | NMNM 126971  | -6969     | 15325 | 10500 | Y                                       |
| BHL Leg #1   | 100     | FSL          | 1650    | FEL          | 24S  | 34E   | 21      | Aliquot SWSE      | 32.196069 | -103.471704 | LEA    | NEW MEXI CO | NEW MEXI CO | F          | NMNM 126971  | -6969     | 15325 | 10500 | Y                                       |



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Drilling Plan Data Report

06/10/2020

APD ID: 10400049567

Submission Date: 10/17/2019

Highlighted data  
reflects the most  
recent changes

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: RAIDER FEDERAL

Well Number: 401H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Geologic Formations

| Formation ID | Formation Name         | Elevation | True Vertical Depth | Measured Depth | Lithologies       | Mineral Resources     | Producing Formation |
|--------------|------------------------|-----------|---------------------|----------------|-------------------|-----------------------|---------------------|
| 563837       | RUSTLER                | 3531      | 1215                | 1215           | SANDSTONE         | NONE                  | N                   |
| 563841       | CAPITAN REEF           | -1855     | 5386                | 5386           | OTHER : CARBONATE | USEABLE WATER         | N                   |
| 563838       | BELL CANYON            | -1897     | 5428                | 5428           | SANDSTONE         | NATURAL GAS, OIL      | N                   |
| 563842       | CHERRY CANYON          | -2797     | 6328                | 6328           | SANDSTONE         | NATURAL GAS, OIL      | N                   |
| 563843       | BRUSHY CANYON          | -4196     | 7727                | 7727           | SANDSTONE         | NATURAL GAS, OIL      | N                   |
| 563844       | BONE SPRING LIME       | -5584     | 9115                | 9115           | OTHER : CARBONATE | NATURAL GAS, OIL      | N                   |
| 563840       | AVALON SAND            | -5672     | 9203                | 9203           | SHALE             | CO2, NATURAL GAS, OIL | N                   |
| 563839       | FIRST BONE SPRING SAND | -6659     | 10190               | 10190          | SANDSTONE         | NATURAL GAS, OIL      | N                   |
| 563835       | BONE SPRING 2ND        | -6870     | 10401               | 10401          | SANDSTONE         | NATURAL GAS, OIL      | Y                   |

## Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M

Rating Depth: 10500

**Equipment:** The BOP and related equipment will meet or exceed the requirements of a 5M-psi system as set forth in On Shore Order No. 2. See attached BOP Schematic. A. Casinghead: 13 5/8" – 5,000 psi SOW x 13" – 5,000 psi WP Intermediate Spool: 13" – 5,000 psi WP x 11" – 5,000 psi WP Tubinghead: 11" – 5,000 psi WP x 7 1/16" – 15,000 psi WP B. Minimum Specified Pressure Control Equipment • Annular preventer • One Pipe ram, One blind ram • Drilling spool, or blowout preventer with 2 side outlets. Choke side will be a 3-inch minimum diameter, kill line shall be at least 2-inch diameter • 3 inch diameter choke line • 2 – 3 inch choke line valves • 2 inch kill line • 2 chokes with 1 remotely controlled from rig floor (see Figure 2) • 2 – 2 inch kill line valves and a check valve • Upper kelly cock valve with handle available • When the expected pressures approach working pressure of the system, 1 remote kill line tested to stack pressure (which shall run to the outer edge of the substructure and be unobstructed) • Lower kelly cock valve with handle available • Safety valve(s) and subs to fit all drill string connections in use • Inside BOP or float sub available • Pressure gauge on choke manifold • All BOPE connections subjected to well pressure shall be flanged, welded, or clamped • Fill-up line above the uppermost preventer. C. Auxiliary Equipment • Audio and visual mud monitoring equipment shall be placed to detect volume changes indicating loss or gain of circulating fluid volume. (OOS 1, III.C.2) • Gas Buster will be used below intermediate casing setting depth. • Upper and lower kelly cocks with handles, safety valve and subs to fit all drill string connections and a pressure gauge installed on choke manifold.

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Requesting Variance?** YES

**Variance request:** Centennial is requesting to use a flex hose on the choke manifold. Please see attachment for specs in section 8.

**Testing Procedure:** The BOP test shall be performed before drilling out of the surface casing shoe and will occur at a minimum: a. when initially installed b. whenever any seal subject to test pressure is broken c. following related repairs d. at 30 day intervals e. checked daily as to mechanical operating conditions. The ram type preventer(s) will be tested using a test plug to 250 psi (low) and 5,000 psi (high) (casinghead WP) with a test plug upon its installation onto the 13 surface casing. If a test plug is not used, the ram type preventer(s) shall be tested to 70% of the minimum internal yield pressure of the casing. The annular type preventer(s) shall be tested to 3500 psi. Pressure will be maintained for at least 10 minutes or until provisions of the test are met, whichever is longer. A Sundry Notice (Form 3160 5), along with a copy of the BOP test report, shall be submitted to the local BLM office within 5 working days following the test. If the bleed line is connected into the buffer tank (header), all BOP equipment including the buffer tank and associated valves will be rated at the required BOP pressure. The BLM office will be provided with a minimum of four (4) hours notice of BOP testing to allow witnessing. The BOP Configuration, choke manifold layout, and accumulator system, will be in compliance with Onshore Order 2 for a 5,000 psi system. A remote accumulator will be used. Pressures, capacities, and specific placement and use of the manual and/or hydraulic controls, accumulator controls, bleed lines, etc., will be identified at the time of the BLM 'witnessed BOP test. Any remote controls will be capable of both opening and closing all preventers and shall be readily accessible.

**Choke Diagram Attachment:**

HP650\_10M\_Choke\_Manifold\_20191010162831.pdf

**BOP Diagram Attachment:**

HP650\_BOP\_Schematic\_CoFlex\_Choke\_5K\_2019\_1\_29\_20191010162910.pdf

**Section 3 - Casing**

| Casing ID | String Type  | Hole Size | Csg Size | Condition | Standard | Tapered String | Top Set MD | Bottom Set MD | Top Set TVD | Bottom Set TVD | Top Set MSL | Bottom Set MSL | Calculated casing length MD | Grade | Weight | Joint Type      | Collapse SF | Burst SF | Joint SF Type | Joint SF | Body SF Type | Body SF |  |
|-----------|--------------|-----------|----------|-----------|----------|----------------|------------|---------------|-------------|----------------|-------------|----------------|-----------------------------|-------|--------|-----------------|-------------|----------|---------------|----------|--------------|---------|--|
| 1         | CONDUCTOR    | 26        | 20.0     | NEW       | API      | N              | 0          | 120           | 0           | 120            | 3531        | 3411           | 120                         | H-40  | 94     | OTHER - Weld    |             |          |               |          |              |         |  |
| 2         | SURFACE      | 17.5      | 13.375   | NEW       | API      | N              | 0          | 1350          | 0           | 1350           | 3531        | 2181           | 1350                        | J-55  | 54.5   | OTHER - BTC     | 1.7         | 4.1      | DRY           | 11.59    | DRY          | 11.59   |  |
| 3         | INTERMEDIATE | 12.25     | 9.625    | NEW       | API      | N              | 0          | 5386          | 0           | 5350           | 3498        | -1819          | 5386                        | J-55  | 40     | LT&C            | 1.31        | 1.42     | DRY           | 2.43     | DRY          | 2.94    |  |
| 4         | PRODUCTION   | 8.75      | 5.5      | NEW       | API      | N              | 0          | 9963          | 0           | 9727           | 3498        | -6196          | 9963                        | P-110 | 20     | OTHER - TCBC-HT | 2.15        | 2.45     | DRY           | 3.23     | DRY          | 3.23    |  |
| 5         | PRODUCTION   | 8.5       | 5.5      | NEW       | API      | N              | 9963       | 15325         | 9927        | 10500          | -6396       | -6969          | 5362                        | P-110 | 20     | OTHER - TCBC-HT | 2.03        | 2.31     | DRY           | 3.05     | DRY          | 3.05    |  |

**Casing Attachments**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Casing Attachments**

---

**Casing ID:** 1                    **String Type:** CONDUCTOR

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

---

**Casing ID:** 2                    **String Type:** SURFACE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CASING\_ASSUMPTIONS\_WORKSHEET\_20180920095914.pdf

---

**Casing ID:** 3                    **String Type:** INTERMEDIATE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CASING\_ASSUMPTIONS\_WORKSHEET\_20180920100112.pdf

---

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Casing Attachments**

**Casing ID:** 4      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CASING\_ASSUMPTIONS\_WORKSHEET\_20190307121343.pdf

Technical\_Data\_Sheet\_HIS\_TCBC\_HT\_5.5\_20\_P110RY\_20200428092149.pdf

**Casing ID:** 5      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

CASING\_ASSUMPTIONS\_WORKSHEET\_20180920100203.pdf

Technical\_Data\_Sheet\_HIS\_TCBC\_HT\_5.5\_20\_P110RY\_20200428092130.pdf

**Section 4 - Cement**

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives |
|-------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|-----------|
| PRODUCTION  | Lead      |                  | 0      | 0         | 0            | 0     | 0       | 0     | 0       |             | 0         |

|           |      |  |   |     |     |      |      |     |   |       |  |
|-----------|------|--|---|-----|-----|------|------|-----|---|-------|--|
| CONDUCTOR | Lead |  | 0 | 120 | 121 | 1.49 | 12.9 | 181 | 0 | Grout | Bentonite 4% BWOC, Cellophane #/sx, CaCl2 2% BWOC. |
|-----------|------|--|---|-----|-----|------|------|-----|---|-------|--|

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: RAIDER FEDERAL

Well Number: 401H

| String Type  | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type                  | Additives  |
|--------------|-----------|------------------|--------|-----------|--------------|-------|---------|-------|---------|------------------------------|--|
| SURFACE      | Lead      |                  | 0      | 850       | 679          | 1.74  | 13.5    | 1181  | 100     | Class C Premium              | Premium Gel Bentonite 4%, C-45 Econolite 0.25%, Phenoseal 0.25#/sk, CaCl 1%, Defoamer C-41P 0.75%  |
| SURFACE      | Tail      |                  | 850    | 1350      | 518          | 1.34  | 14.8    | 695   | 100     | Class C Premium              | C-45 Econolite 0.10%, CaCl 1.0%  |
| INTERMEDIATE | Lead      |                  | 0      | 4886      | 1161         | 3.44  | 10.7    | 3993  | 150     | TXI Lightweight              | Salt 1.77/sk, C-45 Econolite 2.25%, STE 6.00%, Citric Acid 0.18%, C-19 0.10%, CSA-1000 0.20%, C-530P 0.30%, CTB-15 LCM 7#/sk, Gyp Seal 8#/sk |
| INTERMEDIATE | Tail      |                  | 4886   | 5386      | 141          | 1.33  | 14.8    | 188   | 20      | Class C Premium              | C-45 Econolite 0.10%, Citric acid 0.05%, C503P 0.25%   |
| PRODUCTION   | Lead      |                  | 0      | 9963      | 976          | 3.41  | 10.6    | 3329  | 30      | TXI Lightweight              | Salt 8.98#/sk, STE 6.00%, Citric acid 0.20%, CSA-1000 0.23%, C47B 0.10%, C-503P 0.30%  |
| PRODUCTION   | Tail      |                  | 9963   | 15325     | 1238         | 1.24  | 14.2    | 1535  | 25      | 50:25:25 Class H: Poz: CPO18 | Citric acid 0.03%, CSA-1000 0.05%, C47B 0.25%, C-503P 0.30%  |

### Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

**Describe what will be on location to control well or mitigate other conditions:** Sufficient quantities of mud materials will be on the well site at all times for the purpose of assuring well control and maintaining wellbore integrity. Surface interval will employ fresh water mud. The intermediate hole will utilize a diesel emulsified brine fluid to inhibit salt washout and prevent severe fluid losses. The production hole will employ oil base fluid to inhibit formation reactivity and of the appropriate density to maintain well control.

**Describe the mud monitoring system utilized:** Centrifuge separation system. Open tank monitoring with EDR will be used for drilling fluids and return volumes. Open tank monitoring will be used for cement and cuttings return volumes. Mud properties will be monitored at least every 24 hours using industry accepted mud check practices.

### Circulating Medium Table

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

| Top Depth | Bottom Depth | Mud Type             | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | PH | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|----------------------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
| 1350      | 5386         | OTHER : Brine        | 9                    | 10                   |                     |                             |    |                |                |                 |                            |
| 5386      | 1532<br>5    | OTHER :<br>OBM/Brine | 8.8                  | 10                   |                     |                             |    |                |                |                 |                            |
| 0         | 1350         | OTHER : FW           | 8.6                  | 9.5                  |                     |                             |    |                |                |                 |                            |

### Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

Will utilize MWD/LWD (Gamma Ray logging) from intermediate hole to TD of the well.

**List of open and cased hole logs run in the well:**

OTHER,

**Other log type(s):**

GR

**Coring operation description for the well:**

N/A

### Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 5460

**Anticipated Surface Pressure:** 3150

**Anticipated Bottom Hole Temperature(F):** 170

**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO

**Describe:**

**Contingency Plans geohazards description:**

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required?** YES

**Hydrogen sulfide drilling operations plan:**

H2S\_Plan\_Raider\_Federal\_401H\_20191016125729.docx

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

## Section 8 - Other Information

### Proposed horizontal/directional/multi-lateral plan submission:

RAIDER\_FEDERAL\_401H\_Dir\_AC\_Plot\_20191016125752.pdf

### Other proposed operations facets description:

We are planning on using a spudder rig to preset surface casing. Please see attached batch drilling procedure. Gas Capture Plan is attached.

### Other proposed operations facets attachment:

Raider\_Federal\_Com\_502H\_701H\_702H\_Gas\_Capture\_Plan\_20190307124300.docx


CRD\_Batch\_Setting\_Procedures\_20191010165234.pdf

### Other Variance attachment:


H\_P650\_Flex\_Hose\_\_\_Continental\_Hose\_PO\_4500409659\_SN\_67255\_20190307122906.pdf

CDEV\_Multi\_Bowl\_Wellhead\_Running\_Procedure\_3\_String\_Bonesprings\_20191016125815.pdf


CONFIDENTIAL



# H&P650 – Flex 3 Choke Manifold – 10M



# H&P 650



WELL HEAD IS 12" BGL

CASING ASSUMPTIONS WORKSHEET:

Centralizer Program:

Surface:       - 3 welded bow spring centralizers, one on each of the bottom 3 joints, plus one on the shoe joint (4 minimum)  
                  - No Cement baskets will be run

Production:    - 1 welded bow spring centralizer on a stop ring 6' above float shoe  
                  - 1 centralizer every other joint to the top of the tail cement  
                  - 1 centralizer every 4 joints to 500' below the top of the lead cement  
                  - The actual number and placement of centralizers will be determined from hole deviation and potential production zones. Centralizers will be run for maximum practical standoff and through all potential productive zones.

- All casing strings below the conductor shall be tested, prior to drilling out the casing shoe, to 0.22 psi/ft of casing string length or 1500 psi, whichever is greater, but not to exceed 70% of the internal yield pressure of the casing. If pressure declines more than 10 percent in 30 minutes, corrective action will be taken.

No freshly hard banded pipe will be rotated in the surface casing

- CENTENNIAL RESOURCE DEVELOPOMENT will not employ an air-drill rig for the surface casing. The casing shoe will be tested by drilling 5'-10' out from under the shoe and pressure testing to the maximum expected mud weight equivalent as shown in the mud program listed in the drilling plan.

CASING ASSUMPTIONS WORKSHEET:

Centralizer Program:

Surface: - 3 welded bow spring centralizers, one on each of the bottom 3 joints, plus one on the shoe joint (4 minimum)  
- No Cement baskets will be run

Production: - 1 welded bow spring centralizer on a stop ring 6' above float shoe  
- 1 centralizer every other joint to the top of the tail cement  
- 1 centralizer every 4 joints to 500' below the top of the lead cement  
- The actual number and placement of centralizers will be determined from hole deviation and potential production zones. Centralizers will be run for maximum practical standoff and through all potential productive zones.

- All casing strings below the conductor shall be tested, prior to drilling out the casing shoe, to 0.22 psi/ft of casing string length or 1500 psi, whichever is greater, but not to exceed 70% of the internal yield pressure of the casing. If pressure declines more than 10 percent in 30 minutes, corrective action will be taken.

No freshly hard banded pipe will be rotated in the surface casing

- CENTENNIAL RESOURCE DEVELOPOMENT will not employ an air-drill rig for the surface casing. The casing shoe will be tested by drilling 5'-10' out from under the shoe and pressure testing to the maximum expected mud weight equivalent as shown in the mud program listed in the drilling plan.



|               |         |
|---------------|---------|
| <b>Size</b>   | 5.5     |
| <b>Grade</b>  | P110 RY |
| <b>Weight</b> | 20      |

## TCBC-HT


SeAH Steel

| Coupling and Pipe Dimensions (in) |                |                |                 |              |                |                |
|-----------------------------------|----------------|----------------|-----------------|--------------|----------------|----------------|
|                                   | Outer Diameter | Inner Diameter | Coupling Length | Make-up Loss | Wall Thickness | Drift Diameter |
| <b>Coupling</b>                   | 6.300          | 5.383          |                 |              |                |                |
| <b>Pipe</b>                       |                | 4.778          | 8.250           | 4.125        | 0.361          | 4.653          |
| <b>Pin</b>                        |                | 4.778          |                 |              |                |                |


| Torque Values (ft-lbs) |                      |         |                                  |              |
|------------------------|----------------------|---------|----------------------------------|--------------|
| Field End Make-Up      |                      |         | Max. Working Torque <sup>1</sup> | Yield Torque |
| Minimum                | Optimum <sup>2</sup> | Maximum |                                  |              |
| 10,000                 | 13,500               | 18,500  | 22,250                           | 25,200       |

| Yield Stress (x1000 lbs.) |             |
|---------------------------|-------------|
| Tensile                   | Compressive |
| 100%                      | 100%        |

| Maximum Pressure (psi) |          |
|------------------------|----------|
| Internal               | External |
| 100%                   | 100%     |



- <sup>1</sup> Max. Working Torque value is not to be exceeded during operation.
- <sup>2</sup> If Optimum Torque does not meet the Base of Triangle Stamp, M/U to the Base of Triangle.



\*Data are for information purposes only. Though HIS has made efforts to ensure accuracy, HIS makes no warranty for loss or damage due to its use.



**5.5"   20#   .361"   P-110 Restricted Yield (RY)**

### **Dimensions (Nominal)**

|                  |        |        |
|------------------|--------|--------|
| Outside Diameter | 5.500  | in.    |
| Wall             | 0.361  | in.    |
| Inside Diameter  | 4.778  | in.    |
| Drift            | 4.653  | in.    |
| Weight, T&C      | 20.000 | lbs/ft |
| Weight, PE       | 19.830 | lbs/ft |

### **Performance Properties (Minimum)**

|                           |        |          |
|---------------------------|--------|----------|
| Minimum Yield Strength    | 110000 | psi      |
| Maximum Yield Strength    | 125000 | psi      |
| Collapse, PE              | 11100  | psi      |
| Internal Yield Pressure   |        |          |
| PE                        | 12630  | psi      |
| LTC                       | 12360  | psi      |
| BTC                       | 12360  | psi      |
| Yield Strength, Pipe Body | 641    | 1000 lbs |
| Joint Strength            |        |          |
| LTC                       | 548    | 1000 lbs |
| BTC                       | 667    | 1000 lbs |

Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.

CASING ASSUMPTIONS WORKSHEET:

Centralizer Program:

Surface:           - 3 welded bow spring centralizers, one on each of the bottom 3 joints, plus one on the shoe joint (4 minimum)  
                      - No Cement baskets will be run

Production:       - 1 welded bow spring centralizer on a stop ring 6' above float shoe  
                      - 1 centralizer every other joint to the top of the tail cement  
                      - 1 centralizer every 4 joints to 500' below the top of the lead cement  
                      - The actual number and placement of centralizers will be determined from hole deviation and potential production zones. Centralizers will be run for maximum practical standoff and through all potential productive zones.

- All casing strings below the conductor shall be tested, prior to drilling out the casing shoe, to 0.22 psi/ft of casing string length or 1500 psi, whichever is greater, but not to exceed 70% of the internal yield pressure of the casing. If pressure declines more than 10 percent in 30 minutes, corrective action will be taken.

No freshly hard banded pipe will be rotated in the surface casing

- CENTENNIAL RESOURCE DEVELOPMENT will not employ an air-drill rig for the surface casing. The casing shoe will be tested by drilling 5'-10' out from under the shoe and pressure testing to the maximum expected mud weight equivalent as shown in the mud program listed in the drilling plan.

CASING ASSUMPTIONS WORKSHEET:

Centralizer Program:

Surface:           - 3 welded bow spring centralizers, one on each of the bottom 3 joints, plus one on the shoe joint (4 minimum)  
                      - No Cement baskets will be run

Production:       - 1 welded bow spring centralizer on a stop ring 6' above float shoe  
                      - 1 centralizer every other joint to the top of the tail cement  
                      - 1 centralizer every 4 joints to 500' below the top of the lead cement  
                      - The actual number and placement of centralizers will be determined from hole deviation and potential production zones. Centralizers will be run for maximum practical standoff and through all potential productive zones.

- All casing strings below the conductor shall be tested, prior to drilling out the casing shoe, to 0.22 psi/ft of casing string length or 1500 psi, whichever is greater, but not to exceed 70% of the internal yield pressure of the casing. If pressure declines more than 10 percent in 30 minutes, corrective action will be taken.

No freshly hard banded pipe will be rotated in the surface casing

- CENTENNIAL RESOURCE DEVELOPMENT will not employ an air-drill rig for the surface casing. The casing shoe will be tested by drilling 5'-10' out from under the shoe and pressure testing to the maximum expected mud weight equivalent as shown in the mud program listed in the drilling plan.



|               |         |
|---------------|---------|
| <b>Size</b>   | 5.5     |
| <b>Grade</b>  | P110 RY |
| <b>Weight</b> | 20      |

## TCBC-HT


SeAH Steel

| Coupling and Pipe Dimensions (in) |                |                |                 |              |                |                |
|-----------------------------------|----------------|----------------|-----------------|--------------|----------------|----------------|
|                                   | Outer Diameter | Inner Diameter | Coupling Length | Make-up Loss | Wall Thickness | Drift Diameter |
| <b>Coupling</b>                   | 6.300          | 5.383          |                 |              |                |                |
| <b>Pipe</b>                       |                | 4.778          | 8.250           | 4.125        | 0.361          | 4.653          |
| <b>Pin</b>                        |                | 4.778          |                 |              |                |                |


| Torque Values (ft-lbs) |                      |         |                                  |              |
|------------------------|----------------------|---------|----------------------------------|--------------|
| Field End Make-Up      |                      |         | Max. Working Torque <sup>1</sup> | Yield Torque |
| Minimum                | Optimum <sup>2</sup> | Maximum |                                  |              |
| 10,000                 | 13,500               | 18,500  | 22,250                           | 25,200       |

| Yield Stress (x1000 lbs.) |             |
|---------------------------|-------------|
| Tensile                   | Compressive |
| 100%                      | 100%        |

| Maximum Pressure (psi) |          |
|------------------------|----------|
| Internal               | External |
| 100%                   | 100%     |



- <sup>1</sup> Max. Working Torque value is not to be exceeded during operation.
- <sup>2</sup> If Optimum Torque does not meet the Base of Triangle Stamp, M/U to the Base of Triangle.



\*Data are for information purposes only. Though HIS has made efforts to ensure accuracy, HIS makes no warranty for loss or damage due to its use.



**5.5"   20#   .361"   P-110 Restricted Yield (RY)**

### **Dimensions (Nominal)**

|                  |        |        |
|------------------|--------|--------|
| Outside Diameter | 5.500  | in.    |
| Wall             | 0.361  | in.    |
| Inside Diameter  | 4.778  | in.    |
| Drift            | 4.653  | in.    |
| Weight, T&C      | 20.000 | lbs/ft |
| Weight, PE       | 19.830 | lbs/ft |

### **Performance Properties (Minimum)**

|                           |        |          |
|---------------------------|--------|----------|
| Minimum Yield Strength    | 110000 | psi      |
| Maximum Yield Strength    | 125000 | psi      |
| Collapse, PE              | 11100  | psi      |
| Internal Yield Pressure   |        |          |
| PE                        | 12630  | psi      |
| LTC                       | 12360  | psi      |
| BTC                       | 12360  | psi      |
| Yield Strength, Pipe Body | 641    | 1000 lbs |
| Joint Strength            |        |          |
| LTC                       | 548    | 1000 lbs |
| BTC                       | 667    | 1000 lbs |

Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.

# **NEW MEXICO**

**LEA**

**RAIDER FEDERAL**

**RAIDER FEDERAL 401H**

**RAIDER FEDERAL 401H**

**Plan: MAGVAR - PWP0**






## **Standard Planning Report**

**09 July, 2019**



Project: RAIDER FEDERAL  
Site: RAIDER FEDERAL  
Wells: 401H - 302H - 402H  
Design: MAGVAR - PWP0  
RKB: 3531.00

PROJECT DETAILS: LEA COUNTY  
Geodetic System: Universal Transverse Mercator (US Survey Feet)  
Datum: North American Datum 1983  
Ellipsoid: GRS 1980  
Zone: Zone 13N (108 W to 102 W)  
System Datum: Mean Sea Level



Planning Report

|                  |                            |                                     |                                 |
|------------------|----------------------------|-------------------------------------|---------------------------------|
| <b>Database:</b> | EDM 5000.14 Single User Db | <b>Local Co-ordinate Reference:</b> | Well RAIDER FEDERAL 401H        |
| <b>Company:</b>  | NEW MEXICO                 | <b>TVD Reference:</b>               | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Project:</b>  | LEA                        | <b>MD Reference:</b>                | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Site:</b>     | RAIDER FEDERAL             | <b>North Reference:</b>             | True                            |
| <b>Well:</b>     | RAIDER FEDERAL 401H        | <b>Survey Calculation Method:</b>   | Minimum Curvature               |
| <b>Wellbore:</b> | RAIDER FEDERAL 401H        |                                     |                                 |
| <b>Design:</b>   | MAGVAR - PWP0              |                                     |                                 |

|                    |  |                      |                |
|--------------------|--|----------------------|----------------|
| <b>Project</b>     | LEA  |                      |                |
| <b>Map System:</b> | Universal Transverse Mercator (US Survey Feet) | <b>System Datum:</b> | Mean Sea Level |
| <b>Geo Datum:</b>  | North American Datum 1983                      |                      |                |
| <b>Map Zone:</b>   | Zone 13N (108 W to 102 W)                      |                      |                |

|                              |                |                     |                    |                          |                   |
|------------------------------|----------------|---------------------|--------------------|--------------------------|-------------------|
| <b>Site</b>                  | RAIDER FEDERAL |                     |                    |                          |                   |
| <b>Site Position:</b>        |                | <b>Northing:</b>    | 11,694,989.05 usft | <b>Latitude:</b>         | 32° 12' 32.793 N  |
| <b>From:</b>                 | Map            | <b>Easting:</b>     | 2,113,312.04 usft  | <b>Longitude:</b>        | 103° 28' 14.154 W |
| <b>Position Uncertainty:</b> | 0.00 usft      | <b>Slot Radius:</b> | 13-3/16 "          | <b>Grid Convergence:</b> | 0.82 °            |

|                             |                     |           |                            |                    |                      |                   |
|-----------------------------|---------------------|-----------|----------------------------|--------------------|----------------------|-------------------|
| <b>Well</b>                 | RAIDER FEDERAL 401H |           |                            |                    |                      |                   |
| <b>Well Position</b>        | <b>+N/-S</b>        | 0.00 usft | <b>Northing:</b>           | 11,694,989.05 usft | <b>Latitude:</b>     | 32° 12' 32.793 N  |
|                             | <b>+E/-W</b>        | 0.00 usft | <b>Easting:</b>            | 2,113,312.04 usft  | <b>Longitude:</b>    | 103° 28' 14.154 W |
| <b>Position Uncertainty</b> |                     | 0.00 usft | <b>Wellhead Elevation:</b> |                    | <b>Ground Level:</b> | 3,531.00 usft     |

|                  |                     |                    |                        |                      |                            |
|------------------|---------------------|--------------------|------------------------|----------------------|----------------------------|
| <b>Wellbore</b>  | RAIDER FEDERAL 401H |                    |                        |                      |                            |
| <b>Magnetics</b> | <b>Model Name</b>   | <b>Sample Date</b> | <b>Declination (°)</b> | <b>Dip Angle (°)</b> | <b>Field Strength (nT)</b> |
|                  | IGRF2015            | 7/9/2019           | 6.68                   | 60.04                | 47,727.10445890            |

|                          |                                |                     |                      |                      |
|--------------------------|--------------------------------|---------------------|----------------------|----------------------|
| <b>Design</b>            | MAGVAR - PWP0                  |                     |                      |                      |
| <b>Audit Notes:</b>      |                                |                     |                      |                      |
| <b>Version:</b>          | <b>Phase:</b>                  | PROTOTYPE           | <b>Tie On Depth:</b> | 0.00                 |
| <b>Vertical Section:</b> | <b>Depth From (TVD) (usft)</b> | <b>+N/-S (usft)</b> | <b>+E/-W (usft)</b>  | <b>Direction (°)</b> |
|                          | 0.00                           | 0.00                | 0.00                 | 184.13               |

|                                 |                        |                          |                                      |                |
|---------------------------------|------------------------|--------------------------|--------------------------------------|----------------|
| <b>Plan Survey Tool Program</b> | <b>Date</b>            | 7/9/2019                 |                                      |                |
| <b>Depth From (usft)</b>        | <b>Depth To (usft)</b> | <b>Survey (Wellbore)</b> | <b>Tool Name</b>                     | <b>Remarks</b> |
| 1                               | 0.00                   | 15,324.65                | MAGVAR - PWP0 (RAIDER FEDMWD+IFR1+MS |                |
|                                 |                        |                          | OWSG MWD + IFR1 + Mult               |                |

|                              |                        |                    |                              |                     |                     |                                |                               |                              |                |                  |
|------------------------------|------------------------|--------------------|------------------------------|---------------------|---------------------|--------------------------------|-------------------------------|------------------------------|----------------|------------------|
| <b>Plan Sections</b>         |                        |                    |                              |                     |                     |                                |                               |                              |                |                  |
| <b>Measured Depth (usft)</b> | <b>Inclination (°)</b> | <b>Azimuth (°)</b> | <b>Vertical Depth (usft)</b> | <b>+N/-S (usft)</b> | <b>+E/-W (usft)</b> | <b>Dogleg Rate (°/100usft)</b> | <b>Build Rate (°/100usft)</b> | <b>Turn Rate (°/100usft)</b> | <b>TFO (°)</b> | <b>Target</b>    |
| 0.00                         | 0.00                   | 0.00               | 0.00                         | 0.00                | 0.00                | 0.00                           | 0.00                          | 0.00                         | 0.00           |                  |
| 1,800.00                     | 0.00                   | 0.00               | 1,800.00                     | 0.00                | 0.00                | 0.00                           | 0.00                          | 0.00                         | 0.00           |                  |
| 2,800.00                     | 10.00                  | 308.40             | 2,794.93                     | 54.07               | -68.22              | 1.00                           | 1.00                          | 0.00                         | 308.40         |                  |
| 4,500.00                     | 10.00                  | 308.40             | 4,469.10                     | 237.43              | -299.56             | 0.00                           | 0.00                          | 0.00                         | 0.00           |                  |
| 5,500.00                     | 0.00                   | 0.00               | 5,464.03                     | 291.50              | -367.78             | 1.00                           | -1.00                         | 0.00                         | 180.00         |                  |
| 9,963.00                     | 0.00                   | 0.00               | 9,927.03                     | 291.50              | -367.78             | 0.00                           | 0.00                          | 0.00                         | 0.00           |                  |
| 10,863.01                    | 90.00                  | 179.71             | 10,500.00                    | -281.46             | -364.88             | 10.00                          | 10.00                         | 0.00                         | 179.71         |                  |
| 15,325.29                    | 90.00                  | 179.71             | 10,500.00                    | -4,743.68           | -342.15             | 0.00                           | 0.00                          | 0.00                         | 0.00           | LTP - RAIDER FEC |

Planning Report

|                  |                            |                                     |                                 |
|------------------|----------------------------|-------------------------------------|---------------------------------|
| <b>Database:</b> | EDM 5000.14 Single User Db | <b>Local Co-ordinate Reference:</b> | Well RAIDER FEDERAL 401H        |
| <b>Company:</b>  | NEW MEXICO                 | <b>TVD Reference:</b>               | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Project:</b>  | LEA                        | <b>MD Reference:</b>                | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Site:</b>     | RAIDER FEDERAL             | <b>North Reference:</b>             | True                            |
| <b>Well:</b>     | RAIDER FEDERAL 401H        | <b>Survey Calculation Method:</b>   | Minimum Curvature               |
| <b>Wellbore:</b> | RAIDER FEDERAL 401H        |                                     |                                 |
| <b>Design:</b>   | MAGVAR - PWP0              |                                     |                                 |

| Planned Survey        |                 |             |                       |              |              |                         |                         |                        |                       |
|-----------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|
| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
| 0.00                  | 0.00            | 0.00        | 0.00                  | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 100.00                | 0.00            | 0.00        | 100.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 200.00                | 0.00            | 0.00        | 200.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 300.00                | 0.00            | 0.00        | 300.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 400.00                | 0.00            | 0.00        | 400.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 500.00                | 0.00            | 0.00        | 500.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 600.00                | 0.00            | 0.00        | 600.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 700.00                | 0.00            | 0.00        | 700.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 800.00                | 0.00            | 0.00        | 800.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 900.00                | 0.00            | 0.00        | 900.00                | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,000.00              | 0.00            | 0.00        | 1,000.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,100.00              | 0.00            | 0.00        | 1,100.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,200.00              | 0.00            | 0.00        | 1,200.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,300.00              | 0.00            | 0.00        | 1,300.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,400.00              | 0.00            | 0.00        | 1,400.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,500.00              | 0.00            | 0.00        | 1,500.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,600.00              | 0.00            | 0.00        | 1,600.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,700.00              | 0.00            | 0.00        | 1,700.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,800.00              | 0.00            | 0.00        | 1,800.00              | 0.00         | 0.00         | 0.00                    | 0.00                    | 0.00                   | 0.00                  |
| 1,900.00              | 1.00            | 308.40      | 1,899.99              | 0.54         | -0.68        | -0.49                   | 1.00                    | 1.00                   | 0.00                  |
| 2,000.00              | 2.00            | 308.40      | 1,999.96              | 2.17         | -2.74        | -1.97                   | 1.00                    | 1.00                   | 0.00                  |
| 2,100.00              | 3.00            | 308.40      | 2,099.86              | 4.88         | -6.15        | -4.42                   | 1.00                    | 1.00                   | 0.00                  |
| 2,200.00              | 4.00            | 308.40      | 2,199.68              | 8.67         | -10.94       | -7.86                   | 1.00                    | 1.00                   | 0.00                  |
| 2,300.00              | 5.00            | 308.40      | 2,299.37              | 13.54        | -17.09       | -12.28                  | 1.00                    | 1.00                   | 0.00                  |
| 2,400.00              | 6.00            | 308.40      | 2,398.90              | 19.50        | -24.60       | -17.68                  | 1.00                    | 1.00                   | 0.00                  |
| 2,500.00              | 7.00            | 308.40      | 2,498.26              | 26.53        | -33.47       | -24.05                  | 1.00                    | 1.00                   | 0.00                  |
| 2,600.00              | 8.00            | 308.40      | 2,597.40              | 34.64        | -43.70       | -31.40                  | 1.00                    | 1.00                   | 0.00                  |
| 2,700.00              | 9.00            | 308.40      | 2,696.30              | 43.82        | -55.28       | -39.73                  | 1.00                    | 1.00                   | 0.00                  |
| 2,800.00              | 10.00           | 308.40      | 2,794.93              | 54.07        | -68.22       | -49.02                  | 1.00                    | 1.00                   | 0.00                  |
| 2,900.00              | 10.00           | 308.40      | 2,893.41              | 64.85        | -81.83       | -58.80                  | 0.00                    | 0.00                   | 0.00                  |
| 3,000.00              | 10.00           | 308.40      | 2,991.89              | 75.64        | -95.43       | -68.58                  | 0.00                    | 0.00                   | 0.00                  |
| 3,100.00              | 10.00           | 308.40      | 3,090.37              | 86.43        | -109.04      | -78.36                  | 0.00                    | 0.00                   | 0.00                  |
| 3,200.00              | 10.00           | 308.40      | 3,188.85              | 97.21        | -122.65      | -88.14                  | 0.00                    | 0.00                   | 0.00                  |
| 3,300.00              | 10.00           | 308.40      | 3,287.33              | 108.00       | -136.26      | -97.92                  | 0.00                    | 0.00                   | 0.00                  |
| 3,400.00              | 10.00           | 308.40      | 3,385.82              | 118.78       | -149.87      | -107.70                 | 0.00                    | 0.00                   | 0.00                  |
| 3,500.00              | 10.00           | 308.40      | 3,484.30              | 129.57       | -163.48      | -117.47                 | 0.00                    | 0.00                   | 0.00                  |
| 3,600.00              | 10.00           | 308.40      | 3,582.78              | 140.36       | -177.09      | -127.25                 | 0.00                    | 0.00                   | 0.00                  |
| 3,700.00              | 10.00           | 308.40      | 3,681.26              | 151.14       | -190.69      | -137.03                 | 0.00                    | 0.00                   | 0.00                  |
| 3,800.00              | 10.00           | 308.40      | 3,779.74              | 161.93       | -204.30      | -146.81                 | 0.00                    | 0.00                   | 0.00                  |
| 3,900.00              | 10.00           | 308.40      | 3,878.22              | 172.72       | -217.91      | -156.59                 | 0.00                    | 0.00                   | 0.00                  |
| 4,000.00              | 10.00           | 308.40      | 3,976.70              | 183.50       | -231.52      | -166.37                 | 0.00                    | 0.00                   | 0.00                  |
| 4,100.00              | 10.00           | 308.40      | 4,075.18              | 194.29       | -245.13      | -176.15                 | 0.00                    | 0.00                   | 0.00                  |
| 4,200.00              | 10.00           | 308.40      | 4,173.66              | 205.07       | -258.74      | -185.93                 | 0.00                    | 0.00                   | 0.00                  |
| 4,300.00              | 10.00           | 308.40      | 4,272.14              | 215.86       | -272.35      | -195.71                 | 0.00                    | 0.00                   | 0.00                  |
| 4,400.00              | 10.00           | 308.40      | 4,370.62              | 226.65       | -285.96      | -205.49                 | 0.00                    | 0.00                   | 0.00                  |
| 4,500.00              | 10.00           | 308.40      | 4,469.10              | 237.43       | -299.56      | -215.27                 | 0.00                    | 0.00                   | 0.00                  |
| 4,600.00              | 9.00            | 308.40      | 4,567.73              | 247.68       | -312.50      | -224.56                 | 1.00                    | -1.00                  | 0.00                  |
| 4,700.00              | 8.00            | 308.40      | 4,666.63              | 256.86       | -324.08      | -232.88                 | 1.00                    | -1.00                  | 0.00                  |
| 4,800.00              | 7.00            | 308.40      | 4,765.77              | 264.97       | -334.31      | -240.23                 | 1.00                    | -1.00                  | 0.00                  |
| 4,900.00              | 6.00            | 308.40      | 4,865.13              | 272.00       | -343.18      | -246.61                 | 1.00                    | -1.00                  | 0.00                  |
| 5,000.00              | 5.00            | 308.40      | 4,964.67              | 277.96       | -350.69      | -252.01                 | 1.00                    | -1.00                  | 0.00                  |
| 5,100.00              | 4.00            | 308.40      | 5,064.36              | 282.83       | -356.84      | -256.43                 | 1.00                    | -1.00                  | 0.00                  |
| 5,200.00              | 3.00            | 308.40      | 5,164.17              | 286.62       | -361.63      | -259.86                 | 1.00                    | -1.00                  | 0.00                  |
| 5,300.00              | 2.00            | 308.40      | 5,264.08              | 289.33       | -365.05      | -262.32                 | 1.00                    | -1.00                  | 0.00                  |

Planning Report

|                  |                            |                                     |                                 |
|------------------|----------------------------|-------------------------------------|---------------------------------|
| <b>Database:</b> | EDM 5000.14 Single User Db | <b>Local Co-ordinate Reference:</b> | Well RAIDER FEDERAL 401H        |
| <b>Company:</b>  | NEW MEXICO                 | <b>TVD Reference:</b>               | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Project:</b>  | LEA                        | <b>MD Reference:</b>                | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Site:</b>     | RAIDER FEDERAL             | <b>North Reference:</b>             | True                            |
| <b>Well:</b>     | RAIDER FEDERAL 401H        | <b>Survey Calculation Method:</b>   | Minimum Curvature               |
| <b>Wellbore:</b> | RAIDER FEDERAL 401H        |                                     |                                 |
| <b>Design:</b>   | MAGVAR - PWP0              |                                     |                                 |

| Planned Survey        |                 |             |                       |              |              |                         |                         |                        |                       |  |
|-----------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|--|
| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |  |
| 5,400.00              | 1.00            | 308.40      | 5,364.04              | 290.96       | -367.10      | -263.79                 | 1.00                    | -1.00                  | 0.00                  |  |
| 5,500.00              | 0.00            | 0.00        | 5,464.03              | 291.50       | -367.78      | -264.29                 | 1.00                    | -1.00                  | 0.00                  |  |
| 5,600.00              | 0.00            | 0.00        | 5,564.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 5,700.00              | 0.00            | 0.00        | 5,664.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 5,800.00              | 0.00            | 0.00        | 5,764.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 5,900.00              | 0.00            | 0.00        | 5,864.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,000.00              | 0.00            | 0.00        | 5,964.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,100.00              | 0.00            | 0.00        | 6,064.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,200.00              | 0.00            | 0.00        | 6,164.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,300.00              | 0.00            | 0.00        | 6,264.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,400.00              | 0.00            | 0.00        | 6,364.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,500.00              | 0.00            | 0.00        | 6,464.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,600.00              | 0.00            | 0.00        | 6,564.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,700.00              | 0.00            | 0.00        | 6,664.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,800.00              | 0.00            | 0.00        | 6,764.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 6,900.00              | 0.00            | 0.00        | 6,864.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,000.00              | 0.00            | 0.00        | 6,964.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,100.00              | 0.00            | 0.00        | 7,064.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,200.00              | 0.00            | 0.00        | 7,164.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,300.00              | 0.00            | 0.00        | 7,264.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,400.00              | 0.00            | 0.00        | 7,364.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,500.00              | 0.00            | 0.00        | 7,464.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,600.00              | 0.00            | 0.00        | 7,564.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,700.00              | 0.00            | 0.00        | 7,664.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,800.00              | 0.00            | 0.00        | 7,764.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 7,900.00              | 0.00            | 0.00        | 7,864.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,000.00              | 0.00            | 0.00        | 7,964.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,100.00              | 0.00            | 0.00        | 8,064.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,200.00              | 0.00            | 0.00        | 8,164.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,300.00              | 0.00            | 0.00        | 8,264.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,400.00              | 0.00            | 0.00        | 8,364.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,500.00              | 0.00            | 0.00        | 8,464.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,600.00              | 0.00            | 0.00        | 8,564.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,700.00              | 0.00            | 0.00        | 8,664.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,800.00              | 0.00            | 0.00        | 8,764.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 8,900.00              | 0.00            | 0.00        | 8,864.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,000.00              | 0.00            | 0.00        | 8,964.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,100.00              | 0.00            | 0.00        | 9,064.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,200.00              | 0.00            | 0.00        | 9,164.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,300.00              | 0.00            | 0.00        | 9,264.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,400.00              | 0.00            | 0.00        | 9,364.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,500.00              | 0.00            | 0.00        | 9,464.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,600.00              | 0.00            | 0.00        | 9,564.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,700.00              | 0.00            | 0.00        | 9,664.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,800.00              | 0.00            | 0.00        | 9,764.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,900.00              | 0.00            | 0.00        | 9,864.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 9,963.00              | 0.00            | 0.00        | 9,927.03              | 291.50       | -367.78      | -264.29                 | 0.00                    | 0.00                   | 0.00                  |  |
| 10,000.00             | 3.70            | 179.71      | 9,964.01              | 290.31       | -367.78      | -263.10                 | 10.00                   | 10.00                  | 0.00                  |  |
| 10,100.00             | 13.70           | 179.71      | 10,062.73             | 275.20       | -367.70      | -248.03                 | 10.00                   | 10.00                  | 0.00                  |  |
| 10,200.00             | 23.70           | 179.71      | 10,157.33             | 243.18       | -367.54      | -216.11                 | 10.00                   | 10.00                  | 0.00                  |  |
| 10,300.00             | 33.70           | 179.71      | 10,244.94             | 195.22       | -367.29      | -168.29                 | 10.00                   | 10.00                  | 0.00                  |  |
| 10,400.00             | 43.70           | 179.71      | 10,322.88             | 132.78       | -366.98      | -106.03                 | 10.00                   | 10.00                  | 0.00                  |  |
| 10,500.00             | 53.70           | 179.71      | 10,388.80             | 57.75        | -366.60      | -31.22                  | 10.00                   | 10.00                  | 0.00                  |  |
| 10,600.00             | 63.70           | 179.71      | 10,440.69             | -27.59       | -366.17      | 53.86                   | 10.00                   | 10.00                  | 0.00                  |  |

Planning Report

|                  |                            |                                     |                                 |
|------------------|----------------------------|-------------------------------------|---------------------------------|
| <b>Database:</b> | EDM 5000.14 Single User Db | <b>Local Co-ordinate Reference:</b> | Well RAIDER FEDERAL 401H        |
| <b>Company:</b>  | NEW MEXICO                 | <b>TVD Reference:</b>               | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Project:</b>  | LEA                        | <b>MD Reference:</b>                | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Site:</b>     | RAIDER FEDERAL             | <b>North Reference:</b>             | True                            |
| <b>Well:</b>     | RAIDER FEDERAL 401H        | <b>Survey Calculation Method:</b>   | Minimum Curvature               |
| <b>Wellbore:</b> | RAIDER FEDERAL 401H        |                                     |                                 |
| <b>Design:</b>   | MAGVAR - PWP0              |                                     |                                 |

| Planned Survey        |                 |             |                       |              |              |                         |                         |                        |                       |  |
|-----------------------|-----------------|-------------|-----------------------|--------------|--------------|-------------------------|-------------------------|------------------------|-----------------------|--|
| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |  |
| 10,700.00             | 73.70           | 179.71      | 10,476.97             | -120.64      | -365.70      | 146.63                  | 10.00                   | 10.00                  | 0.00                  |  |
| 10,800.00             | 83.70           | 179.71      | 10,496.54             | -218.57      | -365.20      | 244.28                  | 10.00                   | 10.00                  | 0.00                  |  |
| 10,863.01             | 90.00           | 179.71      | 10,500.00             | -281.46      | -364.88      | 306.98                  | 10.00                   | 10.00                  | 0.00                  |  |
| 10,900.00             | 90.00           | 179.71      | 10,500.00             | -318.45      | -364.69      | 343.86                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,000.00             | 90.00           | 179.71      | 10,500.00             | -418.44      | -364.19      | 443.56                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,100.00             | 90.00           | 179.71      | 10,500.00             | -518.44      | -363.68      | 543.26                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,200.00             | 90.00           | 179.71      | 10,500.00             | -618.44      | -363.18      | 642.97                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,300.00             | 90.00           | 179.71      | 10,500.00             | -718.44      | -362.67      | 742.67                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,400.00             | 90.00           | 179.71      | 10,500.00             | -818.44      | -362.16      | 842.37                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,500.00             | 90.00           | 179.71      | 10,500.00             | -918.44      | -361.66      | 942.08                  | 0.00                    | 0.00                   | 0.00                  |  |
| 11,600.00             | 90.00           | 179.71      | 10,500.00             | -1,018.44    | -361.15      | 1,041.78                | 0.00                    | 0.00                   | 0.00                  |  |
| 11,700.00             | 90.00           | 179.71      | 10,500.00             | -1,118.44    | -360.64      | 1,141.48                | 0.00                    | 0.00                   | 0.00                  |  |
| 11,800.00             | 90.00           | 179.71      | 10,500.00             | -1,218.43    | -360.14      | 1,241.19                | 0.00                    | 0.00                   | 0.00                  |  |
| 11,900.00             | 90.00           | 179.71      | 10,500.00             | -1,318.43    | -359.63      | 1,340.89                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,000.00             | 90.00           | 179.71      | 10,500.00             | -1,418.43    | -359.13      | 1,440.59                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,100.00             | 90.00           | 179.71      | 10,500.00             | -1,518.43    | -358.62      | 1,540.30                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,200.00             | 90.00           | 179.71      | 10,500.00             | -1,618.43    | -358.11      | 1,640.00                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,300.00             | 90.00           | 179.71      | 10,500.00             | -1,718.43    | -357.61      | 1,739.70                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,400.00             | 90.00           | 179.71      | 10,500.00             | -1,818.43    | -357.10      | 1,839.41                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,500.00             | 90.00           | 179.71      | 10,500.00             | -1,918.43    | -356.60      | 1,939.11                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,600.00             | 90.00           | 179.71      | 10,500.00             | -2,018.42    | -356.09      | 2,038.81                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,700.00             | 90.00           | 179.71      | 10,500.00             | -2,118.42    | -355.58      | 2,138.51                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,800.00             | 90.00           | 179.71      | 10,500.00             | -2,218.42    | -355.08      | 2,238.22                | 0.00                    | 0.00                   | 0.00                  |  |
| 12,900.00             | 90.00           | 179.71      | 10,500.00             | -2,318.42    | -354.57      | 2,337.92                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,000.00             | 90.00           | 179.71      | 10,500.00             | -2,418.42    | -354.07      | 2,437.62                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,100.00             | 90.00           | 179.71      | 10,500.00             | -2,518.42    | -353.56      | 2,537.33                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,200.00             | 90.00           | 179.71      | 10,500.00             | -2,618.42    | -353.05      | 2,637.03                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,300.00             | 90.00           | 179.71      | 10,500.00             | -2,718.42    | -352.55      | 2,736.73                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,400.00             | 90.00           | 179.71      | 10,500.00             | -2,818.41    | -352.04      | 2,836.44                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,500.00             | 90.00           | 179.71      | 10,500.00             | -2,918.41    | -351.53      | 2,936.14                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,600.00             | 90.00           | 179.71      | 10,500.00             | -3,018.41    | -351.03      | 3,035.84                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,700.00             | 90.00           | 179.71      | 10,500.00             | -3,118.41    | -350.52      | 3,135.55                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,800.00             | 90.00           | 179.71      | 10,500.00             | -3,218.41    | -350.02      | 3,235.25                | 0.00                    | 0.00                   | 0.00                  |  |
| 13,900.00             | 90.00           | 179.71      | 10,500.00             | -3,318.41    | -349.51      | 3,334.95                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,000.00             | 90.00           | 179.71      | 10,500.00             | -3,418.41    | -349.00      | 3,434.66                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,100.00             | 90.00           | 179.71      | 10,500.00             | -3,518.40    | -348.50      | 3,534.36                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,200.00             | 90.00           | 179.71      | 10,500.00             | -3,618.40    | -347.99      | 3,634.06                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,300.00             | 90.00           | 179.71      | 10,500.00             | -3,718.40    | -347.49      | 3,733.77                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,400.00             | 90.00           | 179.71      | 10,500.00             | -3,818.40    | -346.98      | 3,833.47                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,500.00             | 90.00           | 179.71      | 10,500.00             | -3,918.40    | -346.47      | 3,933.17                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,600.00             | 90.00           | 179.71      | 10,500.00             | -4,018.40    | -345.97      | 4,032.88                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,700.00             | 90.00           | 179.71      | 10,500.00             | -4,118.40    | -345.46      | 4,132.58                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,800.00             | 90.00           | 179.71      | 10,500.00             | -4,218.40    | -344.95      | 4,232.28                | 0.00                    | 0.00                   | 0.00                  |  |
| 14,900.00             | 90.00           | 179.71      | 10,500.00             | -4,318.39    | -344.45      | 4,331.99                | 0.00                    | 0.00                   | 0.00                  |  |
| 15,000.00             | 90.00           | 179.71      | 10,500.00             | -4,418.39    | -343.94      | 4,431.69                | 0.00                    | 0.00                   | 0.00                  |  |
| 15,100.00             | 90.00           | 179.71      | 10,500.00             | -4,518.39    | -343.44      | 4,531.39                | 0.00                    | 0.00                   | 0.00                  |  |
| 15,200.00             | 90.00           | 179.71      | 10,500.00             | -4,618.39    | -342.93      | 4,631.09                | 0.00                    | 0.00                   | 0.00                  |  |
| 15,300.00             | 90.00           | 179.71      | 10,500.00             | -4,718.39    | -342.42      | 4,730.80                | 0.00                    | 0.00                   | 0.00                  |  |
| 15,325.29             | 90.00           | 179.71      | 10,500.00             | -4,743.68    | -342.15      | 4,756.00                | 0.00                    | 0.00                   | 0.00                  |  |

Planning Report

|                  |                            |                                     |                                 |
|------------------|----------------------------|-------------------------------------|---------------------------------|
| <b>Database:</b> | EDM 5000.14 Single User Db | <b>Local Co-ordinate Reference:</b> | Well RAIDER FEDERAL 401H        |
| <b>Company:</b>  | NEW MEXICO                 | <b>TVD Reference:</b>               | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Project:</b>  | LEA                        | <b>MD Reference:</b>                | RKB = 3531 + 26.5 @ 3557.50usft |
| <b>Site:</b>     | RAIDER FEDERAL             | <b>North Reference:</b>             | True                            |
| <b>Well:</b>     | RAIDER FEDERAL 401H        | <b>Survey Calculation Method:</b>   | Minimum Curvature               |
| <b>Wellbore:</b> | RAIDER FEDERAL 401H        |                                     |                                 |
| <b>Design:</b>   | MAGVAR - PWP0              |                                     |                                 |

| Design Targets  |           |          |           |           |         |               |              |                  |                   |
|---|-----------|----------|-----------|-----------|---------|---------------|--------------|------------------|-------------------|
| Target Name   |           |          |           |           |         |               |              |                  |                   |
| - hit/miss target   | Dip Angle | Dip Dir. | TVD       | +N/-S     | +E/-W   | Northing      | Easting      | Latitude         | Longitude         |
| - Shape   | (°)       | (°)      | (usft)    | (usft)    | (usft)  | (usft)        | (usft)       |                  |                   |
| LTP - RAIDER FEDEI<br>- plan hits target center<br>- Point  | 0.00      | 0.00     | 10,500.00 | -4,743.68 | -342.15 | 11,690,240.98 | 2,113,037.43 | 32° 11' 45.847 N | 103° 28' 18.136 W |
| FTP - RAIDER FEDEI<br>- plan misses target center by 268.33usft at 10400.00usft MD (10322.88 TVD, 132.78 N, -366.98 E)<br>- Circle (radius 50.00) | 0.00      | 0.00     | 10,500.00 | 333.47    | -348.26 | 11,695,317.53 | 2,112,959.07 | 32° 12' 36.094 N | 103° 28' 18.208 W |

## Centennial Resource Development New Mexico Multi-Well Pad Drilling Batch Setting Procedures

### ➤ Avalon and Bone Springs Formations

13-3/8" Surface Casing - CRD intends to preset 13-3/8" casing to a depth approved in the APD. 17-1/2" Surface Holes will be batch drilled by a Surface Preset rig. Appropriate notifications will be made prior to spudding the well, running and cementing casing and prior to skidding to the rig to the next well on pad.

1. Drill 17-1/2" Surface hole to Approved Depth with Surface Preset Rig and perform wellbore cleanup cycles. Trip out and rack back drilling BHA.
2. Run and land 13-3/8" 54.5# J55 BTC casing to depth approved in APD.
3. Cement 13-3/8" casing with cement to surface and floats holding.
4. Cut / Dress 20" Conductor and 13-3/8" casing as needed, weld on Cameron Multi-bowl system with baseplate supported by 20" conductor (see [Illustration 1-1 Below](#)). Weld performed per Cameron weld procedure.
5. Test Weld to 70% of 13-3/8" casing collapse or ~ 790psi.
6. Install nightcap with Pressure Gauge on wellhead. Nightcap is shown on final wellhead Stack up [Illustration #2-2 page 3](#).
7. Skid Rig to adjacent well to drill Surface hole.
8. Surface casing test will be performed by the Big Rig in order to allow ample time for Cement to develop 500psi compressive strength. Casing test to 0.22 psi/ft or 1500 psi whichever is greater - not to exceed 70% casing burst.




Illustration 1-1

- Intermediate and Production Casing – For all subsequent Intermediate and Production Casing Strings, the Big Rig will remove the nightcap and install and test BOPE. Prior to drill out the 13-3/8" Casing will be tested to 0.22psi/ft or 1500psi whichever is greater. The well will be drilled below 13-3/8" to its intended final TD in the Avalon or Bonesprings formations. Batch drilling will not be executed for casing strings below the 13-3/8". Appropriate notifications will be made prior Testing BOPE, and prior to running/cementing all casing strings. The


## ➤ Wolfcamp Formations

13-3/8" Surface Casing - CRD intends to preset 13-3/8" casing to a depth approved in the APD. Surface Holes will be batch set by a Surface Preset rig. Appropriate notifications will be made prior to spudding the well, running and cementing casing and prior to skidding to the rig to the next well on pad.

1. Drill 17-1/2" Surface hole to Approved Depth with Surface Preset Rig and perform wellbore cleanup cycles. Trip out and rack back drilling BHA.
2. Run and land 13-3/8" 54.5# J55 BTC casing to depth approved in APD.
3. Cement 13-3/8" casing with cement to surface and floats holding.
4. Cut / Dress 20" Conductor and 13-3/8" casing as needed, weld on Cameron Multi-bowl system with baseplate supported by 20" conductor (see [Illustration 1-1](#)). Weld performed per Cameron weld procedure.
5. Test Weld to 70% of 13-3/8" casing collapse or ~ 790psi.
6. Install nightcap with Pressure Gauge on wellhead. Nightcap is shown on final wellhead Stack up [Illustration #2-2 on page 3](#).
7. Subsequent casing test will be performed by the Big Rig in order to allow ample time for Cement to develop 500psi compressive strength. Casing test to 0.22 psi/ft or 1500 psi whichever is greater - not to exceed 70% casing burst.

Intermediate Casing – CRD intends to Batch set all intermediate casing strings to a depth approved in the APD, typically set 100' above KOP in the 3<sup>rd</sup> Bonesprings Carbonate. For the last intermediate section drilled on pad, the associated production interval will immediately follow. Appropriate notifications will be made prior Testing BOPE, and prior to running/cementing all casing strings.

1. Big Rig will remove the nightcap and install and test BOPE.
2. Test Surface casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) - not to exceed 70% casing burst. Cement must have achieved 500psi compressive strength prior to test.
3. Install wear bushing then drill out 13-3/8" shoe-track plus 20' and conduct FIT to minimum of the MW equivalent anticipated to control the formation pressure to the next casing point.
4. Drill Intermediate hole to approved casing point. Trip out of hole with BHA to run Casing.
5. Remove wear bushing then run and land Intermediate Casing with mandrel hanger in wellhead.
6. Cement casing to surface with floats holding.
7. Washout stack then run wash tool in wellhead and wash hanger and pack-off setting area.
8. Install pack-off and test void to 10000 psi for 15 minutes. Nightcap shown on final wellhead stack up [illustration 2-2 on page 3](#).
9. Test casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) - not to exceed 70% casing burst. Cement must have achieved 500psi compressive strength prior to test.
10. Install nightcap – skid rig to adjacent well to drill Intermediate hole.



WITH CAP

Illustration 2-2

Production Casing – CRD intends to Batch set all Production casings, except for the last intermediate hole. In this case the production interval will immediately follow the intermediate section on that well. Appropriate notifications will be made prior Testing BOPE, and prior to running/cementing all casing strings.

1. Big Rig will remove the nightcap and install and test BOPE.
2. Install wear bushing then drill Intermediate shoe-track plus 20' and conduct FIT to minimum MW equivalent to control the formation pressure to TD of well.
3. Drill Vertical hole to KOP – Trip out for Curve BHA.
4. Drill Curve, landing in production interval – Trip for Lateral BHA.

5. Drill Lateral / Production hole to Permitted BHL, perform cleanup cycles and trip out to run 5-1/2" Production Casing.
6. Remove wear bushing then run 5-1/2" production casing to TD landing casing mandrel in wellhead.
7. Cement 5-1/2" Production string to surface with floats holding.
8. Run in with wash tool and wash wellhead area – install pack-off and test void to 10000psi for 15 minutes.
9. Install BPV in 5-1/2" mandrel hanger – Nipple down BOPE and install nightcap.
10. Test nightcap void to 10000psi for 30 minutes per [illustration 2-2 page 3](#).
11. Skid rig to adjacent well on pad to drill production hole.



ContiTech

|                                     |                     |
|-------------------------------------|---------------------|
| CONTITECH RUBBER<br>Industrial Kft. | No:QC-DB- 210/ 2014 |
|                                     | Page: 9 / 113       |

|  |  |  |         |
|--|--|--|---------|
| <b>QUALITY CONTROL<br/>INSPECTION AND TEST CERTIFICATE</b>   |  | CERT. N°: 504  |         |
| PURCHASER: ContiTech Oil & Marine Corp.  |  | P.O. N°: 4500409659  |         |
| CONTITECH RUBBER order N°: 538236  | HOSE TYPE: 3" ID                           | Choke and Kill Hose  |         |
| HOSE SERIAL N°: 67255  | NOMINAL / ACTUAL LENGTH: 10,67 m / 10,77 m |  |         |
| W.P. 68,9 MPa 10000 psi  | T.P. 103,4 MPa 15000 psi                   | Duration: 60 min.  |         |
| Pressure test with water at ambient temperature<br><br><p style="text-align: center;">See attachment. ( 1 page )</p>   |  |  |         |
| ↑ 10 mm = 10 Min.<br>→ 10 mm = 20 MPa  |  |  |         |
| COUPLINGS Type   | Serial N°                                  | Quality  | Heat N° |
| 3" coupling with   | 9251 9254                                  | AISI 4130  | A0579N  |
| 4 1/16" 10K API b.w. Flange end  |  | AISI 4130  | 035608  |
| <b>Not Designed For Well Testing</b>   |  | <b>API Spec 16 C</b>   |         |
|  |  | <b>Temperature rate:"B"</b>                                      |         |
| All metal parts are flawless   |  |  |         |
| WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.  |  |  |         |
| STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements. |  |  |         |
| COUNTRY OF ORIGIN HUNGARY/EU   |  |  |         |
| Date:  | Inspector                                  | Quality Control  |         |
| 20. March 2014.  |  | ContiTech Rubber<br>Industrial Kft.<br>Quality Control Dept.<br> |         |





CONTITECH RUBBER  
Industrial Kft.

No:QC-DB- 210/ 2014

Page: 15 / 113


ContiTech

## Hose Data Sheet

|                                |  |
|--------------------------------|--|
| CRI Order No.                  | 538236   |
| Customer                       | ContiTech Oil & Marine Corp.                                       |
| Customer Order No              | 4500409659   |
| Item No.                       | 1  |
| Hose Type                      | Flexible Hose  |
| <b>Standard</b>                | <b>API SPEC 16 C</b>   |
| Inside dia in inches           | 3  |
| Length                         | 35 ft  |
| Type of coupling one end       | FLANGE 4.1/16" 10K API SPEC 6A TYPE 6BX FLANGE C/W BX155 R.GR.SOUR |
| Type of coupling other end     | FLANGE 4.1/16" 10K API SPEC 6A TYPE 6BX FLANGE C/W BX155 R.GR.SOUR |
| H2S service NACE MR0175        | Yes  |
| Working Pressure               | 10 000 psi   |
| Design Pressure                | 10 000 psi   |
| Test Pressure                  | 15 000 psi   |
| Safety Factor                  | 2,25   |
| Marking                        | USUAL PHOENIX  |
| Cover                          | NOT FIRE RESISTANT   |
| Outside protection             | St.steel outer wrap  |
| Internal stripwound tube       | No   |
| Lining                         | OIL + GAS RESISTANT SOUR   |
| Safety clamp                   | No   |
| Lifting collar                 | No   |
| Element C                      | No   |
| Safety chain                   | No   |
| Safety wire rope               | No   |
| Max.design temperature [°C]    | 100  |
| Min.design temperature [°C]    | -20  |
| Min. Bend Radius operating [m] | 0,90   |
| Min. Bend Radius storage [m]   | 0,90   |
| Electrical continuity          | The Hose is electrically continuous                                |
| Type of packing                | WOODEN CRATE ISPM-15   |

## Centennial Wellhead Running Procedure 3 String Bone Springs Design

1. Drill 17-1/2" surface hole to Total Depth and perform wellbore cleanup cycles.
2. Remove wear bushing then Run and land 13-3/8" casing with mandrel hanger in wellhead.
3. Cement 13-3/8" casing – cement to surface.
4. Dress Conductor and 13-3/8" casing as needed, weld on Cameron Multi-bowl system with baseplate supported by 20" conductor.
5. Test Weld to 70% of 13-3/8" casing collapse.
6. Nipple up and test BOPE with test plug per Onshore Order 2..
7. Test casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) - not to exceed 70% casing burst.
8. Install wear bushing then drillout 13-3/8" shoetrack plus 20' and conduct FIT to minimum of the MW equivalent anticipated to control the formation pressure to the next casing point.
9. Drill 12-1/4" Intermediate hole to 9-5/8" casing point. (Base Capitan Reef).
10. Remove wear bushing then Run and land 9-5/8" Intermediate with mandrel hanger in wellhead.
11. Cement 9-5/8 casing – cement to surface.
12. Washout stack, Run wash tool in wellhead and wash hanger and packoff setting area.
13. Install packoff and test to 5000 psi for 15 minutes.
  - a. Test casing per COA WOC timing (.22 psi/ft or 1500 psi whichever is greater) - not to exceed 70% casing burst.
14. Install wear bushing then drillout 9-5/8" shoetrack plus 20' and conduct FIT to minimum MW equivalent to control the formation pressure to TD of well.
15. Drill 8-3/4" Vertical hole to KOP – Trip out for Curve BHA.
16. Drill 8-3/4" Curve, landing in production interval – Trip for Lateral BHA.
17. Drill 8-1/2" Lateral to Permitted BHL, perform cleanup cycles and trip out to run 5-1/2" Production Casing.
18. Remove wear bushing then run 5-1/2" production casing to TD landing casing mandrel in wellhead.
19. Cement 5-1/2" Production string to surface.
20. Run in with wash tool and wash wellhead area – install packoff and test to 5000psi for 15 minutes.
21. Install BPV in 5-1/2" mandrel hanger – Nipple down BOPE and install nightcap.
22. Test nightcap void to 5000psi for 30 minutes.



|                                  |              |   |                    |
|----------------------------------|--------------|---|--------------------|
| CAMERON CONFIDENTIAL INFORMATION |              |   |                    |
| DO NOT SCALE                     |              | <br>A Schlumberger Company | Surface<br>Systems |
| Drawn by: C.Moore                | Date: 7/1/19 |   | 13-5/8" 10k MN-DS  |
| Checked by: V.Atwell             | Date: 7/1/19 | 02  |                    |
| Drawing No: 1655807-A            |              |   |                    |



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# SUPO Data Report

06/10/2020

APD ID: 10400049567

Submission Date: 10/17/2019

Highlighted data reflects the most recent changes

Operator Name: CENTENNIAL RESOURCE PRODUCTION LLC

Well Name: RAIDER FEDERAL

Well Number: 401H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

RAIDER\_FEDERAL\_COM\_Existing\_Road\_plats\_20191016092937.pdf

Existing Road Purpose: ACCESS,FLUID TRANSPORT

Row(s) Exist? NO

### ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Existing\_Road\_Improvement\_20180920102027.pdf

## Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

RAIDER\_FEDERAL\_COM\_Access\_Road\_maps\_20191016093515.pdf

RAIDER\_FEDERAL\_CTB\_New\_Road\_PLATS\_20191016093530.pdf

New road type: RESOURCE

Length: 796 Feet

Width (ft.): 65

Max slope (%): 2

Max grade (%): 8

Army Corp of Engineers (ACOE) permit required? N

ACOE Permit Number(s):

New road travel width: 20

New road access erosion control: Drainage and erosion will be constantly monitored to prevent compromising the road integrity and to protect the surrounding native topography

New road access plan or profile prepared? N

New road access plan attachment:

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Access road engineering design?** N

**Access road engineering design attachment:**

**Turnout?** N

**Access surfacing type:** OTHER

**Access topsoil source:** ONSITE

**Access surfacing type description:** Caliche

**Access onsite topsoil source depth:** 4

**Offsite topsoil source description:**

**Onsite topsoil removal process:** Equipment will be used to strip 4 inches in depth and stockpile, utilizing berms for run-off

**Access other construction information:**

**Access miscellaneous information:**

**Number of access turnouts:**

**Access turnout map:**

**Drainage Control**

**New road drainage crossing:** CULVERT

**Drainage Control comments:** Will be monitored and repaired as necessary

**Road Drainage Control Structures (DCS) description:** Will be monitored and repaired as necessary

**Road Drainage Control Structures (DCS) attachment:**

TYPICAL\_ACCESS\_CROSS\_SECTIONS\_20180920102337.pdf

**Access Additional Attachments**

**Section 3 - Location of Existing Wells**

**Existing Wells Map?** YES

**Attach Well map:**

RAIDER\_FEDERAL\_COM\_Well\_Proximity\_Map\_20191016095606.pdf

Raider\_Federal\_Com\_302H\_Existing\_Wells\_list\_20191016095910.xlsx

**Section 4 - Location of Existing and/or Proposed Production Facilities**

**Submit or defer a Proposed Production Facilities plan?** SUBMIT

**Production Facilities description:** Handles/Separates Gas, Oil, and Water

**Production Facilities map:**

RAIDER\_FEDERAL\_CTB\_\_\_Location\_Layout\_PLATS\_20191016100045.pdf

Raider\_Federal\_401H\_302H\_402H\_Comingle\_FAC\_Layout\_20191016100023.pdf

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

### Section 5 - Location and Types of Water Supply

#### Water Source Table

**Water source type:** GW WELL

**Water source use type:** OTHER

**Describe use type:** 3rd party procurement for construction control

**Source latitude:**

**Source longitude:**

**Source datum:**

**Water source permit type:** PRIVATE CONTRACT

**Water source transport method:** PIPELINE

**Source land ownership:** PRIVATE

**Source transportation land ownership:** OTHER

**Describe transportation land ownership:** Private

**Water source volume (barrels):** 450000

**Source volume (acre-feet):** 58.00189335

**Source volume (gal):** 18900000

**Water source and transportation map:**

water\_route\_\_\_Raider\_Fed\_20191016100512.pdf

**Water source comments:** Temporary surface lines will be used to transport water for drilling and completion operations from private pit to Raider development. Sec 16, T24S-R34E, NENE.

**New water well?** N

#### New Water Well Info

**Well latitude:**

**Well Longitude:**

**Well datum:**

**Well target aquifer:**

**Est. depth to top of aquifer(ft):**

**Est thickness of aquifer:**

**Aquifer comments:**

**Aquifer documentation:**

**Well depth (ft):**

**Well casing type:**

**Well casing outside diameter (in.):**

**Well casing inside diameter (in.):**

**New water well casing?**

**Used casing source:**

**Drilling method:**

**Drill material:**

**Grout material:**

**Grout depth:**

**Casing length (ft.):**

**Casing top depth (ft.):**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Well Production type:**

**Completion Method:**

**Water well additional information:**

**State appropriation permit:**

**Additional information attachment:**

**Section 6 - Construction Materials**

**Using any construction materials:** YES

**Construction Materials description:** Caliche will be hauled from the existing Quail Ranch fee pit in NW4 NE4 Section 6-T25S-R35E. Pit has been identified for use in the attached exhibit. Any native caliche on the proposed site can be used by "flipping" the location and using all native soils.

**Construction Materials source location attachment:**

caliche\_route\_\_\_Raider\_Fed\_20191016100825.pdf

**Section 7 - Methods for Handling Waste**

**Waste type:** DRILLING

**Waste content description:** Brine water based drilling fluid

**Amount of waste:** 1500 barrels

**Waste disposal frequency :** Monthly

**Safe containment description:** Steel tanks with plastic-lined containment berms

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY      **Disposal location ownership:** COMMERCIAL FACILITY

**Disposal type description:**

**Disposal location description:** Haul to commercial facility

**Waste type:** DRILLING

**Waste content description:** Fresh water based drilling fluid

**Amount of waste:** 1500 barrels

**Waste disposal frequency :** Weekly

**Safe containment description:** Steel tanks with plastic-lined containment berms

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY      **Disposal location ownership:** COMMERCIAL FACILITY

**Disposal type description:**

**Disposal location description:** Haul to commercial facility

|  |                          |
|--|--------------------------|
| <b>Operator Name:</b> CENTENNIAL RESOURCE PRODUCTION LLC |                          |
| <b>Well Name:</b> RAIDER FEDERAL                         | <b>Well Number:</b> 401H |

**Waste type:** SEWAGE

**Waste content description:** Grey Water/Human Waste

**Amount of waste:** 5000 gallons

**Waste disposal frequency :** Weekly

**Safe containment description:** Approved waste storage tanks with containment

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY     **Disposal location ownership:** COMMERCIAL FACILITY

**Disposal type description:**

**Disposal location description:** Haul to commercial facility

**Waste type:** GARBAGE

**Waste content description:** General trash/garbage

**Amount of waste:** 5000 pounds

**Waste disposal frequency :** Weekly

**Safe containment description:** Enclosed trash trailer

**Safe containmant attachment:**

**Waste disposal type:** HAUL TO COMMERCIAL FACILITY     **Disposal location ownership:** COMMERCIAL FACILITY

**Disposal type description:**

**Disposal location description:** Haul to commercial facility

**Reserve Pit**

**Reserve Pit being used?** N

**Temporary disposal of produced water into reserve pit?** NO

**Reserve pit length (ft.)**                      **Reserve pit width (ft.)**

**Reserve pit depth (ft.)**    **Reserve pit volume (cu. yd.)**

**Is at least 50% of the reserve pit in cut?**

**Reserve pit liner**

**Reserve pit liner specifications and installation description**

**Cuttings Area**

**Cuttings Area being used?** NO

**Are you storing cuttings on location?** Y

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Description of cuttings location** Approximately 9771 cubic feet, stored in Steel tanks. Will be hauled to commercial facility per well.

**Cuttings area length (ft.)**

**Cuttings area width (ft.)**

**Cuttings area depth (ft.)**

**Cuttings area volume (cu. yd.)**

**Is at least 50% of the cuttings area in cut?**

**WCuttings area liner**

**Cuttings area liner specifications and installation description**

### Section 8 - Ancillary Facilities

**Are you requesting any Ancillary Facilities?:** N

**Ancillary Facilities attachment:**

**Comments:**

### Section 9 - Well Site Layout

**Well Site Layout Diagram:**

RAIDER\_FEDERAL\_COM\_Location\_Layout\_20191016101452.pdf

**Comments:**

### Section 10 - Plans for Surface Reclamation

**Type of disturbance:** New Surface Disturbance

**Multiple Well Pad Name:** RAIDER PAD

**Multiple Well Pad Number:** 302

**Recontouring attachment:**

RAIDER\_FEDERAL\_COM\_Reclamation\_plat\_20191016101552.pdf

**Drainage/Erosion control construction:** Drainage and erosion will be constantly monitored to prevent compromising the well site integrity, and to protect the surrounding native topography.

**Drainage/Erosion control reclamation:** Upon reclamation, well site will be returned to its native contour. Water breaks will be added if needed, to prevent unnatural erosion and loss of vegetation.

**Well pad proposed disturbance (acres):** 4.434

**Well pad interim reclamation (acres):** 2.53

**Well pad long term disturbance (acres):** 1.904

**Road proposed disturbance (acres):** 1.187

**Road interim reclamation (acres):** 0

**Road long term disturbance (acres):** 1.187

**Powerline proposed disturbance (acres):** 0

**Powerline interim reclamation (acres):** 0

**Powerline long term disturbance (acres):** 0

**Pipeline proposed disturbance (acres):** 0

**Pipeline interim reclamation (acres):** 0

**Pipeline long term disturbance (acres):** 0

**Other proposed disturbance (acres):** 0

**Other interim reclamation (acres):** 0

**Other long term disturbance (acres):** 0

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Total proposed disturbance:** 5.621

**Total interim reclamation:** 2.53

**Total long term disturbance:** 3.091

**Disturbance Comments:** Onsite done for this pad on 4/25/19 with Paul Murphy.

**Reconstruction method:** Come back in with heavy equipment, remove caliche in the reclamation area, and replace with native topsoil. Reconstruction of pad will occur once all wells on location have been drilled and completed.

**Topsoil redistribution:** Surface disturbance will be limited to well site surveyed dimensions. Topsoil will be stored along the west edge of the pad site.

**Soil treatment:** Native caliche will be used in the initial construction of the well pad. Pad will be compacted using fresh water, dust control measures will be implemented as needed.

**Existing Vegetation at the well pad:** Surface disturbance will be limited to well site surveyed dimensions. Topsoil will be stored along the East edge of the pad site.

**Existing Vegetation at the well pad attachment:**

**Existing Vegetation Community at the road:** Will be windrowed to the edge of the disturbance and be utilized as a barrier from water run-off.

**Existing Vegetation Community at the road attachment:**

**Existing Vegetation Community at the pipeline:** Surface disturbance will be limited.

**Existing Vegetation Community at the pipeline attachment:**

**Existing Vegetation Community at other disturbances:** N/A

**Existing Vegetation Community at other disturbances attachment:**

**Non native seed used?** N

**Non native seed description:**

**Seedling transplant description:**

**Will seedlings be transplanted for this project?** N

**Seedling transplant description attachment:**

**Will seed be harvested for use in site reclamation?** N

**Seed harvest description:**

**Seed harvest description attachment:**

**Seed Management**

**Seed Table**

**Seed Summary**

**Total pounds/Acre:**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Seed Type**

**Pounds/Acre**

**Seed reclamation attachment:**

**Operator Contact/Responsible Official Contact Info**

**First Name:**

**Last Name:**

**Phone:**

**Email:**

**Seedbed prep:** Prepare a 3-5 inch deep seedbed, with the top 3-4 inches consisting of topsoil.

**Seed BMP:** Seeding will be done in the proper season, and monitored for the re-establishment of native vegetation.

**Seed method:** Broadcast

**Existing invasive species?** N

**Existing invasive species treatment description:**

**Existing invasive species treatment attachment:**

**Weed treatment plan description:** Spray for noxious weeds and bare ground as needed.

**Weed treatment plan attachment:**

**Monitoring plan description:** All disturbed areas will be closely monitored for any primary or secondary noxious weeds. Should any be found, chemical spraying in accordance with state regulations will be implemented.

**Monitoring plan attachment:**

**Success standards:** No primary or secondary noxious weed will be allowed. Vegetation will be returned to its native standard.

**Pit closure description:** No open pits will be constructed.

**Pit closure attachment:**

**Section 11 - Surface Ownership**

**Disturbance type:** EXISTING ACCESS ROAD

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Disturbance type:** WELL PAD

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Disturbance type:** PIPELINE

**Describe:**

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

|  |                          |
|--|--------------------------|
| <b>Operator Name:</b> CENTENNIAL RESOURCE PRODUCTION LLC |                          |
| <b>Well Name:</b> RAIDER FEDERAL                         | <b>Well Number:</b> 401H |

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Disturbance type:** OTHER

**Describe:** Power Line

**Surface Owner:** PRIVATE OWNERSHIP

**Other surface owner description:**

**BIA Local Office:**

**BOR Local Office:**

**COE Local Office:**

**DOD Local Office:**

**NPS Local Office:**

**State Local Office:**

**Military Local Office:**

**USFWS Local Office:**

**Other Local Office:**

**USFS Region:**

**USFS Forest/Grassland:**

**USFS Ranger District:**

**Section 12 - Other Information**

**Right of Way needed?** N

**Use APD as ROW?**

**ROW Type(s):**

**ROW Applications**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**SUPO Additional Information:** See attached SUPO.

**Use a previously conducted onsite?** Y

**Previous Onsite information:** Onsite conducted with Paul Murphy on 4/25/19

**Other SUPO Attachment**

RAIDER\_FEDERAL\_COM\_Arch\_Survey\_20191016103249.pdf

Raider\_302H\_\_401H\_\_402H\_SUPO\_20191016114455.pdf



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# PWD Data Report

06/10/2020

**APD ID:** 10400049567

**Submission Date:** 10/17/2019

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Well Type:** OIL WELL

**Well Work Type:** Drill

## Section 1 - General

**Would you like to address long-term produced water disposal?** NO

## Section 2 - Lined Pits

**Would you like to utilize Lined Pit PWD options?** N

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Lined pit PWD on or off channel:**

**Lined pit PWD discharge volume (bbl/day):**

**Lined pit specifications:**

**Pit liner description:**

**Pit liner manufacturers information:**

**Precipitated solids disposal:**

**Decribe precipitated solids disposal:**

**Precipitated solids disposal permit:**

**Lined pit precipitated solids disposal schedule:**

**Lined pit precipitated solids disposal schedule attachment:**

**Lined pit reclamation description:**

**Lined pit reclamation attachment:**

**Leak detection system description:**

**Leak detection system attachment:**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Lined pit Monitor description:**

**Lined pit Monitor attachment:**

**Lined pit: do you have a reclamation bond for the pit?**

**Is the reclamation bond a rider under the BLM bond?**

**Lined pit bond number:**

**Lined pit bond amount:**

**Additional bond information attachment:**

**Section 3 - Unlined Pits**

**Would you like to utilize Unlined Pit PWD options?** N

**Produced Water Disposal (PWD) Location:**

**PWD disturbance (acres):**

**PWD surface owner:**

**Unlined pit PWD on or off channel:**

**Unlined pit PWD discharge volume (bbl/day):**

**Unlined pit specifications:**

**Precipitated solids disposal:**

**Describe precipitated solids disposal:**

**Precipitated solids disposal permit:**

**Unlined pit precipitated solids disposal schedule:**

**Unlined pit precipitated solids disposal schedule attachment:**

**Unlined pit reclamation description:**

**Unlined pit reclamation attachment:**

**Unlined pit Monitor description:**

**Unlined pit Monitor attachment:**

**Do you propose to put the produced water to beneficial use?**

**Beneficial use user confirmation:**

**Estimated depth of the shallowest aquifer (feet):**

**Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?**

**TDS lab results:**

**Geologic and hydrologic evidence:**

**State authorization:**

**Unlined Produced Water Pit Estimated percolation:**

**Unlined pit: do you have a reclamation bond for the pit?**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Is the reclamation bond a rider under the BLM bond?**

**Unlined pit bond number:**

**Unlined pit bond amount:**

**Additional bond information attachment:**

**Section 4 - Injection**

**Would you like to utilize Injection PWD options?** N

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Injection PWD discharge volume (bbl/day):**

**Injection well mineral owner:**

**Injection well type:**

**Injection well number:**

**Injection well name:**

**Assigned injection well API number?**

**Injection well API number:**

**Injection well new surface disturbance (acres):**

**Minerals protection information:**

**Mineral protection attachment:**

**Underground Injection Control (UIC) Permit?**

**UIC Permit attachment:**

**Section 5 - Surface Discharge**

**Would you like to utilize Surface Discharge PWD options?** N

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Surface discharge PWD discharge volume (bbl/day):**

**Surface Discharge NPDES Permit?**

**Surface Discharge NPDES Permit attachment:**

**Surface Discharge site facilities information:**

**Surface discharge site facilities map:**

**Section 6 - Other**

**Would you like to utilize Other PWD options?** N

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Other PWD discharge volume (bbl/day):**

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

**Other PWD type description:**

**Other PWD type attachment:**

**Have other regulatory requirements been met?**

**Other regulatory requirements attachment:**



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Bond Info Data Report

06/10/2020

**APD ID:** 10400049567

**Submission Date:** 10/17/2019

Highlighted data reflects the most recent changes

**Operator Name:** CENTENNIAL RESOURCE PRODUCTION LLC

**Well Name:** RAIDER FEDERAL

**Well Number:** 401H

[Show Final Text](#)

**Well Type:** OIL WELL

**Well Work Type:** Drill

## Bond Information

**Federal/Indian APD:** FED

**BLM Bond number:** NMB001471

**BIA Bond number:**

**Do you have a reclamation bond?** NO

**Is the reclamation bond a rider under the BLM bond?**

**Is the reclamation bond BLM or Forest Service?**

**BLM reclamation bond number:**

**Forest Service reclamation bond number:**

**Forest Service reclamation bond attachment:**

**Reclamation bond number:**

**Reclamation bond amount:**

**Reclamation bond rider amount:**

**Additional reclamation bond information attachment:**

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

|  |  |  |  |   |  |
|--|--|--|--|---|--|
| <sup>1</sup> API Number<br><b>30-025-48390</b> |  | <sup>2</sup> Pool Code<br><b>96434</b>                                   |  | <sup>3</sup> Pool Name<br><b>Red Hills-Bone Spring, North</b> |  |
| <sup>4</sup> Property Code<br><b>322254</b>    |  | <sup>5</sup> Property Name<br><b>RAIDER FEDERAL</b>                      |  |   | <sup>6</sup> Well Number<br><b>401H</b>  |
| <sup>7</sup> OGRID No.<br><b>372165</b>        |  | <sup>8</sup> Operator Name<br><b>CENTENNIAL RESOURCE PRODUCTION, LLC</b> |  |   | <sup>9</sup> Elevation<br><b>3530.2'</b> |

<sup>10</sup> Surface Location


| UL or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|--------|
| A             | 21      | 24S      | 34E   |         | 433           | NORTH            | 1302          | EAST           | LEA    |

<sup>11</sup> Bottom Hole Location If Different From Surface

| UL or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|--------|
| O             | 21      | 24S      | 34E   |         | 100           | SOUTH            | 1650          | EAST           | LEA    |

|                                      |                               |                                  |                         |
|--------------------------------------|-------------------------------|----------------------------------|-------------------------|
| <sup>12</sup> Dedicated Acres<br>160 | <sup>13</sup> Joint or Infill | <sup>14</sup> Consolidation Code | <sup>15</sup> Order No. |
|--------------------------------------|-------------------------------|----------------------------------|-------------------------|

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



| LINE TABLE |             |          |
|------------|-------------|----------|
| LINE       | DIRECTION   | LENGTH   |
| L1         | N46°27'48"W | 482.31'  |
| L2         | S89°50'59"W | 2637.82' |

|  |   |  |
|--|---|--|
| <b>NAD 83 (SURFACE HOLE LOCATION)</b><br>LATITUDE = 32°12'32.79" (32.209109°)<br>LONGITUDE = 103°28'14.15" (103.470598°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 440878.89' X: 808170.73'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11694989.05' X: 2113312.04' | <b>NAD 83 (FIRST TAKE POINT)</b><br>LATITUDE = 32°12'36.09" (32.210026°)<br>LONGITUDE = 103°28'18.21" (103.471724°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 441209.60' X: 807819.75'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11695317.53' X: 2112959.07' | <b>NAD 83 (LTP/BHL)</b><br>LATITUDE = 32°11'45.85" (32.196069°)<br>LONGITUDE = 103°28'18.14" (103.471704°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 436131.97' X: 807866.63'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11690240.98' X: 2113037.43' |
|--|---|--|

**<sup>17</sup> OPERATOR CERTIFICATION**  
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*[Signature]* **10/16/19**  
Signature Date

**Kanicia Schlichting**  
Printed Name

**kanicia.schlichting@cdevinc.com**  
E-mail Address


**<sup>18</sup> SURVEYOR CERTIFICATION**  
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

January 24, 2019  
Date of Survey

Signature and Seal of Professional Surveyor:

Certificate Number:

**NOTE:**  
• Distances referenced on plat to section lines are perpendicular.  
• Basis of Bearing is a Transverse Mercator Projection with a Central Meridian of W103°53'00"



- = SURFACE HOLE LOCATION
- ◆ = FIRST TAKE POINT
- = LAST TAKE POINT/  
BOTTOM HOLE LOCATION
- ▲ = SECTION CORNER LOCATED
- △ = SECTION CORNER  
RE-ESTABLISHED.  
(Not Set on Ground.)

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
**OIL CONSERVATION DIVISION**  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

|   |  |  |  |   |  |
|---|--|--|--|---|--|
| <sup>1</sup> API Number                 |  | <sup>2</sup> Pool Code<br><b>96434</b>                                   |  | <sup>3</sup> Pool Name<br><b>Red Hills-Bone Spring, North</b> |  |
| <sup>4</sup> Property Code              |  | <sup>5</sup> Property Name<br><b>RAIDER FEDERAL</b>                      |  | <sup>6</sup> Well Number<br><b>401H</b>                       |  |
| <sup>7</sup> OGRID No.<br><b>372165</b> |  | <sup>8</sup> Operator Name<br><b>CENTENNIAL RESOURCE PRODUCTION, LLC</b> |  | <sup>9</sup> Elevation<br><b>3530.2'</b>                      |  |

<sup>10</sup> Surface Location


| UL or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|--------|
| A             | 21      | 24S      | 34E   |         | 433           | NORTH            | 1302          | EAST           | LEA    |

<sup>11</sup> Bottom Hole Location If Different From Surface

| UL or lot no. | Section | Township | Range | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
|---------------|---------|----------|-------|---------|---------------|------------------|---------------|----------------|--------|
| O             | 21      | 24S      | 34E   |         | 100           | SOUTH            | 1650          | EAST           | LEA    |

|                                      |                               |                                  |                         |
|--------------------------------------|-------------------------------|----------------------------------|-------------------------|
| <sup>12</sup> Dedicated Acres<br>160 | <sup>13</sup> Joint or Infill | <sup>14</sup> Consolidation Code | <sup>15</sup> Order No. |
|--------------------------------------|-------------------------------|----------------------------------|-------------------------|

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



| LINE | DIRECTION   | LENGTH   |
|------|-------------|----------|
| L1   | N46°27'48"W | 482.31'  |
| L2   | S89°50'59"W | 2637.82' |


|  |   |  |
|--|---|--|
| <b>NAD 83 (SURFACE HOLE LOCATION)</b><br>LATITUDE = 32°12'32.79" (32.209109°)<br>LONGITUDE = 103°28'14.15" (103.470598°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 440878.89' X: 808170.73'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11694989.05' X: 2113312.04' | <b>NAD 83 (FIRST TAKE POINT)</b><br>LATITUDE = 32°12'36.09" (32.210026°)<br>LONGITUDE = 103°28'18.21" (103.471724°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 441209.60' X: 807819.75'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11695317.53' X: 2112959.07' | <b>NAD 83 (LTP/BHL)</b><br>LATITUDE = 32°11'45.85" (32.196069°)<br>LONGITUDE = 103°28'18.14" (103.471704°)<br>STATE PLANE NAD 83 (N.M. EAST)<br>Y: 436131.97' X: 807866.63'<br>UTM, NAD 83 (ZONE 13)<br>Y: 11690240.98' X: 2113037.43' |
|--|---|--|

**<sup>17</sup> OPERATOR CERTIFICATION**  
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.  
  
Signature **10/16/19**  
Date  
**Kanicia Schlichting**  
Printed Name  
**kanicia.schlichting@cdevinc.com**  
E-mail Address

**<sup>18</sup> SURVEYOR CERTIFICATION**  
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.  
January 24, 2019  
Date of Survey  
Signature and Seal of Professional Surveyor:



**NOTE:**  
• Distances referenced on plat to section lines are perpendicular.  
• Basis of Bearing is a Transverse Mercator Projection with a Central Meridian of W103°53'00"



- = SURFACE HOLE LOCATION
- ◆ = FIRST TAKE POINT
- = LAST TAKE POINT/ BOTTOM HOLE LOCATION
- ▲ = SECTION CORNER LOCATED
- △ = SECTION CORNER RE-ESTABLISHED. (Not Set on Ground.)

Certificate Number:

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 S. First St., Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Submit Original  
to Appropriate  
District Office

**GAS CAPTURE PLAN**

Date: 10/10/2019

Original Operator & OGRID No.: Centennial Resource Production, LLC 372165  
 Amended - Reason for Amendment: \_\_\_\_\_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

*Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).*

**Well(s)/Production Facility – Name of facility**

The well(s) that will be located at the production facility are shown in the table below.

| Well Name               | API     | Well Location (ULSTR) | Footages           | Expected MCF/D | Flared or Vented | Comments |
|-------------------------|---------|-----------------------|--------------------|----------------|------------------|----------|
| Raider Federal Com 302H | Pending | A-21-24S-34E          | 433 FNL & 1272 FEL | 2400 MCF/D     | Neither          | New Well |
| Raider Federal 401H     | Pending | A-21-24S-34E          | 433 FNL & 1302 FEL | 1350 MCF/D     | Neither          | New Well |
| Raider Federal Com 402H | Pending | A-21-24S-34E          | 433 FNL & 1242 FEL | 1380 MCF/D     | Neither          | New Well |

**Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated Lucid Energy Group low/high pressure gathering system located in Lea County, New Mexico. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. Centennial Resource Production, LLC provides (periodically) to Lucid Energy Group a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Centennial Resource Production, LLC and Lucid Energy Group have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Red Hills Plant located in Sec. 13, Twn. 24S, Rng. 33E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

**Flowback Strategy**

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Lucid Energy Group system at that time. Based on current information, it is Centennial Resource Production, LLC's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

**Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

- NGL Removal – On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 14481

**CONDITIONS OF APPROVAL**

|           |                                |                              |                 |        |        |                |       |              |             |
|-----------|--------------------------------|------------------------------|-----------------|--------|--------|----------------|-------|--------------|-------------|
| Operator: | CENTENNIAL RESOURCE PRODUCTION | 1001 17th Street, Suite 1800 | Denver, CO80202 | OGRID: | 372165 | Action Number: | 14481 | Action Type: | FORM 3160-3 |
|-----------|--------------------------------|------------------------------|-----------------|--------|--------|----------------|-------|--------------|-------------|

| OCD Reviewer | Condition  |
|--------------|--|
| pkautz       | Will require a File As Drilled C-102 and a Directional Survey with the C-104   |
| pkautz       | Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string |