Office	DA661651202Distric	~	tate of New Mexi			Form C-Page 1
<u>District I</u> - (575)		<b></b>	Inerals and Natura	l Resources	WELL API NO.	Revised July 18, 2013
District II - (575)			ΝΙΩΈΡΑ ΑΤΊΩΝΙ Γ	IVISION	30-015-01677	
	OIL CONSERVATION DIVISION  (505) 334-6178  OIL CONSERVATION DIVISION  1220 South St. Francis Dr.				5. Indicate Type	
1000 Rio Brazos	Rd., Aztec, NM 874	10	Santa Fe, NM 875		STATE  6. State Oil & C	
<u>District IV</u> – (505 1220 S. St. Franc 87505	<ol> <li>6) 476-3460</li> <li>fs Dr., Santa Fe, NM</li> </ol>		Juliu I vy I III v 10		B-4575	
(DO NOT USE T	THIS FORM FOR PR	NOTICES AND REPORTED TO DRILL OUT TO DE PERM	R TO DEEPEN OR PLUC		Delhi A State	or Unit Agreement Name
PROPOSALS.)	servoir. Use A Tell: Oil Well		Other	30CH	8. Well Numbe	r #1
2. Name of C		3 345 11 611			9. OGRID Nun	iber
	y Corporation				013837	W/1 44
3. Address of	f Operator <b>) Artesia,NM 88</b>	2210			10. Pool name Empire Abo	or Wildcat
4. Well Loca		0210			Linpire Acco	
1	tion Letter <b>D</b>	: 990feet	from the N	line and	980 feet fron	the Wline
Secti			17S Range		NMPM	County Eddy
3000	ion 33		(Show whether DR, I		Taxonian Co.	
			3672, (			
	12. Che	eck Appropriate B	ox to Indicate Na	ture of Notice	, Report or Othe	er Data
	NOTICE	F INTENTION T	·O:	SILE	SEQUENT R	EPORT OF:
PERFORM R	NOTICE O			REMEDIAL WO		ALTERING CASING
	LY ABANDON	☐ CHANGE PLA	1		RILLING OPNS.	P AND A
PULL OR AL	TER CASING	☐ MULTIPLE C	OMPL 🗌	CASING/CEMEN	NT JOB 🔲	
	COMMINGLE					
	$\Delta C = C \times \Delta T \subset M$					
CLOSED-LO	OPSYSIEM		_	OTHER:		П
OTHER:		_	Clearly state all po	OTHER: ertinent details, a	nd give pertinent d	ates, including estimated date
OTHER:	ribe proposed or	completed operations	s. (Clearly state all po E 19.15.7.14 NMAC	ertinent details, a	nd give pertinent o	ates, including estimated date wellbore diagram of
OTHER: 13. Description of sta	ribe proposed or arting any propos	completed operations	s. (Clearly state all pe E 19.15.7.14 NMAC	ertinent details, a	nd give pertinent dompletions: Attac	ates, including estimated date a wellbore diagram of
OTHER:  13. Description of star proportions	ribe proposed or arting any propos osed completion	completed operations sed work). SEE RUL or recompletion.	E 19.15.7.14 NMAC.	ertinent details, a For Multiple C	ompletions: Attac	n wellbore diagram of
OTHER:  13. Description of star proportion of the proportion of th	ribe proposed or urting any propososed completion 7/21 MIRU plug 3/21 RIH w/ gua	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/age ring to 5900'. PO	E 19.15.7.14 NMAC. /12/21 POH w/ rods DH. Set 4 ½" CIBP @	ertinent details, a For Multiple Co  & pump. ND we  \$ 5850'. Circula	ellhead, NU BOP.	POH w/ 99 stands of tbg. Pressure tested csg, held
OTHER:  13. Description of star proportion of star	ribe proposed or urting any proposed completion 7/21 MIRU plug 8/21 RIH w/ gua PSI. Spotted 25	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/age ring to 5900'. PC sx class C cmt @ 58	E 19.15.7.14 NMAC. (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tap	ertinent details, a For Multiple Co  & pump. ND we  5850'. Circula  gged plug @ 548	ellhead, NU BOP. ted hole w/ MLF. 37'. Spotted 25 sx	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'.
OTHER:  13. Description of star proportion of star	ribe proposed or urting any proposed completion 7/21 MIRU plug 8/21 RIH w/ gua PSI. Spotted 25 rd csg @ 955'. P	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/age ring to 5900'. PC sx class C cmt @ 58/ressured up on perf	E 19.15.7.14 NMAC.  (12/21 POH w/ rods )H. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter	ertinent details, a For Multiple Co  & pump. ND we  5850'. Circula  gged plug @ 548  125 sx class C c	ellhead, NU BOP. ted hole w/ MLF. 7'. Spotted 25 sx mt @ 1005-677'.	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug
OTHER:  13. Description of star proposition of	ribe proposed or arting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. P	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/age ring to 5900'. PO sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx c	E 19.15.7.14 NMAC.  (12/21 POH w/ rods )H. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31	ertinent details, a For Multiple Co  & pump. ND we  5850'. Circula  gged plug @ 548  125 sx class C c  10'. WOC. Tagg	ellhead, NU BOP. ted hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. ' ged plug @ 305'. F	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug erf'd csg @ 140'. Pressured
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 d csg @ 955'. Put csg @ n perfs to 500 P.	completed operations sed work). SEE RUL or recompletion.  rging equipment. 05/age ring to 5900'. PC sx class C cmt @ 58/ressured up on perf @ 410'. Sqz'd 25 sx class I. Spotted 25 sx class C sx clas	E 19.15.7.14 NMAC.  (12/21 POH w/ rods)  OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & 6	& pump. ND we 5850'. Circula gged plug @ 548125 sx class C c 10'. WOC. Tagg	ellhead, NU BOP. ted hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. Yed plug @ 305'. F	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug 'erf'd csg @ 140'. Pressured igged down & moved off.
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pd0'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an	& pump. ND we 5850'. Circula gged plug @ 548125 sx class C c 10'. WOC. Taggerulated to sur ad Gilbert Cord	ellhead, NU BOP. ted hole w/ MLF. 7'. Spotted 25 sx mt @ 1005-677'. ted plug @ 305'. Frace. ND BOP. R ero w/ NM OCD	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug erf'd csg @ 140'. Pressured
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 d csg @ 955'. P 10'. Perf'd csg @ n perfs to 500 P 9/21 Moved in b	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an	& pump. ND we 5850'. Circula gged plug @ 548125 sx class C c 10'. WOC. Taggerulated to sur ad Gilbert Cord	ellhead, NU BOP. ted hole w/ MLF. 7'. Spotted 25 sx mt @ 1005-677'. ted plug @ 305'. Frace. ND BOP. R ero w/ NM OCD	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. verified cmt to surface via
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pd0'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an	& pump. ND we 5850'. Circula gged plug @ 548125 sx class C c 10'. WOC. Taggerulated to sur ad Gilbert Cord	ellhead, NU BOP. ted hole w/ MLF. 7'. Spotted 25 sx mt @ 1005-677'. ted plug @ 305'. Frace. ND BOP. R ero w/ NM OCD	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. verified cmt to surface via
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pd0'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods )H. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an round Dry Hole Ma	ertinent details, a For Multiple Co we pump. ND we 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. Ted plug @ 305'. Frace. ND BOP. R ero w/ NM OCD cellar, cut off dea	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. verified cmt to surface via
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pd0'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an	ertinent details, a For Multiple Co we pump. ND we 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. S7'. Spotted 25 sx mt @ 1005-677'. Ited plug @ 305'. Frace. ND BOP. R ero w/ NM OCD cellar, cut off dea	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. Werified cmt to surface via dmen, cleaned location, & r plugging of well bore only. Liability und ned pending Location cleanup & receipt
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion 7/21 MIRU plug 3/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pd0'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods )H. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head an round Dry Hole Ma	ertinent details, a For Multiple Co we pump. ND we 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. S7'. Spotted 25 sx mt @ 1005-677'. Ited plug @ 305'. Frace. ND BOP. R ero w/ NM OCD cellar, cut off dea	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. Everified cmt to surface via dmen, cleaned location, &
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 8/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pdo'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message ed off.	completed operations sed work). SEE RUL or recompletion.  In ging equipment. 05/age ring to 5900'. PO sx class C cmt @ 58  Pressured up on perf @ 410'. Sqz'd 25 sx class C sx c	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & o Cut off well head an round Dry Hole Ma	ertinent details, a For Multiple Co & pump. ND we 9 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. ted hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. ' ged plug @ 305'. F face. ND BOP. R ero w/ NM OCD ocellar, cut off dea  Approved for bond is reta C-103Q (Sub- may be four www.emnro	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. Everified cmt to surface via dmen, cleaned location, & plugging of well bore only. Liability und ned pending Location cleanup & receipt sequent Report of Well Plugging) which
OTHER:  13. Description of star proposition of	ribe proposed or urting any proposed completion 7/21 MIRU plug 8/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pdo'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message ed off.	completed operations sed work). SEE RUL or recompletion.  gging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58/ressured up on perf £ 410'. Sqz'd 25 sx class Ci. Spotted 25 sx class cackhoe and welder,	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotted class C cmt @ 410-31 ass C cmt @ 190' & o Cut off well head an round Dry Hole Ma	ertinent details, a For Multiple Co & pump. ND we 9 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. ted hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. ' ged plug @ 305'. F face. ND BOP. R ero w/ NM OCD ocellar, cut off dea  Approved for bond is reta C-103Q (Sub- may be four www.emnro	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. verified cmt to surface via dmen, cleaned location, & r plugging of well bore only. Liability und ned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion 7/21 MIRU plug 8/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. Pdo'. Perf'd csg @ n perfs to 500 Pd/21 Moved in bure text message ed off.	completed operations sed work). SEE RUL or recompletion.  In ging equipment. 05/nge ring to 5900'. PC sx class C cmt @ 58  Pressured up on perf @ 410'. Sqz'd 25 sx class C sx c	E 19.15.7.14 NMAC.  (12/21 POH w/ rods OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter class C cmt @ 410-3: ass C cmt @ 190' & Cut off well head an round Dry Hole Ma  Rig Release Da  nd complete to the be	ertinent details, a For Multiple Co & pump. ND we 9 5850'. Circula gged plug @ 548 125 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. S7'. Spotted 25 sx mt @ 1005-677'. Ited plug @ 305'. Frace. ND BOP. R ero w/ NM OCD cellar, cut off dea  Approved for bond is reta C-103Q (Submay be four www.emnrodge and belief.	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. verified cmt to surface via dmen, cleaned location, & r plugging of well bore only. Liability und ned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion  7/21 MIRU plug  8/21 RIH w/ gua  PSI. Spotted 25  2d csg @ 955'. P  10'. Perf'd csg @ n perfs to 500 P  9/21 Moved in b are text message ed off.  fy that the inform	completed operations sed work). SEE RUL or recompletion.  In reging equipment. 05/2 age ring to 5900'. PC sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C sx clas	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head ar round Dry Hole Ma  Rig Release Da  nd complete to the be	& pump. ND web 5850'. Circular ged plug @ 548 125 sx class C crowd and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. Yed plug @ 305'. Frace. ND BOP. R ero w/ NM OCD y cellar, cut off dea  Approved for bond is reta C-103Q (Submay be four www.emnrodge and belief.	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured ligged down & moved off. Everified cmt to surface via dmen, cleaned location, & plugging of well bore only. Liability unned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @ .state.nm.us
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion  7/21 MIRU plug B/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. P  10'. Perf'd csg @  10 perfs to 500 P  19/21 Moved in bure text message 10 perfs to 500 P  10 perfs to 500 P	completed operations sed work). SEE RUL or recompletion.  In reging equipment. 05/2 age ring to 5900'. PC sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C sx clas	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head ar round Dry Hole Ma  Rig Release Da  nd complete to the be	ertinent details, a For Multiple Co & pump. ND we 9 5850'. Circula gged plug @ 548 1 25 sx class C c 10'. WOC. Tagg circulated to sur and Gilbert Cord rker, backfilled  te:	ellhead, NU BOP. Ited hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. Yed plug @ 305'. Frace. ND BOP. R ero w/ NM OCD y cellar, cut off dea  Approved for bond is reta C-103Q (Submay be four www.emnrodge and belief.	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured igged down & moved off. Werified cmt to surface via dmen, cleaned location, & r plugging of well bore only. Liability und ned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @ .state.nm.us
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion  7/21 MIRU plug B/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. P  10'. Perf'd csg @  10 perfs to 500 P  19/21 Moved in bure text message 10 perfs to 500 P  10 perfs to 500 P	completed operations sed work). SEE RUL or recompletion.  In reging equipment. 05/2 age ring to 5900'. PC sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C cmt @ 58/2 ressured up on perf @ 410'. Sqz'd 25 sx class C sx clas	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head ar round Dry Hole Ma  Rig Release Da  nd complete to the be	& pump. ND web 5850'. Circular ged plug @ 548 125 sx class C crowd and Gilbert Cord rker, backfilled	ellhead, NU BOP. Ited hole w/ MLF. 37'. Spotted 25 sx mt @ 1005-677'. Yed plug @ 305'. Frace. ND BOP. R ero w/ NM OCD y cellar, cut off dea  Approved for bond is reta C-103Q (Submay be four www.emnrodge and belief.	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured ligged down & moved off. Everified cmt to surface via dmen, cleaned location, & plugging of well bore only. Liability unned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @ .state.nm.us
OTHER:  13. Description of star proposed	ribe proposed or urting any proposed completion  7/21 MIRU plug B/21 RIH w/ gua PSI. Spotted 25 Pd csg @ 955'. P  10'. Perf'd csg @  10 perfs to 500 P  19/21 Moved in bure text message 10 perfs to 500 P  10 perfs to 500 P	completed operations sed work). SEE RUL or recompletion.  In ging equipment. 05/age ring to 5900'. PO sx class C cmt @ 58/ressured up on perf@ 410'. Sqz'd 25 sx class C stackhoe and welder, e. Installed Above G	E 19.15.7.14 NMAC.  (12/21 POH w/ rods) OH. Set 4 ½" CIBP @ 50-5472'. WOC. Tag is to 500 PSI. Spotter class C cmt @ 410-31 ass C cmt @ 190' & Cut off well head ar round Dry Hole Ma  Rig Release Da  nd complete to the be	& pump. ND we 5850'. Circula 25 sx class C c colo'. WOC. Tagger circulated to sur and Gilbert Cord rker, backfilled te:  st of my knowled atory Technicia colory Technica colory Techni	ellhead, NU BOP. Ited hole w/ MLF. B7'. Spotted 25 sx int @ 1005-677'. Yed plug @ 305'. Frace. ND BOP. R ero w/ NM OCD y cellar, cut off dea  Approved for bond is reta C-103Q (Submay be four www.emnro dge and belief.  an I	POH w/ 99 stands of tbg. Pressure tested csg, held class C cmt @ 3360-2982'. WOC. 05/14/21 Tagged plug Perf'd csg @ 140'. Pressured ligged down & moved off. Everified cmt to surface via dmen, cleaned location, & plugging of well bore only. Liability unned pending Location cleanup & receipt sequent Report of Well Plugging) which d at OCD Web Page, OCD Permitting @ .state.nm.us

Top

290

410

410

648

1210

1952 3360

4990

5590

Formation

B/Salt & Anhy

Tansill

Yates

7 Rivers

San Andres


Queen

Glorieta Tubb

Abo

Mack		PLUGGED	
Author:	Abby-BCM		
Well Name	Delhi A State	Well No.	#1
Field/Pool	Empire Abo	API#:	30-015-01677
County	Eddy	Location	Unit D, 990' FNL & 980' FWL
State	New Mexico		Sec 33, T17S, R28E
Spud Date	7/16/2002	GL:	3672'

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surface Csg	8 5/8	J55	24#	903	12 1/4	300	0
Prod Csg	4 1/2	J55	11.6#	6,052	7 7/8	950	1000' TS



5. Perf'd csg @ 140'. Pressured up on perfs to 500 PSi. Spotted 25 sx class C cmt @ 190' & circulated to surface.

4. Perf'd csg @ 410'. Sqz'd 25 sx class C cmt @ 410-310'. WOC. Tagged plug @ 305'.

8 5/8 24# CSG @ 90 Hole Size: 12 1/4

3. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005-677'. WOC & Tagged @ 640'

677'. WOC & Tagged @ 640'

3. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
677'. WOC & Tagged @ 640'

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI. Spotted 25 sx class C cmt @ 1005
1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pressured up on perfs to 500 PSI.

1. Perf'd csg @ 955'. Pres

2. Spotted 25 sx class C cmt @ 3360-2982'.

1. Set 4  $\frac{1}{2}$ " CIBP @ 5850'. Circulated hole w/ MLF. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 5850-5472'. WOC. Tagged plug @ 5487'.

Perfs @ 5890-5930'

4 1/2 11.6# CSG @ 6,052 Hole Size: 7 7/8

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

CONDITIONS

Action 32148

## **CONDITIONS**

Operator:	OGRID:	
MACK ENERGY CORP	13837	
P.O. Box 960	Action Number:	
Artesia, NM 882110960	32148	
	Action Type:	
	[C-103] Sub. Plugging (C-103P)	

## CONDITIONS

Created By	Condition	Condition Date
gcordero	None	6/21/2021