

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
 August 1, 2011  
 Permit 297776

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

1. Operator Name and Address Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024		2. OGRID Number 328947
		3. API Number 30-015-48642
4. Property Code 331156	5. Property Name ROSE SOUTH	6. Well No. 010H

**7. Surface Location**

UL - Lot L	Section 7	Township 19S	Range 26E	Lot Idn 3	Feet From 2260	N/S Line S	Feet From 700	E/W Line W	County Eddy
---------------	--------------	-----------------	--------------	--------------	-------------------	---------------	------------------	---------------	----------------

**8. Proposed Bottom Hole Location**

UL - Lot L	Section 12	Township 19S	Range 25E	Lot Idn L	Feet From 2430	N/S Line S	Feet From 50	E/W Line W	County Eddy
---------------	---------------	-----------------	--------------	--------------	-------------------	---------------	-----------------	---------------	----------------

**9. Pool Information**

PENASCO DRAW;SA-YESO (ASSOC)	50270
------------------------------	-------

**Additional Well Information**

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type Private	15. Ground Level Elevation 3384
16. Multiple N	17. Proposed Depth 8535	18. Formation Yeso	19. Contractor	20. Spud Date 8/16/2021
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	12.25	9.625	36	1300	438	0
Prod	8.75	7	32	3100	1399	0
Prod	8.75	5.5	20	8535	1399	0

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type Double Ram	Working Pressure 5	Test Pressure 5000	Manufacturer Shaffer
--------------------	-----------------------	-----------------------	-------------------------

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC <input checked="" type="checkbox"/> and/or 19.15.14.9 (B) NMAC <input checked="" type="checkbox"/> if applicable. Signature:	<b>OIL CONSERVATION DIVISION</b>
Printed Name: Electronically filed by Sarah Chapman	Approved By: Kurt Simmons
Title: Regulatory Director	Title: Petroleum Specialist - A
Email Address: schapman@spurepllc.com	Approved Date: 7/2/2021      Expiration Date: 7/2/2023
Date: 6/29/2021      Phone: 832-930-8613	Conditions of Approval Attached

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-015-		<sup>2</sup> Pool Code 50270		<sup>3</sup> Pool Name PENASCO DRAW; SA-YESO (ASSOC)	
<sup>4</sup> Property Code		<sup>5</sup> Property Name ROSE SOUTH			<sup>6</sup> Well Number 10H
<sup>7</sup> GRID NO. 328947		<sup>8</sup> Operator Name SPUR ENERGY PARTNERS LLC.			<sup>9</sup> Elevation 3384'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet From the	East/West line	County
3	7	19S	26E		2260	SOUTH	700	WEST	EDDY

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	12	19S	25E		2430	SOUTH	50	WEST	EDDY

<sup>12</sup> Dedicated Acres 320	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

<p><sup>16</sup> <b>GEODETIC DATA</b> NAD 83 GRID - NM EAST</p> <p><b>SURFACE LOCATION (SL)</b> N: 608956.2 - E: 512401.0 LAT: 32.6740305° N LONG: 104.4273749° W</p> <p><b>FIRST TAKE POINT (FTP)</b> 2430' FSL &amp; 100' FEL - SEC 12 N: 609134.3 - E: 511600.8 LAT: 32.6745180° N LONG: 104.4299760° W</p> <p><b>LAST TAKE POINT (LTP)</b> 2430' FSL &amp; 100' FWL - SEC 12 N: 609120.8 - E: 506446.7 LAT: 32.6744670° N LONG: 104.4467264° W</p> <p><b>BOTTOM HOLE (BH)</b> N: 609120.7 - E: 506396.8 LAT: 32.6744665° N LONG: 104.4468888° W</p>	<p><b>CORNER DATA</b> NAD 83 GRID - NM EAST</p> <p>A: FOUND BOLT N: 606691.2 - E: 506353.0</p> <p>B: FOUND 1/2" REBAR N: 612008.3 - E: 506339.4</p> <p>C: FOUND 5/8" REBAR N: 611978.8 - E: 511694.1</p> <p>D: FOUND ALUM CAP "ILLEGIBLE" N: 612006.0 - E: 514294.2</p> <p>E: FOUND 3" PIPE N: 612034.2 - E: 516918.2</p> <p>F: FOUND SPIKE NAIL N: 609327.0 - E: 516948.7</p> <p>G: FOUND SPIKE NAIL N: 606619.9 - E: 516980.1</p> <p>H: FOUND 1" PIPE N: 606673.4 - E: 514339.7</p> <p>I: FOUND 1/2" REBAR N: 606705.1 - E: 511706.5</p>	<p><b><sup>17</sup> OPERATOR CERTIFICATION</b> <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i></p> <p><i>Sarah Chapman</i> 03/03/2021 Signature Date</p> <p>SARAH CHAPMAN Printed Name</p> <p>SCHAPMAN@SPUREPLLC.COM E-mail Address</p>	<p><b><sup>18</sup> SURVEYOR CERTIFICATION</b> <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i></p> <p>12-10-2020 Date of Survey</p> <p>Signature and Seal of Professional Surveyor</p> <p>19680 Certificate Number</p> 
---	--	--	---

LS20120749

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Comments

Permit 297776

**PERMIT COMMENTS**

Operator Name and Address: Spur Energy Partners LLC [328947] 9655 Katy Freeway Houston, TX 77024	API Number: 30-015-48642
	Well: ROSE SOUTH #010H

Created By	Comment	Comment Date
schapman01	Approved NSL attached for your use.	6/29/2021

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Conditions

Permit 297776

**PERMIT CONDITIONS OF APPROVAL**

Operator Name and Address: Spur Energy Partners LLC [328947] 9655 Katy Freeway Houston, TX 77024	API Number: 30-015-48642
	Well: ROSE SOUTH #010H

OCD Reviewer	Condition
ksimmons	Notify OCD 24 hours prior to casing & cement
ksimmons	Will require a File As Drilled C-102 and a Directional Survey with the C-104
ksimmons	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud
kpickford	Will require a administrative order for non-standard location prior to placing the well on production
kpickford	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
kpickford	Cement is required to circulate on both surface and intermediate1 strings of casing
kpickford	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system

## Spur Energy Partners LLC – Rose South 10H

### 1. Geologic Formations

Formation	Depth	Lithology	Expected Fluids
Quaternary	0'	Dolomite, other: Caliche	Useable Water
Top San Andres	915'	Dolomite, Limestone	Natural Gas, Oil
Lower San Andres	1950'	Dolomite, Limestone	Natural Gas, Oil
Glorieta	2460'	Dolomite, Siltstone	Natural Gas, Oil
Top Yeso	2575'	Dolomite	Natural Gas, Oil
Base Yeso	4150'	Dolomite	Natural Gas, Oil

\*H<sub>2</sub>S, water flows, loss of circulation, abnormal pressures, etc.

### 2. Casing Program

#### *Primary Plan:*

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Hole Size (in)	Casing Interval		Csg. Size (in)	Weight (lbs)	Grade	Conn.	SF	SF Burst	Body SF	Joint SF
	From (ft)	To (ft)					Collapse		Tension	Tension
12.25	0	1300	9.625	36	J-55	BTC	1.125	1.2	1.4	1.4
8.75	0	3100	7	32	L-80	BK-HT	1.125	1.2	1.4	1.4
8.75	3100	8535	5.5	20	L-80	BK-HT	1.125	1.2	1.4	1.4
SF Values will meet or Exceed										

## Spur Energy Partners LLC – Rose South 10H

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

### 3. Cementing Program

#### Primary Plan:

Casing String	Top (ft)	Bottom (ft)	% Excess
Surface (Lead)	0	950	100%
Surface (Tail)	950	1300	165%
Production (Lead)	0	2100	0%
Production (Tail)	2100	8535	50%

Casing String	# Sks	Wt. (lb/gal)	Yld (ft <sup>3</sup> /sack)	H2O (gal/sk)	500# Comp. Strength (hours)	Slurry Description
Surface (Lead)	270	12.2	2.31	13.48	8:12	Clas C Premium Plus Cement
Surface (Tail)	168	13.2	1.84	9.92	6:59	Clas C Premium Plus Cement
Production (Lead)	133	11.8	2.54	15.29	N/A	Clas C Premium Plus Cement
Production (Tail)	1266	13.2	1.81	9.81	N/A	Clas C Premium Plus Cement

### Spur Energy Partners LLC – Rose South 10H

#### 4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12.25" Hole	13-5/8"	5M	Annular	✓	70% of working pressure
			Blind Ram	✓	250 psi / 5000 psi
		Pipe Ram	✓		
		Double Ram			
		Other*			
8.75" Hole	13-5/8"	5M	Annular	✓	70% of working pressure
			Blind Ram	✓	250 psi / 5000 psi
		Pipe Ram	✓		
		Double Ram			
		Other*			

**\*Spur Energy Partners LLC will be utilizing a 5M BOP Stack\***

Condition	Specify what type and where?
BH Pressure at deepest TVD	1303 psi
Abnormal Temperature	No
BH Temperature at deepest TVD	103°F

\*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.	
Y	Are anchors required by manufacturer?
A conventional wellhead system will be employed. The wellhead and connection to the BOPE will meet all API 6A requirements. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. See attached schematics.	

## Spur Energy Partners LLC – Rose South 10H

### 5. BOP Break Testing Request

Spur Energy Partners LLC requests permission to adjust the BOP break testing requirements as per the verbal agreement reached over the phone between SPUR/BLM on September 7, 2020. A separate sundry will be sent prior to spud that reflects the pad-based break testing plan.

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill the production section, where the surface casing point is shallower than the 3 Bone Spring or 10,000 TVD.
- When skidding to drill a production section that does not penetrate the 3<sup>rd</sup> Bone Spring or deeper.

If the kill line is broken prior to skid, four tests will be performed.

- 1) The void between the wellhead and the spool (this consists of two tests)
- 2) The spool between the kill lines and the choke manifold (this consists of two tests)

If the kill line is not broken prior to skid, two tests will be performed.

- 1) The void between the wellhead and the pipe rams

### 6. Mud Program

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times. The following is a general list of products: Barite, Bentonite, Gypsum, Lime, Soda Ash, Caustic Soda, Nut Plug, Cedar Fiber, Cotton Seed Hulls, Drilling Paper, Salt Water Clay, CACL2. Spur will use a closed mud system.

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From (ft)	To (ft)				
0	1300	Water-Based Mud	8.6-8.9	32-36	N/C
1300	8535	Water-Based Mud	8.6-8.9	32-36	N/C

What will be used to monitor the loss or gain of fluid?	PVT/MD PASON/Visual Monitoring
---	--------------------------------



**Spur Energy Partners LLC – Rose South 10H**

**7. Logging and Testing Procedures**

<b>Logging, Coring and Testing.</b>		
Yes	Will run GR from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.	
No	Logs are planned based on well control or offset log information.	
No	Drill stem test? If yes, explain	
No	Coring? If yes, explain	
<b>Additional logs planned</b>	<b>Interval</b>	
No	Resistivity	
No	Density	
No	CBL	
Yes	Mud log	SCP - TD
No	PEX	

**8. Drilling Conditions**

Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal isolation.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

**Total estimated cuttings volume: 824.3 bbls.**

**Spur Energy Partners LLC – Rose South 10H**

**9. Other facets of operation**

	<b>Yes/No</b>
Will more than one drilling rig be used for drilling operations? If yes, describe. Spur Energy Partners LLC. requests the option to contract a Surface Rig to drill, set surface casing, and cement for this well. If the timing between rigs is such that Spur Energy Partners LLC. would not be able to preset surface, the Primary Rig will MIRU and drill the well in its entirety per the APD. Please see the attached document for information on the spudder rig.	Yes

Attachments

- Directional Plan
- H2S Contingency Plan
- Akita 57 Attachments
- Transcend Spudder Rig Attachments
- BOP Schematics

**10. Company Personnel**

<b>Name</b>	<b>Title</b>	<b>Office Phone</b>	<b>Mobile Phone</b>
Christopher Hollis	Drilling Manager	832-930-8629	713-380-7754
Johnny Nabors	Senior Vice President Operations	832-930-8502	281-904-8811



# U. S. Steel Tubular Products

## 9.625 36/0.352 J55

8/19/2015 9:44:40 AM

MECHANICAL PROPERTIES	Pipe	BTC	LTC	STC	
Minimum Yield Strength	55,000	--	--	--	psi
Maximum Yield Strength	80,000	--	--	--	psi
Minimum Tensile Strength	75,000	--	--	--	psi

DIMENSIONS	Pipe	BTC	LTC	STC	
Outside Diameter	9.625	10.625	10.625	10.625	in.
Wall Thickness	0.352	--	--	--	in.
Inside Diameter	8.921	8.921	8.921	8.921	in.
Standard Drift	8.765	8.765	8.765	8.765	in.
Alternate Drift	--	--	--	--	in.
Nominal Linear Weight, T&C	36.00	--	--	--	lbs/ft
Plain End Weight	34.89	--	--	--	lbs/ft

PERFORMANCE	Pipe	BTC	LTC	STC	
Minimum Collapse Pressure	2,020	2,020	2,020	2,020	psi
Minimum Internal Yield Pressure	3,520	3,520	3,520	3,520	psi
Minimum Pipe Body Yield Strength	564,000	--	--	--	lbs
Joint Strength	--	639	453	394	lbs
Reference Length	--	11,835	8,389	7,288	ft


MAKE-UP DATA	Pipe	BTC	LTC	STC	
Make-Up Loss	--	4.81	4.75	3.38	in.
Minimum Make-Up Torque	--	--	3,400	2,960	ft-lbs
Maximum Make-Up Torque	--	--	5,660	4,930	ft-lbs

### Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products  
10343 Sam Houston Park Dr., #120  
Houston, TX 77064

1-877-893-9461  
connections@uss.com  
www.usstubular.com



**SEMI PREMIUM CONNECTIONS**  
FIELD TESTED. FIELD PROVEN.

## Precision Connections BK-HT

### 7 in. 32 lb/ft HC-L80 with 7.875 in. Coupling OD

#### Pipe Body

Nominal OD	7.000	inches
Nominal Weight	32.00	lb/ft
Wall Thickness	0.453	inches
Plain End Weight	31.67	lb/ft
Drift	6.000	inches
Nominal ID	6.094	inches
Grade	HC-L80	
Min Yield	80,000	lbf/in <sup>2</sup>
Min Tensile	95,000	lbf/in <sup>2</sup>
Critical Section Area	9.317	in <sup>2</sup>
Pipe Body Yield Strength	745	kips
Min Internal Yield Pressure	9,060	psi
Collapse Pressure	9,290	psi


#### Connection

Coupling OD	7.875	inches
Coupling Length	9.000	inches
Make Up Loss	4.500	inches
Critical Section Area	11.859	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	745	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	46.5	° / 100 ft
Min Make Up Torque	9,250	ft-lbs
Yield Torque	35,650	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




SEMI  
**PREMIUMCONNECTIONS**  
FIELD TESTED. FIELD PROVEN.

### Torque Data Sheet - Precision Connections BK-HT

7 in. 32 lb/ft HC-L80 with 7.875 in. Coupling OD


Min Make Up Torque	9,250	ft-lbs	Max Operating Torque	30,300	ft-lbs
Max Make Up Torque	26,750	ft-lbs	Yield Torque	35,650	ft-lbs
Optimum Torque	12,850	ft-lbs			

#### Representative Torque Turn Graph



v1.2

7/26/2018



## Precision Connections BK-HT

### 5.5 in. 20 lb/ft HC-L80 with 6.3 in. Coupling OD

#### Pipe Body

Nominal OD	5.500	inches
Nominal Weight	20.00	lb/ft
Wall Thickness	0.361	inches
Plain End Weight	19.81	lb/ft
Drift	4.653	inches
Nominal ID	4.778	inches
Grade	HC-L80	
Min Yield	80,000	lbf/in <sup>2</sup>
Min Tensile	95,000	lbf/in <sup>2</sup>
Critical Section Area	5.828	in <sup>2</sup>
Pipe Body Yield Strength	466	kips
Min Internal Yield Pressure	9,190	psi
Collapse Pressure	9,490	psi

#### Connection

Coupling OD	6.300	inches
Coupling Length	8.250	inches
Make Up Loss	4.125	inches
Critical Section Area	8.456	in <sup>2</sup>
Internal Pressure Rating	100%	
External Pressure Rating	100%	
Tension Efficiency	100%	
Connection Strength	466	kips
Compression Efficiency	100%	
Uniaxial Bend Rating	58.2	° / 100 ft
Min Make Up Torque	6,050	ft-lbs
Yield Torque	23,250	ft-lbs

v1.2

7/26/2018

This documentation contains confidential and proprietary information not to be reproduced or divulged in whole or in part to anyone outside of your company without prior written authorization from Precision Connections, LLC, and such documentation and information is provided to you upon such conditions of confidentiality.




**SEMI PREMIUM CONNECTIONS**  
FIELD TESTED. FIELD PROVEN.

### Torque Data Sheet - Precision Connections BK-HT

5.5 in. 20 lb/ft HC-L80 with 6.3 in. Coupling OD

Min Make Up Torque	6,050	ft-lbs	Max Operating Torque	19,800	ft-lbs
Max Make Up Torque	17,450	ft-lbs	Yield Torque	23,250	ft-lbs
Optimum Torque	8,400	ft-lbs			

**Representative Torque Turn Graph**



v1.2

7/26/2018



# Spur Energy Partners, LLC

Eddy County, NM (NAD 83 - NME)

ROSE SOUTH

#10H

Wellbore #1

Plan: PLAN #1

## Standard Planning Report

24 June, 2021







Planning Report



<b>Database:</b>	WBDS_SQL_2	<b>Local Co-ordinate Reference:</b>	Well #10H
<b>Company:</b>	Spur Energy Partners, LLC	<b>TVD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Project:</b>	Eddy County, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Site:</b>	ROSE SOUTH	<b>North Reference:</b>	Grid
<b>Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	PLAN #1		

<b>Project</b>	Eddy County, NM (NAD 83 - NME)		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	ROSE SOUTH				
<b>Site Position:</b>		<b>Northing:</b>	607,781.50 usft	<b>Latitude:</b>	32.6708016
<b>From:</b>	Map	<b>Easting:</b>	512,403.70 usft	<b>Longitude:</b>	-104.4273627
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13.200 in	<b>Grid Convergence:</b>	-0.051 °

<b>Well</b>	#10H					
<b>Well Position</b>	<b>+N/-S</b>	1,174.70 usft	<b>Northing:</b>	608,956.20 usft	<b>Latitude:</b>	32.6740305
	<b>+E/-W</b>	-2.70 usft	<b>Easting:</b>	512,401.00 usft	<b>Longitude:</b>	-104.4273749
<b>Position Uncertainty</b>		0.00 usft	<b>Wellhead Elevation:</b>		<b>Ground Level:</b>	3,384.00 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2020	6/24/2021	6.973	60.180	47,667.64485588

<b>Design</b>	PLAN #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.00	0.00	0.00	269.85

<b>Plan Survey Tool Program</b>	<b>Date</b>	6/24/2021			
<b>Depth From (usft)</b>	<b>Depth To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>	
1	0.00	8,535.88	PLAN #1 (Wellbore #1)	MWD+IGRF	
				OWSG MWD + IGRF or WM	

<b>Plan Sections</b>										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.000	
733.94	8.68	49.05	732.28	21.50	24.77	2.00	2.00	0.00	49.049	
1,715.44	8.68	49.05	1,702.54	118.57	136.63	0.00	0.00	0.00	0.000	
2,827.30	60.00	269.85	2,638.26	179.31	-336.11	6.00	4.62	-12.52	-141.969	
3,027.30	60.00	269.85	2,738.26	178.86	-509.32	0.00	0.00	0.00	0.000	
3,331.71	90.44	269.85	2,815.00	178.10	-800.20	10.00	10.00	0.00	0.000	PLAT #10H FTP: 2'
8,485.98	90.44	269.85	2,775.38	164.63	-5,954.30	0.00	0.00	0.00	0.000	PLAT #10H LTP: 2'
8,535.88	90.44	269.85	2,775.00	164.50	-6,004.20	0.00	0.00	0.00	0.000	PLAT #10H BHL: 2'



Planning Report

<b>Database:</b>	WBDS_SQL_2	<b>Local Co-ordinate Reference:</b>	Well #10H
<b>Company:</b>	Spur Energy Partners, LLC	<b>TVD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Project:</b>	Eddy County, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Site:</b>	ROSE SOUTH	<b>North Reference:</b>	Grid
<b>Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	PLAN #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	2.00	49.05	399.98	1.14	1.32	-1.32	2.00	2.00	0.00
500.00	4.00	49.05	499.84	4.57	5.27	-5.28	2.00	2.00	0.00
600.00	6.00	49.05	599.45	10.29	11.85	-11.88	2.00	2.00	0.00
700.00	8.00	49.05	698.70	18.27	21.06	-21.10	2.00	2.00	0.00
733.94	8.68	49.05	732.28	21.50	24.77	-24.83	2.00	2.00	0.00
800.00	8.68	49.05	797.59	28.03	32.30	-32.38	0.00	0.00	0.00
900.00	8.68	49.05	896.44	37.92	43.70	-43.80	0.00	0.00	0.00
1,000.00	8.68	49.05	995.30	47.81	55.10	-55.22	0.00	0.00	0.00
1,100.00	8.68	49.05	1,094.15	57.70	66.49	-66.64	0.00	0.00	0.00
1,200.00	8.68	49.05	1,193.01	67.59	77.89	-78.07	0.00	0.00	0.00
1,300.00	8.68	49.05	1,291.86	77.48	89.29	-89.49	0.00	0.00	0.00
1,400.00	8.68	49.05	1,390.72	87.37	100.68	-100.91	0.00	0.00	0.00
1,500.00	8.68	49.05	1,489.57	97.26	112.08	-112.33	0.00	0.00	0.00
1,600.00	8.68	49.05	1,588.43	107.15	123.48	-123.76	0.00	0.00	0.00
1,700.00	8.68	49.05	1,687.28	117.04	134.87	-135.18	0.00	0.00	0.00
1,715.44	8.68	49.05	1,702.54	118.57	136.63	-136.94	0.00	0.00	0.00
1,750.00	7.16	38.75	1,736.78	121.96	139.95	-140.27	6.00	-4.40	-29.81
1,800.00	5.62	15.27	1,786.47	126.75	142.55	-142.88	6.00	-3.07	-46.96
1,850.00	5.47	343.88	1,836.25	131.41	142.53	-142.87	6.00	-0.30	-62.77
1,900.00	6.80	318.34	1,885.97	135.91	139.90	-140.26	6.00	2.65	-51.09
1,950.00	8.97	303.04	1,935.50	140.24	134.67	-135.03	6.00	4.34	-30.59
2,000.00	11.51	294.04	1,984.70	144.40	126.84	-127.22	6.00	5.09	-18.00
2,050.00	14.24	288.35	2,033.44	148.37	116.45	-116.84	6.00	5.45	-11.38
2,100.00	17.05	284.48	2,081.59	152.14	103.51	-103.91	6.00	5.63	-7.74
2,150.00	19.92	281.69	2,129.00	155.70	88.07	-88.48	6.00	5.73	-5.58
2,200.00	22.82	279.58	2,175.56	159.04	70.17	-70.58	6.00	5.80	-4.22
2,250.00	25.74	277.93	2,221.14	162.15	49.85	-50.27	6.00	5.84	-3.31
2,300.00	28.68	276.59	2,265.60	165.03	27.17	-27.61	6.00	5.87	-2.68
2,350.00	31.62	275.48	2,308.83	167.66	2.20	-2.64	6.00	5.90	-2.22
2,400.00	34.58	274.54	2,350.71	170.03	-25.00	24.55	6.00	5.91	-1.87
2,450.00	37.54	273.74	2,391.13	172.15	-54.35	53.90	6.00	5.92	-1.61
2,500.00	40.51	273.03	2,429.96	174.00	-85.78	85.32	6.00	5.93	-1.41
2,550.00	43.48	272.41	2,467.12	175.59	-119.19	118.73	6.00	5.94	-1.25
2,600.00	46.46	271.85	2,502.49	176.90	-154.50	154.03	6.00	5.95	-1.12
2,650.00	49.43	271.35	2,535.98	177.93	-191.60	191.13	6.00	5.95	-1.01
2,700.00	52.41	270.88	2,567.50	178.68	-230.40	229.93	6.00	5.96	-0.93
2,750.00	55.39	270.45	2,596.95	179.15	-270.80	270.33	6.00	5.96	-0.85
2,800.00	58.37	270.06	2,624.27	179.33	-312.67	312.20	6.00	5.96	-0.80
2,827.30	60.00	269.85	2,638.26	179.31	-336.11	335.64	6.00	5.96	-0.76
2,900.00	60.00	269.85	2,674.60	179.15	-399.07	398.60	0.00	0.00	0.00
3,000.00	60.00	269.85	2,724.60	178.92	-485.67	485.20	0.00	0.00	0.00
3,027.30	60.00	269.85	2,738.26	178.86	-509.32	508.85	0.00	0.00	0.00
3,050.00	62.27	269.85	2,749.21	178.81	-529.19	528.73	10.00	10.00	0.00
3,100.00	67.27	269.85	2,770.52	178.69	-574.41	573.94	10.00	10.00	0.00
3,150.00	72.27	269.85	2,787.80	178.57	-621.31	620.84	10.00	10.00	0.00
3,200.00	77.27	269.85	2,800.93	178.44	-669.54	669.07	10.00	10.00	0.00
3,250.00	82.27	269.85	2,809.81	178.31	-718.73	718.26	10.00	10.00	0.00
3,300.00	87.27	269.85	2,814.37	178.18	-768.50	768.04	10.00	10.00	0.00
3,331.71	90.44	269.85	2,815.00	178.10	-800.20	799.73	10.00	10.00	0.00
3,400.00	90.44	269.85	2,814.48	177.92	-868.49	868.02	0.00	0.00	0.00



Planning Report

<b>Database:</b>	WBDS_SQL_2	<b>Local Co-ordinate Reference:</b>	Well #10H
<b>Company:</b>	Spur Energy Partners, LLC	<b>TVD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Project:</b>	Eddy County, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Site:</b>	ROSE SOUTH	<b>North Reference:</b>	Grid
<b>Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	PLAN #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
3,500.00	90.44	269.85	2,813.71	177.66	-968.49	968.02	0.00	0.00	0.00
3,600.00	90.44	269.85	2,812.94	177.40	-1,068.49	1,068.02	0.00	0.00	0.00
3,700.00	90.44	269.85	2,812.17	177.14	-1,168.48	1,168.01	0.00	0.00	0.00
3,800.00	90.44	269.85	2,811.40	176.88	-1,268.48	1,268.01	0.00	0.00	0.00
3,900.00	90.44	269.85	2,810.63	176.61	-1,368.48	1,368.01	0.00	0.00	0.00
4,000.00	90.44	269.85	2,809.86	176.35	-1,468.47	1,468.01	0.00	0.00	0.00
4,100.00	90.44	269.85	2,809.09	176.09	-1,568.47	1,568.00	0.00	0.00	0.00
4,200.00	90.44	269.85	2,808.33	175.83	-1,668.47	1,668.00	0.00	0.00	0.00
4,300.00	90.44	269.85	2,807.56	175.57	-1,768.46	1,768.00	0.00	0.00	0.00
4,400.00	90.44	269.85	2,806.79	175.31	-1,868.46	1,867.99	0.00	0.00	0.00
4,500.00	90.44	269.85	2,806.02	175.05	-1,968.46	1,967.99	0.00	0.00	0.00
4,600.00	90.44	269.85	2,805.25	174.79	-2,068.45	2,067.99	0.00	0.00	0.00
4,700.00	90.44	269.85	2,804.48	174.52	-2,168.45	2,167.98	0.00	0.00	0.00
4,800.00	90.44	269.85	2,803.71	174.26	-2,268.45	2,267.98	0.00	0.00	0.00
4,900.00	90.44	269.85	2,802.95	174.00	-2,368.44	2,367.98	0.00	0.00	0.00
5,000.00	90.44	269.85	2,802.18	173.74	-2,468.44	2,467.98	0.00	0.00	0.00
5,100.00	90.44	269.85	2,801.41	173.48	-2,568.44	2,567.97	0.00	0.00	0.00
5,200.00	90.44	269.85	2,800.64	173.22	-2,668.43	2,667.97	0.00	0.00	0.00
5,300.00	90.44	269.85	2,799.87	172.96	-2,768.43	2,767.97	0.00	0.00	0.00
5,400.00	90.44	269.85	2,799.10	172.69	-2,868.43	2,867.96	0.00	0.00	0.00
5,500.00	90.44	269.85	2,798.33	172.43	-2,968.42	2,967.96	0.00	0.00	0.00
5,600.00	90.44	269.85	2,797.57	172.17	-3,068.42	3,067.96	0.00	0.00	0.00
5,700.00	90.44	269.85	2,796.80	171.91	-3,168.42	3,167.96	0.00	0.00	0.00
5,800.00	90.44	269.85	2,796.03	171.65	-3,268.41	3,267.95	0.00	0.00	0.00
5,900.00	90.44	269.85	2,795.26	171.39	-3,368.41	3,367.95	0.00	0.00	0.00
6,000.00	90.44	269.85	2,794.49	171.13	-3,468.41	3,467.95	0.00	0.00	0.00
6,100.00	90.44	269.85	2,793.72	170.87	-3,568.40	3,567.94	0.00	0.00	0.00
6,200.00	90.44	269.85	2,792.95	170.60	-3,668.40	3,667.94	0.00	0.00	0.00
6,300.00	90.44	269.85	2,792.19	170.34	-3,768.40	3,767.94	0.00	0.00	0.00
6,400.00	90.44	269.85	2,791.42	170.08	-3,868.39	3,867.93	0.00	0.00	0.00
6,500.00	90.44	269.85	2,790.65	169.82	-3,968.39	3,967.93	0.00	0.00	0.00
6,600.00	90.44	269.85	2,789.88	169.56	-4,068.39	4,067.93	0.00	0.00	0.00
6,700.00	90.44	269.85	2,789.11	169.30	-4,168.38	4,167.93	0.00	0.00	0.00
6,800.00	90.44	269.85	2,788.34	169.04	-4,268.38	4,267.92	0.00	0.00	0.00
6,900.00	90.44	269.85	2,787.57	168.78	-4,368.38	4,367.92	0.00	0.00	0.00
7,000.00	90.44	269.85	2,786.81	168.51	-4,468.37	4,467.92	0.00	0.00	0.00
7,100.00	90.44	269.85	2,786.04	168.25	-4,568.37	4,567.91	0.00	0.00	0.00
7,200.00	90.44	269.85	2,785.27	167.99	-4,668.37	4,667.91	0.00	0.00	0.00
7,300.00	90.44	269.85	2,784.50	167.73	-4,768.36	4,767.91	0.00	0.00	0.00
7,400.00	90.44	269.85	2,783.73	167.47	-4,868.36	4,867.91	0.00	0.00	0.00
7,500.00	90.44	269.85	2,782.96	167.21	-4,968.36	4,967.90	0.00	0.00	0.00
7,600.00	90.44	269.85	2,782.19	166.95	-5,068.35	5,067.90	0.00	0.00	0.00
7,700.00	90.44	269.85	2,781.42	166.68	-5,168.35	5,167.90	0.00	0.00	0.00
7,800.00	90.44	269.85	2,780.66	166.42	-5,268.35	5,267.89	0.00	0.00	0.00
7,900.00	90.44	269.85	2,779.89	166.16	-5,368.34	5,367.89	0.00	0.00	0.00
8,000.00	90.44	269.85	2,779.12	165.90	-5,468.34	5,467.89	0.00	0.00	0.00
8,100.00	90.44	269.85	2,778.35	165.64	-5,568.34	5,567.88	0.00	0.00	0.00
8,200.00	90.44	269.85	2,777.58	165.38	-5,668.33	5,667.88	0.00	0.00	0.00
8,300.00	90.44	269.85	2,776.81	165.12	-5,768.33	5,767.88	0.00	0.00	0.00
8,400.00	90.44	269.85	2,776.04	164.86	-5,868.33	5,867.88	0.00	0.00	0.00
8,485.98	90.44	269.85	2,775.38	164.63	-5,954.30	5,953.85	0.00	0.00	0.00
8,500.00	90.44	269.85	2,775.28	164.59	-5,968.32	5,967.87	0.00	0.00	0.00
8,535.88	90.44	269.85	2,775.00	164.50	-6,004.20	6,003.75	0.00	0.00	0.00



Planning Report



<b>Database:</b>	WBDS_SQL_2	<b>Local Co-ordinate Reference:</b>	Well #10H
<b>Company:</b>	Spur Energy Partners, LLC	<b>TVD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Project:</b>	Eddy County, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3404.00usft (AKITA 57)
<b>Site:</b>	ROSE SOUTH	<b>North Reference:</b>	Grid
<b>Well:</b>	#10H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	PLAN #1		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
PLAT #10H SHL: 226i - plan hits target center - Point	0.00	0.00	0.00	0.00	0.00	608,956.20	512,401.00	32.6740305	-104.4273749
PLAN #10H KOP: 171 - plan hits target center - Point	0.00	0.00	1,702.54	118.57	136.63	609,074.77	512,537.63	32.6743567	-104.4269312
PLAT #10H BHL: 243i - plan hits target center - Point	0.00	0.00	2,775.00	164.50	-6,004.20	609,120.70	506,396.80	32.6744665	-104.4468887
PLAT #10H LTP: 243C - plan misses target center by 0.03usft at 8485.98usft MD (2775.38 TVD, 164.63 N, -5954.30 E) - Point	0.00	360.00	2,775.38	164.60	-5,954.30	609,120.80	506,446.70	32.6744669	-104.4467265
PLAT #10H FTP: 243C - plan hits target center - Point	0.00	360.00	2,815.00	178.10	-800.20	609,134.30	511,600.80	32.6745180	-104.4299760





Company: Spur Energy Partners, LLC  
 Project: Eddy County, NM (NAD 83 - NME)  
 Site: ROSE SOUTH  
 Well: #10H  
 Wellbore: Wellbore #1  
 Rig: AKITA 57  
 Design: PLAN #1 / 9:09, June 24 2021



WELL DETAILS: #10H

RKB = 20' @ 3404.00usft (AKITA 57)


	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
	0.00	0.00	608956.20	512401.00	32.6740305	-104.4273749

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
PLAT #10H SHL: 2260' FSL & 700' FWL	0.00	0.00	0.00	608956.20	512401.00	32.6740305	-104.4273749
PLAN #10H KOP: 1715.44' MD	1702.54	118.57	136.63	609074.77	512537.63	32.6743567	-104.4269312
PLAT #10H BHL: 2430' FSL & 50' FWL	2775.00	164.50	-6004.20	609120.70	506396.80	32.6744665	-104.4468887
PLAT #10H LTP: 2430' FSL & 100' FWL	2775.38	164.60	-5954.30	609120.80	506446.70	32.6744669	-104.4467265
PLAT #10H FTP: 2430' FSL & 100' FEL	2815.00	178.10	-800.20	609134.30	511600.80	32.6745180	-104.4299760

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	
3	733.94	8.68	49.05	732.28	21.50	24.77	2.00	49.049	-24.83	
4	1715.44	8.68	49.05	1702.54	118.57	136.63	0.00	0.000	-136.94	
5	2827.30	60.00	269.85	2638.26	179.31	-336.11	6.00	-141.969	335.64	
6	3027.30	60.00	269.85	2738.26	178.86	-509.32	0.00	0.000	508.85	
7	3331.71	90.44	269.85	2815.00	178.10	-800.20	10.00	0.000	799.73	
8	8485.98	90.44	269.85	2775.38	164.63	-5954.30	0.00	0.000	5953.85	
9	8535.88	90.44	269.85	2775.00	164.50	-6004.20	0.00	0.000	6003.75	









Azimuths to Grid North  
 True North: 0.05°  
 Magnetic North: 7.02°  
 Magnetic Field  
 Strength: 47667.6snT  
 Dip Angle: 60.18°  
 Date: 6/24/2021  
 Model: IGRF2020

PROJECT DETAILS: Eddy County, NM (NAD 83 - NME)

Geodetic System: US State Plane 1983  
 Datum: North American Datum 1983  
 Ellipsoid: GRS 1980  
 Zone: New Mexico Eastern Zone  
 System Datum: Mean Sea Level

**Disclaimer:**  
 All Plan Details, boundary lines and offset well location/ survey data is provided by customer and subject to customer approval.








# **Permian Drilling Hydrogen Sulfide Drilling Operations Plan Rose South 10H**

Open drill site. No homes or buildings are near the proposed location.

## **1. Escape**

Personnel shall escape upwind of wellbore in the event of an emergency gas release. Escape can take place through the lease road on the Southeast side of the location. Personnel need to move to a safe distance and block the entrance to location. If the primary route is not an option due to the wind direction, then a secondary egress route should be taken.

Secondary Briefing Area



WIND: Prevailing winds are from the Southwest

Secondary Egress

State of New Mexico  
 Energy, Minerals and Natural Resources Department

Submit Electronically  
 Via E-permitting

Oil Conservation Division  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

## NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

### Section 1 – Plan Description Effective May 25, 2021

**I. Operator:** SPUR ENERGY PARTNERS LLC **OGRID:** 328947 **Date:** 06 / 22 / 2021

**II. Type:**  Original  Amendment due to  19.15.27.9.D(6)(a) NMAC  19.15.27.9.D(6)(b) NMAC  Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
ROSE SOUTH 10H		3-7-19S-26E	2260' FSL 700' FWL	457 BBL/D	475 MCF/D	1829 BBL/D
ROSE SOUTH 50H		3-7-19S-26E	2280' FSL 700' FWL	356 BBL/D	556 MCF/D	1782 BBL/D

**IV. Central Delivery Point Name:** ROSE SOUTH CTB [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
ROSE SOUTH 10H		08/16/2021	08/23/2021	09/29/2021	10/18/2021	10/18/2021
ROSE SOUTH 50H		08/24/2021	08/31/2021	09/29/2021	10/18/2021	10/18/2021

**VI. Separation Equipment:**  Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:**  Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:**  Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.



**Section 2 – Enhanced Plan**

**EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

**IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

**X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

**XI. Map.**  Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system  will  will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator  does  does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

Attach Operator’s plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:**  Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

### Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.**  Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.**  Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	<i>Sarah Chapman</i>
Printed Name:	SARAH CHAPMAN
Title:	REGULATORY DIRECTOR
E-mail Address:	SCHAPMAN@SPUREPLLC.COM
Date:	06/22/2021
Phone:	832-930-8613
<b>OIL CONSERVATION DIVISION</b> <b>(Only applicable when submitted as a standalone form)</b>	
Approved By:	
Title:	
Approval Date:	
Conditions of Approval:	



## Natural Gas Management Plan – Attachment

VI. Separation equipment will be sized by construction engineering staff based on anticipated daily production to ensure adequate capacity.

VII. Spur Energy Partners LLC (“Spur”) will take the following actions to comply with the regulations listed in 19.15.27.8:

- A. Spur will maximize the recovery of natural gas by minimizing waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. Spur will ensure that our wells will be connected to a natural gas gathering system with sufficient capacity to transport natural gas.
- B. All drilling operations will be equipped with a rig flare at least 100 feet from the nearest surface hole location. Rig flare will be utilized to combust any natural gas that is brought to surface during normal operations. In the case of emergency, flaring volumes will be reported appropriately.
- C. During completion operations any natural gas brought to surface will be flared. Immediately following completion operations, wells will flow to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. If natural gas does not meet gathering pipeline specifications, Spur will flare for 60 days or until natural gas meets the pipeline specifications. Spur will ensure flare is properly sized and is equipped with an automatic igniter or continuous pilot. Gas samples will be taken twice per week and natural gas will be routed into a gathering system as soon as the pipeline specifications are met.
- D. Natural gas will not be flared with the exception of 19.15.27.8(D)(1-4). If there is no adequate takeaway for the separator gas, wells will be shut-in until that natural gas gathering system is available with exception of emergency or malfunction situations. Volumes will be reported appropriately.
- E. Spur will comply with performance standards pursuant to 19.15.27.8(E)(1-8). All equipment will be designed and sized to handle maximum pressures to minimize waste. Storage tanks constructed after May 25, 2021 will be equipped with an automatic gauging system that reduces venting of natural gas. Flare stacks installed or replaced after May 25, 2021 will be equipped with an automatic igniter or continuous pilot. Spur will conduct AVO inspections as described in 19.15.27.8(E)(5)(a) with frequencies specified in 19.15.27.8(E)(5)(b) and (c). All emergencies or malfunctions will be resolved as quickly and safely as possible to minimize waste.
- F. The volume of natural gas that is vented or flared as the result of an emergency or malfunction during drilling and/or completion operations will be estimated and reported accordingly. The volume of natural gas that is vented, flared or beneficially used during production operations, will be measured and reported accordingly. Spur will install equipment to measure the volume of natural gas flared from existing piping or a flowline piped from equipment such as high-pressure separators, heater treaters, or VRUs associated with a well or facility associated with a well authorized by an APD after May 25, 2021 that has an average daily production of less than 60,000 cubic feet of natural gas. If metering is not practicable due to circumstances such as low flow rate or low pressure venting or flaring, Spur will estimate the volume of flared or vented natural gas. Measuring equipment will conform to industry standards and will not be equipped with a manifold



that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing equipment.

VIII. For maintenance activities involving production equipment and compression, venting be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production equipment, the associated producing wells will be shut-in to eliminate venting. For maintenance of VRUs, all natural gas normally routed to the VRU will be routed to flare.