Received by OCD: 9/20/2021 2:03:45 PM

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: EAGLE 34 F FED

Sundry Print Report of 10

Well Location: T17S / R27E / SEC 34 / County or Parish/State: EDDY /

NM

Well Number: 11 Type of Well: OIL WELL Allottee or Tribe Name:

SENW /

Lease Number: NMLC064050A Unit or CA Name: Unit or CA Number:

US Well Number: 300152908400S1 Well Status: Producing Oil Well Operator: REDWOOD

OPERATING LLC

Accepted for record – NMOCD gc 9/21/2021

#### Notice of Intent

Type of Submission: Notice of Intent Type of Action Plug and Abandonment

Date Sundry Submitted: 07/22/2021 Time Sundry Submitted: 09:38

Date proposed operation will begin: 09/19/2021

Procedure Description: 1. Set 5 1/2" CIBP @ 1490. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 1490-1290'. 2. Spot 25 sx cmt @ 1130-930'. WOC & Tag (8 5/8" Shoe) 3. Spot 25 sx cmt @ 200' to surface. 4. Cut off well

head, verify cmt at surface, weld on Dry Hole Marker.

\* No Changes \*

#### Surface Disturbance

Is any additional surface disturbance proposed?: No

#### NOI Attachments

#### **Procedure Description**

Redwood\_Eagle\_34F\_Fed\_11\_Proposed\_WBD 20210722093845.pdf

Redwood\_Eagle\_34F\_Fed\_11\_Current\_WBD\_20210722093837.pdf

Released to Imaging: 9/22/2021 8:18:52 AM

Received by AGD: 2020/2034 2 03:45 PM

Well Location: T17S / R27E / SEC 34 /

SENW /

County or Parish/State: EDD Page 2 of 10

IM

Well Number: 11

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMLC064050A

Unit or CA Name:

Unit or CA Number:

US Well Number: 300152908400S1

Well Status: Producing Oil Well

Operator: REDWOOD OPERATING LLC

#### Conditions of Approval

#### Specialist Review

Eagle\_34\_F\_Fed\_11\_Sundry\_ID\_2509176\_20210807102434.pdf

#### **Operator Certification**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: ABIGAIL ANDERSON

Signed on: JUL 22, 2021 09:38 AM

Name: REDWOOD OPERATING LLC

Title: Regulatory

Street Address: PO BOX 13077

City: ODESSA

State: TX

Phone: (432) 580-7161

Email address: ABBYM@BCMANDASSOCIATES.COM

#### Field Representative

Representative Name: Cole Ponce

Street Address: PO Box 1370

City: Artesia

State: NM

Zip: 88211

Phone: (575)748-1288

Email address: ColePonce@mec.com

#### **BLM Point of Contact**

**BLM POC Name: LONG VO** 

**BLM POC Title:** Petroleum Engineer

**BLM POC Phone:** 5752345972

BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved Disposition Date: 08/07/2021

Signature: Long Vo Released to Imaging: 9/22/2021 8:18:52 AM

## PLUG AND ABANDONMENT CONDITIONS OF APPROVAL

OPERATOR'S NAME: Redwood Operating LLC

LEASE NO.: NMLC064050A WELL NAME & NO.: Eagle 34 F Fed 11

US Well Number: | 3001529084

LOCATION: Section 34, T.17 S., R.27 E., NMPM

COUNTY: | Eddy County, New Mexico

- 1. Set 5 1/2" CIBP @ 1490. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 1490-1290'.
- 2. Spot 25 sx cmt @ 1130-930'. WOC & Tag (8 5/8" Shoe)
- 3. Spot 25 sx cmt @ 200' to surface.
- 4. Cut off well head, verify cmt at surface, weld on Dry Hole Marker.

Approval Subject to General Requirements and Special Stipulations Attached

Redwood		Propose	d
Author: Well Name	Abby @ BCM Eagle 34F Fed	Well No.	#11
Field/Pool	Red Lake; Qn-GRBG-SA	API#:	30-015-29084
County	Eddy	Location:	Sec 34 T17S, R27E
State	New Mexico	÷	1650 FNL & 1650 FWL
Spud Date	11/23/1996	GL:	3553

Description	0.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOO
Surface Csg	8 5/8	J55	24#	1,078	12 1/4	500	0
Prod Csg	5 1/2	J55	15.5#	2,599	7 7/8	625	0

High Cave

Top
638
818
1170
1408
1446

F	01
3. Spot 25 sx cmt @ 200' to surface.	Zu Zu
	re
8 5/8 24# CSG @ 1,078 Hole Size: 12 1/4	
2. Spot 25 sx cmt @ 1130-930', WOC & Tag (8 5/8" Shoe)	
1 Set 5 1/2" CIPD C 4 125 C	
1. Set 5 1/2" CIBP @ 1490. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 1490-1290'.	
Perfs @ 1537-2339'	
5 1/2 15.5# CSG @ 2.599	
5 1/2 15.5# CSG @ 2,599 Hole Size: 7 7/8	

Released to Imaging: 9/22/2021 8:18:52 AM

Received by OGD: 9/20/2021 2:03:45 PM

#### BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

#### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with The cut off.
- The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD:



# United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 mu/koB'miq'makh



In Reply Refer To: 1310

### Reciamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to

- The Application for Permit to Drill or Reenter (APD, Form 3160-3). Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up from in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- Previous instruction had you waiting for a BLM specialist to inspect the location and provide you With recismation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation. equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5. Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify

- The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

CONDITIONS

Action 50319

#### **CONDITIONS**

Operator:	OGRID:
Redwood Operating LLC	330211
PO Box 1370	Action Number:
Artesia, NM 882111370	50319
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

#### CONDITIONS

Created By	Condition	Condition Date
gcordero	None	9/21/2021