

Well Name: BUENA SUERTE 30 G	Well Location: T26N / R11W / SEC 30 / NESE / 36.456543 / 108.038859	County or Parish/State: SAN JUAN / NM
Well Number: 1T	Type of Well: OTHER	Allottee or Tribe Name: EASTERN NAVAJO
Lease Number: I149IND7971	Unit or CA Name:	Unit or CA Number:
US Well Number: 300453203300S1	Well Status: Producing Gas Well	Operator: DJR OPERATING LLC

Subsequent Report

Type of Submission: Subsequent Report	Type of Action: Plug and Abandonment
Date Sundry Submitted: 04/28/2021	Time Sundry Submitted: 09:28
Date Operation Actually Began: 04/09/2021	

Actual Procedure: The subject well was Plugged & Abandoned on 04/09/2021 per the attached detailed As Plugged Wellbore Diagram and Marker.

SR Attachments

Actual Procedure

- Buena_Suerte_30G_1T_PXA_Marker_20210428092634.pdf
- Buena_Suerte_30G_1T_EOWR___AsPlugged_WBD_20210428092634.pdf

Well Name: BUENA SUERTE 30 G	Well Location: T26N / R11W / SEC 30 / NESE / 36.456543 / 108.038859	County or Parish/State: SAN JUAN / NM
Well Number: 1T	Type of Well: OTHER	Allottee or Tribe Name: EASTERN NAVAJO
Lease Number: I149IND7971	Unit or CA Name:	Unit or CA Number:
US Well Number: 300453203300S1	Well Status: Producing Gas Well	Operator: DJR OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: DACYE SHULL	Signed on: APR 28, 2021 09:27 AM
Name: DJR OPERATING LLC	
Title: Regulatory Technician	
Street Address: 1 ROAD 3263	
City: AZTEC	State: NM
Phone: (505) 632-3476	
Email address: DSHULL@DJRLLC.COM	

Field Representative

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: WILLIAM F TAMBEKOU	BLM POC Title: PETROLEUM ENGINEER
BLM POC Phone: 7192698500	BLM POC Email Address: wtambekou@blm.gov
Disposition: Accepted	Disposition Date: 05/04/2021
Signature: William Max Tambekou	

DJR Operating, LLC
Buena Suerte 30G 1T
API # 30-045-32033
NE/SE, Unit I, Sec. 30, T26N, R11W
San Juan County, NM



P&A End of Well Report
DJR Operating, LLC
Buena Suerte 30G 1T
API: 30-045-32033
NESE I-30-26N-11W
San Juan County, NM

Spud Date: 03/16/2006

Plugged Date: 04/09/2021

4/8/21: Set CR at 1200'. PT casing, Good test. Plugs 1 and 2: Fruitland perms: Mix and pump 15 sx class G cement through CR. Sting out and place 15 sx Class G cement above CR. Tag at 1060'.

4/9/21: Plug 3: From top of plug 2 at 1060', mix and place 130 sx Class G cement to surface. TOOH. Plug 4: Top off 5 1/2" casing with 16 sx Class G cement. TOC in casing = surface, annulus = 32'. Install P&A marker. Top off annulus and cellar with 21 sx Class G cement.

All cement used: Class G cement mixed at 15.8 ppg, 1.15 yield.

BLM Representative onsite to witness: Derrick McCuller

DJR Operating, LLC P&A End of Well Report

Buena Suerte 30G 1T

API # 30-045-32033

NE/SE Unit I Sec.30, T26N, R11W

San Juan County, NM

GL 6160'

KB 6173'

Spud Date 3/16/2006

SURF CSG

Hole size 12.25"

Csg Size: 8.625"

Wt: 24#

Grade: K-55

ID: 8.097"

Depth 134'

casing cap ft³/ft: .3575"

TOC: Circ to surf

FORMATION TOPS

Nacimiento

Ojo Alamo 286'

Kirtland 399'

Fruitland 1120'

Pictured Cliffs 1274'

PROD CSG

Hole size 7.875"

Csg Size: 5.5"

Wt: 15.5#

Grade: J-55

ID: 4.950"

Depth 1413'

casing cap ft³/ft: 0.1336

sq/Csq capacity ft³/ft 0.1926

TOC: Circ to surf

Fruitland Coal perms
1234'-1254'

PBTD
TD 1425'

4-9-2021: TOC in casing = surface, annulus = 32'. Install P&A marker. Top off annulus and cellar with 21 sx Class G cement.

4-9-2021: Plug 4: Top off 5 1/2" casing with 16 sx Class G cement.

4-9-2021: Plug 3: From top of plug 2 at 1060', mix and place 130 sx Class G cement to surface. TOOH.

4-8-2021: Plugs 1 and 2: Fruitland perms: Mix and pump 15 sx class G cement through CR. Sting out and place 15 sx Class G cement above CR. Tag at 1060'

4-8-2021: Set CR at 1200'. PT casing, Good test.

All cement used was class G mixed at 15.8 ppg, yield 1.15

Regulatory representative, Derrick McCuller, BLM

GPS Coordinates: Lat: 36.45657110027969, Lng: -108.03887134417892

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 56504

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 56504
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	11/3/2021