

<b>Well Name:</b> BISTI GALLUP 22	<b>Well Location:</b> T25N / R12W / SEC 22 / SWSE / 36.38127 / 108.09556	<b>County or Parish/State:</b> SAN JUAN / NM
<b>Well Number:</b> 15	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM25449	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 3004534132	<b>Well Status:</b> Oil Well Shut In	<b>Operator:</b> DJR OPERATING LLC

### Subsequent Report

**Type of Submission:** Subsequent Report

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 02/10/2021

**Time Sundry Submitted:** 08:54

**Date Operation Actually Began:** 12/11/2020

**Actual Procedure:** The subject well was Plugged & Abandoned on 12/11/20 per the attached End of Well Report, Wellbore Diagram, and Marker.

### SR Attachments

#### Actual Procedure

Bisti\_Gallup\_22\_\_15\_PA\_Marker\_20210210085445.pdf

Bisti\_Gallup\_22\_\_15\_EOWR\_AsPlugged\_WBD\_20210210085445.pdf

### BLM Point of Contact

**BLM POC Name:** WILLIAM F TAMBEKOU

**BLM POC Title:** PETROLEUM ENGINEER

**BLM POC Phone:** 7192698500

**BLM POC Email Address:** wtambekou@blm.gov

**Disposition:** Accepted

**Disposition Date:** 04/01/2021

**Signature:** William Max Tambekou

**DJR Operating, LLC  
Bisti Gallup 22-15  
API # 30-045-34132  
SW/SE, Unit O, Sec. 22, T25N, R12W  
San Juan County, NM**



P&A End of Well Report  
DJR Operating, LLC  
API: 30-045-34132  
SWSE O-22-25N-12W  
San Juan County, NM

Spud Date: 11/25/2007

Plugged Date: 12/11/2020

12/01/20: Plug 1: Gallup: TIH with 2 3/8" tbg, mix and pump balanced plug of 60 sx class G + 2% CaCl<sub>2</sub> from 4840' , tagged plug at 4490'. PT casing, did not test, no flow at BH.

Plug 2: Mancos: Mix and pump 20 sx class G cement plug from 3790'. WOC. 12-10-2020, tagged plug at 3570'. PT casing, did not test, no flow at BH.

12/10/20: Plug 3: Mesaverde: TIH to 2235', mix and pump balanced plug of 24 sx class G + 2% CaCl<sub>2</sub> from 2235'. WOC. Tagged plug at 2058'. PT casing, did not test.

Plug 4: Chacra, Mix and pump balanced plug of 24 sx class G cement from 1512' . WOC ON, 12-11-2020: tagged plug at 1306'. PT casing, did not test.

12/11/20: Plug 5: Pictured Cliffs, Fruitland, Kirtland: Mix and pump balanced plug of 85 sx class G + 2% CaCl<sub>2</sub> from 1171'. WOC. Tagged plug at 525'. PT casing to 650 psi, good test.

Plug 6: 525' to surface, mix and pump 60 sx balanced plug of class G cement from 525'.  
TOC; Casing= 40', annulus = 9'. Top off plug: Pumped 25 sx class G to top off.

All cement used: Class G cement mixed at 15.8 ppg. 1.15 yield.

BLM Representative onsite to witness: Darin Halliburton

**P&A End of Well Report  
DJR Operating, LLC  
Bisti Gallup 22-15**

API # 30-045-34132  
SW/SE, Unit O, Sec 22, T25N, R12W  
San Juan County, New Mexico

GL 6346'  
KB NA  
Spud Date 11/25/2007

**SURF CSG**

Hole size 12.25"  
Csg Size: 8.625"  
Wt: 24#  
Grade: J-55  
ID: 8.097"  
Depth 390'  
Csg cap ft3: 0.3576  
TOC: Circ  
surf

**FORMATION TOPS**

Nacimiento	Surface
Ojo Alamo	N/A
Kirtland	567'
Fruitland Coal	851'
Pictured Cliffs	1121'
Lewis	1280'
Chacra	1455'
Mesaverde	2185'
Mancos	3720'
Gallup	4623'

**PROD CSG**

Hole size 7.875"  
Csg Size: 5.5"  
Wt: 15.5#  
Grade: J-55  
ID: 4.95"  
Depth 5162'  
Csg cap ft3: 0.1336  
Csg/Csg Ann ft3: 0.1926  
Csg/OH cap ft3: 0.1732  
TOC: Circ  
surf

12-20-2007: Perfed holes at 600', sqzd with 200 sx, 12 bbls cement to surface.

Perfs  
4751'-4833'

5121'  
5170'

12-11-2020: TOC; Casing= 40', annulus = 9'.  
Top off plug: Pumped 25 sx class G to top off.

**Cut off WH**

12-11-2020: Plug 6: 525' to surface, mix and pump 60 sx balanced plug of class G cement from 525'.

12-11-2020: Plug 5: Pictured Cliffs, Fruitland, Kirtland: Mix and pump balanced plug of 85 sx class G + 2% CaCl<sub>2</sub> from 1171'. WOC. Tagged plug at 525'. PT casing to 650 psi, good test.

12-10-2020: Plug 4: Chacra, Mix and pump balanced plug of 24 sx class G cement from 1512'. WOC ON, 12-11-2020: tagged plug at 1306'. PT casing, did not test.

12-10-2020: Plug 3: Mesaverde: TIH to 2235', mix and pump balanced plug of 24 sx class G + 2% CaCl<sub>2</sub> from 2235'. WOC. Tagged plug at 2058'. PT casing, did not test.

DV Tool 3483'

12-01-2020: Plug 2: Mancos: Mix and pump 20 sx class G cement plug from 3790'. WOC. 12-10-2020, tagged plug at 3570'. PT casing, did not test, no flow at BH.

12-01-2020: Plug 1: Gallup: TIH with 2 3/8" tbg, mix and pump balanced plug of 60 sx class G + 2% CaCl<sub>2</sub> from 4840', tagged plug at 4490'. PT casing, did not test, no flow at BH.

All cement used was class G cement, mixed at 15.8 ppg, yield 1.15  
Regulatory representative on site, Darin Halliburton, BLM  
GPS coordinates; Lat: 36.38129846658558, Lng: -108.09552806429565

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 57742

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 57742
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	11/4/2021