

Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM  
 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised July 18, 2013

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-025-30354
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2516
7. Lease Name or Unit Agreement Name State -9-
8. Well Number 1
9. OGRID Number
10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
 DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
 PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
 Rover Petroleum, LLC

3. Address of Operator  
 17304 Preston Rd. Ste 300 Dallas, TX 75252

4. Well Location

Unit Letter G : 2310 feet from the N line and 1980 feet from the E line  
 Section 9 Township 17-S Range 33-E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
 DOWNHOLE COMMINGLE ☐  
 CLOSED-LOOP SYSTEM ☐  
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS ☐ P AND A ☐  
 CASING/CEMENT JOB ☐  
 OTHER: ☐

1. SET CIBP @ 4,358' - CIRCULATE WELL W/ 67 BBLS MLF - TEST CSG
2. SPOT 25 SX CLASS C CMT @ 4,358' - 4,140'
3. SPOT 25 SX CLASS C CMT @ 3,797' - 3,497' WOC & Tag
4. SPOT 25 SX CLASS C CMT @ 2,845' - 2,550' WOC & TAG
5. PERF @ 1,680' - SQZ 85 SX CLASS C CMT FROM 1,680' - 1,400' WOC & TAG
6. PERF @ 404' - SQZ 120 SX CLASS C MCT FROM 404' TO SURFACE/ VERIFY

4" diameter 4' tall Above Ground Marker

SEE ATTACHED CONDITIONS  
 OF APPROVAL

hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Operations Supervisor DATE 03/08/2022

Type or print name Johnny Rodriguez E-mail address: jrodriguez@brigade.energy PHONE: (432) 248-2019

For State Use Only

APPROVED BY:  TITLE Compliance Officer A DATE 3/15/22

Conditions of Approval (if any): 575-263-6633

## **Rover Petroleum, LLC**

### **P&A Procedure**

**Well Name:** State -9- # 1      **API#:** 30-025-30354

1. Notify OCD Regulatory 24 hours prior to commencing work.
2. MIRU / POOW W/ RODS & TUBING
3. SET CIBP @ 4,358' – Circulate well w/ 67 bbls MLF – Test Casing
4. Spot 25 sx Class C cmt @ 4,358' – 4,140'
5. Spot 25 sx Class C cmt @ 3,797' – 3,497'
6. Spot 25 sx Class C cmt @ 2,845' – 2,550' Woc & Tag
7. Perf @ 1,680' – Sqz 85 sx Class C cmt from 1,680' – 1,400' Woc & Tag
8. Perf @ 404' – Sqz 120 sx Class C cmt from 404' to Surface/Verify
9. Cut Wellhead <sup>9'</sup> below ground level & install dry hole marker.

RKB @ \_\_\_\_\_

GL @ 4189DATE 5-92LEASE & WELL NO. State 9-1**TAMARACK PETROLEUM  
WELL BORE SKETCH**Legal Description 2310' FNL AND 1980' FELSec 9 T-17-S, R-33-E LGA N.M.Field MALJAMAR

Status \_\_\_\_\_ BOPD \_\_\_\_\_ BWPD \_\_\_\_\_ GOR \_\_\_\_\_

Csg. 8 5/8" 24 # GR. @ 354' TOC @ SFC ' 200 Sx,  
4 1/2" 10-5 # K-55 GR. @ 4600' TOC @ 2200' (temp.)

Tbg. \_\_\_\_\_ "EUE \_\_\_\_\_ # \_\_\_\_\_ GR. @ \_\_\_\_\_' SNG \_\_\_\_\_'

Pkr. \_\_\_\_\_ @ \_\_\_\_\_' other \_\_\_\_\_ @ \_\_\_\_\_'

**Stimulation History:**

	Interval	Date	Type	Gals.	#Sd.	MP	ISDP	IR	Downt.
1.	<u>4408-80</u>	<u>5-88</u>	<u>15%</u>	<u>1500</u>		<u>3300</u>		<u>2</u>	
2.				<u>65,000</u>	<u>12200</u>	<u>3800</u>	<u>3300</u>	<u>11.3</u>	<u>C66</u>
3.									
4.									

Hole/Casing Condition \_\_\_\_\_

Workover Proposal \_\_\_\_\_

8 5/8"  
24 #  
@ 354'

**Tbg. Details**

O-4362

2 3/8" 4.7 #

J-55 + bog

140 jts 2 3/8"

SN

1 jt 2 3/8"

2 3/8" x 4' perf sub

BPMA

1 jt 2 3/8"

**Rod Details**

134 3/4"

43 5/8"

1" x 6' gas anchor

2" x 1 1/4" x 16' pump

4408

4480

Perfs - Grayburg

PBTD

45534 1/2" 10.5 # @ 4600'

Eng. \_\_\_\_\_

WI \_\_\_\_\_

WELL NAME State -9- #1

BRIGADE

Oil Field Services


LOCATION G: 2310 FNL, 1980 FEL  
Sec. 9, T-175, R 33-E (Lea County)

GL \_\_\_\_\_ KB \_\_\_\_\_

API # 30 - 025 - 30354

CASING PROGRAM / T.O.C.

8 5/8" - 24 #	354'	Surface
4 1/2" - 10.5 #	4,600'	2,200 TS



- Perf @ 404' - 592/205x  
cmt from 404' to surface.

- Perf @ 1,680' - 592.855x cmt  
from 1,680' - 1,400' woc & Tag.

- Spot 255x cmt @ 2,545'.  
2,550' woc & Tag.

- Spot 255x cmt @ 3,797' - 3,497'

- CIBPE 4,358' - Circulate well w/ 6766's MLF - Test csg -  
spot 255x cmt 4,358' - 4,140'

## TOPS

T. Anhy - 1,450'

T. Salt - 1,630'

B. Salt - 2,600'

T. Yates - 2,795'

T. Queen - 3,747'

T. Grayburg - 4,190'

Perfs

4,408' - 4,480'



**CONDITIONS OF APPROVAL  
FOR PLUGGING AND ABANDONMENT  
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

**Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) Potash---(In the R-111-P Area (Potash Mine Area),  
A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing.

### **DRY HOLE MARKER REQUIREMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

### **SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

### **SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION**

## **Rover Petroleum, LLC**

### **P&A Procedure**

**Well Name:** State -9- # 1      **API#:** 30-025-30354

1. Notify OCD Regulatory 24 hours prior to commencing work.
2. MIRU / POOW W/ RODS & TUBING
3. SET CIBP @ 4,358' – Circulate well w/ 67 bbls MLF – Test Casing
4. Spot 25 sx Class C cmt @ 4,358' – 4,140'
5. Spot 25 sx Class C cmt @ 3,797' – 3,497'
6. Spot 25 sx Class C cmt @ 2,845' – 2,550' Woc & Tag
7. Perf @ 1,680' – Sqz 85 sx Class C cmt from 1,680' – 1,400' Woc & Tag
8. Perf @ 404' – Sqz 120 sx Class C cmt from 404' to Surface/Verify
9. Cut Wellhead 1' below ground level & install dry hole marker.

RKB @ \_\_\_\_\_

GL @ 4189DATE 5-92LEASE & WELL NO. State 9-1**TAMARACK PETROLEUM  
WELL BORE SKETCH**Legal Description 2310' FNL AND 1980' FELSec 9 T-17-S, R-33-E LGA N.M.Field MALJAMAR

Status \_\_\_\_\_ BOPD \_\_\_\_\_ BWPD \_\_\_\_\_ GOR \_\_\_\_\_

Csg. 8 5/8" 24 # GR. @ 354' TOC @ SFC ' 200 Sx,  
4 1/2" 10-5 # K-55 GR. @ 4600' TOC @ 2200' (temp.)

Tbg. \_\_\_\_\_ "EUE \_\_\_\_\_ # \_\_\_\_\_ GR. @ \_\_\_\_\_' SNG \_\_\_\_\_'

Pkr. \_\_\_\_\_ @ \_\_\_\_\_' other \_\_\_\_\_ @ \_\_\_\_\_'

**Stimulation History:**

	Interval	Date	Type	Gals.	#Sd.	MP	ISDP	IR	Downt.
1.	<u>4408-80</u>	<u>5-88</u>	<u>15%</u>	<u>1500</u>		<u>3300</u>		<u>2</u>	
2.				<u>65,000</u>	<u>12200</u>	<u>3800</u>	<u>3300</u>	<u>11.3</u>	<u>C66</u>
3.									
4.									

Hole/Casing Condition \_\_\_\_\_

Workover Proposal \_\_\_\_\_

8 5/8"  
24 #  
@ 354'

**Tbg. Details**

O-4362

2 3/8" 4.7 #

J-55 + bog

140 jts 2 3/8"

SN

1 jt 2 3/8"

2 3/8" x 4' perf sub

BPMA

1 jt 2 3/8"

**Rod Details**

134 3/4"

43 5/8"

1" x 6' gas anchor

2" x 1 1/4" x 16' pump

4408

4480

Perfs - Grayburg

PBTD

45534 1/2" 10.5 # @ 4600'

Eng. \_\_\_\_\_

WI \_\_\_\_\_



# BRIGADE


Figure 1. Schematic representation of the experimental design. The subjects were divided into two groups: the control group and the experimental group. The control group was divided into two subgroups: the control group and the experimental group. The experimental group was divided into two subgroups: the control group and the experimental group. The control group was divided into two subgroups: the control group and the experimental group. The experimental group was divided into two subgroups: the control group and the experimental group.

GL \_\_\_\_\_ KB \_\_\_\_\_

RF # 30 - 025 - 30354

CASING PROGRAM / T.O.C

8 <sup>5</sup> / <sub>8</sub> " - 24 #	354'	Surface
4 <sup>1</sup> / <sub>2</sub> " - 10.5 #	4,600'	2,200 TS



- Perf @ 404' - 592/209x  
cm + from 404' to surface.

- Perf @ 1,680' - Sq. 85 spcmt  
from 1,680' - 1,400' was d Tgs.

- Spot 25 5X cm at 2,545'.  
2,550' WOC & Tog.

- Spot 25 sx cmnt @ 3,797' - 3,497'

-CIBP4,358' - Circulate well w/ 6766's MLF-Test csg -  
spot 255x cm + 4,358' - 4,140'

## TOPS

T. Anby - 1,450'

T. Salt - 11630

B. 54 H - 2,600'

T. Yates - 2,795'

T. Queen - 3,747'

T. Grayburg - 4,190'

Perfs  
4,408' - 4,480'

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

COMMENTS  
  
Action 89100

COMMENTS

Operator: ROVER OPERATING, LLC 17304 Preston Road Dallas, TX 75252	OGRID: 371484
	Action Number: 89100
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	3/15/2022

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 89100

CONDITIONS

Operator: ROVER OPERATING, LLC 17304 Preston Road Dallas, TX 75252	OGRID: 371484
	Action Number: 89100
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	See attached conditions of approval	3/15/2022