

| Well Name    | Well Number | US Well Number | Lease Number | Case Number | Operator |
|--------------|-------------|----------------|--------------|-------------|----------|
| CORRAL GORGE | 31H         | 3001547212     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 34H         | 3001547201     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 35H         | 3001547205     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 311H        | 3001547215     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 36H         | 3001547206     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 32H         | 3001547214     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 37H         | 3001547207     | NMNM15303    | NMNM15303   | OXY USA  |
| CORRAL GORGE | 38H         | 3001547208     | NMNM15303    | NMNM15303   | OXY USA  |

Notice of Intent

Sundry ID: 2651969

Type of Submission: Notice of Intent

Type of Action: Other

Date Sundry Submitted: 01/11/2022

Time Sundry Submitted: 10:00

Date proposed operation will begin: 02/01/2022

Procedure Description: OXY USA Inc. respectfully requests approval to amend the AAPD for the subject batch of wells. See the attached revised BOP Break testing language and additional casing specification sheet for reference.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

CorralGorgeBulkDrillingSundryAttachment\_1\_11\_22\_20220111095821.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

**Operator Electronic Signature:** LESLIE REEVES

**Signed on:** JAN 11, 2022 09:58 AM

**Name:** OXY USA INCORPORATED

**Title:** Advisor Regulatory

**Street Address:** 5 GREENWAY PLAZA, SUITE 110

**City:** HOUSTON                      **State:** TX

**Phone:** (713) 497-2492

**Email address:** LESLIE\_REEVES@OXY.COM

Field Representative

**Representative Name:**

**Street Address:**

**City:**                                      **State:**                                      **Zip:**

**Phone:**

**Email address:**

BLM Point of Contact

**BLM POC Name:** CHRISTOPHER WALLS

**BLM POC Title:** Petroleum Engineer

**BLM POC Phone:** 5752342234

**BLM POC Email Address:** cwalls@blm.gov

**Disposition:** Approved

**Disposition Date:** 03/04/2022

**Signature:** Chris Walls

**Bulk Sundry – Corral Gorge CC**

| Well Name                           | API Number   |
|-------------------------------------|--------------|
| Corral Gorge 12_13 Federal Com 311H | 30-015-47215 |
| Corral Gorge 12_13 Federal Com 31H  | 30-015-47212 |
| Corral Gorge 12_13 Federal Com 32H  | 30-015-47214 |
| Corral Gorge 12_13 Federal Com 34H  | 30-015-47201 |
| Corral Gorge 12_13 Federal Com 35H  | 30-015-47205 |
| Corral Gorge 12_13 Federal Com 36H  | 30-015-47206 |
| Corral Gorge 12_13 Federal Com 37H  | 30-015-47207 |
| Corral Gorge 12_13 Federal Com 38H  | 30-015-47208 |

**Additional Casing Connection Attachments:**

- TNSWedge461\_5.500in\_20.00#\_P110CY

**BOP Break Testing Request – Verbiage Update**

Oxy requests permission to adjust the BOP break testing requirements as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill an intermediate section where ICP is set into the third Bone Spring or shallower.

If the kill line is broken prior to skid, two tests will be performed.

- 1) Wellhead flange, co-flex hose, kill line connections and upper pipe rams
- 2) Wellhead flange, HCR valve, check valve, upper pipe rams

If the kill line is not broken prior to skid, only one test will be performed.

- 1) Wellhead flange, co-flex hose, check valve, upper pipe rams



5.500" 20.00 lb/ft P110-CY

TenarisHydril Wedge 461™ Matched Strength



Special Data Sheet

TH DS-20.0359

12 August 2020

Rev 00

|                    |           |                |           |                      |                  |
|--------------------|-----------|----------------|-----------|----------------------|------------------|
| Nominal OD         | 5.500 in. | Wall Thickness | 0.361 in. | Grade                | P110-CY          |
| Min Wall Thickness | 87.5%     | Type           | CASING    | Connection OD Option | MATCHED STRENGTH |

Pipe Body Data

| Geometry                |              |                  | Performance  |                     |                |
|-------------------------|--------------|------------------|--------------|---------------------|----------------|
| Nominal OD              | 5.500 in.    | Nominal ID       | 4.778 in.    | Body Yield Strength | 641 x 1000 lbs |
| Nominal Weight          | 20.00 lbs/ft | Wall Thickness   | 0.361 in.    | Internal Yield      | 12640 psi      |
| Standard Drift Diameter | 4.653 in.    | Plain End Weight | 19.83 lbs/ft | SMYS                | 110000 psi     |
| Special Drift Diameter  | N/A          | OD Tolerance     | API          | Collapse Pressure   | 11110 psi      |

Connection Data

| Geometry             |                  | Performance            |                | Make-up Torques           |              |
|----------------------|------------------|------------------------|----------------|---------------------------|--------------|
| Matched Strength OD  | 6.050 in.        | Tension Efficiency     | 100%           | Minimum                   | 17000 ft-lbs |
| Make-up Loss         | 3.775 in.        | Joint Yield Strength   | 641 x 1000 lbs | Optimum                   | 18000 ft-lbs |
| Threads per in.      | 3.40             | Internal Yield         | 12640 psi      | Maximum                   | 21600 ft-lbs |
| Connection OD Option | MATCHED STRENGTH | Compression Efficiency | 100%           | Operational Limit Torques |              |
| Coupling Length      | 7.714 in.        | Compression Strength   | 641 x 1000 lbs | Operating Torque          | 32000 ft-lbs |
|                      |                  | Bending                | 92 °/100 ft    | Yield Torque              | 38000 ft-lbs |
|                      |                  | Collapse               | 11110 psi      | Buck-On Torques           |              |
|                      |                  |                        |                | Minimum                   | 21600 ft-lbs |
|                      |                  |                        |                | Maximum                   | 23100 ft-lbs |

Notes

\*If you need to use torque values that are higher than the maximum indicated, please contact a local Tenaris technical sales representative

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 87332

CONDITIONS

|                                                                    |                                                      |
|--------------------------------------------------------------------|------------------------------------------------------|
| Operator:<br>OXY USA INC<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>16696                                      |
|                                                                    | Action Number:<br>87332                              |
|                                                                    | Action Type:<br>[C-103] NOI Change of Plans (C-103A) |

CONDITIONS

|            |           |                |
|------------|-----------|----------------|
| Created By | Condition | Condition Date |
| jagarcia   | None      | 3/28/2022      |