

Well Name	Well Number	US Well Number	Lease Number	Case Number	Operator
CORRAL GORGE	31H	3001547212	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	34H	3001547201	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	35H	3001547205	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	311H	3001547215	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	36H	3001547206	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	32H	3001547214	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	37H	3001547207	NMNM15303	NMNM15303	OXY USA
CORRAL GORGE	38H	3001547208	NMNM15303	NMNM15303	OXY USA

Notice of Intent

Sundry ID: 2651969

Type of Submission: Notice of Intent

Date Sundry Submitted: 01/11/2022

Date proposed operation will begin: 02/01/2022

Type of Action: Other

Time Sundry Submitted: 10:00

Procedure Description: OXY USA Inc. respectfully requests approval to amend the AAPD for the subject batch of wells. See the attached revised BOP Break testing language and additional casing specification sheet for reference.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

CorralGorgeBulkDrillingSundryAttachment_1_11_22_20220111095821.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: LESLIE REEVES

Signed on: JAN 11, 2022 09:58 AM

Name: OXY USA INCORPORATED

Title: Advisor Regulatory

Street Address: 5 GREENWAY PLAZA, SUITE 110

City: HOUSTON **State:** TX

Phone: (713) 497-2492

Email address: LESLIE_REEVES@OXY.COM

Field Representative

Representative Name:

Street Address:

City: **State:** **Zip:**

Phone:

Email address:

BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234

BLM POC Email Address: cwalls@blm.gov

Disposition: Approved

Disposition Date: 03/04/2022

Signature: Chris Walls

Bulk Sundry – Corral Gorge CC

Well Name	API Number
Corral Gorge 12_13 Federal Com 311H	30-015-47215
Corral Gorge 12_13 Federal Com 31H	30-015-47212
Corral Gorge 12_13 Federal Com 32H	30-015-47214
Corral Gorge 12_13 Federal Com 34H	30-015-47201
Corral Gorge 12_13 Federal Com 35H	30-015-47205
Corral Gorge 12_13 Federal Com 36H	30-015-47206
Corral Gorge 12_13 Federal Com 37H	30-015-47207
Corral Gorge 12_13 Federal Com 38H	30-015-47208

Additional Casing Connection Attachments:

- TNSWedge461_5.500in_20.00#_P110CY

BOP Break Testing Request – Verbiage Update

Oxy requests permission to adjust the BOP break testing requirements as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill an intermediate section where ICP is set into the third Bone Spring or shallower.

If the kill line is broken prior to skid, two tests will be performed.

- 1) Wellhead flange, co-flex hose, kill line connections and upper pipe rams
- 2) Wellhead flange, HCR valve, check valve, upper pipe rams

If the kill line is not broken prior to skid, only one test will be performed.

- 1) Wellhead flange, co-flex hose, check valve, upper pipe rams



5.500" 20.00 lb/ft P110-CY
TenarisHydril Wedge 461™ Matched
Strength



Special Data Sheet
TH DS-20.0359
12 August 2020
Rev 00

Nominal OD	5.500 in.	Wall Thickness	0.361 in.	Grade	P110-CY
Min Wall Thickness	87.5%	Type	CASING	Connection OD Option	MATCHED STRENGTH

Pipe Body Data

Geometry			Performance		
Nominal OD	5.500 in.	Nominal ID	4.778 in.	Body Yield Strength	641 x 1000 lbs
Nominal Weight	20.00 lbs/ft	Wall Thickness	0.361 in.	Internal Yield	12640 psi
Standard Drift Diameter	4.653 in.	Plain End Weight	19.83 lbs/ft	SMYS	110000 psi
Special Drift Diameter	N/A	OD Tolerance	API	Collapse Pressure	11110 psi

Connection Data

Geometry		Performance		Make-up Torques	
Matched Strength OD	6.050 in.	Tension Efficiency	100%	Minimum	17000 ft-lbs
Make-up Loss	3.775 in.	Joint Yield Strength	641 x 1000 lbs	Optimum	18000 ft-lbs
Threads per in.	3.40	Internal Yield	12640 psi	Maximum	21600 ft-lbs
Connection OD Option	MATCHED STRENGTH	Compression Efficiency	100%	Operational Limit Torques	
Coupling Length	7.714 in.	Compression Strength	641 x 1000 lbs	Operating Torque	32000 ft-lbs
		Bending	92 °/100 ft	Yield Torque	38000 ft-lbs
		Collapse	11110 psi	Buck-On Torques	
				Minimum	21600 ft-lbs
				Maximum	23100 ft-lbs

Notes

*If you need to use torque values that are higher than the maximum indicated, please contact a local Tenaris technical sales representative

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 87333

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 87333
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
jagarcia	None	3/28/2022