

Submit a Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-21631
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name TRACY D
8. Well Number 001
9. OGRID Number 192463
10. Pool name or Wildcat LA HUERTA; STRAWN (GAS)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	
2. Name of Operator OXY USA WTP LIMITED PARTNERSHIP	
3. Address of Operator P.O. BOX 4294 HOUSTON, TX 77210	
4. Well Location	
Unit Letter K : 1980 feet from the SOUTH line and 1980 feet from the WEST line	
Section 33 Township 21S Range 27E NMPM County EDDY	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input checked="" type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>	
--	--	--	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

THE PA JOB SUMMARY AND FINAL WELLBORE DIAGRAM ARE ATTACHED FOR THE SUBJECT WELL.

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stephen Janacek TITLE REGULATORY ENGINEER DATE 4/28/22

Type or print name STEPHEN JANACEK E-mail address: STEPHEN_JANACEK@OXY.COM PHONE: 713-493-1986
For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 5/2/2022
Conditions of Approval (if any):

Tracy D #1 (30-015-21631)

PA Job Summary- 4/9/22- 4/20/22

RU WL / RIH W GR , TAG TOP OF PKR @ 11,060' TOH AND
RAN BACK IN , SET CIBP @ 11,055' RD WL.

SPOT 25 SXS CLASS 'H' CMT 15.6#, 1.18 YIELD, 3.09 MIX,
6.21 SLURRY , 39.7 DISPLACEMENT.

WELLBORE 0 PSI / TAG TOC @ 10,768' , TEST CSG @ 500
PSI , HELD GOOD / SPOT 25 SXS CLASS 'H' CMT @ 10,427'
, 15.6#, 1.18 YIELD , 3.09 MIX, 6.2 SLURRY / LD 14 JTS 2
3/8 L-80 TBG TO SPOT 40 SXS CLASS 'H' CMT @ 10,014',
15.6#, 1.18 YIELD , 4.9 MIX, 9.93 SLURRY / LD 42 JTS 2 3/8
L-80 TBG TO SPOT 25 SXS CLASS 'H' CMT @ 8740' , 15.6#,
1.18 YIELD, 3.09 MIX, 6.2 SLURRY / LD 70 JTS 2 3/8 L-80
TBG , EOT @ 6530'

TBG 0 PSI / CSG 0 PSI / INT 50 PSI / SPOT 25 SXS CLASS
'H' CMT , 15.6# , 1.18 YIELD, 3.09 MIX, 6.2 SLURRY 22
DISPLACEMENT.

LD 44 JTS 2 3/8 L-80 TBG ON RACKS / STOOD BACK 164
JTS 2 3/8.

RIH W 5.5 AD-1 PKR FOLLOWED BY 148 JTS 2 3/8 L-80
TBG / PKR SET @ 4646'.

RU WL PICK UP CCL 1-9/16 GUN 3.5 GRAM CHARGE .2"
ENTRY HOLE 12" PENETRATION WENT DOWN TO
PERFORATE @ 5286' RD WL.

INJECTION RATE OF 2 BPM W 500 PSI,
SQUEEZE 40 SXS CLASS 'C' CMT, 14.8# , 1.32 YIELD, 6
MIX, 9.3 SLURRY , 26.8 DISPLACEMENT / ISIP 350 PSI.

TBG 0 PSI / CSG 0 PSI / RIH W TBG TO TAG TOC @ 5023' .
POOH , LD 82 JTS 2 3/8 L-80 TBG ON RACKS.
PICK UP CCL 1-9/16 GUN 3.5 GRAM CHARGE .2" ENTRY HOLE 12" PENETRATION WENT DOWN TO PERFORATE @ 3314' RD WL.
WAIT ON VACUUM TRUCK W LOAD OF FRESH TO MIX CMT / TRUCK BROKE DOWN ON THE RD.
INJECTION RATE @ 2 BPM W 400 PSI / SQUEEZE 145 SXS CLASS 'C' CMT, 14.8#, 1.32 YIELD, 21.7 MIX, 33.9 SLURRY, 24.4 DISPLACEMENT / ISIP 220 PSI.
WOC.
RIH W TBG TAG TOC @ 3070'
PICK UP CCL 1-9/16 GUN 3.5 GRAM CHARGE .2" ENTRY HOLE 12" PENETRATION WENT DOWN TO PERFORATE @ 3050' RD WL.
MOVED DOWN TO 3100' , SPOT 25 SXS CLASS 'C' CMT .
RIH TO TAG TOC @ 2830'
SPOT 25 SXS CLASS 'C' CMT , 14.8#, 1.32 YIELD, 3.75 MIX, 5.8 SLURRY, 10.9 DISPLACEMENT.
WOC.
TAG TOC @ 2490' / PICK UP CCL 1-9/16 GUN 3.5 GRAM CHARGE .2" ENTRY HOLE 12" PENETRATION WENT DOWN TO PERFORATE @ 450' RD WL.
INJECTION RATE @ 2.5 BPM W 300 PSI / SQUEEZE 40 SXS CLASS 'C' CMT 14.8#,1.32 YIELD, 6 MIX, 9.3 SLURRY, 7.3 DISPLACEMENT.
WOC.
TAG TOC @ 348' / PICK UP CCL 1-9/16 GUN 3.5 GRAM CHARGE .2" ENTRY HOLE 12" PENETRATION WENT DOWN TO PERFORATE @ 60' RD WL.
RD WORK FLOOR / ND 7 1/16 5K HYD BOP.
INJECTION RATE @ 2.5 BPM W 250 PSI / SQUEEZE 25 SXS CLASS 'C' CMT, 14.8#, 1.32 YIELD, 3.75 MIX, 5.8 SLURRY, CIRCULATING TO SURFACE, ISIP 500 PSI, WASH OVER LINES.

Stephen Janacek
4/27/2022

Final Wellbore
TRACY D #001
30-015-21631-0000
Eddy

String 1
OD 13.375 in
TD 400 ft
TOC 0 ft


String 2
OD 9.625 in
TD 3000 ft
TOC 0 ft

PERF @ 3050'. SPOT 25 SXS CL C
CMT. TAG @ 2830'.

SPOT 25 SX CL H CMT 10427'-
~10177'.

String 3
OD 5.5 in
TD 11575 ft
TOC 5910 ft
PBD 11540 ft

Prod Zone
11133 ft
11441 ft



District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 102250

CONDITIONS

Operator: OXY USA WTP LIMITED PARTNERSHIP P.O. Box 4294 Houston, TX 772104294	OGRID: 192463
	Action Number: 102250
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	5/2/2022