

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address SPUR ENERGY PARTNERS LLC 9655 KATY FREEWAY, SUITE 500 HOUSTON, TX 77024		² OGRID Number 328947
		³ Reason for Filing Code/ Effective Date NW 02/17/2022
⁴ API Number 30 - 0 15-48643	⁵ Pool Name PENASCO DRAW; SA-YESO (ASSOC)	⁶ Pool Code 50270
⁷ Property Code 331156	⁸ Property Name ROSE SOUTH	⁹ Well Number 20H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
4	7	19S	26E		1125	SOUTH	700	WEST	EDDY

¹¹ Bottom Hole Location

FTP: 1380' FSL 106' FEL LTP: 1377' FSL 147' FWL

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	12	19S	25E		1379	SOUTH	58	WEST	EDDY
¹² Lse Code P	¹³ Producing Method Code P	¹⁴ Gas Connection Date TBD	¹⁵ C-129 Permit Number		¹⁶ C-129 Effective Date		¹⁷ C-129 Expiration Date		

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
221115	FRONTIER FIELD SERVICES, LLC 4200 EAST SKELLY DRIVE, SUITE 700, TULSA, OK 74135	G
33479	HOLLYFRONTIER REFINING & MARKETING 2828 N. HARWOOD, SUITE 1300, DALLAS, TX 75201	O

IV. Well Completion Data

²¹ Spud Date 08/11/2021	²² Ready Date 11/03/2021	²³ TD 2934'V/8815'M	²⁴ PBTD 2934'V/8815'M	²⁵ Perforations 3621'-8725'	²⁶ DHC, MC
²⁷ Hole Size		²⁸ Casing & Tubing Size	²⁹ Depth Set		³⁰ Sacks Cement
12-1/4"		9-5/8" 36# J-55 BTC	1301'		445 SXS (CIRC TO SURFACE)
8-3/4"		7" 32# L-80 BK-HT	3325'		1460 SXS (CIRC TO SURFACE)
8-3/4"		5-1/2" 20# L-80 BK-HT	8815'		1460 SXS (CIRC TO SURFACE)
		3-1/2" J-55 TBG	2950'		

V. Well Test Data

³¹ Date New Oil 11/16/2021	³² Gas Delivery Date TBD	³³ Test Date 01/08/2022	³⁴ Test Length 24-HOURS	³⁵ Tbg. Pressure 282	³⁶ Csg. Pressure 137
³⁷ Choke Size N/A	³⁸ Oil 1754	³⁹ Water 4697	⁴⁰ Gas 1081		⁴¹ Test Method PUMPING ON ESP

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Sarah Chapman</i>		OIL CONSERVATION DIVISION	
Printed name: SARAH CHAPMAN		Approved by: <i>[Signature]</i>	
Title: REGULATORY DIRECTOR		Title: Petroleum Engineer	
E-mail Address: SCHAPMAN@SPURENERGY.COM		Approval Date: 06/29/22	
Date: 02/17/2022	Phone: 832-930-8613		

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☒ AMENDED REPORT
AS-DRILLED

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-48643		² Pool Code 50270	³ Pool Name PENASCO DRAW; SA-YESO (ASSOC)
⁴ Property Code 331156	⁵ Property Name ROSE SOUTH		⁶ Well Number 20H
⁷ OGRID NO. 328947	⁸ Operator Name SPUR ENERGY PARTNERS LLC.		⁹ Elevation 3386'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet From the	East/West line	County
4	7	19S	26E		1125	SOUTH	700	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no. L	Section 12	Township 19S	Range 25E	Lot Idn	Feet from the 1379	North/South line SOUTH	Feet from the 58	East/West line WEST	County EDDY
12 Dedicated Acres 320	13 Joint or Infill	14 Consolidation Code	15 Order No.						

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.

¹⁶

GEODETIC DATA
NAD 83 GRID – NM EAST

SURFACE LOCATION (SL)
N: 607821.4 – E: 512403.6
LAT: 32.6709113° N
LONG: 104.4273631° W

FIRST TAKE POINT (FTP)
1380' FSL & 106' FEL – SEC 12
N: 608084.1 – E: 511597.5
LAT: 32.6716313° N
LONG: 104.4299837° W
MD: 3621.0 – TVD: 3063.7

LAST TAKE POINT (LTP)
1377' FSL & 147' FWL – SEC 12
N: 608067.8 – E: 506496.8
LAT: 32.6715727° N
LONG: 104.4465600° W
MD: 8725.0 – TVD: 2938.4

BOTTOM HOLE (BH)
N: 608069.6 – E: 506406.9
LAT: 32.6715773° N
LONG: 104.4468522° W
MD: 8815.0 – TVD: 2934.1

CORNER DATA
NAD 83 GRID – NM EAST

A: FOUND BOLT F: FOUND SPIKE NAIL
N: 606691.2 – E: 506353.0 N: 609327.0 – E: 516948.7

B: FOUND 1/2" REBAR G: FOUND SPIKE NAIL
N: 612008.3 – E: 506339.4 N: 606619.9 – E: 516980.1

C: FOUND 5/8" REBAR H: FOUND 1" PIPE
N: 611978.8 – E: 511694.1 N: 606673.4 – E: 514339.7

D: FOUND ALUM CAP "ILLEGIBLE" I: FOUND 1/2" REBAR
N: 612006.0 – E: 514294.2 N: 606705.1 – E: 511706.5

E: FOUND 3" PIPE
N: 612034.2 – E: 516918.2

(B) (C) (D) (E)

LOT 1
39.34 Ac.

LOT 2
39.51 Ac.

LOT 3
39.67 Ac.

LOT 4
39.84 Ac.

BH 58'

LTP

FTP

SL

1379'

700'

1125'

12 7

(A) (I) (H) (G)

¹⁷ **OPERATOR CERTIFICATION**

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Sarah Chapman 11/04/2021
Signature Date
SARAH CHAPMAN
Printed Name
SCHAPMAN@SPUREENERGY.COM
E-mail Address

¹⁸ **SURVEYOR CERTIFICATION**

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

10-28-2021
Date of Survey
Signature and Seal of Professional Surveyor

19680
Certificate Number

LS20120751AC



I **Larry Wright** certify that I am employed by **Wellbenders Directional Services**. That I did on the day(s) of **09/25/21** thru **09/29/21** conduct or supervise the taking of a **MWD Survey** from a depth of **155'** to a depth of **8815'**; that the data is true, correct, complete and within the limitations of the tool as set forth by **Wellbenders Directional Services**; that I am authorized and qualified to make this report; that this survey was conducted at the request of **Spur Energy Partners** for the **Rose South 20H** API No. **30-015-48643** in **Eddy County, New Mexico**; and that I have reviewed this report and find that it conforms to the principles and procedures as set forth by **Wellbenders Directional Services**.

Larry Wright

*1125 Beach Airport Rd, Conroe, Texas
77301*



Spur Energy Partners, LLC

Eddy County, NM (NAD 83 - NME)

ROSE SOUTH

#20H

Wellbore #1

Survey: Survey #1

Standard Survey Report

29 September, 2021





Survey Report



Company:	Spur Energy Partners, LLC	Local Co-ordinate Reference:	Well #20H
Project:	Eddy County, NM (NAD 83 - NME)	TVD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Site:	ROSE SOUTH	MD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Well:	#20H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	WBDS_SQL_2

Project	Eddy County, NM (NAD 83 - NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site		ROSE SOUTH			
Site Position:		Northing:	607,781.50 usft	Latitude:	32.6708016
From:	Map	Easting:	512,403.70 usft	Longitude:	-104.4273627
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	-0.051 °

Well	#20H					
Well Position	+N/-S	0.00 usft	Northing:	607,821.40 usft	Latitude:	32.6709112
	+E/-W	0.00 usft	Easting:	512,403.50 usft	Longitude:	-104.4273635
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,386.00 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	7/24/2021	6.963	60.174	47,657.26778606

Design	Wellbore #1				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	269.85	

Survey Program	Date	9/29/2021			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
7.00	8,815.00	Survey #1 (Wellbore #1)	MWD+IGRF	OWSG MWD + IGRF or WMM	

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
7.00	0.00	0.00	7.00	0.00	0.00	0.00	0.00	0.00	0.00	
155.00	0.79	348.04	155.00	1.00	-0.21	0.21	0.53	0.53	0.00	
244.00	1.01	3.94	243.98	2.38	-0.28	0.28	0.37	0.25	17.87	
330.00	2.02	20.56	329.95	4.56	0.30	-0.31	1.27	1.17	19.33	
417.00	2.29	21.21	416.89	7.61	1.47	-1.49	0.31	0.31	0.75	
505.00	3.69	30.49	504.77	11.69	3.54	-3.57	1.68	1.59	10.55	
593.00	4.79	30.49	592.53	17.30	6.84	-6.89	1.25	1.25	0.00	
680.00	5.80	31.19	679.16	24.19	10.96	-11.02	1.16	1.16	0.80	
764.00	7.21	29.78	762.61	32.40	15.78	-15.86	1.69	1.68	-1.68	



Survey Report



Company:	Spur Energy Partners, LLC	Local Co-ordinate Reference:	Well #20H
Project:	Eddy County, NM (NAD 83 - NME)	TVD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Site:	ROSE SOUTH	MD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Well:	#20H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	WBDS_SQL_2

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
851.00	8.00	34.54	848.85	42.12	21.92	-22.03	1.16	0.91	5.47	
936.00	9.80	38.40	932.82	52.66	29.77	-29.91	2.23	2.12	4.54	
1,027.00	12.60	40.51	1,022.08	66.28	41.03	-41.20	3.11	3.08	2.32	
1,109.00	13.30	42.88	1,101.99	79.99	53.26	-53.47	1.07	0.85	2.89	
1,196.00	13.90	42.41	1,186.56	95.04	67.11	-67.36	0.70	0.69	-0.54	
1,254.00	14.90	43.49	1,242.73	105.60	76.95	-77.22	1.79	1.72	1.86	
1,318.00	16.13	44.63	1,304.40	117.89	88.85	-89.16	1.98	1.92	1.78	
1,443.00	15.08	43.93	1,424.79	141.96	112.33	-112.71	0.85	-0.84	-0.56	
1,569.00	13.05	42.17	1,547.01	164.31	133.26	-133.69	1.65	-1.61	-1.40	
1,696.00	9.98	40.94	1,671.44	183.26	150.10	-150.58	2.42	-2.42	-0.97	
1,823.00	7.78	36.37	1,796.91	198.49	162.41	-162.93	1.82	-1.73	-3.60	
1,947.00	7.82	34.70	1,919.76	212.19	172.19	-172.74	0.19	0.03	-1.35	
2,011.00	7.82	16.59	1,983.17	219.94	175.91	-176.49	3.83	0.00	-28.30	
2,074.00	7.69	356.47	2,045.61	228.26	176.88	-177.47	4.29	-0.21	-31.94	
2,137.00	8.70	328.78	2,107.99	236.54	174.15	-174.76	6.40	1.60	-43.95	
2,200.00	10.24	307.95	2,170.15	244.06	167.26	-167.90	5.92	2.44	-33.06	
2,263.00	12.88	293.01	2,231.88	250.25	156.37	-157.03	6.30	4.19	-23.71	
2,355.00	16.40	280.27	2,320.90	256.58	134.14	-134.82	5.16	3.83	-13.85	
2,418.00	20.26	275.34	2,380.70	259.18	114.52	-115.20	6.60	6.13	-7.83	
2,481.00	23.91	273.06	2,439.06	260.88	90.91	-91.59	5.95	5.79	-3.62	
2,544.00	28.13	271.65	2,495.67	261.99	63.30	-63.99	6.77	6.70	-2.24	
2,605.00	31.38	270.42	2,548.62	262.52	33.04	-33.72	5.42	5.33	-2.02	
2,668.00	34.86	269.46	2,601.37	262.47	-1.38	0.69	5.59	5.52	-1.52	
2,731.00	39.16	269.19	2,651.67	262.02	-39.29	38.61	6.83	6.83	-0.43	
2,794.00	43.78	268.93	2,698.86	261.33	-81.00	80.31	7.34	7.33	-0.41	
2,857.00	47.38	269.54	2,742.95	260.74	-125.98	125.30	5.76	5.71	0.97	
2,920.00	50.51	269.89	2,784.32	260.50	-173.48	172.80	4.99	4.97	0.56	
2,983.00	53.49	270.07	2,823.11	260.49	-223.12	222.44	4.74	4.73	0.29	
3,044.00	56.62	270.25	2,858.04	260.63	-273.12	272.43	5.14	5.13	0.30	
3,107.00	61.27	270.42	2,890.53	260.95	-327.07	326.39	7.38	7.38	0.27	
3,138.00	62.37	270.33	2,905.17	261.13	-354.39	353.71	3.56	3.55	-0.29	
3,169.00	62.59	270.07	2,919.49	261.22	-381.89	381.20	1.03	0.71	-0.84	
3,201.00	62.99	270.16	2,934.13	261.28	-410.34	409.66	1.27	1.25	0.28	
3,231.00	63.30	269.98	2,947.68	261.31	-437.11	436.42	1.16	1.03	-0.60	
3,263.00	63.69	269.89	2,961.96	261.28	-465.75	465.06	1.24	1.22	-0.28	
3,294.00	63.96	269.63	2,975.63	261.16	-493.57	492.88	1.15	0.87	-0.84	
3,326.00	64.31	269.54	2,989.59	260.95	-522.36	521.68	1.12	1.09	-0.28	
3,357.00	66.20	269.63	3,002.57	260.75	-550.51	549.83	6.10	6.10	0.29	
3,420.00	71.69	270.16	3,025.19	260.65	-609.28	608.60	8.75	8.71	0.84	
3,483.00	76.31	270.69	3,042.56	261.10	-669.82	669.14	7.38	7.33	0.84	
3,546.00	80.84	270.77	3,055.03	261.89	-731.55	730.87	7.19	7.19	0.13	
3,610.00	84.62	270.51	3,063.13	262.60	-795.02	794.33	5.92	5.91	-0.41	
3,673.00	89.58	270.25	3,066.32	263.01	-857.92	857.23	7.88	7.87	-0.41	
3,799.00	92.62	269.72	3,063.90	262.98	-983.88	983.19	2.45	2.41	-0.42	



Survey Report



Company:	Spur Energy Partners, LLC	Local Co-ordinate Reference:	Well #20H
Project:	Eddy County, NM (NAD 83 - NME)	TVD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Site:	ROSE SOUTH	MD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Well:	#20H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	WBDS_SQL_2

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
3,924.00	91.65	270.69	3,059.24	263.43	-1,108.79	1,108.10	1.10	-0.78	0.78
4,050.00	92.57	270.42	3,054.60	264.65	-1,234.70	1,234.00	0.76	0.73	-0.21
4,174.00	91.16	270.77	3,050.57	265.93	-1,358.63	1,357.92	1.17	-1.14	0.28
4,300.00	90.02	271.21	3,049.27	268.11	-1,484.60	1,483.89	0.97	-0.90	0.35
4,426.00	90.73	270.60	3,048.44	270.10	-1,610.58	1,609.86	0.74	0.56	-0.48
4,552.00	92.00	269.81	3,045.44	270.55	-1,736.54	1,735.82	1.19	1.01	-0.63
4,679.00	90.81	270.51	3,042.33	270.91	-1,863.50	1,862.78	1.09	-0.94	0.55
4,806.00	92.13	269.89	3,039.07	271.35	-1,990.45	1,989.73	1.15	1.04	-0.49
4,932.00	90.15	270.07	3,036.56	271.31	-2,116.42	2,115.70	1.58	-1.57	0.14
5,059.00	90.73	269.54	3,035.59	270.87	-2,243.41	2,242.70	0.62	0.46	-0.42
5,185.00	91.78	268.93	3,032.83	269.19	-2,369.37	2,368.66	0.96	0.83	-0.48
5,312.00	90.24	269.10	3,030.59	267.01	-2,496.33	2,495.62	1.22	-1.21	0.13
5,438.00	90.77	268.14	3,029.48	263.97	-2,622.28	2,621.58	0.87	0.42	-0.76
5,564.00	91.91	266.56	3,026.53	258.15	-2,748.11	2,747.42	1.55	0.90	-1.25
5,691.00	91.56	267.26	3,022.69	251.31	-2,874.86	2,874.20	0.62	-0.28	0.55
5,816.00	89.89	269.02	3,021.11	247.25	-2,999.78	2,999.12	1.94	-1.34	1.41
5,943.00	90.99	268.31	3,020.13	244.29	-3,126.74	3,126.09	1.03	0.87	-0.56
6,069.00	91.34	271.30	3,017.57	243.87	-3,252.70	3,252.05	2.39	0.28	2.37
6,195.00	92.22	270.86	3,013.65	246.24	-3,378.61	3,377.96	0.78	0.70	-0.35
6,316.00	90.99	271.30	3,010.27	248.52	-3,499.54	3,498.88	1.08	-1.02	0.36
6,438.00	90.64	270.16	3,008.53	250.07	-3,621.52	3,620.85	0.98	-0.29	-0.93
6,557.00	91.03	269.37	3,006.80	249.58	-3,740.50	3,739.84	0.74	0.33	-0.66
6,678.00	92.04	269.63	3,003.55	248.53	-3,861.45	3,860.79	0.86	0.83	0.21
6,799.00	91.91	268.84	2,999.38	246.91	-3,982.37	3,981.71	0.66	-0.11	-0.65
6,920.00	92.79	269.72	2,994.42	245.40	-4,103.25	4,102.60	1.03	0.73	0.73
7,039.00	92.31	270.33	2,989.13	245.45	-4,222.14	4,221.48	0.65	-0.40	0.51
7,157.00	91.08	270.69	2,985.64	246.50	-4,340.08	4,339.42	1.09	-1.04	0.31
7,278.00	90.95	270.33	2,983.49	247.57	-4,461.05	4,460.39	0.32	-0.11	-0.30
7,399.00	91.25	270.25	2,981.17	248.19	-4,582.03	4,581.36	0.26	0.25	-0.07
7,524.00	91.34	269.72	2,978.35	248.15	-4,707.00	4,706.33	0.43	0.07	-0.42
7,650.00	91.38	269.37	2,975.36	247.15	-4,832.96	4,832.29	0.28	0.03	-0.28
7,776.00	92.18	267.17	2,971.44	243.35	-4,958.83	4,958.18	1.86	0.63	-1.75
7,902.00	92.26	267.52	2,966.56	237.52	-5,084.60	5,083.96	0.28	0.06	0.28
8,028.00	91.91	269.10	2,961.98	233.81	-5,210.46	5,209.83	1.28	-0.28	1.25
8,152.00	92.00	268.93	2,957.75	231.68	-5,334.37	5,333.74	0.16	0.07	-0.14
8,278.00	91.52	270.33	2,953.88	230.86	-5,460.30	5,459.68	1.17	-0.38	1.11
8,404.00	91.43	273.06	2,950.63	234.59	-5,586.19	5,585.56	2.17	-0.07	2.17
8,530.00	92.09	272.53	2,946.76	240.73	-5,711.98	5,711.33	0.67	0.52	-0.42
8,656.00	92.57	271.30	2,941.64	244.94	-5,837.81	5,837.14	1.05	0.38	-0.98
8,740.00	92.79	271.13	2,937.71	246.72	-5,921.69	5,921.03	0.33	0.26	-0.20
8,815.00	92.79	271.13	2,934.06	248.19	-5,996.59	5,995.92	0.00	0.00	0.00



Survey Report



Company:	Spur Energy Partners, LLC	Local Co-ordinate Reference:	Well #20H
Project:	Eddy County, NM (NAD 83 - NME)	TVD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Site:	ROSE SOUTH	MD Reference:	RKB = 20' @ 3406.00usft (AKITA 57)
Well:	#20H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Wellbore #1	Database:	WBDS_SQL_2

Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
FINAL TD/ BIT PROJ: - survey hits target center - Point	0.00	0.00	2,934.06	248.19	-5,996.59	608,069.60	506,406.91	32.6715773	-104.4468522
ACTUAL LTP: 1377' F - survey misses target center by 32.45usft at 8740.00usft MD (2937.71 TVD, 246.72 N, -5921.69 E) - Point	0.00	0.00	2,936.13	247.36	-5,954.10	608,068.76	506,449.40	32.6715752	-104.4467141
ACTUAL FTP: 1379' F - survey hits target center - Point	0.00	360.00	3,063.60	262.64	-800.20	608,084.04	511,603.30	32.6716312	-104.4299648

Survey Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
3,138.00	2,905.17	261.13	-354.39	START TANGENT: 3138.00' MD/ 2905.17' TVD
3,326.00	2,989.59	260.95	-522.36	END TANGENT: 3326.00' MD/ 2989.59' TVD
3,615.20	3,063.60	262.64	-800.20	ACTUAL FTP: 3615.20' MD/ 3063.60' TVD
8,772.45	2,936.13	247.36	-5,954.10	ACTUAL LTP: 8772.45' MD/ 2936.13' TVD
8,815.00	2,934.06	248.19	-5,996.59	Projection to Bit: 8815.00' MD/ 2934.06' TVD
8,815.00	2,934.06	248.19	-5,996.59	Final Station Closure Distance= 6001.72 /Direction= 272.37
8,815.00	2,934.06	248.19	-5,996.59	TD: Latitude= 32.6715773 / Longitude= -104.4468522
8,815.00	2,934.06	248.19	-5,996.59	TD: Y= 608069.59 / X= 506406.91

Checked By: _____ Approved By: _____ Date: _____



Company: Spur Energy Partners, LLC
Project: Eddy County, NM (NAD 83 - NME)
Site: ROSE SOUTH
Well: #20H
Wellbore: Wellbore #1
Rig: AKITA 57
Design: PLAN #1 / 7:40, September 29 2021



WELL DETAILS: #20H

RKB = 20' @ 3406.00usft (AKITA 57)

3386.00


+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
0.00	0.00	607821.40	512403.50	32.6709112	-104.4273635

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
PLAT #20H SHL: 1125' FSL & 700' FWL	0.00	0.00	0.00	607821.40	512403.50	32.6709112	-104.4273635
PLAN #20H KOP @ 1977.68' MD	1959.16	185.66	147.16	608007.06	512550.66	32.6714219	-104.4268858
FINAL TD/ BIT PROJ: 1378' FSL & 57' FWL	2934.06	248.19	-5996.59	608069.59	506406.91	32.6715773	-104.4468522
ACTUAL LTP: 1377' FSL & 100' FWL	2936.13	247.36	-5954.10	608068.76	506449.40	32.6715751	-104.4467141
PLAT #20H BHL: 1380' FSL & 50' FWL	2945.00	249.60	-6004.10	608071.00	506399.40	32.6715812	-104.4468766
PLAT #20H LTP: 1380' FSL & 100' FWL	2946.10	249.70	-5954.10	608071.10	506449.40	32.6715816	-104.4467141
PLAT #20H FTP: 1380' FSL & 100' FEL	3060.00	263.10	-800.20	608084.50	511603.30	32.6716324	-104.4299648
ACTUAL FTP: 1379' FSL & 100' FEL	3063.60	262.64	-800.20	608084.04	511603.30	32.6716312	-104.4299648

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	0.00	
2	300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.000	0.00	
3	772.86	9.46	38.40	770.72	30.51	24.19	2.00	38.401	-24.27	
4	1977.68	9.46	38.40	1959.16	185.66	147.16	0.00	0.000	-147.64	
5	3079.99	60.00	269.85	2883.38	264.33	-327.86	6.00	-132.218	327.17	
6	3279.99	60.00	269.85	2983.38	263.88	-501.06	0.00	0.000	500.37	
7	3592.64	91.27	269.85	3060.00	263.10	-800.20	10.00	0.000	799.51	
8	8747.82	91.27	269.85	2946.10	249.73	-5954.10	0.00	0.000	5953.43	
9	8797.83	91.27	269.85	2945.00	249.60	-6004.10	0.00	0.000	6003.43	







Azimuths to Grid North
True North: 0.05°
Magnetic North: 7.01°

Magnetic Field
Strength: 47657.3snT
Dip Angle: 60.17°
Date: 7/24/2021
Model: IGRF2020

PROJECT DETAILS: Eddy County, NM (NAD 83 - NME)

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone
System Datum: Mean Sea Level


Disclaimer:
All Plan Details, boundary
lines and offset well
location/ survey data is
provided by customer and
subject to customer
approval.



START TANGENT: 3138.00' MD/ 2905.17' TVD
END TANGENT: 3326.00' MD/ 2989.59' TVD

ACTUAL FTP: 1379' FSL & 100' FEL
ACTUAL FTP: 3615.20' MD/ 3063.60' TVD

ACTUAL LTP: 8772.45' MD/ 2936.13' TVD
Projection to Bit: 8815.00' MD/ 2934.06' TVD
Final Station Closure Distance= 6001.72 /Direction= 272.37
TD: Latitude= 32.6715773 / Longitude= -104.4468522
TD: Y= 608069.59 / X= 506406.91



Plan: PLAN #1 (#20H/Wellbore #1) AKITA 57

Created By: Matthew May Date: 7:40, September 29 2021

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017					
WELL COMPLETION OR RECOMPLETION REPORT AND LOG								1. WELL API NO. 30-015-48643		
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name ROSE SOUTH		
								6. Well Number: 20H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER _____										
8. Name of Operator SPUR ENERGY PARTNERS LLC						9. OGRID 328947				
10. Address of Operator 9655 KATY FREEWAY, SUITE 500, HOUSTON, TX 77024						11. Pool name or Wildcat PENASCO DRAW; SA-YESO (ASSOC)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	4	7	19S	26E		1125	SOUTH	700	WEST	EDDY
BH:	L	12	19S	25E		1379	SOUTH	58	WEST	EDDY
13. Date Spudded 08/11/2021	14. Date T.D. Reached 09/29/2021		15. Date Rig Released 09/30/2021		16. Date Completed (Ready to Produce) 11/3/2021			17. Elevations (DF and RKB, RT, GR, etc.) 3386' GR		
18. Total Measured Depth of Well 2934'V/8815'M			19. Plug Back Measured Depth 2934'V/8815'M		20. Was Directional Survey Made? YES			21. Type Electric and Other Logs Run GAMMA RAY		
22. Producing Interval(s), of this completion - Top, Bottom, Name										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
9-5/8"		36		1301'		12-1/4"		445 SXS (CIRC TO SURFACE)		0
7"		32		3325'		8-3/4"		1460 SXS (CIRC TO SURFACE)		0
5-1/2"		20		8815'		8-3/4"		1460 SXS (CIRC TO SURFACE)		0
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET			
					3-1/2"	2950'				
26. Perforation record (interval, size, and number) 10/18/2021 Pressure test csg to 6000# for 30 minutes, good test. 10/19/2021 RIH & cleanout to PBTD @ 8815'. RIH & perf from 3621'-8725', total 900 shots/ft @ 0.42 shot size. Frac in 25 stages w/ 12282606 gal slickwater and 5016324# sand. 10/28/2021 rig down wireline and cleanout. RIH & set 3-1/2" J-55 tbg @ 2950'.						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						3621'-8725'		12282606 GAL SLICKWATER & 5016324# SAND		
28. PRODUCTION										
Date First Production 11/16/2021		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING ON ESP				Well Status (Prod. or Shut-in) PRODUCING				
Date of Test 01/08/2022	Hours Tested 24-HOURS	Choke Size N/A	Prod'n For Test Period	Oil - Bbl 1754	Gas - MCF 1081	Water - Bbl. 4697	Gas - Oil Ratio			
Flow Tubing Press. 282	Casing Pressure 137	Calculated 24-Hour Rate	Oil - Bbl. 1754	Gas - MCF 1081	Water - Bbl. 4697	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) FLARED							30. Test Witnessed By JERRY MATHEWS			
31. List Attachments WBD, AS-DRILLED C-102, DIRECTIONAL AND FINAL C-104										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.							33. Rig Release Date:			
34. If an on-site burial was used at the well, report the exact location of the on-site burial: Latitude _____ Longitude _____ NAD83										
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief Printed Name SARAH CHAPMAN Title REGULATORY DIRECTOR Date 02/17/2022 Signature <i>Sarah Chapman</i> E-mail Address SCHAPMAN@SPURENERGY.COM										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A "
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres 915'	T. Simpson	T. Mancos	T. McCracken
T. Glorieta 2460'	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T. YESO 2575'	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology
915' 2460'	2460' 2575'	1545' 115'	DOLOMITE DOLOMITE

Surface
9 5/8" J-55 36# BTC
0-1,301'
141 bbl 12.0 ppg lead 330sx
38 bbls of 13.2 ppg tail 115sx
TOC Surface

Production
7" L-80 32# BK-HT
0-3,325'
X/O
5 1/2" L-80 20# BTC
3,325'-8,815'
97 bbl 11.4 ppg lead 230sx
342 bbl 13.2 ppg Tail 1230sx
TOC surface

LATERAL DETAILS	
STAGES	25
TOP PERF	3,621'
BOTTOM PERF	8,725'
CLUSTERS	
STAGE LENGTH	
PBTD	8,746'
TD	8,815'

CASING						
	CONDUCTOR	SURFACE	INTERMEDIATE	PRODUCTION 1	PRODUCTION 2	TUBING
HOLE		12 1/4"		8 3/4"	8 3/4"	
CASING		9 5/8"		7"	5 1/2"	3 1/2"
WEIGHT		36		32	20	
GRADE		J-55		L-80	L-80	
TOP		0		0	3,325'	2950'
BOTTOM		1,301'		3,325'	8,815'	
ID		8.921		6.094	4.778	
DRIFT		8.765		5.969	4.653	
BURST		3520		9060	9190	
COLLAPSE		2020		8830	8830	
BBL/FT		0.0773		0.0361	0.0222	

2,934'	TVD	GROUND ELEV.	3,386'	LOG ELEV. (RKB)	20'
--------	-----	--------------	--------	-----------------	-----

TOP PERF	3,621'					BOTTOM PERF	8,725'
----------	--------	--	--	--	--	-------------	--------

PBTD	8,746'
------	--------

TD	8,815'
----	--------

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 82354

ACKNOWLEDGMENTS

Operator: Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024	OGRID: 328947
	Action Number: 82354
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 82354

CONDITIONS

Operator: Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024	OGRID: 328947
	Action Number: 82354
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
llowe	None	6/29/2022