

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30 - 025 - 36917
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V0 - 6659
7. Lease Name or Unit Agreement Name Buffett BFF State
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Trinity, Wolfcamp

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Steward Energy II

3. Address of Operator
2400 Dallas Hwy, ste 400, Frisco, TX 75034

4. Well Location
Unit Letter N : 330 feet from the South line and 2310 feet from the West line
Section 15 Township 12S Range 38E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
GR 3817'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- DOWNHOLE COMMINGLE
- CLOSED-LOOP SYSTEM
- OTHER:

- PLUG AND ABANDON**
- CHANGE PLANS
- MULTIPLE COMPL

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING/CEMENT JOB
- ALTERING CASING
- P AND A

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Note changes to procedure

1. Set CIBP @ 8985'. Pressure Test casing
2. Spot 25 sacks cement - Class H. WOC + Tag
3. POOH to 5860', circulating 9.5# brine
4. Spot 25 sacks cement - Class C. WOC + Tag
5. POOH to 3032', circulating 9.5# brine
6. Spot 25 sacks cement - Class C. WOC + Tag
7. ~~Fill from 500'~~ ^{XXXXXXX} Fill from 500' to surface with 65 sacks of cmt
P&S 500' Circ cement to surface
8. Cut off WH + install marker.

POOH to 4600', circulating 9.5# brine
~~Spot 25~~ ^{XX} Spot 25 SX cement - class C. WOC + tag
P&S 50 SX Class C

Spot 25 sax Class C 2300 Top of salt

See attached conditions of approval

Spud Date:

8/1/2022

Rig Release Date:

4" Diameter 4' tall above ground marker

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vanessa Lopez TITLE Dr. Regulatory Analyst DATE 6/7/22
 Type or print name Vanessa Lopez E-mail address: Vanessa.Lopez@stewardenergy.com PHONE: 214.277.0500
For State Use Only

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 7/6/22
 Conditions of Approval

**CONDITIONS OF APPROVAL
FOR PLUGGING AND ABANDONMENT
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at **(575)-263-6633** at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

Company representative will be on location during plugging procedures.

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

- 19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
- 20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Potash---(In the R-111-P Area (Potash Mine Area),

A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, woe 4 hours and tag, this plug will be SO' below the bottom and 50' above the top of the Formation.

21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, woe and tagged. These plugs will be set SO' below formation bottom to 50' above formation top inside the casing.

DRY HOLE MARKER REQ.UIRMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least 1/4" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

- 1. Operator name
- 2. Lease and Well Number
- 3. API Number
- 4. Unit letter
- 5. Quarter Section (feet from the North, South, East or West)
- 6. Section, Township and Range
- 7. Plugging Date
- 8. County

SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

General	Company: Steward Energy II	Prospect: TRINITY
	Well Name: Buffett BFF State #1	TD (MD/TVD): 9920'
	County: Lea	Elevation: GR - 3817', KB - 3832'
	State: New Mexico	Latitude & longitude (SL):
	API Number: 30-025-36917	Section-Township-Range (SL): 15-12S-38E
	Spud Date: 3/7/2005	Surface Location: 330' FSL & 2310' FWL
	As Of Date: 5/2/2022	Bottom Hole Location:

--	--

Formation	Depth		Casing Profile	Hole Size	Casing Specifications	Cement Specifications	
	MD	TVD					
Cement Fill	500'			17 1/2"	13 3/8", 48#, H-40	Cemented w/ 440 sx	
13 3/8" Casing @ 426'							
Cement Plug	3032'			12 1/4"	9 5/8", 36# & 40#, J-55	Cemented w/ 1,520 sx	
Yates	3082'						
5/8" Casing @ 4600'							
Cement Plug	4600'			8 3/4"	5 1/2" 15.5# & 17# J-55	Cemented w/ 1,118 sx	
Cement Plug	5860'						
Glorieta	5910'						
Tubb	7170'						
CIBP	8985'			Tubing		Tubing Details	
Wolfcamp	9034'					CIBP w/ 35' cmt @9515'	
Wolfcamp	9526'			5 1/2" Casing @ 9,920'			

Comments	

General	Company:		Steward Energy II		Prospect:	TRINITY		
	Well Name:		Buffett BFF State #1		TD (MD/TVD):	9920'		
	County:		Lea		Elevation:	GR - 3817', KB - 3832'		
	State:		New Mexico		Latitude & longitude (SL):			
	API Number:		30-025-36917		Section-Township-Range (SL):	15-12S-38E		
	Spud Date:		3/7/2005		Surface Location:	330' FSL & 2310' FWL		
	As Of Date:		5/2/2022		Bottom Hole Location:			
	Formation		Depth		Casing Profile	Hole Size	Casing Specifications	Cement Specifications
	MD	TVD						
						17 1/2"	13 3/8", 48#, H-40	Cemented w/ 440 sx
	13 3/8" Casing @ 426'							
	Yates		3082'					
						12 1/4"	9 5/8", 36# & 40#, J-55	Cemented w/ 1,520 sx
	5/8" Casing @ 4600'							
	Glorieta		5910'					
						8 3/4"	5 1/2" 15.5# & 17# J-55	Cemented w/ 1,118 sx
	Tubb		7170'					
	Wolfcamp		9034'					
	Wolfcamp		9526'					
	5/12" Casing @ 9,920'							
Comments								

General	Company: <i>Steward Energy II</i>		Prospect: <i>TRINITY</i>																																																																																																																																				
	Well Name: <i>Buffett BFF State #1</i>		TD (MD/TVD): <i>9920'</i>																																																																																																																																				
	County: <i>Lea</i>		Elevation: <i>GR - 3817', KB - 3832'</i>																																																																																																																																				
	State: <i>New Mexico</i>		Latitude & longitude (SL):																																																																																																																																				
	API Number: <i>30-025-36917</i>		Section-Township-Range (SL): <i>15-12S-38E</i>																																																																																																																																				
	Spud Date: <i>3/7/2005</i>		Surface Location: <i>330' FSL & 2310' FWL</i>																																																																																																																																				
	As Of Date: <i>5/2/2022</i>		Bottom Hole Location:																																																																																																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Formation</th> <th colspan="2">Depth</th> <th rowspan="2">Casing Profile</th> <th rowspan="2">Hole Size</th> <th rowspan="2">Casing Specifications</th> <th rowspan="2">Cement Specifications</th> </tr> <tr> <th>MD</th> <th>TVD</th> </tr> </thead> <tbody> <tr> <td>Cement Fill</td> <td>500'</td> <td></td> <td rowspan="18"> </td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="3">13 3/8" Casing @ 426'</td> <td>17 1/2"</td> <td>13 3/8", 48#, H-40</td> <td>Cemented w/ 440 sx</td> </tr> <tr> <td>Cement Plug</td> <td>3032'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Yates</td> <td>3082'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="3">5/8" Casing @ 4600'</td> <td>12 1/4"</td> <td>9 5/8", 36# & 40#, J-55</td> <td>Cemented w/ 1,520 sx</td> </tr> <tr> <td>Cement Plug</td> <td>4600'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Cement Plug</td> <td>5860'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Glorieta</td> <td>5910'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Tubb</td> <td>7170'</td> <td></td> <td>8 3/4"</td> <td>5 1/2" 15.5# & 17# J-55</td> <td>Cemented w/ 1,118 sx</td> </tr> <tr> <td>CIBP</td> <td>8985'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Wolfcamp</td> <td>9034'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Wolfcamp</td> <td>9526'</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="3">5/12" Casing @ 9,920'</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6"> <table border="1"> <thead> <tr> <th colspan="2">Tubing</th> <th>Tubing Details</th> </tr> </thead> <tbody> <tr> <td colspan="2"></td> <td>CIBP w/ 35' cmt @9515'</td> </tr> </tbody> </table> </td> </tr> <tr> <td rowspan="5">Comments</td> <td colspan="6"></td> </tr> <tr> <td colspan="6"></td> </tr> <tr> <td colspan="6"></td> </tr> <tr> <td colspan="6"></td> </tr> <tr> <td colspan="6"></td> </tr> </tbody> </table>					Formation	Depth		Casing Profile	Hole Size	Casing Specifications	Cement Specifications	MD	TVD	Cement Fill	500'						13 3/8" Casing @ 426'			17 1/2"	13 3/8", 48#, H-40	Cemented w/ 440 sx	Cement Plug	3032'					Yates	3082'					5/8" Casing @ 4600'			12 1/4"	9 5/8", 36# & 40#, J-55	Cemented w/ 1,520 sx	Cement Plug	4600'					Cement Plug	5860'					Glorieta	5910'					Tubb	7170'		8 3/4"	5 1/2" 15.5# & 17# J-55	Cemented w/ 1,118 sx	CIBP	8985'					Wolfcamp	9034'					Wolfcamp	9526'					5/12" Casing @ 9,920'						<table border="1"> <thead> <tr> <th colspan="2">Tubing</th> <th>Tubing Details</th> </tr> </thead> <tbody> <tr> <td colspan="2"></td> <td>CIBP w/ 35' cmt @9515'</td> </tr> </tbody> </table>						Tubing		Tubing Details			CIBP w/ 35' cmt @9515'	Comments																														
Formation	Depth		Casing Profile	Hole Size		Casing Specifications	Cement Specifications																																																																																																																																
	MD	TVD																																																																																																																																					
Cement Fill	500'																																																																																																																																						
13 3/8" Casing @ 426'				17 1/2"	13 3/8", 48#, H-40	Cemented w/ 440 sx																																																																																																																																	
Cement Plug	3032'																																																																																																																																						
Yates	3082'																																																																																																																																						
5/8" Casing @ 4600'				12 1/4"	9 5/8", 36# & 40#, J-55	Cemented w/ 1,520 sx																																																																																																																																	
Cement Plug	4600'																																																																																																																																						
Cement Plug	5860'																																																																																																																																						
Glorieta	5910'																																																																																																																																						
Tubb	7170'			8 3/4"	5 1/2" 15.5# & 17# J-55	Cemented w/ 1,118 sx																																																																																																																																	
CIBP	8985'																																																																																																																																						
Wolfcamp	9034'																																																																																																																																						
Wolfcamp	9526'																																																																																																																																						
5/12" Casing @ 9,920'																																																																																																																																							
<table border="1"> <thead> <tr> <th colspan="2">Tubing</th> <th>Tubing Details</th> </tr> </thead> <tbody> <tr> <td colspan="2"></td> <td>CIBP w/ 35' cmt @9515'</td> </tr> </tbody> </table>						Tubing		Tubing Details			CIBP w/ 35' cmt @9515'																																																																																																																												
Tubing		Tubing Details																																																																																																																																					
		CIBP w/ 35' cmt @9515'																																																																																																																																					
Comments																																																																																																																																							

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 115905

COMMENTS

Operator: STEWARD ENERGY II, LLC 2600 Dallas Parkway Frisco, TX 75034	OGRID: 371682
	Action Number: 115905
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	7/7/2022

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS
 Action 115905

CONDITIONS

Operator: STEWARD ENERGY II, LLC 2600 Dallas Parkway Frisco, TX 75034	OGRID: 371682
	Action Number: 115905
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	See attached conditions of approval Note changes to procedure	7/6/2022