

District I
1625 N. French Dr., Hobbs, NM 88240

State of New Mexico
Energy, Minerals & Natural Resources

Form C-104
Revised August 1, 2011

District II
811 S. First St., Artesia, NM 88210

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☒ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address OXY USA INC. P.O. BOX 50250 MIDLAND, TX 79710		² OGRID Number: 16696
		³ Reason for Filing Code/ Effective Date: NW - 05/28/2022
⁴ API Number 30 - 015-48881	⁵ Pool Name PURPLE SAGE WOLFCAMP *NSL-8241	⁶ Pool Code 98220
⁷ Property Code: 329988	⁸ Property Name: TAILS CC 10-3 FEDERAL COM	⁹ Well Number: 31H

II. ¹⁰ Surface Location

Ul or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
N	10	24S	29E		220	SOUTH	1725	WEST	EDDY

¹¹ Bottom Hole Location FTP- 151' FSL 334' FWL LTP- 186' FNL 338' FWL

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L4	3	24S	29E		40	NORTH	339	WEST	EDDY
¹² Lse Code F	¹³ Producing Method Code : P	¹⁴ Gas Connection Date: 06/04/22	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
214754	LPC CRUDE OIL, INC.	O
151618	ENTERPRISE FIELD SERVICES LLC	G

IV. Well Completion Data

²¹ Spud Date 12/18/21	²² Ready Date 05/28/2022	²³ TD 20909'M 10265'V	²⁴ PBTD 20861'M 10264'V	²⁵ Perforations 10463-20763'	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
14-3/4"	10-3/4"	520'	515		
9-7/8"	7-5/8"	9699'	2623		
6-3/4"	5-1/2"	20889'	872		
	2-3/8" tbg	9977'	na		

V. Well Test Data

³¹ Date New Oil 06/04/22	³² Gas Delivery Date 06/04/22	³³ Test Date 07/10/22	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure	³⁶ Csg. Pressure 860
³⁷ Choke Size 128/128	³⁸ Oil 4015	³⁹ Water 6770	⁴⁰ Gas 6810		⁴¹ Test Method F

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief.

Signature: 

Printed name: JANA MENDIOLA

Title: SR. REGULATORY ANALYST

E-mail Address:
Janalyn_mendiola@oxy.com

Date: 08/26/2022 Phone: 422-685-5936

OIL CONSERVATION DIVISION

Approved by:

Title: Petroleum Engineer

Approval Date: 09/20/22

COA: (1) File 3160-4 Completion Report within 10 days to NMOCD after BLM approval. (2) File all Logs

1625 N. French Dr., Hobbs, NM 88240
 Phone: (575) 393-6161 Fax: (575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone: (575) 748-1283 Fax: (575) 748-9720
District III
 1000 Rio Brazos Road, Aztec, NM 87410
 Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505
 Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
 Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Revised August 1, 2011
 Submit one copy to appropriate
 District Office

☒ AMENDED REPORT


WELL LOCATION AND ACREAGE DEDICATION AS-DRILLED PLAT

¹ API Number 30-015-48881	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP
⁴ Property Code 329988	Property Name TAILS CC 10_3 FED COM	⁶ Well Number 31H
⁷ OGRID No. 16696	⁸ Operator Name OXY USA INC	⁹ Elevation 2940'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
N	10	24S	29E		220	SOUTH	1725	WEST	EDDY
¹¹ Bottom Hole Location If Different From Surface									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D E-4	3	24S	29E		40	NORTH	339	WEST	EDDY
¹² Dedicated Acres 1278.62	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No. NSL-8241						

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



Distances/areas relative to NAD 83 Combined Scale Factor: 0.999778625 Convergence Angle: 00°11'10.650012"




OXY



Borehole:	Well:	Field:	Structure:
Tails CC 10_3 Federal Com 31H	Tails CC 10_3 Federal Com 31H	NM Eddy County (NAD 83)	Oxy Tails CC 10_3 Federal Com Pad

Gravity & Magnetic Parameters	Surface Location	NAD83 New Mexico State Plane, Eastern Zone, US Feet	Miscellaneous
Model: IFR1 MagDec: 6.81° Dip: 59.951° Date: 12-Mar-2022 FS: 47606.5nT Gravity FS: 998.471mgn (9.80665 Based)	Lat: N 32 13 31.70 Lon: W 103 58 31.26	Northing: 445944.8RUS Easting: 652035.9RUS Grid Conv: 0.1909° Scale Fact: 0.99992313	Slot: Tails CC 10_3 Federal Com 31H Plan: Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0° to 20909°MD TVD Ref: RKB(2965.1ft above MSL)

Critical Points								
Critical Point	MD	INCL	AZIM	TVD	VSEC	N(+)S(-)	E(+)W(-)	DLS
WRP	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
SHL	25.00	0.00	0.00	25.00	0.00	0.00	0.00	
First Gyro Survey	103.04	0.40	235.74	103.04	-0.12	-0.15	-0.23	0.51
Last Gyro Survey	538.47	0.46	338.57	538.45	2.97	2.66	-2.43	0.25
First SLB Survey	542.00	0.24	338.47	541.98	2.99	2.68	-2.44	6.23
Actual KOP	9770.10	14.45	261.80	9626.06	-256.10	-426.99	-1209.72	3.02
Wolfcamp Intersection	10391.36	51.64	353.94	10112.10	67.39	-125.17	-1387.81	7.07
100' FSL Crossing	10398.00	51.77	354.51	10116.22	72.60	-119.99	-1388.33	7.07
Exit Target Box	12939.00	87.86	0.16	10248.71	2549.68	2385.47	-1356.08	1.52
Enter Target Box	14062.00	91.46	354.54	10285.55	3660.24	3506.01	-1361.37	4.73
100' FNL Crossing	20848.00	89.88	0.40	10264.91	10384.98	10285.45	-1434.35	0.36
Final MWD	20878.00	90.05	0.45	10264.94	10414.66	10315.44	-1434.13	0.62
Proj to TD	20909.00	90.05	0.45	10264.91	10445.33	10346.44	-1433.89	0.00



Schlumberger



Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909'MD Survey Geodetic Report (Def Survey)

Report Date: April 04, 2022 - 08:38 AM Client: OXY Field: NM Eddy County (NAD 83) Structure / Slot: Oxy Tails CC 10_3 Federal Com Pad / Tails CC 10_3 Federal Com 31H Well: Tails CC 10_3 Federal Com 31H Borehole: Tails CC 10_3 Federal Com 31H UWI / API#: Unknown / Unknown Survey Name: Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909'MD Survey Date: January 24, 2022 Tort / AHD / DDI / ERD Ratio: 319.159' / 12144.535 ft / 6.896' / 1.180 Coordinate Reference System: NAD83 New Mexico State Plane, Eastern Zone, US Feet Location Lat / Long: N 32° 13' 31.69803", W 103° 58' 31.26064" Location Grid N/E Y/X: N 445944.800 RUS, E 652035.900 RUS CRS Grid Convergence Angle: 0.1909 ° Grid Scale Factor: 0.99992313 Version / Patch: 2.10.829.1	Survey / DLS Computation: Minimum Curvature / Lubinski Vertical Section Azimuth: 352.074 ° (Grid North) Vertical Section Origin: 0.000 ft, 0.000 ft TVD Reference Datum: RKB TVD Reference Elevation: 2965.100 ft above MSL Seabed / Ground Elevation: 2940.100 ft above MSL Magnetic Declination: 6.810 ° Total Gravity Field Strength: 998.470mgm (9.80665 Based) Gravity Model: GARM Total Magnetic Field Strength: 47608.500 nT Magnetic Dip Angle: 59.951 ° Declination Date: March 12, 2022 Magnetic Declination Model: IFR1 North Reference: Grid North Grid Convergence Used: 0.1900 ° Total Corr Mag North->Grid North: 6.6200 ° Local Coord Referenced To: Well Head	
---	--	--

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Closure (ft)	Closure Azimuth (°)	Northing (RUS)	Easting (RUS)	Latitude (N/S ° ' '')	Longitude (E/W ° ' '')
WRP	0.00	0.00	0.00	0.00	0.00	0.00	0.00	N/A	0.00	0.00	445944.80	652035.90	N 32 13 31.70	W 103 58 31.26
SHL	25.00	0.00	0.00	25.00	0.00	0.00	0.00	0.00	0.00	0.00	445944.80	652035.90	N 32 13 31.70	W 103 58 31.26
First Gyro Survey	103.04	0.40	235.74	103.04	-0.12	-0.15	-0.23	0.51	0.27	235.74	445944.65	652035.67	N 32 13 31.70	W 103 58 31.26
	194.29	0.39	308.71	194.29	-0.04	-0.14	-0.73	0.51	0.74	259.27	445944.66	652035.17	N 32 13 31.70	W 103 58 31.27
	281.51	0.50	317.85	281.51	0.49	0.33	-1.22	0.15	1.26	285.13	445945.13	652034.68	N 32 13 31.70	W 103 58 31.27
	375.92	0.65	329.92	375.91	1.33	1.10	-1.76	0.20	2.08	301.92	445945.90	652034.14	N 32 13 31.71	W 103 58 31.28
	470.33	0.63	340.61	470.31	2.34	2.05	-2.20	0.13	3.01	312.95	445946.85	652033.70	N 32 13 31.72	W 103 58 31.29
Last Gyro Survey	538.47	0.46	338.57	538.45	2.97	2.66	-2.43	0.25	3.60	317.61	445947.46	652033.47	N 32 13 31.72	W 103 58 31.29
First SLB Survey	542.00	0.48	338.47	542.00	2.98	2.67	-2.44	0.23	3.62	317.73	445947.48	652033.46	N 32 13 31.72	W 103 58 31.29
	558.00	0.11	257.00	557.98	3.22	2.88	-2.44	0.21	3.90	317.86	445947.68	652033.27	N 32 13 31.73	W 103 58 31.29
	753.00	0.10	13.67	752.98	3.28	2.94	-2.70	0.19	3.99	317.41	445947.74	652033.20	N 32 13 31.73	W 103 58 31.29
	913.00	0.10	160.41	912.98	3.28	2.94	-2.62	0.12	3.94	318.31	445947.74	652033.28	N 32 13 31.73	W 103 58 31.29
	1008.00	0.10	158.13	1007.98	3.12	2.79	-2.56	0.00	3.79	317.41	445947.59	652033.34	N 32 13 31.73	W 103 58 31.29
	1102.00	0.13	315.66	1101.98	3.12	2.79	-2.61	0.24	3.82	316.93	445947.59	652033.29	N 32 13 31.73	W 103 58 31.29
	1197.00	0.11	251.55	1196.98	3.19	2.84	-2.77	0.14	3.97	315.69	445947.64	652033.13	N 32 13 31.73	W 103 58 31.29
	1291.00	0.10	277.68	1290.98	3.20	2.82	-2.94	0.05	4.07	313.84	445947.62	652032.96	N 32 13 31.73	W 103 58 31.29
	1384.00	0.10	134.86	1383.98	3.16	2.77	-2.96	0.20	4.06	313.14	445947.57	652032.94	N 32 13 31.73	W 103 58 31.29
	1479.00	0.13	186.51	1478.98	2.98	2.61	-2.91	0.11	3.91	311.84	445947.41	652032.99	N 32 13 31.72	W 103 58 31.29
	1573.00	0.15	334.23	1572.98	3.00	2.61	-2.98	0.29	3.96	311.26	445947.41	652032.92	N 32 13 31.72	W 103 58 31.30
	1667.00	0.11	209.11	1666.98	3.04	2.64	-3.08	0.25	4.06	310.69	445947.44	652032.82	N 32 13 31.72	W 103 58 31.30
	1762.00	0.07	218.52	1761.98	2.93	2.52	-3.16	0.04	4.04	308.60	445947.32	652032.74	N 32 13 31.72	W 103 58 31.30
	1857.00	0.13	23.56	1856.98	2.98	2.57	-3.15	0.21	4.07	309.25	445947.92	652032.75	N 32 13 31.72	W 103 58 31.30
	1951.00	0.13	3.94	1950.98	3.18	2.78	-3.10	0.05	4.16	311.86	445947.58	652032.80	N 32 13 31.73	W 103 58 31.30
	2046.00	0.15	320.22	2045.98	3.39	2.98	-3.17	0.11	4.35	313.22	445947.78	652032.73	N 32 13 31.73	W 103 58 31.30
	2141.00	0.13	108.93	2140.98	3.45	3.04	-3.15	0.28	4.38	314.00	445947.84	652032.75	N 32 13 31.73	W 103 58 31.30
	2235.00	0.15	111.38	2234.98	3.34	2.96	-2.93	0.02	4.17	315.27	445947.76	652032.97	N 32 13 31.73	W 103 58 31.29
	2330.00	0.15	35.23	2329.98	3.37	3.02	-2.75	0.19	4.08	317.70	445947.82	652033.15	N 32 13 31.73	W 103 58 31.29
	2425.00	0.17	269.61	2424.98	3.48	3.12	-2.82	0.30	4.20	317.92	445947.92	652033.08	N 32 13 31.73	W 103 58 31.29
	2519.00	0.11	14.57	2518.98	3.58	3.20	-2.93	0.24	4.34	317.54	445948.00	652032.97	N 32 13 31.73	W 103 58 31.29
	2614.00	0.12	34.94	2613.98	3.74	3.37	-2.85	0.04	4.42	319.79	445948.17	652033.05	N 32 13 31.73	W 103 58 31.29
	2709.00	0.17	60.70	2708.98	3.86	3.53	-2.67	0.09	4.42	322.83	445948.32	652033.23	N 32 13 31.73	W 103 58 31.29
	2804.00	0.10	185.68	2803.98	3.83	3.51	-2.56	0.25	4.34	323.93	445948.31	652033.34	N 32 13 31.73	W 103 58 31.29
	2899.00	0.06	55.99	2898.98	3.77	3.46	-2.52	0.15	4.28	323.86	445948.26	652033.37	N 32 13 31.73	W 103 58 31.29
	2993.00	0.10	136.48	2992.98	3.73	3.42	-2.43	0.12	4.20	324.63	445948.22	652033.47	N 32 13 31.73	W 103 58 31.29
	3088.00	0.09	106.42	3087.98	3.53	3.34	-2.30	0.06	4.06	325.41	445948.14	652033.60	N 32 13 31.73	W 103 58 31.29
	3183.00	0.12	190.48	3182.98	3.50	3.22	-2.25	0.15	3.93	325.07	445948.02	652033.65	N 32 13 31.73	W 103 58 31.29
	3277.00	0.07	176.97	3276.98	3.35	3.07	-2.26	0.06	3.81	323.56	445947.87	652033.64	N 32 13 31.73	W 103 58 31.29
	3372.00	0.29	213.32	3371.98	3.11	2.81	-2.39	0.25	3.69	319.56	445947.61	652033.51	N 32 13 31.73	W 103 58 31.29
	3467.00	0.81	244.23	3466.97	2.72	2.32	-3.13	0.61	3.89	306.49	445947.12	652032.77	N 32 13 31.72	W 103 58 31.30
	3561.00	1.54	241.13	3560.95	2.07	1.42	-4.83	0.78	5.06	286.33	445946.22	652031.07	N 32 13 31.71	W 103 58 31.32
	3656.00	2.12	252.31	3655.90	1.32	0.77	-7.63	1.22	7.63	272.00	445945.07	652028.27	N 32 13 31.70	W 103 58 31.30
	3751.00	2.97	251.93	3750.81	0.58	-1.03	-11.64	0.89	11.69	264.94	445943.77	652024.26	N 32 13 31.69	W 103 58 31.40
	3845.00	3.51	244.59	3844.66	-0.71	-3.02	-16.55	0.72	16.83	259.66	445941.78	652019.35	N 32 13 31.67	W 103 58 31.45
	3940.00	4.20	246.05	3939.44	-2.54	-5.68	-22.36	0.73	23.07	255.74	445939.12	652015.54	N 32 13 31.64	W 103 58 31.52
	4034.00	5.22	242.72	4033.12	-4.91	-9.04	-29.31	1.12	30.67	252.86	445935.76	652006.59	N 32 13 31.61	W 103 58 31.60
	4129.00	6.01	244.49	4127.67	-7.85	-13.16	-37.64	0.85	39.87	250.73	445931.64	651998.27	N 32 13 31.57	W 103 58 31.70
	4224.00	7.25	247.22	4222.03	-17.62	-40.66	-50.81	0.81	49.62	249.11	445927.18	651986.22	N 32 13 31.54	W 103 58 31.70
	4318.00	8.25	246.15	4315.17	-14.24	-22.64	-59.29	1.08	63.47	249.11	445922.17	651976.61	N 32 13 31.48	W 103 58 31.95
	4413.00	8.25	246.40	4409.19	-17.96	-28.12	-71.77	0.04	77.09	248.60	445916.68	651964.13	N 32 13 31.42	W 103 58 32.10
	4507.00	8.59	245.80	4502.17	-21.74	-33.70	-84.36	0.37	90.84	248.22	445911.10	651951.55	N 32 13 31.37	W 103 58 32.24
	4602.00	9.16	245.86	4596.04	-25.84	-39.70	-97.73	0.60	105.49	247.89	445905.10	651938.18	N 32 13 31.31	W 103 58 32.40
	4697.00	10.15	246.10	4689.69	-30.26	-46.18	-112.28	1.04	121.41	247.64	445898.62	651923.63	N 32 13 31.24	W 103 58 32.57
	4792.00	13.29	245.73	4782.70	-35.56	-54.70	-130.12	1.35	140.70	247.81	445891.27	651905.79	N 32 13 31.19	W 103 58 32.70
	4886.00	14.17	249.42	4874.01	-40.10	-61.50	-150.96	0.95	163.00	247.83	445883.30	651894.95	N 32 13 31.09	W 103 58 33.02
	4981.00	13.78	247.34	4966.20	-45.52	-69.95	-172.28	0.67	185.94	247.90	445874.86	651863.63	N 32 13 31.01	W 103 58 33.27
	5076.00	13.34	246.10	5058.55	-51.42	-78.75	-192.74	0.56	208.21	247.78	445866.06	651843.17	N 32 13 30.93	W 103 58 33.51
	5171.00	13.47	246.84	5150.96	-57.34	-87.54	-212.94	0.23	230.23	247.65	445857.27	651822.98	N 32 13 30.84	W 103 58 33.74
	5265.00	13.04	245.56	5242.46	-63.23	-96.23	-232.66	0.55	251.77	247.53	445848.57	651803.26	N 32 13 30.75	W 103 58 33.97
	5360.00	13.59	246.79	5343.91	-69.22	-104.01	-252.67	0.73	273.65	247.53	445839.74	651783.25	N 32 13 30.71	W 103 58 34.21
	5454.00	12.80	246.05	5426.42	-74.65	-113.31	-272.48	0.89	295.13	247.42	445831.50	651763.44	N 32 13 30.59	W 103 58 34.50
	5549.00	12.71	249.46	5519.08	-79.49	-120.91	-292.03	0.34	316.07	247.51	445823.90	651743.89	N 32 13 30.51	W 103 58 34.66
	5644.00	13.90	249.51	5611.53	-84.25	-128.57	-312.50	1.25	337.92	247.64	445816.24	651723.42	N 32 13 30.44	W 103 58 34.90
	5738.00	13.05	249.46	5702.94	-89.03	-136.25	-333.02	0.90	359.81	247.75	445808.56	651702.91	N 32 13 30.36	W 103 58 35.14</

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100R)	Closure (ft)	Closure Azimuth (°)	Northing (NUS)	Easting (EUS)	Latitude (N/S ° ' '')	Longitude (W/E ° ' '')
Actual KOP	9519.00	14.00	252.04	9382.44	-247.56	-410.24	-1151.31	0.13	1222.21	250.39	445534.60	650884.68	N 32 13 27.68	W 103 58 44.66
	9614.00	14.08	252.97	9474.61	-251.39	-417.16	-1173.29	0.25	1245.24	250.43	445527.67	650862.71	N 32 13 27.81	W 103 58 44.93
	9689.00	13.78	252.11	9547.40	-254.38	-422.58	-1190.51	0.49	1263.28	250.46	445522.25	650845.48	N 32 13 27.56	W 103 58 45.14
	9770.10	14.45	261.80	9626.06	-256.10	-426.99	-1209.72	3.02	1282.86	250.56	445517.84	650826.28	N 32 13 27.51	W 103 58 45.36
	9775.00	14.50	262.35	9630.81	-256.10	-427.16	-1210.93	3.02	1284.06	250.57	445517.67	650825.06	N 32 13 27.51	W 103 58 45.37
	9870.00	25.15	303.28	9720.44	-242.65	-417.60	-1239.80	17.80	1308.24	251.39	445527.24	650796.19	N 32 13 27.61	W 103 58 45.71
	9965.00	31.74	316.83	9804.21	-208.87	-388.23	-1273.85	9.67	1331.70	253.05	445556.60	650762.15	N 32 13 27.99	W 103 58 46.10
	10059.00	37.39	325.63	9881.44	-163.05	-346.58	-1306.92	8.01	1352.10	255.15	445598.25	650729.08	N 32 13 28.31	W 103 58 46.49
	10154.00	43.65	333.15	9953.66	-106.12	-293.44	-1338.07	8.35	1369.86	257.63	445651.39	650697.94	N 32 13 28.84	W 103 58 46.85
	10249.00	47.46	340.71	10020.22	-40.72	-231.08	-1364.47	6.95	1383.90	260.39	445713.74	650671.54	N 32 13 29.46	W 103 58 47.15
Wolfcamp Intersection	10343.00	50.79	349.69	10081.80	29.72	-162.47	-1382.45	8.04	1391.96	263.30	445782.35	650653.56	N 32 13 30.14	W 103 58 47.36
	10391.36	51.64	353.94	10112.10	67.39	-125.17	-1387.81	7.07	1393.44	264.85	445819.64	650648.20	N 32 13 30.50	W 103 58 47.42
	10398.00	51.77	354.51	10116.22	72.60	-119.99	-1388.33	7.07	1393.57	265.06	445824.82	650647.68	N 32 13 30.56	W 103 58 47.43
	10438.00	52.60	357.93	10140.71	104.11	-98.46	-1390.42	7.07	1393.22	266.36	445856.64	650645.60	N 32 13 30.87	W 103 58 47.45
	10533.00	62.44	0.18	10191.70	183.54	-8.44	-1391.64	10.55	1391.67	269.65	445936.38	650644.37	N 32 13 31.66	W 103 58 47.46
	10627.00	72.95	2.57	10227.33	269.22	78.37	-1389.49	11.42	1391.70	273.23	446023.17	650646.52	N 32 13 32.52	W 103 58 47.43
	10722.00	86.30	4.53	10244.41	360.58	171.42	-1383.68	14.20	1394.26	277.06	446116.21	650652.33	N 32 13 33.44	W 103 58 47.36
	10817.00	95.10	2.68	10233.75	453.56	266.13	-1377.72	9.47	1403.18	280.93	446210.93	650658.29	N 32 13 34.38	W 103 58 47.29
	10911.00	91.63	358.42	10237.23	546.34	359.93	-1376.82	5.84	1423.09	284.65	446304.70	650659.19	N 32 13 35.30	W 103 58 47.27
	10975.00	91.51	357.68	10235.97	609.97	423.86	-1379.00	1.17	1442.67	287.09	446368.63	650657.01	N 32 13 35.94	W 103 58 47.30
100' FSL Crossing	11019.00	91.08	356.95	10234.98	653.78	467.80	-1381.06	1.93	1458.14	288.71	446412.57	650654.95	N 32 13 36.37	W 103 58 47.32
	11113.00	91.51	357.38	10232.85	747.38	561.67	-1385.71	0.65	1495.21	292.06	446506.42	650650.30	N 32 13 37.30	W 103 58 47.37
	11208.00	91.86	359.99	10230.06	841.70	656.59	-1387.89	2.77	1535.36	295.32	446601.34	650648.12	N 32 13 38.24	W 103 58 47.39
	11303.00	89.15	1.73	10229.22	935.57	751.56	-1386.46	3.39	1577.06	298.46	446696.30	650649.55	N 32 13 39.18	W 103 58 47.37
	11397.00	89.06	4.82	10230.69	1027.76	845.39	-1381.09	3.29	1619.29	301.47	446790.12	650654.92	N 32 13 40.11	W 103 58 47.31
	11491.00	88.74	6.75	10231.68	1116.07	938.90	-1371.62	1.67	1662.18	304.39	446883.62	650654.39	N 32 13 41.03	W 103 58 47.19
	11586.00	91.02	5.18	10231.05	1211.28	1033.38	-1361.75	2.13	1709.45	307.19	446978.10	650674.26	N 32 13 41.97	W 103 58 47.07
	11680.00	91.28	2.36	10229.16	1303.30	1127.15	-1355.57	3.01	1762.96	309.74	447071.86	650680.44	N 32 13 42.90	W 103 58 47.00
	11774.00	91.59	0.77	10226.81	1395.98	1221.08	-1353.00	1.72	1822.54	312.07	447165.78	650683.01	N 32 13 43.83	W 103 58 46.96
	11868.00	90.45	359.45	10225.13	1489.04	1315.06	-1352.82	1.86	1886.66	314.19	447259.76	650683.19	N 32 13 44.75	W 103 58 46.96
Exit Target Box	11962.00	89.26	358.52	10225.37	1582.36	1409.04	-1354.49	1.61	1954.49	316.13	447353.73	650681.52	N 32 13 45.69	W 103 58 46.97
	12056.00	88.13	356.96	10227.51	1675.87	1502.94	-1358.87	2.05	2025.71	317.90	447447.62	650677.82	N 32 13 46.57	W 103 58 47.01
	12151.00	87.69	358.24	10230.98	1770.36	1597.79	-1362.17	1.42	2099.63	319.55	447542.46	650673.84	N 32 13 47.55	W 103 58 47.06
	12246.00	88.13	0.43	10234.44	1864.53	1692.71	-1363.27	2.35	2173.43	321.15	447637.38	650672.74	N 32 13 48.49	W 103 58 47.07
	12340.00	88.70	0.94	10237.04	1957.44	1786.67	-1362.14	0.81	2246.69	322.68	447731.33	650673.86	N 32 13 49.42	W 103 58 47.05
	12435.00	87.73	359.85	10240.00	2051.39	1881.62	-1361.49	1.54	2322.53	324.11	447826.27	650674.52	N 32 13 50.36	W 103 58 47.04
	12530.00	89.86	1.07	10242.00	2145.34	1976.59	-1360.73	2.58	2399.68	325.46	447921.23	650675.28	N 32 13 51.30	W 103 58 47.02
	12625.00	89.04	0.76	10242.91	2239.21	2071.57	-1359.21	0.92	2477.67	326.73	448016.21	650676.80	N 32 13 52.24	W 103 58 47.00
	12719.00	87.92	0.50	10245.40	2332.18	2165.53	-1358.55	1.41	2556.40	327.98	448110.16	650677.46	N 32 13 53.17	W 103 58 46.99
	12814.00	90.50	1.28	10246.71	2426.10	2260.51	-1357.44	2.01	2636.77	329.02	448205.13	650678.56	N 32 13 54.11	W 103 58 46.98
Enter Target Box	12908.00	88.32	0.25	10247.68	2519.01	2354.49	-1356.19	2.56	2717.14	330.06	448299.10	650679.82	N 32 13 55.04	W 103 58 46.96
	12939.00	87.86	0.16	10248.71	2549.68	2385.47	-1356.08	1.52	2743.98	330.38	448330.08	650679.93	N 32 13 55.35	W 103 58 46.96
	13003.00	86.90	359.98	10251.64	2612.99	2449.40	-1356.00	1.52	2799.70	331.03	448394.01	650680.01	N 32 13 55.98	W 103 58 46.95
	13098.00	86.60	0.01	10257.03	2706.93	2544.25	-1356.01	0.32	2883.05	331.94	448488.85	650680.00	N 32 13 56.92	W 103 58 46.95
	13192.00	86.35	0.49	10259.80	2799.87	2638.07	-1356.07	0.67	2965.98	332.98	448582.66	650680.41	N 32 13 57.91	W 103 58 46.94
	13287.00	86.08	1.36	10260.98	2893.46	2732.85	-1354.07	0.96	3049.91	333.64	448677.44	650681.94	N 32 13 58.78	W 103 58 46.92
	13382.00	86.13	1.94	10275.53	2986.92	2827.59	-1351.34	0.61	3133.91	334.46	448772.17	650684.67	N 32 13 59.72	W 103 58 46.88
	13477.00	85.41	3.13	10282.54	3080.09	2922.24	-1347.15	1.46	3217.81	335.25	448866.81	650688.86	N 32 14 0.66	W 103 58 46.83
	13563.00	85.95	1.25	10289.02	3164.50	3007.93	-1343.87	2.27	3294.48	335.93	448952.49	650692.14	N 32 14 1.51	W 103 58 46.79
	13658.00	88.14	0.28	10293.92	3258.28	3102.79	-1342.60	2.52	3380.81	336.60	449047.34	650693.40	N 32 14 2.44	W 103 58 46.77
100' FNL Crossing	13752.00	86.67	0.25	10297.61	3351.48	3196.76	-1343.52	3.47	3467.24	337.20	449141.31	650694.12	N 32 14 3.37	W 103 58 46.75
	13847.00	92.29	356.86	10294.09	3445.98	3291.66	-1347.19	3.26	3556.68	337.74	449236.20	650698.82	N 32 14 4.31	W 103 58 46.82
	13941.00	92.46	356.49	10290.19	3539.59	3385.43	-1352.55	3.03	3645.61	338.22	449329.96	650683.46	N 32 14 5.24	W 103 58 46.88
	14036.00	92.15	355.56	10286.37	3634.29	3480.12	-1359.13	1.03	3736.10	338.67	449424.65	650676.88	N 32 14 6.18	W 103 58 46.95
	14062.00	91.46	354.54	10285.55	3660.24	3506.01	-1361.37	4.73	3761.04	338.78	449450.53	650674.63	N 32 14 6.43	W 103 58 46.97
	14131.00	89.62	351.84	10284.90	3729.22	3574.51	-1369.55	4.73	3827.90	339.04	449519.03	650686.45	N 32 14 7.11	W 103 58 47.07
	14225.00	89.32	10286.37	3867.18	3867.38	3684.08	-1384.08	2.09	3919.19	339.02	449611.87	650691.92	N 32 14 8.55	W 103 58 47.23
	14324.00	90.24	353.17	10287.79	3918.16	3761.36	-1397.68	3.57	4012.65	339.62	449705.86	650693.33	N 32 14 9.96	W 103 58 47.39
	14415.00	90.89	355.98	10286.85	4013.06	3855.92	-1406.66	3.04	4104.49	339.96	449800.42	650629.35	N 32 14 9.90	W 103 58 47.49
	14509.00	91.11	359.73	10285.21	4106.55	3949.82	-1410.18	4.00	4194.01	340.35	449894.31	650625.83	N 32 14 10.83	W 103 58 47.52
Final MWD	14604.00	91.54	2.32	10283.01	4200.36	4044.78	-1408.48	2.76	4282.99	340.80	449989.26	650627.53	N 32 14 11.77	W 103 58 47.50
	14698.00	92.14	0.82	10279.99	4293.02	4138.69	-1405.90	1.72	4370.96	341.24	450083.16	650630.11	N 32 14 12.70	W 103 58 47.47
	14793.00	92.93	359.72	10275.79	4386.95	4233.59	-1405.46	1.42	4460.79	341.64	450178.06	650630.55	N 32 14 13.64	W 103 58 47.46
	14887.00	92.67	0.33	10279.40	4479.20	4327.45	-1405.42	1.47	4549.97					

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Closure (ft)	Closure Azimuth (°)	Northing (ftUS)	Easting (ftUS)	Latitude (N/S ° ' ")	Longitude (E/W ° ' ")
Survey Type:	Def Survey													
Survey Error Model:	ISCWSA Rev 3 *** 3-D 95.000% Confidence 2.7955 sigma													
Survey Program:														
Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size (in)	Casing Diameter (in)	Survey Tool Type	Borehole / Survey						
	1	0.000	25.000	1/98.425	26.400	26.400	GYD_GC+DROP+OH-Depth Only	Tails CC 10_3 Federal Com 31H / Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909MD						
	1	25.000	25.000	Act Stns	26.400	26.400	GYD_GC+DROP+OH-Depth Only	Tails CC 10_3 Federal Com 31H / Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909MD						
	1	25.000	538.470	Act Stns	26.400	26.400	GYD_GC+DROP+OH	Tails CC 10_3 Federal Com 31H / Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909MD						
	1	538.470	20909.000	Act Stns	26.400	26.400	A010Mb_MWD+IFR1+SAG+MS	Tails CC 10_3 Federal Com 31H / Oxy Tails CC 10_3 Federal Com 31H Gyro+MWD 0' to 20909MD						

Intent ☐ As Drilled ☐

API #		
Operator Name:	Property Name:	Well Number

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
Latitude					Longitude				NAD

Is this well the defining well for the Horizontal Spacing Unit? ☐Is this well an infill well? ☐

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018

Well Name: TAILS CC 10_3 FED COM	Well Location: T24S / R29E / SEC 10 / SESW / 32.225471 / -103.97535	County or Parish/State: EDDY / NM
Well Number: 31H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM81616	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001548881	Well Status: Drilling Well	Operator: OXY USA INCORPORATED

Subsequent Report

Sundry ID: 2689259	
Type of Submission: Subsequent Report	Type of Action: Workover Operations
Date Sundry Submitted: 08/25/2022	Time Sundry Submitted: 03:37
Date Operation Actually Began: 05/05/2022	

Actual Procedure: RUPU 05/05/22, RIH & clean out to PBTD @ 20861', pressure test casing to 6000# for 30 min, good test. RIH & perf @ 20763-10463' Total 1462 holes. Frac in 43 stages w/ 256723BBL Produced Water + 253973BBL Brackish Water (> 1,000 mg/I TDS and 10,000 mg/I TDS) w/ 25676294# sand, RD Liberty 05/23/22. Well ready to produce 05/28/22. 08/09/22 RIH with 2-3/8" L80 tbg & gas lift set @ 9977', RD 08/10/22. Formation Tops for this completion are as follows: RUSTLER 196'M 196'V SALADO 474'M 474'V CASTILE 1384'M 1384'V DELAWARE 2962'M 2962'V BELL CANYON 2985'M 2985'V CHERRY CANYON 3847'M 3847'V BRUSHY CANYON 5127'M 5117'V BONE SPRING 6768'M 6705'V 1ST BONE SPRING 7802'M 7711'V 2ND BONE SPRING 8635'M 8524'V 3RD BONE SPRING 9743'M 9599'V WOLFCAMP 10141'M 9944'V

Received by OCD: 8/26/2022 9:18:53 PM

Page 9 of 14

Well Name: TAILS CC 10_3 FED COM	Well Location: T24S / R29E / SEC 10 / SESW / 32.225471 / -103.97535	County or Parish/State: EDDY / NM
Well Number: 31H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM81616	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001548881	Well Status: Drilling Well	Operator: OXY USA INCORPORATED


Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JANA MENDIOLA	Signed on: AUG 25, 2022 03:36 PM
Name: OXY USA INCORPORATED	
Title: Regulatory Coordinator	
Street Address: PO BOX 50250	
City: Midland	State: TX
Phone: (432) 685-5936	
Email address: Janalyn_mendiola@oxy.com	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505			Form C-105 Revised April 3, 2017													
WELL COMPLETION OR RECOMPLETION REPORT AND LOG							1. WELL API NO. 30-015-48881											
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)							2. Type of Lease ☐ STATE ☐ FEE ☒ FED/INDIAN 3. State Oil & Gas Lease No.											
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER							5. Lease Name or Unit Agreement Name TAILS CC 10-3 FEDERAL COM 6. Well Number: 31H											
8. Name of Operator: OXY USA INC.				9. OGRID: 16696														
10. Address of Operator: P.O. BOX 50250 MIDLAND, TX 79710				11. Pool name or Wildcat PURPLE SAGE WOLFCAMP														
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County								
Surface:	N	10	24S	29E		220	SOUTH	1725	WEST	EDDY								
BH:	L4	3	24S	29E		40	NORTH	339	WEST	EDDY								
13. Date Spudded 12/18/21	14. Date T.D. Reached 03/30/2022	15. Date Rig Released 04/02/2022			16. Date Completed (Ready to Produce) 05/28/2022			17. Elevations (DF and RKB, RT, GR, etc.) 2940' GL										
18. Total Measured Depth of Well 20909'M 10265'V			19. Plug Back Measured Depth 20861'M 10264'V			20. Was Directional Survey Made? YES		21. Type Electric and Other Logs Run CBL										
22. Producing Interval(s), of this completion - Top, Bottom, Name 10463-20763' Wolfcamp																		
23. CASING RECORD (Report all strings set in well)																		
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED								
10.75" J55		45.5		520'		14.75"		515sx-surf circ										
7.625" HCL80		26.4		9699'		9.875"		2623sx-surf										
5.5" P110CY		20		20889'		6.75"		872sx-TOC@9199'										
24. LINER RECORD																		
SIZE	TOP	BOTTOM		SACKS CEMENT		SCREEN		25. TUBING RECORD										
								SIZE										
								2.375"										
								DEPTH SET										
								9977'										
26. Perforation record (interval, size, and number) 10463-20763' Total 1462 holes, Hole Size=0.42						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>10463-20763'</td> <td>256723BBL Produced Water + 253973BBL Brackish Water w/ 25676294# sand</td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </table>					DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	10463-20763'	256723BBL Produced Water + 253973BBL Brackish Water w/ 25676294# sand				
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED																	
10463-20763'	256723BBL Produced Water + 253973BBL Brackish Water w/ 25676294# sand																	
28. PRODUCTION																		
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)												
06/04/2022		Gas Lift				Prod.												
Date of Test	Hours Tested	Choke Size	Prod'n For	Oil - Bbl	Gas - MCF	Water - Bbl.	Gas - Oil Ratio											
07/10/2022	24 hrs.	128/128	Test Period	4015	6810	6770	1696											
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (Corr.)												
	860		4015	6810	6770													
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD							30. Test Witnessed By											
31. List Attachments WBD																		
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.							33. Rig Release Date:											
34. If an on-site burial was used at the well, report the exact location of the on-site burial:																		
Latitude _____ Longitude _____ NAD83																		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief																		
Printed																		
Signature: 		Name: <u>Jana Mendiola</u>			Title: <u>Sr. Regulatory Analyst</u>			Date: <u>08/26/2022</u>										
E-mail Address: <u>janalyn_mendiola@oxy.com</u>																		

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Rustler 196'	T. Bell Canyon 2985'	T. Ojo Alamo	T. Penn A"
T. Salado 474'	T. Strawn	T. Kirtland	T. Penn. "B"
T. Castile 1384'	T. Atoka	T. Fruitland	T. Penn. "C"
T. Delaware 2962'	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. Cherry Canyon 3847'	T. Devonian	T. Cliff House	T. Leadville
T. Brushy Canyon 5127'	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs 6768'	T. Todilto	
T. Abo	T. 1 st Bone Springs 7802'	T. Entrada	
T. Wolfcamp 10141'	T. 2 nd Bone Springs 8635'	T. Wingate	
T. Penn	T. 3 rd Bone Springs 9743'	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....

No. 2, from.....to.....

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.


No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

OXY USA Inc.
Tails CC 10-3 Federal Com 31H
API No. 30-015-48881



14-3/4" hole @ 558'
10-3/4" csg @ 520'
w/ 515sx-TOC-Surf Circ.

9-7/8" hole @ 9719'
7-5/8" csg @ 9699'
w/ 2623sx-TOC-Surf Circ.

6-3/4" hole @ 20909'
5-1/2" csg @ 20889'
w/ 872sx-TOC-9199'

2-3/8" tbg w/ gas lift @ 9977'

Perfs @ 10463-20763'

TD- 20909'M 10265'V

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 138616

ACKNOWLEDGMENTS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 138616
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 138616

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 138616
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
Ilowe	COA: (1) File 3160-4 Completion Report within 10 days to NMOCD after BLM approval. (2) File all Logs	9/20/2022