For State Use Only:

APPROVED BY:

Patricia L Martinez

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 313305 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-49176 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS HAMMS STATE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 223H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location Unit Letter \underline{M} : $\underline{1071}$ feet from the \underline{S} line and feet 495 from the W 27E NMPM Township 23S Range County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3189 GR Pit or Below-grade Tank Application or Closure ___ Distance from nearest fresh water well__ __ Depth to Groundwater___ _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casings See Attached 2/7/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Yield Open Size Size lb/ft TOC Held Drop Hole 02/07/22 Surf FreshWater 17.5 13.375 54.5 J55 0 349 450 1.34 С 1500 0 Ν 03/07/22 Int1 Brine 9.875 7.625 29.7 P110 0 9150 1172 1.35 TXI 1500 0 Ν 03/23/22 OilBasedMud 20 P110 Prod 6.75 5.5 8159 14489 476 1.32 D Ν I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 4/20/2022 Type or print name Christian Combs E-mail address ccombs@taprk.com Telephone No. 720-360-4028

TITLE

DATE

10/13/2022 8:19:14 AM

Hamms State 223H – Intermediate and Production

3/3/2022: Test BOPS. Drill 9.875 intermediate hole to 9259 ft.

3/7/2022: Run 7.625 inch 29.7 lb P-110 intermediate casing to 9150 ft. Pump 20 bbls chem wash, 20 bbls vis water, followed by 878 sks of 10.5 ppg lead cmt, 294 sks of 13.2 ppg tail cmt. Drop plug and displace with 418 bbls of freshwater. 258 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test.

3/19/2022: Drill 6.75 inch production hole to 14505 ft

3/23/2022: Run 5.5 inch 20 lb P-110 production casing to 14489 ft MD. Pump 40 bbls MPE, 102 bbls MRF, then 476 sks of 14.5 ppg tail cmt. Drop plug and displace with 10 bbls sugar water, 211 bbls brine. 10 bbls MPE returned to surface. Est TOC at 8159 ft.

Intermediate Casing Details: Casing ran: 3/7/2022, Fluid Type Brine, Hole 9.875 inch to 9259 ft, Csg Size 7.625 inch, Weight 29.7 lbs, Grade P-110, Est TOC 0 ft, Depth set 9150 ft, Cement 1172 sks, Yield 3.56 lead/1.35 tail, Class TXI, Pressure Held 1500 psi, Pres Drop 0.

Production Casing details: Casing Date: 3/23/2022, Fluid Type Oil Based Mud, Hole 6.75 inch hole to 14505 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 14489 ft, EST TOC 8159 ft, Cement 476 sacks, yield 1.32 tail, Class D.

3/22/2022: TD Reached at 14505 ft MD, 9827 ft TVD. Plug Back Measured depth at 14443 ft MD, 9825 ft TVD. Rig Release on 3/24/2022 at 17:00.