Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED

Expires: October 31, 20
5 Lease Serial No.

BURE	AU OF LAND MANAGEMENT		3. Lease Seriai No.	MULTIPLE	
SUNDRY NO	OTICES AND REPORTS ON W	/ELLS	6. If Indian, Allottee	6. If Indian, Allottee or Tribe Name	
	rm for proposals to drill or to se Form 3160-3 (APD) for suc	MULTIPLE			
SUBMIT IN TR	RIPLICATE - Other instructions on pag		eement, Name and/or No.		
1. Type of Well			MULTIPLE		
Oil Well Gas We	ll Other		8. Well Name and No	O. MULTIPLE	
2. Name of Operator EOG RESOURCE	ES INCORPORATED		9. API Well No. MUI	_TIPLE	
3a. Address 1111 BAGBY SKY LOBB		(include area code			
4. Location of Well (Footage, Sec., T.,R.,, MULTIPLE	M., or Survey Description)		11. Country or Parish MULTIPLE	n, State	
12. CHEC	K THE APPROPRIATE BOX(ES) TO INI	DICATE NATURE	OF NOTICE, REPORT OR OT	THER DATA	
TYPE OF SUBMISSION		TYI	PE OF ACTION		
✓ Notice of Intent Subsequent Report	Casing Repair New	raulic Fracturing Construction	Production (Start/Resume) Reclamation Recomplete	Water Shut-Off Well Integrity Other	
Final Abandonment Notice		and Abandon Back	Temporarily Abandon Water Disposal		
the Bond under which the work will be completion of the involved operations completed. Final Abandonment Notice is ready for final inspection.) EOG Resources Inc. (EOG) responded in the second support of the second supp	pe perfonned or provide the Bond No. on fig. If the operation results in a multiple consess must be filed only after all requirement spectfully submits a batch sundry for the #715H #716H #736H #737H	file with BLM/BIA npletion or recomp is, including reclan e wells below:	Required subsequent reports m letion in a new interval, a Form	3160-4 must be filed once testing has been	
14. I hereby certify that the foregoing is tr STAR HARRELL / Ph: (432) 848-916	, , , , ,	Regulatory Title	/ Specialist		
Signature I		Date	12/05/2	2022	
	THE SPACE FOR FED	ERAL OR ST	ATE OFICE USE		
Approved by					
KEITH P IMMATTY / Ph: (575) 988-	4722 / Approved	Title ENG	INEER	12/05/2022 Date	
	d. Approval of this notice does not warran uitable title to those rights in the subject leact operations thereon.		RLSBAD		
	U.S.C Section 1212, make it a crime for an		ly and willfully to make to any d	department or agency of the United States	

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

(Form 3160-5, page 2)

Additional Information

Batch Well Data

JEFE 29 FED COM 737H, US Well Number: 3002548850, Case Number: NMNM108971, Lease Number: NMNM108971, Operator: EOG RESOURCES INCORPORATED

JEFE 29 FED COM 736H, US Well Number: 3002548843, Case Number: NMNM108971, Lease Number: NMNM108971, Operator:EOG RESOURCES INCORPORATED

JEFE 29 FED COM 715H, US Well Number: 3002548857, Case Number: NMNM108971, Lease Number: NMNM108971, Operator: EOG RESOURCES INCORPORATED

JEFE 29 FED COM 716H, US Well Number: 3002548858, Case Number: NMNM108971, Lease Number: NMNM108971, Operator:EOG RESOURCES INCORPORATED



Jefe 29 Fed Com Batch

Revised Permit Information 12/02/2022:

Well Name: Jefe 29 Fed Com Batch

Location: SHL: Section 29, T-25-S, R-32-E, Lea Co., N.M. BHL: Section 32, T-25-S, R-32-E, Lea Co., N.M.

Casing Design A

Hole	Interval MD		Interva	ıl TVD	Csg				
Size	From (ft)	To (ft)	From (ft)	To (ft)	OD	Weight	Grade	Conn	
12-1/4"	0	1,190	0	1,190	9-5/8"	36#	J-55	LTC	
8-3/4"	0	10,982	0	10,900	7-5/8"	29.7#	HCP-110	FXL	
6-3/4"	0	10,482	0	10,400	5-1/2"	20#	P110-EC	DWC/C IS MS	
6-3/4"	10,482	10,982	10,400	10,900	5-1/2"	20#	P110-EC	Vam Sprint SF	
6-3/4"	10,982	19,616	10,900	11,970	5-1/2"	20#	P110-EC	DWC/C IS MS	

Variance is requested to waive the centralizer requirements for the 7-5/8" casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4 hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 5-1/2" casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive the annular clearance requirements for the 5-1/2" casing by 7-5/8" casing annulus to the proposed top of cement.

EOG requests permission to allow deviation from the 0.422" annulus clearance requirement from Onshore Order #2 under the following conditions:

- Annular clearance to meet or exceed 0.422" between intermediate casing ID and production casing coupling only on the first 500' overlap between both casing strings.
- Annular clearance less than 0.422" is acceptable for the production open hole section.

Cementing Program:

		Wt.	Yld	Slurry Description		
Depth	No. Sacks	ppg	Ft3/sk	Siulty Description		
1,190' 9-5/8"	330	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl2 + 0.25 lb/sk Cello- Flake (TOC @ Surface)		
	80	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 990')		
10,900' 7-5/8"	500	14.2	1.11	1st Stage (Tail): Class C + 0.6% Halad-9 + 0.45% HR-601 + 3% Microbond (TOC @ 6,675')		
	1140	14.8	1.5	2nd Stage (Bradenhead squeeze): Class C + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (TOC @ surface)		
19,616' 5-1/2"	800	14.2	1.31	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 10,400')		



Jefe 29 Fed Com Batch

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Pre-Mag-M	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

EOG requests variance from minimum standards to pump a two stage cement job on the 7-5/8" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon (6,875') and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. If necessary, a top out consisting of 143 sacks of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yld, 12.91 ppg) will be executed as a contingency. Top will be verified by Echo-meter.

EOG will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program.

EOG will report to the BLM the volume of fluid (limited to 5 bbls) used to flush intermediate casing valves following backside cementing procedures.

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,190'	Fresh - Gel	8.6-8.8	28-34	N/c
1,190' – 10,900' Brine		10.0-10.2	28-34	N/c
10,900' - 11,579'	Oil Base	8.7-9.4	58-68	N/c - 6
11,579' – 19,616'	Oil Base	10.0-14.0	58-68	4 - 6



Jefe 29 Fed Com Batch

Wellhead & Offline Cementing:

EOG Resources Inc. (EOG) respectfully requests a variance from the minimum standards for well control equipment testing of Onshore Order No. 2 (item III.A.2.a.i) to allow a testing schedule of the blow out preventer (BOP) and blow out prevention equipment (BOPE) along with Batch Drilling & Offline cement operations to include the following:

- Full BOPE test at first installation on the pad.
- Full BOPE test every 30 days per Onshore Order No. 2.
- Function test BOP elements per Onshore Order No. 2.
- Break testing BOP and BOPE coupled with batch drilling operations and option to
 offline cement and/or remediate (if needed) any surface or intermediate sections,
 according to attached offline cementing support documentation.
- After the well section is secured, the BOP will be disconnected from the wellhead and walked with the rig to another well on the pad.
- TA cap will also be installed per Wellhead vendor procedure and pressure inside
 the casing will be monitored via the valve on the TA cap as per standard batch
 drilling ops.
- See attached "EOG BLM Variance 3a -Offline Cement Intermediate Operational Procedure"



Jefe 29 Fed Com Batch

Revised Wellbore


KB: 3371'

GL: 3346'

Section 29

T-25-S, R-32-E

API: 30-025-****



District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 163841

CONDITIONS

Operator:	OGRID:
EOG RESOURCES INC	7377
P.O. Box 2267	Action Number:
Midland, TX 79702	163841
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	12/23/2022