

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-35253
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Texaco BE
8. Well Number 8
9. OGRID Number 328947
10. Pool name or Wildcat LOCO HILLS; GLORIETA-YESO

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other: Injection	
2. Name of Operator Spur Energy Partners LLC	
3. Address of Operator 9655 Katy Freeway, Ste. 500, Houston, TX 77024	
4. Well Location Unit Letter <u>B</u> : <u>330</u> feet from the <u>NORTH</u> line and <u>2310</u> feet from the <u>EAST</u> line Section <u>16</u> Township <u>17S</u> Range <u>30E</u> NMPM County <u>Eddy</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3680' GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/13/22: MIRU then ND WH & NU Bop, having trouble trying to release pkr then POOH w/ tbg & pkr then SDFN.

10/14/22: RU WL then RIH & set CIBP at 4272', POOH & RD WL; POOH w/ tbg then RU WL to run CBL & RD WL, RIH open ended to top of CIBP & SDFN.

10/17/22: Test CIBP to 500psi- held good for 30 min then circulate well w/ 70bbbls mud; **PLUG #1 – mix & pump 25sxs Class C cement** from eot at 4272' to toc at 4020' then POOH to woc, RIH w/ tbg & tag **PLUG #1 at 4010'** then pull up tbg to 2120'; **PLUG #2 – mix & pump 25sxs Class C cement** from eot at 2120' to toc at 1868' then SDFN to woc.

10/18/22: POOH to get pkr out then RIH & tag **PLUG #2 at 1870'**; pull up to next plug & spoke to OCD about combining plugs #3 & #4; **PLUG #3 – mix & pump 45sxs Class C cement** from eot at 1415' to toc at 960' then POOH to woc; RIH w/ tbg & tag **PLUG #3 at 952'** then pull up tbg for next plug; **PLUG #4 – mix & pump 25sxs Class C cement** from eot at 514' to toc at 262' then SDFN to woc.

10/19/22: RIH w/ tbg & tag **PLUG #4 at 289'**; RU WL then RIH & perforate at 180'; POOH & RD WL; RIH w/ tbg & pkr to check injection rate - no rate; notify OCD & they instructed to perforate again at 100'; RU WL then RIH & perforate at 100'; POOH & RD WL then RIH to check rate - no rate; notify OCD & they instructed us to set a balance plug from 230' to surface then LD tbg; **PLUG #5 – mix & pump 30sxs Class C Cement** from eot at 230' to surface then SDFN.

10/20/22: RD equipment then ND Bop & RDMO.

Spud Date:

Rig Release Date:

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sarah Chapman TITLE REGULATORY DIRECTOR DATE 01/05/2023

Type or print name SARAH CHAPMAN E-mail address: SCHAPMAN@SPUREENERGY.COM PHONE: 832-930-8664

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 1/19/2023

Texaco B5.8
9/9/2022 10:01:14 AMEddy County, NM
API# 30-015-35253SPUD DATE: 5/1/2007
CONVERT TO INJ: 8/1/2011perforations
at 180' + 100'13-3/8" CSG @ 413'
CMT w/ 928 SX8-5/8" CSG @ 1,365'
CMT w/ 600 SX

INJECTION PACKER @ ~4,267'

5-1/2" CSG @ 6,026'
CMT w/ 1,675 SX

CURRENT WBD

Plug #5-30sxs Class C
230'-surfaceplug #4-25sxs Class C
514'-289'Plug #3-45sxs Class C
1415'-952'Plug #2-25sxs Class C
2120'-1870'Plug #1-25sxs Class C
4272'-4010'**PERFS:**

4,367' - 4,681'

4,922' - 5,721'

CIBP at 4272'

12-12-07 Perf @ 4367'-4681', 1 SPF, 32 holes.
12-13-07 Acidize w/3,000 gals 15% HCL. Frac w/ 94,674 gals 40# linear gel; 31,626 gal 30# linear gel; 600# Scalesorb-3; 8,000# LiteProp 125 14/30. 67,442# 16/30 white sand; 13,953# SiberProp 16/30 resin coated. Flush w/4,200 gals laden fluid.

5-24-07 Perf w/ 2 SPF @ 5576' - 5721'. 50 holes.

5-25-07 Acidize w/ 2500 gals acid.

5-29-07 Frac 5576' - 5721' w/ 90,401 gals gel, 8000# LiteProp, 89,820# 16/30 sand.

5-30-07 Perf w/ 2 SPF 5310' - 5470'. 60 holes.

5-31-07 Acidize w/ 2500 gals acid.

6-01-07 Frac 5310' - 5470' w/ 8032# LiteProp, 88,500# 16/30 sand, & 92,577 gals 30# & 40# gel.

6-04-07 Perf w/ 2 SPF @ 4922' - 5204. 66 holes.

6-05-07 Acidize w/ 2500 gals acid.

6-06-07 Frac 4922' - 5204' w/ 8021# LiteProp, 89,800# 16/30 sand, & 99,334# 30# & 40# gel.

6-07-07 RIH w/ 181 jts 2-7/8" J55 tbg, SN @ 5739'. RIH w/ 2-1/2 x 2 x 24' pump. Hung well on.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 173162

CONDITIONS

Operator: Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024	OGRID: 328947
	Action Number: 173162
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	1/19/2023