

Sundry Print Report

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: SCHLITZ FED COM Well Location: T25S / R26E / SEC 16 / County or Parish/State: EDDY /

SESE / 33.1246797 / -104.2926126

Well Number: 156H Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM0019836 Unit or CA Name: Unit or CA Number:

US Well Number: 3001549974 Well Status: Drilling Well Operator: TAP ROCK

OPERATING LLC

Subsequent Report

Sundry ID: 2701502

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 11/04/2022 Time Sundry Submitted: 07:39

Date Operation Actually Began: 10/12/2022

Actual Procedure: Well spud on 10/12/2022 at 23:00 10/12/2022: Drill 17.5 inch surface hole to 538. 10/13/2022: Run 13.375 inch 54.5 lb J55 surface casing to 523 ft. Pump 20 bbls water spacer, followed by 495 sks of 14.8 ppg tail cmt. Drop plug and displace with 72 bbls brine. 50 bbls of cement returned back to surface. Pressure test casing to 1500 PSI for 30 minutes, good test. 10/14/2022: Test BOPS. Drill 12.25 intermediate hole to 2012 ft. 10/14/2022: Run 9.625 inch 40 lb J-55 intermediate casing to 1997 ft. Pump 20 bbls chem wash, 20 bbls vis spacer, followed by 370 sks of 12.8 ppg lead cmt, 210 sks of 14.8 ppg tail cmt. Drop plug and displace with 150 bbls of cut brine. 38 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1500 for 30 minutes, good test. 10/16/2022: Drill 8.75 inch production hole to 7319 then switch to 7.875 inch to 17721 ft. 10/27/2022: Run 5.5 inch 20 lb P-110 production casing to 17707 ft MD. Pump 40 bbls fresh water, then 425 sks of 10.5 ppg lead and 1690 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls sugar water and 371 bbls fresh water. 101 bbls cement returned to surface. Est TOC at 0 ft. Surface Casing Details: Casing ran: 10/23/2022, Fluid Type Fresh Water, Hole 17.5 inch, Csg Size 13.375 inch, Weight 54.5 lbs, Grade J55, Est TOC 0 ft, Depth set 523 ft, Cement 495 sacks, Yield 1.34 tail, Class C. Pressure test: 1500 PSI, Pressure Drop: 0. Intermediate Casing Details: Casing ran: 10/14/2022, Fluid Type Brine, Hole 12.25 inch to 2012, Csg Size 9.625 inch, Weight 40 lbs, Grade J-55, Est TOC 0 ft, Depth set 1997 ft, Cement 580 sks, Yield 1.86 lead/1.34 tail, Class C, Pressure Held 1500 psi, Pres Drop 0. Production Casing details: Casing Date: 10/27/2022, Fluid Type Oil Based Mud, Hole 8.75 inch hole to 7319 ft then switch to 7.875 inch to 17721 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 17707 ft, EST TOC 0 ft, Cement 2115 sacks, yield 4.11 lead/1.53 tail, Class 50/50 POZ tail. 10/25/2022: TD Reached at 17721 ft MD, 7644 ft TVD. Plug Back Measured depth at 17658 ft MD, 7648 ft TVD. Rig Release on 10/27/2022 at 16:00

Page 1 of 2

eived by OCD: 12/1/2022 11:03:43 AM Well Name: SCHLITZ FED COM

Lease Number: NMNM0019836

Well Location: T25S / R26E / SEC 16 /

SESE / 33.1246797 / -104.2926126

County or Parish/State: EDD 1/2

NM

Well Number: 156H

Type of Well: CONVENTIONAL GAS

Unit or CA Name:

Unit or CA Number:

Allottee or Tribe Name:

US Well Number: 3001549974

Well Status: Drilling Well

Operator: TAP ROCK OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JEFFREY TRLICA Signed on: NOV 04, 2022 07:39 AM

Name: TAP ROCK OPERATING LLC

Title: Regulatory Analyst

Street Address: 523 PARK POINT DRIVE SUITE 200

City: GOLDEN State: CO

Phone: (720) 772-5910

Email address: JTRLICA@TAPRK.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: Jonathon W Shepard

BLM POC Phone: 5752345972

Disposition: Accepted

Signature: Jonathon Shepard

BLM POC Title: Petroleum Engineer

BLM POC Email Address: jshepard@blm.gov

Disposition Date: 11/30/2022

Page 2 of 2

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 163006

CONDITIONS

Operator:	OGRID:
TAP ROCK OPERATING, LLC	372043
523 Park Point Drive	Action Number:
Golden, CO 80401	163006
	Action Type:
	[C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By		Condition Date
gramirez	PT details for the 5.5" casing must be submitted on the next drilling sundry.	1/27/2023