

<b>Well Name:</b> MOLLY PITCHER	<b>Well Location:</b> T30N / R14W / SEC 14 / SENE / 36.814243 / -108.27089	<b>County or Parish/State:</b> SAN JUAN / NM
<b>Well Number:</b> 4 SWD	<b>Type of Well:</b> INJECTION - ENHANCED RECOVERY	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM628	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 300453095400S1	<b>Well Status:</b> Abandoned	<b>Operator:</b> DUGAN PRODUCTION CORPORATION

**Subsequent Report**

**Sundry ID:** 2712839

**Type of Submission:** Subsequent Report

**Type of Action:** Plug and Abandonment

**Date Sundry Submitted:** 01/26/2023

**Time Sundry Submitted:** 04:11

**Date Operation Actually Began:** 12/27/2022

**Actual Procedure:** Dugan Production P&A'd the well as per the following procedure on 12/27/2023-01/10/2023: 1) MI&RU Aztec Well Services Rig 481. TOOH & LD 2-7/8" injection tubing & injection packer. 2) RU Wireline. Run wireline. Set 5½" CR @ 4082'. TIH w/2-3/8" work string. Load hole and circulate clean. Pressure test casing to 600 psi for 30 mins. Casing tested good. 3) Sting in cement retainer and spot 8 sks (9.2 cu ft) Class G cement to cover 50' below the CR inside 5½" casing @ 4082' to 4132' below the cement retainer. Sting out of the CR. Spot plug w/12 sks (13.8 cu ft) above the retainer from 4082' to 3971' (1.15 cu ft/sk, 15.8#/gal). Total cement spotted above and below CR, 20 sks, 23 cu ft. Displace w/13 bbls fresh water. Plug I, inside 5½" casing, Point Lookout, 20 sks, 23 cu ft, 3971'-4132'. 4) Spot Plug II inside 5½" casing from 3297' to 3141' w/18 sks (20.7 cu ft) Class G cement to cover Mesaverde top. Displace w/12 bbls fresh water. Plug II, inside 5½" casing, Mesaverde, 18 sks, 20.7 cu ft, 3193'-3293'. 5) Spot Plug III inside 5½" casing from 2766' to 2610' w/18 sks (20.7 cu ft) Class G neat cement to cover Chacra top. Displace w/10 bbls fresh water. Plug III, inside 5½" casing, Chacra, 18 sks, 20.7 cu ft, 2610'-2766'. 6) Spot Plug IV inside 5½" casing from 1777' to 1605' w/18 sks (20.7 cu ft) Class G cement to cover the Pictured Cliffs top. Displace w/6 bbls fresh water. Plug III, inside 5½" casing, Pictured Cliffs, 18 sks, 20.7 cu ft, 1605'-1777'. 7) Spot Plug V inside 5½" casing from 1402'-1246' w/18 sks (20.7 cu ft) Class G cement to cover the Fruitland top. Displace w/4.5 bbls fresh water. Plug IV, inside 5½" casing, Fruitland, 18 sks, 20.7 cu ft, 1246'-1402'. 8) Spot inside Plug VI inside 5½" casing from 295' to surface w/45 sks (51.8 cu ft) Class G cement to cover the surface casing shoe, Kirtland & Ojo Alamo tops to surface. Circulated 1 bbl cement to surface. WOC 4 hrs. Plug V, inside 5½" casing, Surface-Kirtland-Ojo Alamo, 45 sks, 51.8 cu ft, 0'-295'. 9) WOC 4 hrs. Cut wellhead. Tag TOC at surface. Fill cellar w/25 sks (28.8 cu ft) Class G neat cement. Install dry hole marker. Clean location. 10) Well P&A'd 1/10/2023. Bill Diers w/BLM FFO witnessed job.

Well Name: MOLLY PITCHER

Well Location: T30N / R14W / SEC 14 / SENE / 36.814243 / -108.27089

County or Parish/State: SAN JUAN / NM

Well Number: 4 SWD

Type of Well: INJECTION - ENHANCED RECOVERY

Allottee or Tribe Name:

Lease Number: NMNM628

Unit or CA Name:

Unit or CA Number:

US Well Number: 300453095400S1

Well Status: Abandoned

Operator: DUGAN PRODUCTION CORPORATION

### SR Attachments

#### Actual Procedure

Molly\_Pitcher\_SWD\_4\_Post\_PA\_schematic\_20230126160655.pdf

### Operator

*I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a*

Operator Electronic Signature: TYRA FEIL

Signed on: JAN 26, 2023 04:06 PM

Name: DUGAN PRODUCTION CORPORATION

Title: Authorized Representative

Street Address: PO Box 420

City: Farmington

State: NM

Phone: (505) 325-1821

Email address: tyrafeil@duganproduction.com

### Field

Representative Name: ALIPH REENA

Street Address: PO BOX 420

City: FARMINGTON

State: NM

Zip: 87499-0420

Phone: (505)325-1821

Email address: Aliph.Reena@duganproduction.com

### BLM Point of Contact

BLM POC Name: KENNETH G RENNICK

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5055647742

BLM POC Email Address: krennick@blm.gov

Disposition: Accepted

Disposition Date: 01/26/2023

Signature: Kenneth Rennick



**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
 Action 180288

**CONDITIONS**

Operator: DUGAN PRODUCTION CORP PO Box 420 Farmington, NM 87499	OGRID: 6515
	Action Number: 180288
	Action Type: [C-103] Sub. Plugging (C-103P)

**CONDITIONS**

Created By	Condition	Condition Date
mkuehling	well plugged 1/10/2023	2/20/2023