

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised August 1, 2011

| | | |
|---|--|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | WELL API NO. 30-015-00285 |
| 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> | | 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 2. Name of Operator BXP Operating, LLC | | 6. State Oil & Gas Lease No. |
| 3. Address of Operator 1515 Calle Sur, Suite 174, Hobbs, NM 88240 | | 7. Lease Name or Unit Agreement Name Everest |
| 4. Well Location Unit Letter <u> </u> L <u> </u> : <u> </u> 2310 <u> </u> feet from the <u> </u> South <u> </u> line and <u> </u> 990 <u> </u> feet from the <u> </u> West <u> </u> line Section <u> </u> 14 <u> </u> Township <u> </u> 18S <u> </u> Range <u> </u> 26E <u> </u> NMPM <u> </u> County <u> </u> Eddy <u> </u> | | 8. Well Number 002 |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) | | 9. OGRID Number 329487 |
| 10. Pool name or Wildcat Atoka; San Andres | | 10. Pool name or Wildcat Atoka; San Andres |

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☒ XX
 CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE M. Y. Merchant TITLE Agent DATE 3.7.2023
 Type or print name M. Y. Merchant E-mail address: mymerch@penncoill.com PHONE: (575)492-1236
 For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 3/15/23
 Conditions of Approval (if any):

**Plugging Report
Everest #2
API 30-015-00285**

1/5/2023 Move rig to location. Removed the fence from around the well and set large matting board. Spot rig over the wellhead and shut down.

1/6/2023 Rigged up. POOH with 57 ¾" rods. Pump barrel and standing valve was left in the hole. Dug out around the wellhead and replaced the casing connections. Installed BOP. Stood back 17 stands of 2 3/8" tubing and encountered oil standing in the tubing. Shut down. Will have to use mud bucket and vac truck to pull remaining tubing.

1/9/2023 Rigged up vacuum truck and mud bucket and finished pulling the tubing. Made gauge ring run and set 5 ½" CIBP at 1477'. Tagged CIBP with tubing and circulated MLF. Tested casing to 800#. Casing good. Spot 25 sx Class C cement on top of CIBP with CaCl. WOC and tagged at 1225'. Perforated casing at 1137'. Set packer at 770' and pressured up to 500#. Held. Bled off back to the truck. Repeated to 750# and held. POOH with packer and RIH with tubing to 1191'. Spot 25 sx cement across the perfs. POOH and SION.

1/10/2023 Tagged cement at 916'. Dug out surface head. Perforated casing at 250'. Pressured up on perforations to 500# and held. No rate. Spot cement from 320' to surface with 35 sx. Rigged down. Removed the wellhead. Good cement to surface. Installed Below ground marker, removed the anchors and cleaned the pit.

Received by OCD: 8/8/2022 10:43:02 AM

Page 7 of 8

BXP Operating, LLC
Everest #2

CURRENT
30-015-00285

INSTALL DRY HOLE MARKER
CUT OFF WELLHEAD & VERIFY CMT

~~FILL TO SURFACE W/ CMT~~
~~POOH TO 250'~~

Perf @ 250' and attempt to sqz cmt to surface

8 5/8" 24# @ 1087' w/ 475 sx (circ)

perf @ 1137' and attempt to sqz 40 sx cmt
WOC & Tag

CIBP @ 1477' - Test casing 500psi for 30 min. spot 25 sx cmt - WOC & tag

~~SPOT 50 SY CMT (COVERS 8 5/8" SHOE)~~
~~SET CIBP @ 1427'~~

Perfs 1527' - 1674'
5 1/2 "14# @ 1743' w/ 450 sx (circ)

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 195415

CONDITIONS

| | |
|--|--|
| Operator: BXP Operating, LLC 11757 KATY FREEWAY HOUSTON, TX 77079 | OGRID: 329487 |
| | Action Number: 195415 |
| | Action Type: [C-103] Sub. Plugging (C-103P) |

CONDITIONS

| | | |
|------------|-----------|----------------|
| Created By | Condition | Condition Date |
| gcordero | None | 3/15/2023 |