

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-01566
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Cockburn B State Com
8. Well Number 2
9. OGRID Number 331199
10. Pool name or Wildcat E-K; Yates-Seven Rivers_ Queen; Vacuum; Morrow East
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [] Gas Well [] Other []
2. Name of Operator Maverick Permian LLC
3. Address of Operator 1111 Bagby Street, Suite 1600 Houston, TX 77002
4. Well Location Unit Letter H : 1980 feet from the North line and 660 feet from the East line Section 1 Township 18S Range 33E NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON [X]
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Maverick Permian LLC respectfully requests approval to plug and abandon the Cockburn B State Com #2, attached are the P&A Summary, Current and proposed WBD's.

Run CBL log if one does not exist

See attached conditions of approval

4" Diameter 4' tall above ground marker

Note changes to procedure

Spud Date:

[Empty box for Spud Date]

Rig Release Date:

[Empty box for Rig Release Date]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Sr. Regulatory Analyst DATE 03/09/2023

Type or print name Lauri M. Stanfield E-mail address: Lauri.Stanfield@mavresources.com PHONE: 713-437-8052

For State Use Only

APPROVED BY: [Signature] TITLE Compliance Officer A DATE 3/20/23



Maverick Permian, LLC
A Subsidiary of Maverick Natural Resources
1111 Bagby Street • Suite 1600
Houston • Texas • 77002
713-437-8000

COCKBURN B STATE COM #2
API #30-025-01566
1980' FNL 660' FEL
UNIT H, SECTION 1, TOWNSHIP 18 SOUTH, RANGE 33 EAST
LEA COUNTY, NM

4-1/2" CIBP @ 13,605' w/ 20' CMT on TOP @ 13,585' (01/01/2004)

4-1/2" CIBP @ 13,317' Tagged @ 13,288' (08/18/2015) **Run CBL log**

Mix & Spot 350' cmt plug on top of 4-1/2" CIBP f/ 13,317' - 12,967" w/ (5.25 bbls / 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4 hrs. Tag & Rec.

Isolation Plug: Mix & Spot 350' cmt plug in 4-1/2" csg f/ 11,290'-10,890' w/ (5.25 bbls/ 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4 hrs. Tag & Rec. (Penn Sand)

Iso Plug: Mix & Spot 350' cmt plug in 4-1/2" csg f/ 8,525' - 8,175' w/ (5.25 bbls / 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4hrs. Tag & Rec. (Isolates Abo Formation)

Perf 4-1/2" csg @ 6,874'. Attempt SQZ. Do not exceed 500 psi on SQZ.

Iso Plug: Mix, Spot, & SQZ 100' cmt plug in 4-1/2", 4-1/2" x 7-7/8" open hole w/ (12 bbls / 66 cuft / 50 sx) (Includes 100% excess. Class "C" Cmt 1.32 yield. WOC 4 hrs. Tag & Record. (Isolates Glorieta Formation.

Perf 4-1/2" csg @ 5,068'. Attempt SQZ. Do not exceed 500 psi on SQZ.

Iso Plug: Mix, Spot, & SQZ 100' cmt plug in 4-1/2", 4-1/2" x 7-7/8" open hole w/ (12 bbls / 66 cuft / 50 sx) (Includes 100% excess) Class "C" Cmt. 1.32 yield. WOC 4 hrs. Tag & Record. (Isolates San Anches Formation)

Perf 4-1/2" Csg @ 4,620'. Attempt SQZ. Do not exceed 500 psi.

Iso Plug: Mix, Spot, SQZ 550' plug in 4-1/2", 4-1/2" x 7", 4-1/2" x Open Hole w/ (20 bbls / 110 cuft / 84 sx) Class "C" 1.32 yield cmt. WOC 4hrs. Tag & Record. Isolates (Queen & Graybury Formations)

Perf 4-1/2" Csg @ 3,505'. Attempt SQZ. Do not exceed 500 psi on SQZ.



Maverick Permian, LLC
A Subsidiary of Maverick Natural Resources
1111 Bagby Street • Suite 1600
Houston • Texas • 77002
713-437-8000

Iso Plug: Mix, Spot, SQZ 175' plug in 4-1/2", 4-1/2" x 7" annuli w/ (6.0 bbls / 33 cuft / 25 sx)
Class "C" 1.32 yield. WOC 4 hrs. Tag & Record. (7Rivers)

Perf 4-1/2" & 7" Csg @ 3,084'. Attempt SQZ. Do not exceed 500 psi on SQZ.

Iso Plug: Mix, Spot, SQZ 255' plug in 4-1/2", 4-1/2" x 7", 7" x 8-5/8" annuli w/ (21 bbls / 119 cuft / 89 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record. (Salt & Yates)

Perf 4-1/2" & 7" Csg. @ 1,867'. Attempt SQZ. Do not exceed 500psi on SQZ.

Isolation Plug: Mix, Spot, SQZ 280' plug in 4-1/2", 4-1/2" x 7", 7" x 8-5/8" annuli w/ (15 bbls / 82 cuft / 62 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record. (Anhy & Salt)


Perf 4-1/2, 7", and 8-5/8" Csgs 50' below Surface Csg shoe @ 364'. Attempt to SQZ. Do not exceed 500 psi on SQZ.

Surface Plug: Mix, Spot, and Attempt SQZ Cmt plug in 4-1/2", 4-1/2 x 7", 7" x 8-5/8", 8-5/8" x 11-3/4" annuli w/(36 bbls / 202 cuft / 267 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record.

State: New Mexico
 County: Lea
 Field:
 Spud Date: 6/12/1961
 KB:

Maverick Resources
 Well: Cockburn B State COM #2
 API# 30-025-01566

Current WBD
 03.06.2023
 Drawn by: J. McCullough-Axis Energy Serv.



State: New Mexico
 County: Lea
 Field:
 Spud Date: 6/12/1961
 KB:

Maverick Resources
 Well: Cockburn B State COM #2
 API# 30-025-01566

Proposed WBD
 03.07.2023
 Drawn by: J. McCullough-Axis Energy Serv.

Surface Csg: 11-3/4" 42# H-40 TOC: to Surface


Formation Tops	
Anhy	1,687'
Salt	1,867'
Salt	2,882'
Yates	3,034'
7Rivers	3,455'
Queen	4,121'
Graybury	4,570'
San Anches	5,018'
Glorieta	6,824'
Abo	8,350'
Penn	11,090'

8-5/8" 24# J-55. TOC: Circulated to Surface

7" 20# & 23# J-55 TOC @ 2,950'

Formations Tops	
Anhy	1,687'
Salt	1,867'
Salt	2,882'
Yates	3,034'
7Rivers	3,455'
Queen	4,121'
Graybury	4,570'
San Anches	5,018'
Glorieta	6,824'
Abo	8,350'
Penn	11,090'

4-1/2" 13# P-110. TOC: 8,300' by CBL



Surface Plug: Mix, Spot, and Attempt SQZ Cmt plug in 4-1/2", 4-1/2 x 7", 7" x 8-5/8", 8-5/8" x 11-3/4" annuli w/ (36 bbls / 202 cuft / 267 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record.

Perf 4-1/2, 7", and 8-5/8" Csgs 50' below Surface Csg shoe @ 364'. Attempt to SQZ. Do not exceed 500 psi on SQZ.
 Isolation Plug: Mix, Spot, SQZ 280' plug in 4-1/2", 4-1/2" x 7", 7" x 8-5/8" annuli w/ (15 bbls / 82 cuft / 62 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record. (Anhy & Salt)
 Perf 4-1/2" & 7" Csg. @ 1,867'. Attempt SQZ. Do not exceed 500psi on SQZ.

Iso Plug: Mix, Spot, SQZ 255' plug in 4-1/2", 4-1/2" x 7", 7" x 8-5/8" annuli w/ (21 bbls / 119 cuft / 89 sx) Class "C" 1.32 yield cmt. WOC 4 hrs. Tag & Record. (Salt & Yates)
 Perf 4-1/2" & 7" Csg @ 3,084'. Attempt SQZ. Do not exceed 500 psi on SQZ.
 Iso Plug: Mix, Spot, SQZ 175' plug in 4-1/2", 4-1/2" x 7" annuli w/ (6.0 bbls / 33 cuft / 25 sx) Class "C" 1.32 yield. WOC 4 hrs. Tag & Record. (7Rivers)
 Perf 4-1/2" Csg @ 3,505'. Attempt SQZ. Do not exceed 500 psi on SQZ.

Iso Plug: Mix, Spot, SQZ 550' plug in 4-1/2", 4-1/2" x 7", 4-1/2" x Open Hole w/ (20 bbls / 110 cuft / 84 sx) Class "C" 1.32 yield cmt. WOC 4hrs. Tag & Record. Isolates (Queen & Graybury Formations)
 Perf 4-1/2" Csg @ 4,620'. Attempt SQZ. Do not exceed 500 psi.

Iso Plug: Mix, Spot, & SQZ 100' cmt plug in 4-1/2", 4-1/2" x 7-7/8" open hole w/ (12 bbls / 66 cuft / 50 sx) (Includes 100% excess) Class "C" Cmt. 1.32 yield. WOC 4 hrs. Tag & Record. (Isolates San Anches Formation)
 Perf 4-1/2" csg @ 5,068'. Attempt SQZ. Do not exceed 500 psi on SQZ.
 Iso Plug: Mix, Spot, & SQZ 100' cmt plug in 4-1/2", 4-1/2" x 7-7/8" open hole w/ (12 bbls / 66 cuft / 50 sx) (Includes 100% excess. Class "C" Cmt 1.32 yield. WOC 4 hrs. Tag & Record. (Isolates Glorieta Formation.
 Perf 4-1/2" csg @ 6,874'. Attempt SQZ. Do not exceed 500 psi on SQZ.

Iso Plug: Mix & Spot 350' cmt plug in 4-1/2" csg f/ 8,525' - 8,175' w/ (5.25 bbls / 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4hrs. Tag & Rec. (Isolates Abo Formation)

Isolation Plug: Mix & Spot 350' cmt plug in 4-1/2" csg f/ 11,290'-10,890' w/ (5.25 bbls / 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4 hrs. Tag & Rec. (Penn Sand)

Mix & Spot 350' cmt plug on top of 4-1/2" CIBP f/ 13,317' - 12,967" w/ (5.25 bbls / 29.5 cuft / 25 sx) 1.18 yield Class "H" cmt. WOC 4 hrs. Tag & Rec.
 4-1/2" CIBP @ 13,317' Tagged @ 13,288' (08/18/2015)

Perfs f/ 13,410' - 13,450' (01/22/2004)

4-1/2" CIBP @ 13,605' w/ 20' CMT on TOP @ 13,585' (01/01/2004)
 Perfs f/ 13,674'- 13,702' (11/13/2002)

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office II at **(575)-263-6633** at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. **A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs.** Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Cherry Canyon - Eddy County
 - L) **Potash**---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
 2. Lease and Well Number
 3. API Number
 4. Unit Letter
 5. Quarter Section (feet from the North, South, East or West)
 6. Section, Township and Range
 7. Plugging Date
 8. County
- (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 195219

COMMENTS

Operator: Maverick Permian LLC 1111 Bagby Street Suite 1600 Houston, TX 77002	OGRID: 331199
	Action Number: 195219
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	3/21/2023

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 195219

CONDITIONS

Operator: Maverick Permian LLC 1111 Bagby Street Suite 1600 Houston, TX 77002	OGRID: 331199
	Action Number: 195219
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	See attached COA	3/20/2023